**Af-006** Room: C415 Time: June 26 10:50-11:10

## Deep resistivity structure of the Takamatsu crator, Japan

# Tada-nori Goto[1], Takayuki Kimura[2], Yoshihiro Hiramatsu[3], Yoshiaki Ishihara[4], Muneyoshi Furumoto[4], Yoshiteru Kono[5]

[1] Dept. Environmental Earth Sci., Aichi Univ. Educ., [2] Dept. Environmental Earth Sci., Aichi Univ. Educ., [3] Earth Sci., Kanazawa Univ, [4] Dept. Earth Sci., Kanazawa Univ., [5] Earth Science, Graduate Schl.Nat.Sci.Tech., Kanazawa Univ.

http://www.mater.aichi-edu.ac.jp/envsci/goto/

The magnetotelluric(MT) sounding was carried out around the Takamatsu crator, located in Takamatsu city, Southwest Japan. Two station for the wide-band MT survey and fifteen sites for the AMT survey were set around the crator. We tried to remove noise from time series data by using a new GUI program. The noise rejection is quite effective so that subsurface structure deeper than 10 km was obtained in this study. The obtained resistivity structure at the center of the crator shows a modelately resistive surface and a conductive layer at depth range of 100 - 200 m. Below them a resistive layer (>1000 Ohmm) underlies. In this study, we cannot obtain a crator-like resistivity structure around the Takamatsu crator.