MIS036-P126   :   :5   27   14:15-16:15

Multiscale Tsunami Simulation of Tohoku Earthquake

David Yuen[1*]
David Yuen[1*]

[1]University of Minnesota
[1]University of Minnesota

Multi-scale   Tsunami Simulation   of Tohoku Earthquake

David L. George, USGS , Vancouver, Washington, U.S.A.
David A. Yuen, and Erik O.D. Sevre ,
  Dept. of Geology and Geophysics, University of Minnesota, Minneapolis, MN   55455-0219, U.S.A.
Shigenori Maruyama, Dept. of Earth and Planetary Sciences, Tokyo Institute of Technology, 153, Tokyo, Japan
Y. Yanai and Atshushi Utsunomiya , Japan Geocommunications Co. Ltd, Shinjuku , Tokyo, Japan

The recent M 9.0 Tohoku earthquake has dealt northeastJapan a great blow and the   resultant tsunami waves have caused great destruction and loss of lives. We have employed state-of-the-art numerical methods to study the tsunami run-up problem by means of a high-resolution finite volume method with special focus on the inundation problem. The Riemann solver under the auspices of th GEOCLAW package is applied to the nonlinear shallow-water equations that works robustly with fine-scale seafloor bathymetry and dry states associated with the land and the buildings. Very high- resolution bottom seafloor topography near the Japanese coast, less than 100 meters , was employed in this study

We have employed the adaptive mesh refinement (AMR) method to study this multi-scale phenomenon of tsunami waves interacting with the coast. Grid sizes vary greatly by more than two-orders in magnitude allowing for multi-resolution capability. We are particularly interested in the waves coming toward the nuclear plant at Fukushima and to study the maximum height of the waves leaping over the building structures   along the coast. The influences of high-resolution bathymetry on amplifying the run-up waves will be emphasized

: tsunami, riemann solver, run-up waves, adaptive mesh refinement
Keywords: tsunami, riemann solver, run-up waves, adaptive mesh refinement