

## 二段式軽ガス銃を用いた開放系気相化学分析: 炭酸塩岩の衝突脱ガス Shock-induced devolatilization from calcite in an open system using a two-stage light gas gun

黒澤 耕介<sup>1\*</sup>, 大野 宗祐<sup>2</sup>, 杉田 精司<sup>3</sup>, 三重野 哲<sup>4</sup>, 松井 孝典<sup>2</sup>, 長谷川 直<sup>1</sup>

KUROSAWA, Kosuke<sup>1\*</sup>, OHNO, Sohuke<sup>2</sup>, SUGITA, Seiji<sup>3</sup>, Tetsu Mieno<sup>4</sup>, MATSUI, Takafumi<sup>2</sup>, HASEGAWA, Sunao<sup>1</sup>

<sup>1</sup> 宇宙航空研究開発機構 宇宙科学研究所, <sup>2</sup> 千葉工大 惑星探査研究センター, <sup>3</sup> 東大 新領域 複雑理工, <sup>4</sup> 静岡大 理 物理  
<sup>1</sup>ISAS, JAXA, <sup>2</sup>PERC, Chiba Institute of Technology, <sup>3</sup>Graduate School of Frontier Science, The Univ. of Tokyo, <sup>4</sup>Faculty of Science, Shizuoka Univ.

We investigated shock-induced decarbonation of non-porous calcite in an open system at a wide range of peak shock pressures using a two-stage light gas gun and a quadrupole mass spectrometer. A new experimental technique that avoids chemical contamination from the acceleration gas from the gun was developed. We also conducted high-speed imaging and spectroscopic observations simultaneously to investigate the validity of our experimental procedure. We newly found that the decarbonation efficiency along the Hugoniot curve changes around 50 GPa, which is close to the predicted pressure for incipient decarbonation by ANEOS. Although shock-induced decarbonation was detected at the pressure lower than 50 GPa as well as the previous experimental studies, decarbonation may be caused by local energy concentration due to shear banding, resulting in low decarbonation efficiency. We constructed a simple theoretical model for shock-induced decarbonation during isentropic release based on the entropy method and the lever rule under our experimental condition. The predicted CO<sub>2</sub> amount as a function of peak shock pressure agrees well the experimental results at >50 GPa, strongly suggesting that the shock-induced CO<sub>2</sub> amount is determined only by the entropy for the peak shock state, incipient and complete decarbonation at the ambient pressure. We can use the new method for the quantitative measurements of the chemical composition of impact-induced gases from solid materials without any modification. The new technique is very useful to investigate the required peak shock pressure for vaporization/devolatilization of geologic materials and the final chemical composition in impact-induced vapor clouds.

キーワード: 衝突脱ガス, 気相化学分析, 開放系, 二段式軽ガス銃, 質量分析器, 炭酸塩岩

Keywords: Impact-induced devolatilization, Gas-phase chemical analysis, Open system, Two-stage light gas gun, Mass spectrometry, Carbonate