

Social and economic consequences of March 11, 2011 Tohoku disaster in Japan Social and economic consequences of March 11, 2011 Tohoku disaster in Japan

ELENA PETROVA^{1*}

PETROVA, ELENA^{1*}

¹Lomonosov Moscow State University, Faculty of Geography

¹Lomonosov Moscow State University, Faculty of Geography

The last two years set a sad record in the number and scale of natural disasters and clearly demonstrated high vulnerability of the global economy to their impact. The most serious consequences have the so-called natural-technological disasters that have place when natural hazards trigger accidents and disasters at technological objects such as nuclear power plants, chemical plants or oil refineries and pipelines. Natural-technological disasters caused by earthquakes and devastating tsunamis have the most serious impact. One of the most large-scaled natural-technological disasters occurred on March 11, 2011 in Japan as a result of a massive 9.0-magnitude earthquake off the northeast coast of Honshu Island, that caused a more than 30-meter tsunami. A distinctive feature of such events is their synergistic nature with a disaster impact on the technosphere, resulting in simultaneous occurrences of numerous technospheric accidents. This disaster was yet another tragic confirmation of the vulnerability of modern techno-sphere and society, even such a highly developed one, as the Japanese, to the impact of natural hazards. The greatest number of fatalities and losses was caused in the Miyagi, Iwate, Fukushima, Chiba, and Ibaraki prefectures. The infrastructure in the north-east of the country is damaged to a considerable extent (more than 130 thousand houses have been completely or partially destroyed, another 265 thousand homes were seriously damaged, thousands of miles of communications, roads and railways, more than 70 bridges were destroyed). With a total damage between 400-700 billion USD in total losses and approximately 19000 deaths and almost 6000 injures, this disaster proved to be the most expensive and the most destructive on record (earthquake-report.com/2012). Of these, direct losses will reach between 294 billion USD and 374 billion USD. The earthquake and tsunami caused a number of technological accidents, including accidents at "Fukushima-1" and "Onagava" nuclear power plants, explosions and fires at refineries in Chiba, and at a petrochemical plant in Sendai, a number of other fires, railway, water, road, and other accidents. 148 lives have been lost in fires, 260 houses have been destroyed by fires.

The most serious consequence of the Tohoku event was a series of accidents at "Fukushima-1" nuclear power plant, which resulted in several leaks of radioactive substances into the atmosphere and the ocean. The accident was initially assigned to the 5-th, and later to the highest 7-th level of danger on 7-point International Nuclear Event Scale (INES). Right after the accident people (about 77 thousand) were evacuated from the 20-kilometer zone around the power plant, and the presence of people in the exclusion zone was prohibited. Later the evacuation area was extended to 60 kilometers.

About 41 percent of economic losses (including both direct and indirect losses) were caused by earthquake, about 36 percent by tsunami and about 23 percent due to the Fukushima disaster. The disaster had an impact on economic development not only in Japan but also in other countries. Many Japanese companies have suffered significant losses. The NPP Hamaoka situated in the Shizuoka Prefecture (200 km from Tokyo) with a predicted high probability of massive earthquake, was stopped. However, Japan, as well as Russia, does not intend to completely abandon nuclear power. Meanwhile some other countries declared a revision of their atomic energy programs. For example, the German government announced the decision to stop the operation of all the country's nuclear power plants by 2022.

Hopefully the lessons of the disaster will contribute to the increasing of safety of nuclear power plants and other high-risk facilities. One of the main lessons of this tragedy lies in the fact that while placing, constructing and operating such facilities, it is necessary to consider carefully the potential impacts, including natural hazards.

キーワード: natural-technological disaster, social losses, economic consequences, disaster prevention, vulnerability

Keywords: natural-technological disaster, social losses, economic consequences, disaster prevention, vulnerability

企業と地域コミュニティの災害軽減に関する考察～東日本大震災からの教訓 Protecting industry and communities: Lessons from the Great East Japan Earthquake of 11 March 2011

多々納裕一¹, 梶谷 義雄^{1*}, クルーズ・アナマリア², クラウスマン・エリザベス³
Tatano, Hirokazu¹, KAJITANI, Yoshio^{1*}, Cruz, Ana Maria², Krausmann, Elisabeth³

¹ 京都大学防災研究所, ² 京都大学防災研究所 (フランス・リージョナルオフィス), ³ 欧州共同研究センター

¹Disaster Prevention Research Institute, Kyoto University, ²Regional Office, Disaster Prevention Research Institute, Kyoto University, ³Institute for the Protection and Security of the Citizen, Joint Research Centre, European Commission

This paper presents the preliminary results and analysis of an ongoing study of impacts of the Great Eastern Japan earthquake and tsunami of 11 March 2011 on industry in Miyagi, Ibaraki and Chiba Prefectures. This study is a joint effort by the Disaster Prevention Research Institute of Kyoto University and the Joint Research Centre of the European Commission. The study involved a series of field trips to the affected areas, interviews with government officials and interviews and visits with industry owners /operators. The purpose of the study is to assess performance of risk management practices including mitigation, preparedness and response measures to deal with the earthquake and tsunami; impacts on the community of any pollution incidents or chemical accidents ensued, as well as overall economic and supply chain impacts on industry.

Keywords: NaTech, Economic Impact, Business Continuity, Community Protection

東日本大震災後の沿岸域における土地利用計画の再考 Re-thinking of Land use planning at coastal area in Japan after Tsunami disaster

松島 肇^{1*}

MATSUSHIMA, Hajime^{1*}

¹ 松島 肇

¹Hajime MATSUSHIMA

1. Introduction

One of the five most powerful earthquakes in the world since modern record-keeping, which was a magnitude 9.0 (Mw) undersea megathrust earthquake off the coast of Japan, occurred at 14:46 JST (05:46 UTC) on Friday, 11 March 2011 (Ministry of Land, Infrastructure, Transportation and Tourism, Great East Japan Earthquake report (106), 6 Feb. 2012). The earthquake triggered powerful tsunami waves that reached heights of up to 40m in Miyako, Iwate Prefecture, and which, in the Sendai area, travelled up to 10km inland. The Japanese National Police Agency confirmed 15,860 deaths, 6,011 injured, and 3,281 people missing, as well as over 372,000 buildings damaged or destroyed. Although most coastal area has invested the huge seawalls which stand up to 12 m high, the tsunami simply washed over the top of some seawalls, collapsing some in the process. This tsunami was beyond the assumption scale of the seawall design greatly, but the equivalent scale tsunami was occurred at same area in the past several times, e.g. 869 Jogan tsunami, 1896 Meiji-Sanriku tsunami, 1933 Sanriku tsunami, etc.

2. Why is the history repeated?

Japan is narrow and steep mountainous island country surrounded by the sea. About 35% of populations are concentrated in coastal lowland area, almost same as inundation area of this 2011 tsunami, within 10km from coastline and up to 30m from sea level. In this Sanriku area, people moved to hills after every tsunami disaster, however they gradually back to lowland again. Even if a lot of monuments, which warned of the danger of the tsunami, were left, the memory of their danger has gradually faded and the history has been repeated over and over again. While some villages, which keep staying on the hills, have avoided this 2011 tsunami disaster.

3. Design with nature

One of the big issues of land use in coastal area is that the city area got too close to the sea. Because the population has been increased until in 2005, we needed to develop more urban area and farmland. The development of coastal area brought economic growth. But the expanse of the city resulted in the increase of enormous cost to maintain their infrastructures, e.g. roads, water and drainage services, and seawall to protect the properties. These developments destroyed natural settings in coastal area and their ecosystem services, especially from coastal sand dune. One of the most important ecosystem services of coastal sand dune is the coastal defense as natural dike. In Netherland, the coastal sand dune is strictly protected instead of seawall. In addition with the coastal defense, coastal sand dune supply dune water as drinking water in Netherland. Everard et. al. (2010) showed that the coastal sand dune provided not only support biodiversity, but also a wide range of ecosystem services. In Japan, most coastal dunes were lost caused by erosion, development, planting coastal forest, and establishment of seawalls. But now, Japanese populations have decreased to since 2005. Especially in the Tohoku region, populations decreased to since 1970s and the abandoned farmlands have rapidly increased since 2000. We should consider the setback from the coast and the restoration of coastal sand dunes as reconstruction plan. In this plan, the seawalls are not necessary, coastal forest moving to more inland area where will work well, and landfilled road, which stands seaside of the city, being inner dike instead of the seawalls. 2011 Tsunami disaster has showed that the liner protection, e.g. huge seawall, could not prevent their damage. The new reconstruction plan should be made effective configuration of these multiplex defense structures of land use to reduce the damage of tsunami, considered the landscape, population trend and future vision.

References

Everard M, Jones L and Watts B (2010) Have we neglected the societal importance of sand dunes? An ecosystem services perspective. *Aquatic Conservation: Marine and Freshwater Ecosystem* 20, 476-487.

An estimate of the risk of accidents An estimate of the risk of accidents

Valery Kudin^{1*}
KUDIN, Valery^{1*}

¹Lomonosov Moscow State University, Moscow, Russia.

¹Lomonosov Moscow State University, Moscow, Russia.

An estimate of the risk of accidents

Kudin V.N.

Lomonosov Moscow State University, Moscow, Russia.

An analytical dependency of the risk value from the characteristics of inaccuracy of the coming events, which are particularly connected with natural hazards, is proposed. It is noted that algorithm of risk management to realization of the event should contain the operations of the process partition on controlled stages.

The theory of the risk was broadly developed and used at the end of 19th century, due to development of mathematicians and statistics. For undertaking numerical calculation of risk, game theory, theory of chances, theories of the catastrophes and decision making are used. The risk is objective and exists in any sufficiently complex system, so the development of approaches to risk assessment is important for environmental, economic, technical applications, and many other branches of human activity.

The following determinations of the risk are known: in sociologies it is a possible danger, loss, or failure; in mathematician it is a feature of a statistical process, expressing loss. Covering a wide range of human activities and spheres of its existence, it can be assumed that the risk is the uncertainty in the realization occurrence of a possible event. Nuance in above definition of risk is to emphasize the difference between the amount of risk and the value of the probability of an event. For example, if the risk is zero, the event is sure to be done. However, if the probability of its occurrence is zero, it means that the event will not happen.

In an effort to maintain a formal risk assessment tool, you should find an universal mathematical operation that expresses the value of risk by any objective characteristic stability of the event. In physics there is the concept of entropy, the information on which is a measure of the uncertainty of the event. From general considerations, we can assume that an increase (decrease) in the instability of the events will increase (decrease) the risk. On the other hand, the more we know about the history of the origin of the event, the less is uncertainty in the prediction of new developments. Thus, the expectation, based on knowledge of the previous information allows us to apply the exponential dependence of the risk from entropy. This nonlinear correlation indicates only a principle of correspondence of the risk value and the entropy and does not contain an exhaustive level of strictness. The proposed mathematical operation is used as a tool for the systematic ordering of material related events, and provides a convenient way of interpolation with other conditions, which allows to refine the knowledge and set goals for the experiments.

The use of the exponential correlation is that it is being used, along with multiple feature of the real condition, can estimate a quality of results and extrapolations of an approaching event. Such a calculation indicates an amount of risk that an entity may operate.

Thereby, the role of the subject is not reduced to a passive contemplate, it allows you to create sensibly, acting responsible. This constructive approach is especially important when working with a large number of realities, where only limited range of situations and estimated treatment effects on individual attention given the opportunity to obtain useful conclusions.

キーワード: risk, natural hazards, environmental, entropy, mathematicians, statistics

Keywords: risk, natural hazards, environmental, entropy, mathematicians, statistics

災害復興と観光 –宮城県石巻市を事例として–

Post-Disaster Reconstruction and Tourism –the case of Ishinomaki City, Miyagi Prefecture

大森 信治郎^{1*}, 青木陽二²

OHMORI, Shinjiro^{1*}, AOKI, Yoji²

¹ 石巻専修大学 経営学部, ² なし

¹Ishinomaki Senshu University Faculty of Business Administration, ²none

本報告は2011年3月11日以降の被災地における地域の状況及びその推移について、自身が被災者である報告者の視点を織り交ぜながら、社会的及び社会心理学的に考察を加えようとするものである。巨大な自然災害後の地域社会の復興過程において人間の営為、とりわけ移動、交流がどのようになされたのか。また、ツーリズムは其中でどのような役割を果たしているのか。被災地として最も大きな物的・人的被害を受けた自治体の一つである宮城県石巻市を事例として報告する。

被災者の状況と被災地の復旧段階

被災者のおかれた状況によって、現地の一年間の復旧過程は主に4つの段階に分けて理解することができる。生存の確保の時期、生活の確保の時期、生計の確保の時期、生活環境の整備の時期、の4つの段階である。

被災者心理と支援活動

被災者の緊張感は時間の経過とともに低減する。緊張感は感受性を高める働きを持つ。このことは来訪者に対する被災者の感情と密接な関係を持つと考えられる。

ボランティアかツーリストか

震災直後多くのボランティアが来訪し、復旧に大きな役割を果たした。大手の旅行会社をはじめ多くの「ボランティアツアー」が企画実施された。被災者の中には、被災状況を観光されることに少なからぬ抵抗感を持つ者もいる。しかし、一方では観光は復興に重要な役割を果たしている現象でもある。

“ Reconstruction Support Tourism ”

被災地をめぐる観光の復興に対する役割に注目して、これを“ Reconstruction Support Tourism ”(以下RST)と呼ぶことを提唱する。一部に、自然災害を含めて本来当事者或いは人類にとって好ましくない事象をめぐる観光を“ ダーク・ツーリズム ”と呼ぶ傾向があるが、少なくとも被災地の訪問のすべてにこの語を用いるのは極めて不適切と考えられる。

知の集積の必要性

RSTの例としては、ボランティアツーリズムなどがあげられるが、ひとつの可能性として考えられるものの中に、防災研修ツアーがある。こうしたツアーを実施するためには、現地に災害や防災に関する大きな知の集積が必要であると考えられる。本ミーティングに参加されている皆様の協力をお願いしたい。

キーワード: 災害復興, 観光, ボランティア, 復興支援, 緊張感, 被災者の感受性

Keywords: post-disaster reconstruction, tourism, volunteer, reconstruction support, stress level (degree of tension), sensitivity of disaster victims

2011 Japan tsunami hydrograph and flow velocity measurements from survivor videos using LiDAR

2011 Japan tsunami hydrograph and flow velocity measurements from survivor videos using LiDAR

Hermann Fritz^{1*}, David A. Phillips², Akio Okayasu³, Takenori Shimozone³, Haijiang Liu⁴, Fahad Mohammed¹, Vassilis Skanavis⁵, Costas E. Synolakis⁶, Tomoyuki Takahashi⁷

FRITZ, Hermann^{1*}, David A. Phillips², Akio Okayasu³, Takenori Shimozone³, Haijiang Liu⁴, Fahad Mohammed¹, Vassilis Skanavis⁵, Costas E. Synolakis⁶, TAKAHASHI, Tomoyuki⁷

¹Civil and Environmental Engineering, Georgia Institute of Technology, Savannah, GA 31407, USA, ²UNAVCO, Boulder, CO 80301, USA, ³Ocean Sciences, Tokyo University of Marine Science and Technology, Tokyo 109-0075, Japan, ⁴Civil Engineering, the University of Tokyo, 7-3-1 Hongo, Bunkyo-ku, Tokyo 113-8656, Japan, ⁵Environmental Engineering, Technical University of Crete, Chanea 73100, Greece, ⁶Civil and Environmental Engineering, University of Southern California, Los Angeles, CA 90089, USA, ⁷Department of Safety Science, Kansai University, Osaka 569-1098, Japan

¹Civil and Environmental Engineering, Georgia Institute of Technology, Savannah, GA 31407, USA, ²UNAVCO, Boulder, CO 80301, USA, ³Ocean Sciences, Tokyo University of Marine Science and Technology, Tokyo 109-0075, Japan, ⁴Civil Engineering, the University of Tokyo, 7-3-1 Hongo, Bunkyo-ku, Tokyo 113-8656, Japan, ⁵Environmental Engineering, Technical University of Crete, Chanea 73100, Greece, ⁶Civil and Environmental Engineering, University of Southern California, Los Angeles, CA 90089, USA, ⁷Department of Safety Science, Kansai University, Osaka 569-1098, Japan

On March 11, 2011, a magnitude Mw 9.0 earthquake occurred off the coast of the Tohoku region causing catastrophic damage and loss of life in Japan. Numerous tsunami reconnaissance trips were conducted in Japan (Tohoku Earthquake and Tsunami Joint Survey Group). This report focuses on the surveys at 9 tsunami eyewitness video recording locations in Yoriisohama, Kesenuma, Kamaishi and Miyako along the Sanriku coast in Japan and the subsequent video image calibration, processing, tsunami hydrograph and flow velocity analysis. Selected tsunami video recording sites were visited, eyewitnesses interviewed and some ground control points recorded during the initial tsunami reconnaissance from April 9 to 25.

A follow-up survey from June 9 to 15, 2011 focused on terrestrial laser scanning (TLS) at locations with previously identified high quality eyewitness videos. We acquired precise topographic data using TLS at nine video sites with multiple scans acquired from different instrument positions at each site. These ground-based LiDAR measurements produce a 3-dimensional point cloud dataset. Digital photography from a scanner-mounted camera yields photorealistic 3D images. Integrated GPS measurements allow accurate georeferencing of the TLS data in an absolute reference frame such as WGS84. We deployed a Riegl VZ-400 scanner (1550 nm wavelength laser, 42,000 measurements/second, <600 meter max range) and peripheral equipment from the UNAVCO instrument pool.

The original full length videos recordings were recovered from eyewitnesses and the Japanese Coast Guard (JCG). Multiple videos were synchronized and referenced in time (UTC). The analysis of the tsunami videos follows a four step procedure developed for the analysis of 2004 Indian Ocean tsunami videos at Banda Aceh, Indonesia (Fritz et al., 2006). The first step requires the calibration of the sector of view present in the eyewitness video recording based on visually identifiable ground control points measured in the LiDAR point cloud data. In a second step the video image motion induced by the panning of the video camera was determined from subsequent raw color images by means of planar particle image velocimetry (PIV) applied to fixed objects in the field of view. The third step involves the transformation of the raw tsunami video images from image coordinates to world coordinates. The mapping from video frame to real world coordinates follows the direct linear transformation (DLT) procedure (Holland et al., 1997). Finally, the tsunami surface current and flooding velocity vector maps are determined by applying the digital PIV analysis method to the rectified tsunami video images with floating debris clusters resulting in instantaneous tsunami velocity vector fields. Tsunami currents up to 10 m/s per second were measured in Kesenuma Bay making navigation impossible.

キーワード: tsunami, Tohoku 2011, LiDAR, Japan, earthquake

Keywords: tsunami, Tohoku 2011, LiDAR, Japan, earthquake

Natural Hazards and Nuclear Power Plants: measures to minimize the risk of a nuclear accident

Natural Hazards and Nuclear Power Plants: measures to minimize the risk of a nuclear accident

Tatiana Tutnova^{1*}

TUTNOVA, Tatiana^{1*}

¹Institute of Oriental Studies of the Russian Academy of Sciences

¹Institute of Oriental Studies of the Russian Academy of Sciences

In the aftermath of Fukushima natural-technological disaster the global opinion on nuclear energy divided even deeper. While Germany, Italy and the USA are currently reevaluating their previous plans on nuclear growth, many states are committed to expand nuclear energy output. In China and France, where the industry is widely supported by policymakers, there is little talk about abandoning further development of nuclear energy. Moreover, China displays the most remarkable pace of nuclear development in the world: it is responsible for 40% of worldwide reactors under construction, and aims at least to quadruple its nuclear capacity by 2020. In these states the consequences of Fukushima natural-technological accident will probably result in safety checks and advancement of new reactor technologies. Thus, China is buying newer reactor design from the USA which relies on advanced "passive safety systems".

Nuclear industry has drawn lessons from previous nuclear accidents where technological and human factors played crucial role. But the Fukushima lesson shows that the natural hazards, nevertheless, were undervalued. Though the ongoing technological advancements make it possible to increase the safety of nuclear power plants with consideration of natural risks, it is not just a question of technology improvement. A necessary action that must be taken is the reevaluation of the character and sources of the potential hazards which natural disasters can bring to nuclear industry. One of the examples is a devastating impact of more than one natural disaster happening at the same time. This subject, in fact, was not taken into account before, while it must be a significant point while planning sites for new nuclear power plants.

Another important lesson unveiled is that world nuclear industry needs advanced mechanisms of international oversight. The urgent necessity is to develop and adopt a joint mechanism for international consultation in case of serious accident at a nuclear power plant. It is necessary to work out the list of constraining provisions for building and operating nuclear plants in regions where potential risks of natural-technological catastrophes exist. These provisions should include risk estimate for every particular region, as well as the list of preventive measures to secure the safe operation of nuclear plants located at those sites. As it was stated before, the synergy effects of more than one potential hazard must be taken into account.

The main goal of my report is to represent possible methods for mitigating safety risks associated with natural hazards and technological disasters, review the effectiveness of existing oversight mechanisms, and encourage a cooperative discussion on these issues.

キーワード: Natural hazards, Technological disaster, Synergy effect, Nuclear energy policy, Safety risk evaluation

Keywords: Natural hazards, Technological disaster, Synergy effect, Nuclear energy policy, Safety risk evaluation

An Example of a Historical Natural Disaster and its Influence on the Japanese-Russian Relations An Example of a Historical Natural Disaster and its Influence on the Japanese-Russian Relations

Anastasia Petrova^{1*}

PETROVA, Anastasia^{1*}

¹Institute of Oriental Studies of the Russian Academy of Sciences

¹Institute of Oriental Studies of the Russian Academy of Sciences

A series of powerful Ansei Great Earthquakes hit Japan at the end of 1854 ? beginning of 1855. They started on 23 December, 1854 with the Ansei-T?kai Quake, which had a magnitude of 8.4; its epicenter ranged from the centre of Suruga Bay to the south-east into the ocean. It was followed by the Ansei-Nankai Quake on 24 December. The consequences of these earthquakes and the following tsunami were terrible for Japan: more than 20,000 buildings were destroyed, many people (about 30,000) died in several Japanese regions. But this horrible natural disaster also had some different consequences. At that time frigate Diana, the flagship of the Russian diplomatic mission, stayed in Shimoda: the leader of the mission admiral Yevfimiy Putyatin was conducting long and difficult negotiations trying to start the official relations between Russia and Japan, when Shimoda was hit by the tsunami. Several members of the mission described their impressions in their memoirs. For example, the chaplain Vasily Makhov wrote: "Water from the bottom of the sea drilled and boiled as in cauldron, its waves swirled, rised and spilled into the splashes; billows came from the sea one after another, one stronger than another with unusual noise and furious roar pressed water, captured the coasts, instantly flooded the place father and father ? bigger and bigger..." Shimoda was almost completely destroyed (only 16 houses survived the disaster). Diana was also seriously damaged and soon sank in a storm while sailing to Heda village for repairs. The crew had to move to the shore, and was quartered in Heda. Putiatin asked to provide his expedition with materials and workers for building a new ship so as Russian sailors could return to their homeland, and Japan agreed. Works were carried out in Heda with the help of plans salvaged from the Diana, and required a cooperation of Russian sailors and Japanese carpenters. In about two months a two-masted schooner was built, which was christened Heda in honor of the city that helped with its construction. The Heda was the first western-style ship built in Japan, and thus can be called a "grandfather" of a Japanese oceanic navy. On 26 January, 1855 the Russian-Japanese negotiations were successfully concluded, and the Treaty of Shimoda was signed, marking the start of official relations between Russia and Japan. Thus a terrible natural disaster framed one of the most vivid pages in history of the Japanese-Russian relationship.

キーワード: natural disasters, earthquake, japanese-russian relations, tsunami, Shimoda

Keywords: natural disasters, earthquake, japanese-russian relations, tsunami, Shimoda

平成 23 年東北地方太平洋沖地震津波の被害からみた海岸林の存在効果 The existence effects of coastal forest by damages caused by the 2011 of the Pacific Coast of Tohoku Earthquake Tsunami

岡田 穰^{1*}

OKADA, Minoru^{1*}

¹ 専修大学北海道短期大学

¹Hokkaido College, Senshu University

The purpose of this study is to verify and evaluate the protective effect of coastal forests against damage caused by the March 11, 2011 earthquake and tsunami on the Pacific Coast of Tohoku and to propose a tentative plan for strategic planting of coastal forests.

This field survey was carried out in Nagahama, Ishinomaki City, and Miyagi prefecture, where the coastal forest contains Japanese Red Pines (*Pinus densiflora*) and Japanese Black Pines (*Pinus thunbergii*). There are the residential areas around the coastal forest, and many buildings in these residential areas were washed away and destroyed by the tsunami.

We used aerial photo and local damage investigations to confirm the extent of damage to buildings around the coastal forest. During the aerial photo investigation, we analyzed the sites of the buildings that were washed away and the locations of rubble by comparing aerial photos taken in June 2010 (before the tsunami) with those taken between 12?18 March, 2011 (after the tsunami), in the study area (1,000 x 700 m). During the local damage investigation in August 2011, we performed ground-level surveys and classified buildings into 8 damage grades and by checking the water line marks left by the tsunami. The positions of the building pulled down after the August investigation were checked in October 2011.

In the areas with coastal forest (area of the coastal forest and the back of coastal forest) and those without the coastal forest (buildings behind the tide embankment), the height above the sea level and height of the tsunami water were almost the same and the landform was flat. However, buildings in coastal forest areas suffered less damage than those in areas without the coastal forest. Thus, the wave force-reducing effect of coastal forest was verified. Areas without coastal forest had many washed-out buildings and rubble (particularly within 200 m of the tide embankment). The presence of coastal forests restricts land use near the seashore, where tsunami damage is greatest. Thus, it can be suggested that coastal forests reduce the damage caused to the buildings, which would have otherwise existed near the seashore, and reduce the inflow of rubble into the land. Buildings pulled down after the August investigation were checked in both areas in October; the degree of damage to the buildings in these 2 areas was varied. Therefore, it can guess that the evaluation of effect against the tsunami of a coastal forest by residents is not enough, and a coastal forest is expected the preservation and practical use which gives many functions (existing reason) besides the disaster prevention effect.

キーワード: 海岸林, 津波, 存在効果, 多面的機能

Keywords: coastal forest, tsunami, existense effect, multiple functions

Partition of a process as a tool of risk reduction Partition of a process as a tool of risk reduction

Valery Kudin^{1*}, Elena Petrova¹
KUDIN, Valery^{1*}, Elena Petrova¹

¹Lomonosov Moscow State University, Moscow, Russia.

¹Lomonosov Moscow State University, Moscow, Russia.

Partition of a process as a tool of risk reduction.

Kudin V.N., Petrova E.G.

Lomonosov Moscow State University, Moscow, Russia.

The algorithm of risk management for implementing events, which are related to natural hazards, is proposed. It includes operations that divide the process into manageable steps.

Covering a wide range of human activities and spheres of its existence, it can be assumed that the risk is the uncertainty in the realization occurrence of a possible event. Nuance in above definition of risk is to emphasize the difference between the amount of risk and the value of the probability of an event. For example, if the risk is zero, the event is sure to be done. However, if the probability of its occurrence is zero, it means that the event will not happen. Indeed, the probability of any outcome is an independent characteristic of the event.

From general considerations, we can assume that an increase (decrease) in the instability of the events will increase (decrease) the risk. On the other hand, the more we know about the history of the origin of the event, the less is uncertainty in the prediction of new developments. Thus, the expectation, based on knowledge of the previous information allows us to apply the exponential dependence of the risk from entropy.

Power engineering of the developed countries passed the same way, which passed the weapon - from Greek fire to hydrogen bomb. The energy industrial boom has focused on nuclear reactor that is an analogue of the atomic bomb as if were in delayed-action. For instance, France is the first in the world on atomic power station: about 80% of power there "is done" by nuclear reactors. France is literally littered with them, and terrorism or disaster threatens her at least a new Chernobyl, God forbid.

Physicists offer to move to thermonuclear power plants on the microexplosion, which in principle are safe: they themselves do not explode more than do it themselves inside their reactor. For a nuclear reactor resulting risk can increase substantially, as when the final product resulting entropy is defined by the sum of the entropies, is high (controlled by the inaccuracy in the late act of the reaction). In thermonuclear on a large number of microexplosions resulting risk according to the exponential function does not increase this quantity of controlled implosions, only one of which actually determines the entropy of the output power. In turn, thermonuclear microexplosions will provide more energy from the middle of the XXI century.

Thus, according to the exponential dependence of the risk from the entropy we may conclude that the algorithm to reduce the risk is required to maintain operation of division the process into stages in order to find the most unreliable link. This approach based on the partition process into a series of controlled steps can be proposed to assess consequences of an accident, various scientific and technical proposals, economic projects, test ideas, and more. Therefore, experiments should be avoided, not consisting of duly observed phases. For example, we must adhere to the attention and the work of the most powerful accelerator in the U.S. Brookhaven National Laboratory, for reception "at once" new, so-called quark-gluon plasma, where there is a risk of spontaneous emergence of a black hole that could swallow up not only the lab, but also the entire planet.

キーワード: risk, natural hazards, ecology, entropy, mathematicians, statistics

Keywords: risk, natural hazards, ecology, entropy, mathematicians, statistics

Modern Activity of Bezymianny Volcano and Danger to Aviation Modern Activity of Bezymianny Volcano and Danger to Aviation

Olga Girina^{1*}

GIRINA, Olga^{1*}

¹Institute of Volcanology and Seismology FED RAS

¹Institute of Volcanology and Seismology FED RAS

Bezymianny volcano is one of the most active volcanoes of Kamchatka, Russia. Volcanic activity of Bezymianny started in October 1955 from moderate explosive eruptions, which lasted for about half a year. On March 30 the climactic eruption occurred: catastrophic directed blast and strong Plinian activity. The total volume of eruptive products was over 3 km³. A growth of the lava dome Novy into the explosive crater continues from 1956 till present.

During the 1965-2010 occurred 41 Vulcanian type strong explosive eruptions of the volcano, while 20 of them producing ash up to 10-15 km a.s.l. First strong explosive eruption occurred in 1965. Since 1977, strong explosive eruptions were noting one or two times per year. The most powerful eruption was in 1985, the volume of eruptive products (tephra and pyroclastic flow deposits) reached 0.05 km³.

After powerful eruptions, a lava flow could effuse during a few years. A direction of lava effusing changed, so that by 2005 all the slopes of the dome were covered by thick lava flows. After the 1985 eruption, a lava flow effused about 4 years. In 2006-2010, a lava flow moved down the volcanic south-eastern flank about 1.2 km. After the eruption in 1980, lava flow moved up to 1.5 km.

All explosive eruptions of the volcano were accompanied by the formation of pyroclastic flows and surges. The largest flow with length of 12.5 km was formed in 1985. Most widespread of pyroclastic surges were by eruptions in 1985, 1997, 2000, 2005, 2010. The volume of pyroclastic flow deposits for 45 years was about 0.4 km³.

All explosive eruptions of the volcano were dangerous for international and local aviation but volcanological experience and daily complex analysis the remote sensing data (seismic, video, satellite) of the volcanic activity since 2002 allowed scientists of Kamchatkan Volcanic Eruption Response Team (IVS FED RAS) predict many eruptions of Bezymianny and increasing aviation safety at Kamchatka.

キーワード: Bezymianny, explosive, eruption, pyroclastic, danger, aviation

Keywords: Bezymianny, explosive, eruption, pyroclastic, danger, aviation