

## Similarities in relief structure and landforms between Yakushima Island in Japan and Dartmoor in southwest England

SHIMAZU, Hiroshi<sup>1\*</sup>

<sup>1</sup>Rissho University

Relief structure and landforms was examined in two granitic mountains, Yakushima Island in south Japan and Dartmoor in southwest England. This study aims to compare these geomorphological characteristics between two mountains which have different geomorphological and geological settings.

Yakushima Island mainly consists of the Yakushima Granite dated at about 16Ma, which intruded into the Kumage formations of the Palaeogene. The highest peak is 1936 meters a.s.l. The area of the island is about 500 sq. kilometers. Dartmoor is underlain by a major batholith dated at 280 Ma which intruded into the sedimentary rocks of the Devonian and the Carboniferous. The area of Dartmoor is about 1000 sq. kilometers. The highest peak is 621meters a.s.l. Yakushima Island has been uplifted since the middle Pleistocene with high rate, whereas Dartmoor is in the tectonically stable environment.

In this study digital terrain model was used for analysis of the relief structure. The standard deviation of altitude in a 1 sq. kilometer unit is used for expressing relief. Each unit square includes 25 lattice points of a grid system with intervals of 250 meters. It is obtained from 1:50,000 scale topographic maps in Yakushima Island area and from a 50m-DTM made by Ordnance Survey Britain (OS) in Dartmoor area.

Although mean altitude and mean relief in Yakushima Island are higher than that in Dartmoor, shape of cross sections and pattern of altitudinal change in relief within each area is quite similar. The both mountains have a circle-like planform and a domelike profile. Relief increases with altitude in lower part of the both mountains. In the higher altitude area which is located in the central part of the two mountains relief decreases with altitude. This shows that relief structure of the both areas is characterized by the higher relief rims and the lower relief central parts. The cross sections of the dissected rivers show that the valleys with steep side slopes are found near the rims of the mountains and shallow valleys with gentle side slopes are found in the central part of the mountains. Although altitude, relief and inclination of slope are quite different between the two mountains, several similarities are found in relief structure and landforms, which could characterize the granitic mountains.

Keywords: granitic mountains, relief structure, landform, Yakushima Island, Dartmoor

## Development of faro topography in the Indian Ocean atoll

KAN, Hironobu<sup>1\*</sup>, YOKOYAMA, Yusuke<sup>2</sup>, SUZUKI, Atsushi<sup>3</sup>, Yosuke NAKASHIMA<sup>4</sup>, Mahmood RIYAZ<sup>5</sup>

<sup>1</sup>Okayama Univ., <sup>2</sup>Univ. Tokyo, AORI, <sup>3</sup>Geological Survey of Japan, AIST, <sup>4</sup>Ariake National College of Technology, <sup>5</sup>Asian Institute of Technology, Thailand

Faro (little ring-shaped reef, miniature atoll) is a circular reef, usually less than 3 or 4 km in diameter surrounding a shallow secondary lagoon of depths generally less than 20 m which is a characteristic feature in Maldivian coral reef. Because faros rise from the lagoon floor and edges of atolls, their mode of formation must differ from oceanic atolls whose foundations extend to great ocean depths (McLean 2011). However, there has been no substantive study of faros in Maldives.

Holocene reef structure and formation process are observed through an ocean-lagoon transect across the atoll-rim by observations of drilling cores and submarine exposure of reef interior at North Male Atoll, Maldives. We found a distinct faro formation during the Holocene reef development in Male Island which is the first report for substantive study on faro development.

The drilling penetrated 53.5m is conducted at the southeastern part of Male Island where former reef-crest lies under the present reclaimed land. Five reef units are defined from lithofacies of the core. In each reef unit, coral-algal bindstone accumulated on the top of loose reef sediments. The top unit is the post-glacial reef. The other four units are the Pleistocene reefs. The thickness of the post-glacial reef is around 8m where the coral-algal bindstone forms the uppermost 3.3m.

The post-glacial reef structure is also observed at a lagoon slope of the northeastern Male Reef from an exposure of reef interior down to 25m deep where a reef failure happened. The exposure composed of the post-glacial reef. The rigid reef structure is observed at the upper 2m of the lagoon-slope. The antecedent atoll-rim topography of the post-glacial reef is shallower at the rim and deeper beside the lagoon in the North Male Atoll.

AMS datings of the coral/algal samples show the development of the atoll-rim reef after 8,000 cal yBP. The upward reef growth in the early to middle Holocene is the same pace with the sea-level rise at the seaward edge and lagoon-ward edge which reached to the sea-level in the middle Holocene. The typical faro topography formed in this stage. The additional upward reef growth observed from drilling core at the seaward edge indicates the middle Holocene sea-level highstand in Maldives. Faro lagoon is buried by loose reef sediments after the middle Holocene.

Keywords: atoll, faro reef, coral reef, drilling core, Holocene, Maldives

## Natural levees and human settlement in the Song Hong (Red River) delta, Northern Vietnam

FUNABIKI, Ayako<sup>1\*</sup>, SAITO, Yoshiki<sup>2</sup>, VU Van Phai<sup>3</sup>, NGUYEN Hieu<sup>3</sup>, HARUYAMA, Shigeko<sup>4</sup>

<sup>1</sup>College of Humanities and Sciences, Nihon University, <sup>2</sup>Geological Survey of Japan, AIST, <sup>3</sup>Hanoi University of Science, Vietnam National University, <sup>4</sup>Mie University, Graduate School of Bio resources

The Song Hong (Red River) delta, northern Vietnam, is characterized by huge natural levees in an area of the delta plain known as the West Floodplain where fluvial sedimentation predominates. The natural levees along the Day River, a major distributary of the Song Hong, are larger than those of the main course of the Song Hong. The Day River levees are 3.8 km wide and rise 3.5 m above the adjacent backswamps and have played an important role in human settlements since the late Metal age. We reconstructed the Holocene evolution of the Day River levees to determine their relationship to Holocene sea-level change, delta progradation, and the distribution of archaeological sites on the delta plain. During the early Holocene, the accumulation of sediment discharged by the Song Hong enhanced both aggradation of the levees and river mouth progradation within the drowned valley of the Song Hong. Radiocarbon dates from cores, trench exposures, and archaeological sites record a dramatic slowing of aggradation when sea level stabilized during 6.4 cal kyr BP (the Holocene sea-level highstand). As sea level fell to the present level during 4.0 cal kyr BP, the river mouth prograded rapidly toward the Gulf of Bac Bo (Gulf of Tonkin) and the river channels extended seaward. In the West Floodplain, lateral accretion overtook vertical accretion to generate the present longitudinal profiles of the Song Hong and Day rivers. During this period, human settlements spread across the backswamp and Holocene terrace area, lagging around 2 kyr behind the shoreline migration.

Keywords: accumulation rate, archaeological sites, delta, natural levees, sea-level change

## HOLOCENE ENVIRONMENTAL CHANGES IN KHUDER PEATLAND, NORTHERN MONGOLIA

KASHIMA, Kaoru<sup>1\*</sup>, FUKUMOTO, Yu<sup>1</sup>, ORKHONSELENGE, A.<sup>2</sup>, Ulgiichimeg Ganzorig<sup>2</sup>

<sup>1</sup>Faculty of Sciences, Kyushu University, <sup>2</sup>Institute of Geography, Mongolian Academy of Sciences

Holocene paleoenvironment in Khuder peat bog, the northern Mongolia was reconstructed by diatom and pollen analyses on peat boring samples. Diatom records of two boring cores showed a general chronology of peat land development from stream environments, marsh and then to the present acidic peat bog established as early as in the mid Holocene. Pollen and diatom records revealed Mid-Holocene drought from 6,000 to 3,000 cal yr BP and its periodic extent was correlative with other studies in Mongolia and the southern Siberia.

Abrupt changes of water environment and vegetation observed are associated with global climatic changes such as the Bond events occurred in North Atlantic Ocean. Cooler period of Little Ice Age and the warmer period of Medieval Warm Period were also remarkably manifested respectively as dry and wetter spells implying a strong connection of climate changes around the Northern hemisphere. However, climate changes contradictive with the results of other studies were also often observed, so the geographical features, pedology and orography should be the key control factors for the moisture balance of the area. We inferred that the observed climatic changes would be reflecting displacement of continental dry region as the study area is located in the transitional vegetation zones between Siberian taiga and Mongolian arid steppe.

Keywords: Northern Mongolia, Holocene, Climate change, Peat sediment

## Disastrous flood events found in lacustrine sediments around Lake Biwa

ITONO, Taeko<sup>1\*</sup>, WAKASA Madoka<sup>1</sup>, KASHIWAYA, Kenji<sup>1</sup>

<sup>1</sup>Kanazawa University

Lacustrine sediments have high-resolution regional environmental records on lake and its surrounding catchments in addition to global information. Therefore they are of great use for reconstructing past hydro-environmental fluctuations and understanding lake-catchment processes. Lake-catchment systems with many instrumental stations are of great use for past environmental reconstruction in detail and process-understanding of the systems (e.g. Lake Biwa).

Here we discuss about hydro-environmental fluctuation in the instrumental observation period on the basis of physical properties of sediments. Some sediment core samples were obtained with 1-m sampler in Lake Biwa and Lake Yogo, central Japan.

Analytical results for the core sediments, obtained in Lake Biwa, show that disastrous flood events, Isewan Typhoon (1959) and Meiji heavy rainfall (1896), are clearly recorded in physical properties of sediments; density and mineral content are good proxies of rainfall intensity (100mm excess rainfall); and grain size distribution in lakes may be a function of rainfall intensity in the catchment and transporting distance from the river mouth. Additionally, we compare results of physical properties of sediments in Lake Biwa with those in Lake Yogo during the flood events in detail.

Keywords: flood event, lacustrine sediment, lake-catchment process

## Impact of volcanic activity on Late Holocene sedimentation pattern of a river-lake system in Hokkaido

PARKNER, Thomas<sup>1\*</sup>, Seji Yanai<sup>2</sup>

<sup>1</sup>Graduate School of Life and Environmental Sciences, University of Tsukuba, <sup>2</sup>Ishikawa University

Sediment production and sediment transfer through fluvial systems into oceans is very high on the Japanese Islands compared to other regions of the world, as most rivers in Japan are relatively short, show high gradients and are disturbed by human activity. In this study we reconstruct the sedimentation history of the floodplain of Bibi River and Lake Utonai to analyse the impact of volcanic activity on this river-lake system located in Southern Hokkaido. Bibi River is 17 km long and its catchment of 88 km<sup>2</sup> consists of the Eastern slopes of the active volcanic complex Shikotsu-Tarumae. The flat, 4.1 km<sup>2</sup>-large floodplain formed 3000 years ago after the regression of the Pacific Ocean. Bibi River drains into the North-Eastern section of Lake Utonai, which has a total area of 2.3km<sup>2</sup> with a maximum depth of 1m. During the last 3,000 years the catchment has been continually used for agriculture and was systematically developed since the beginning of the last century.

To analyze the volcanic impact 6 cores on the floodplain and 7 cores in the lake were taken. To distinguish between air-fall sediment and fluvially transported sediment the cores were sliced into 3cm or 5cm thick samples. For the 620 samples the parameters dry density and ignition loss mean grain size, sorting, skewness and kurtosis were determined.

Three air-fall deposits were identified as Ta-a (1736 A.D.), Ta-b (1667 A.D.), and Ta-c (3000 yBP) which each deposited 1.4 Mio t to 1.8 Mio t sediment on the floodplain and in the lake. Layer thickness on the floodplain depended on eruption direction. For the lake deposits, lake currents seem to focus of the air-fall tephra during flotation. About 0.6 Mio t of fluvial sediment was deposited on the floodplain during the last 3,000 years. During the period 1667 A.D. - 3,000 yBP an average of 0.070t/ha/y were deposited with an increasing sedimentation rates downstream. During 1736 A.D. and 1667 A.D. an average of 1.5t/ha/y accumulated on the floodplain with highest rates in the middle reach. Sedimentation rates decreased to 0.69t/ha/y during the recent period (2006 A.D. - 1736 A.D.), but showed very high values near road construction sites of the last century. Lake deposition reached 0.05t/ha/y (present - 1736 A.D.), 0.47t/ha/y (1736 A.D. to 1667 A.D) and 0.04t/ha/y (1667 A.D. to 3,000 yBP) with highest sedimentation rates in the northern section due to sediment focusing.

Results suggest that the sediment stored on the floodplain and in the lake is dominated by air-fall tephra (4.6 Mio t out of 5.2 Mio t). Even though the catchment was disturbed by human activity only very little fluvial sediment was deposited on the floodplain or in the lake after the Ta-a eruption. This indicates that mid-Holocene coastal plains can significantly reduce sediment transfer through fluvial systems into oceans by buffering sediment on floodplains and lakes. This finding might not only apply to the study area, but also to other volcanically disturbed catchments with mid-Holocene coastal plains. In such systems the impact of volcanic activity may dominate over human and climate impact.

Keywords: volcanic impact, river, lake, Late Holocene

## Leachability of heavy metals and arsenic in soils due to contamination of disposal cement building materials

KITAGUCHI, Ryuta<sup>1</sup>, HACHINOHE, Shoichi<sup>2</sup>, OGUCHI, Chiaki T.<sup>3\*</sup>

<sup>1</sup>Dept. Civil & Env. Eng., Saitama Univ., <sup>2</sup>CESS, <sup>3</sup>GRIS, Saitama Univ.

Today, concrete is used in everywhere. These concrete structures get moved away when they end their roles, a very small amount of concrete is left and the soil pH rises. Some geological layers inherently contain substantial amounts of heavy metals and previous studies show us that heavy metals in natural sediments sometimes cause soil pollution. Thus, the heavy metals tend to be leached out from these sediments according to the difference of pH conditions. This study focuses to find out the interrelation between the amount of heavy metals and pH differences. The leaching test is carried out using soil and mortar samples with several mixture proportion. The liquid and solid proportion is 1:10. After 6h shaking, the soil water samples were extracted and pH and EC were measured. Then, heavy metal contents were measured using ICP-MS and ICP-AES. Results are as follows; most of heavy metals (Al Fe Mn Se and As) are leached out and the contents are higher in higher pH and lower pH. Therefore, it will be necessary to measure the soil pH condition when concrete and cement materials were used in the structure.

Keywords: leaching, heavy metals, arsenic, soil, cement

## Experimental study of rock strengthening tuff, limestone, and andesite by using nanolime and other consolidants

SONG, Wonsuh<sup>1\*</sup>, MORGOS, Andras<sup>2</sup>

<sup>1</sup>Terrestrial Environment Research Center, University of Tsukuba, <sup>2</sup>Graduate school of Conservation, Tokyo University of the Arts

This study is focussing to the efficiency and evaluation of up-to-date consolidants (a non-aqueous colloidal nanolime ( $\text{Ca}(\text{OH})_2$ ) suspension, a well-known oligomeric tetraethoxysilane product (Wacker SILRESR BS OH 100), an extremely low viscous epoxy resin (Araldite 2020) and for cultural heritage the most frequently used thermoplastic acrylic resin (Paraloid<sup>TM</sup> B-72 or also called Acryloid<sup>TM</sup> B-72) which is known from its good durability, high transparency and non-yellowing film-properties for the consolidation of Oya-tuff. The consolidation effect of nanolime particles were also studied on Ryukyu-limestone and Indonesian basaltic andesite.

The actuality of this study is given by the fact, that degradation (corrosion) of the rocks is incredible speeded up in the last decades by the increased air-pollution e.g. acid rain etc. This makes the stone buildings, objects and sites much more vulnerable. The stone material weakens and loses its original binder to a considerable depth. Consecutively many stone historical constructions require consolidation, conservation and restoration in recent days.

The consolidants were tested by the measurement of tensile strength, Equotip surface hardness, p-wave velocity.

Keywords: Rock strengthening, nanolime, resin, tuff, limestone, andesite



## Difference in surface-stone dislocation by ground cover on wind-beaten slopes in temperate low mountains in winter

SETO, Masayuki<sup>1\*</sup>, TAMURA, Toshikazu<sup>2</sup>

<sup>1</sup>Geosphere research institute of Saitama University, <sup>2</sup>Rissho University

Hillslopes below the tree line, which is usually protected from frost action with vegetation cover, are subjected to seasonal periglacial mass-movements when vegetation is removed by, e.g., strong wind and/or human activity. Among various factors which may control the occurrence of such azonal periglacial processes on wind-beaten slopes in temperate low mountains, we took notice of ground-surface condition.

There is wind-beaten bare ground near the Goreibitsu pass in northeastern Japan forest zone (c. 900m a.s.l., 37.5N). While mean annual air temperature is 7.3 degree, air temperature in winter reaches about -10 degree on the bare ground. This bare ground is composed of four layers/horizons; I: Angular flat stones with no matrix; IIA: Very dark brown humic clay loam (Sand 8.9%, Silt 78.5%, Clay 12.5%) with few angular stones; IIAB: Dark brown clay-loam to loam (Sand 1.1%, Silt 79.3%, Clay 19.6%) with common angular stones; IIC: Dull brown to dull orange brown loam (Sand 9.7%, Silt 76.2%, Clay 14.0%) with many angular stones. IIA remains only under vegetation around the bare ground.

We observed air temperature, ground surface temperature, ground temperature and dislocation of surface stones (Layer I) in four winter seasons from 2006-07 to 2009-10. Dislocation of surface stones was observed by changes of the nine painted lines. Length and dominant angle of these lines are 8.3-25.3m and 6-20 degrees respectively.

Ground-surface condition is divided into the following two types: one is the C type, which is covered with thick Layer I, and the other is the F type, where small stones scattered on almost exposed IIAB. We applied the division to the record of surface-stone dislocation in 2007-08 winter.

Records of ground temperature show that freezing and thawing repeated only in the upper part of IIAB horizon at several, not all, points. Mean values of stone dislocation in a winter on C type and F type ground surface were 0.35m and 0.52m, respectively. It is obvious that a bigger dislocation occurred on F type ground surface than on C type one.

The difference is considered the consequence of more intense and frequent occurrence of freezing and thawing on F type ground surface where IIAB almost exposes than on C type one where IIAB is continuously overlain with stones (Layer I). On both types of ground, freezing and thawing which are the major driving force of surface stone dislocation occur in the upper part of IIAB. Differential occurrence of surface stone movement is thus considered the results of differential response of fine earth layer with or without stony cover to freezing temperature. It seems one of the characteristics of periglacial mass-movements on slopes in temperate low mountains.

Keywords: Solifluction, Surface materials, Low altitude mountain slopes

## Terrestrial laser scanning of cliff face at Kegon Falls

HAYAKAWA, Yuichi S.<sup>1\*</sup>

<sup>1</sup>Center for Spatial Information Science

Mechanisms of bedrock erosion at waterfalls have been studied so far for several cases, but there remain some uncertainties in erosional processes with regard to detailed form of rocks composing a waterfall. In this study, detailed form of cliffs around Kegon Falls in Nikko, Japan is examined using a terrestrial laser scanner (TLS). Kegon Falls has a total height of 97 m, with a vertical drop of surface water and outflows of underground water at the lower portion of the cliff. The form of cliffs around the waterfall was measured using a TLS (Topcon GLS-1500) from an observatory facing the waterfall, and the obtained point cloud was georeferenced using a GNSS-based position coordinates of measurement targets. The point cloud was then rotated in order to create a digital elevation model (DEM) on a vertical plane. Longitudinal and transverse profiles were then extracted from the vertical DEM. The stability of the collapsed portion in the cliff indicates that the collapse in 1986 could have likely occurred with crack propagation along joints within the former cliff. The stability analysis also suggests that catastrophic collapse of whole of the waterfall face seems to hardly occur, because the igneous rock composing the cliff is strong enough to keep its current overhanging shape. Actually smaller-scale collapses of the cliff face have occurred in recent years. Whereas, frequent occurrence of freeze-thaw weathering seems to be responsible for the formation of a depression at the bottom of the upper cliff of lava. The load and tractive force by surface water flow (up to 100 t/s when flooding) may support faster removal of rock blocks behind the water drop. Multiple processes are thus responsible for the erosion of the cliff face of Kegon Falls.

Keywords: waterfall, erosion, bedrock, cliff, terrestrial laser scanning

## Geomorphic Evidence of Uplifting Associated with Old Kanto Earthquakes Before 1703 in a Coast of Miura Peninsula, Japan

KIM, Haeng Yoong<sup>1\*</sup>, KUMAKI, Yohta<sup>2</sup>, SATAKE, Kenji<sup>1</sup>

<sup>1</sup>ERI, Univ. Tokyo, <sup>2</sup>Geography, Senshu Univ.

The 1923 Kanto earthquake (M7.9) and the 1703 Kanto earthquake (M $\sim$ 8.2) were two of recent great earthquakes generated by the slip on the boundary between the subducting Philippine Sea plate and the overlying plate. These earthquakes devastated the southern Kanto area, resulting in more than 105,000 deaths mainly in Tokyo in 1923 and in more than 10,000 deaths in 1703, respectively.

In 1923, the amount of the coseismic uplift was measured as  $\sim$ 1.5 m in the southern part of the Miura and Boso peninsulas. On the other hand, in 1703, the amount of the coseismic uplift was measured as  $\sim$ 1.5 m in Miura and 4-5 m in Boso, respectively, from the emerged wave-cut-bench and -notch, and the fossil remains along the coast [eg., Matsuda et al. (1978), Shishikura et al. (2007)].

In Miura Peninsula, in addition, three additional steps of marine terrace surface are formed at 7 to 20 m above MSL, at  $\sim$ 5200,  $\sim$ 3300 and  $\sim$ 1500 cal. BC, and these are called Nobi 1, 2 and 3 in order from top [Kumaki, 1985; 14C Age was calibrated]. These terraces are inferred to have been formed with coseismic uplift. In addition, two or three additional steps of marine terrace surface are identified in the levels between the Nobi 3 and 1703 emerged coast at the Bishamon Bay in the southern tip of the Peninsula [Geographic Department of Geographical Survey Institute, 1981]. However, the formation date is very poorly taken. Recently, at the head of Koajiro bay in southwestern Miura, tsunami deposits associated with pre-1703 earthquake was dated between 1060 and 1400 cal. AD [Shimazaki et al. (2011)]. However, the amount of uplift is not studied.

We need to know the amount of the vertical crustal movement and the occurrence date for the Kanto earthquake prior to 1703, for better understanding the earthquake cycle, and thus to estimate the average recurrence time and the magnitude of earthquake for estimating the future earthquake hazard. So we sought the trace of the crustal movement along the coastal region in the southwestern Miura Peninsula. To identify the uplifts associated with recent great Kanto earthquakes, we made a high-density (50 cm mesh) digital elevations map by aerial measurements of the Light Detection and Ranging (LiDAR) in southwestern coast of the Peninsula. In addition, we analyzed air photos taken in 1946, 1963 and 1966.

As a result, five to six steps of marine terrace surface were observed between the Nobi 3 surface and the present coastline, including the 1923 and 1703 emerged terrace surfaces, in the alluvial valley. These terrace surfaces are edged in a small cliff of the height of 1-2 m. In addition, LiDAR data indicate flights of wave-cut-bench on rocky coast (8 m above MSL) in Jogashima, southernmost tip of Miura. These marine terrace surfaces may indicate additional evidence of the uplift associated with the Kanto earthquakes.

Compared the 1:25,000 of old topographic map made in 1921 by Land Survey Department and in 1966 by Geography Survey Institute, the regradation of the coastline is identified in the coast area of Miura. The coastline was shifted from the land side to the sea side, thus the zone between 1921 and 1966 coastlines was dried from the sea to the land. At the bay head of Koajiro, the sea was dried up approx. 300 m in the length. The lowest level of terrace surface which was identified from LiDAR Data and old topographic map have been formed by 1923.

Keywords: Pre-1703 Kanto Earthquake, Recurrence time, Amount of Uplift, Marine terrace surface, Coastline

## Study in salt weathering of reconstituted stones used in the Orval Abbey, Belgium

NGUYEN, Thi Hai Duong<sup>1\*</sup>, FUJIMAKI, Toshiaki<sup>2</sup>, OGUCHI, Chiaki T.<sup>3</sup>

<sup>1</sup>Dept. Civil & Env. Eng., Saitama Univ., <sup>2</sup>Graduate School of Sci. & Eng., Saitama Univ., <sup>3</sup>GRIS, Saitama Univ.

The Orval Abbey, a major monument of southern Wallonia, Belgium, was partly destroyed and rebuilt several times between the Middle Ages and the present time. The oldest parts are made of natural stones of Bajocian limestones (BJ) and Sinemurian limestones (SN), and the most recent parts are mostly made of reconstituted stones. The making process of reconstituted stones is not known. According to the previous studies, the reconstituted stones are much more susceptible to weathering than the natural limestones. To investigate the reason behind the salt susceptibility of the reconstituted stones, field works and laboratory investigations such as Mercury Intrusion Porosimetry, Scanning Electron Microscopy coupled with Electron Dispersive Spectroscopy, Ion Chromatography, X-Ray Diffractometry were carried out. Results of the investigations revealed that sulfur and sodium, which were the main source of the formation of the damaging sodium sulfate, have been detected in mortars, the soil water and river water, and the reconstituted stones themselves. Results of field works indicated that the temperature and humidity conditions of Site 3, where reconstituted stones were mainly used, fluctuated drastically compared with those of other sites. This condition favors the cyclic transformation of thenardite to mirabilite, which is known as the main damaging mechanism of sodium sulfate. Moreover, MIP analysis unveiled the fact that the pore size distribution of the reconstituted stones favored the salt damage, i.e. it consisted of large fraction of microporosity. The calculated salt susceptibility indices of reconstituted stones were also very high compared to those of natural limestones.

Keywords: weathering, sodium sulphate, thenardite, Oval Abbey, reconstituted stone

## Influence of environmental conditions and test method on sodium sulfate weathering of four Japanese building stones

SWE, Yu<sup>1\*</sup>, OGUCHI, Chiaki T.<sup>1</sup>

<sup>1</sup>Geosphere Research Institute of Saitama University, <sup>2</sup>Geosphere Research Institute of Saitama University

Many standard and laboratory salt weathering tests have been elaborated to investigate the mechanisms of salt damage, which have threatened our priceless cultural heritage made of porous stones. The tests are also used to investigate the relative destructiveness of salts, and durability of different rocks for selecting proper ones for restoration works. Some results of these studies, however, have become debatable due to employing different test methods and environmental conditions. So far, comparative studies about test conditions are scarce. In addition, there are arguments about sodium sulfate, which is the most widely used salt in laboratory tests, as to which phase of the salt, i.e. thenardite or mirabilite, is responsible for the sodium sulfate damage. To solve these arguments, a series of laboratory experiments was performed by using two types of salt supply techniques: continuous partial immersion (CPI) and cyclic total immersion (CTI). Both tests were conducted under three different environmental conditions: (i) 20°C and 60% RH for 24 h (CPI 1); (ii) 45°C and 40% RH for 24 h (CPI 2); (iii) 45°C and 30% RH for 12 h and 10°C and 70% RH for 12 h (CPI 3); (iv) 3 h immersion at 20°C, 19 h drying at 45°C, and 2 h cooling at 20°C (CTI 1); (v) 3 h immersion and 21 h drying at 45°C (CTI 2); and (vi) 3 h immersion at 20°C, 17 h drying at 105°C, and 4 h cooling at 20°C. CPI 2 and CTI 2 tests were designed to investigate the destructiveness of sheer thenardite. All tests were run for fifty 24-h cycles. Prismatic specimens (5 x 5 x 15 cm<sup>3</sup>) of four types of Japanese building stones, namely Oya Tuff, Ashino Tuff, Indian Sandstone, and Tago Sandstone were used. A range of hydromechanical properties were investigated. For salt supply, saturated sodium sulfate solution (at 20°C) was used in all tests. It is observed that durability ranking of the rocks did not perfectly reflect their hydromechanical properties. Oya Tuff was consistently the least salt resistance in all of the tests, mirroring its properties. However, in contrary to their hydromechanical properties, Tago Sandstone, Ashino Tuff, and Indian Sandstone showed different durability against sodium sulfate in different tests, indicating the unreliability of rock properties in predicting salt susceptibility. Differing to what have been perceived, at the same upper-limit temperature, CPI tests were found generally more destructive than CTI tests, except for the extraordinarily aggressive CTI 3 test driven by a very high drying temperature. The results of CPI 2 and CTI 2 tests revealed that thenardite alone could cause significant damage, although the induced damage was smaller than that of mirabilite-involved tests such as CTI 1, CTI 3, and CPI 3. This suggests that in addition to the immense power of mirabilite attack, the contribution of thenardite in rock decay during drying cannot be discounted in CTI tests. In fact, it was the cyclic conversion of thenardite-mirabilite mechanism, which causes severe damage, no matter what salt supply technique is employed. Moreover, the two salt supply techniques produced markedly different damage patterns: CTI tests induced granular disintegration, spalling, fragmentation, or crumbling, whereas CPI tests mainly produced scaling, cracking, or efflorescing depending on environmental conditions and rock properties. The reason behind this is the continuous accumulation of salts deep inside the CPI-specimens, which produced severe internal cracking and thick scaling, in contrast to the cyclic disintegration of outermost surfaces of CTI-specimens, which did not favor the salt accumulation.

Keywords: salt weathering, continuous partial immersion, cyclic total immersion, thenardite, mirabilite

## Mineralogical characterization of a stone by using colorimetry

NAKAYAMA, Taishi<sup>1\*</sup>, OGUCHI, Chiaki T.<sup>2</sup>

<sup>1</sup>GRIS, <sup>2</sup>GRIS,Saitama Univ.

In this study, the possibility of the exploitation of visible-reflectance spectrum as the technique to non-destructively specify the mineral species in situ was investigated. Color measurement of various samples was performed using colorimetry. Samples employed were reagents and standard samples, such as a argillite i.e., quartz, common feldspar, sodium feldspar, white mica, calcite, hematite, magnetite, limonite, a sulfide of iron, calcium sulfate, kaolinite, bauxite, calcium carbonate, sodium sulfate, red iron ore, limonite, aluminum sulfate, sodium chloride, sodium hydrogen sulfate, and potassium alum. In addition, salts and moss adhesive rock samples extracted from the Orval Abbey of Belgium, and salts collected from the Yoshimi-hyakua were also measured. In order to examine the possibility of mineral specification by a color spectrum, it is necessary to (1) measure the color of a standard sample, (2) measure the color of the mineral extracted from the field, and (3) identify the mineral by more laboratory-based techniques, such as SEM-EDS and XRD. After the examination, it turned out that the spectrum of the sample extracted from the fields and the spectrum of a corresponding standard sample looked very similar. It is also observed that the color spectrum could better describe a very small quantity difference, rather than the  $L^*a^*b^*$  value. It is concluded that the identification or specification of a mineral using the visible-reflectance spectrum technique is possible. However, there still are many difficulties, such as construction of a database and examination of an error of measurement, to address in order to successfully employ this technique in field.

Keywords: mineral species, visible-reflectance spectrum, color measurement

## Dissolution rate of limestone at a doline in the Akiyoshidai karst plateau

Sanae Akiyama<sup>2</sup>, HATTANJI, Tsuyoshi<sup>1\*</sup>, MATSUSHI, Yuki<sup>3</sup>, Yukinori Matsukura<sup>4</sup>

<sup>1</sup>Faculty of Life and Environmental Sciences, University of Tsukuba, <sup>2</sup>Graduate School of Life and Environmental Sciences, University of Tsukuba, <sup>3</sup>Disaster Prevention Research Institute, Kyoto University, <sup>4</sup>University of Tsukuba

The spatial variation of limestone dissolution rates is significant for landform evolution of karst terrain including doline. Although many laboratory experiments and field observations have elucidated dissolution rate of limestone under specific conditions, but few studies estimated dissolution rates in situ around doline. This study aims to estimate the current rate of dissolution at a doline in the Akiyoshidai karst plateau in Yamaguchi Prefecture, combining the following two methods. One is electric resistivity survey and measurement of soil property, which reveal subsurface structure of the doline including the depth of the soil-rock interface and the spatial variations of soil moisture contents. The other is weathering experiments and hydrological observations, which reveal the relationship between limestone dissolution rates and the environmental factors including moisture contents, water chemistry, temperature, and CO<sub>2</sub> concentration.

Electrical resistivity imaging (ERI) survey reveals spatial variations of resistivity in soil or bedrock below slope and bottom of the doline. Comparing the result of the resistivity imaging with manual sounding using a cone penetrometer, resistivity value of 300 ohm m approximately corresponded to the soil-rock interface ranging from 1 m deep at upper doline slope to 10 m deep at bottom of doline. Low resistivity (50-100 ohm m) zones, which are equivalent to saturation zones, existed above the soil-rock interface even in drier seasons, indicating that soil is hydrologically saturated through the year immediately above the soil-rock interface.

In the field weathering experiment, limestone tablets (rock fragment of 3.5 cm in diameter and 1 cm thick) were buried in soil at 4 sites of the doline: S1 located at the upper slope; S3 located at the middle of slope; S5 located at the lower slope; S6 located at bottom of the doline. In these sites, soil moisture contents and ground temperature were monitored 10-min intervals, and manual measurement of concentration of CO<sub>2</sub> in the soil air and soil water sampling were carried out about every two months. The experiments and observation were conducted for total 768 days from 2009 to 2011.

The dissolution rates of tablet were 1.6-3.3%/y at S1 and S3, where soil moisture saturation sustained for a long time after precipitation. The smallest dissolution rate was 0.11-0.55%/y at S5, where the period of high soil moisture was short after precipitation. The result of regression analysis revealed that dissolution rate of tablets were strongly controlled by  $W_{97}$  ( $R^2=0.65$ ), which is defined as the proportion of the duration of saturation (degree of saturation >97%) to whole time of the experiment. Furthermore, combination of two variables,  $W_{97}$  and mean value of estimated CO<sub>2</sub> concentration show a stronger correlation with dissolution rate of tablets ( $R^2=0.74$ ), although  $W_{97}$  primary controls dissolution rate of limestone tablets.

For the case that the soil immediately above the soil-rock interface is saturated ( $W_{97}$  of 100%) throughout year, dissolution rate of limestone would be 3.90%/y, which corresponds to denudation rate of 137 mm/kyr. This rate is slightly faster than the long-term denudation rates inferred from cosmogenic <sup>36</sup>Cl concentrations at the same site. Low resistivity zones with high soil moisture also exist beneath some parts of the slope as well as the bottom of the doline, implying that such slopes have a fast dissolution rate equivalent to the bottom of doline.

Keywords: limestone, karst, doline, electric resistivity survey, dissolution rate

## Granulomeric and mineralogic investigation of liquefaction induced by the 2011 megaquake at the Watarase flood-retarding

SETO, Masayuki<sup>1\*</sup>, Takaaki Asai<sup>2</sup>, Toshiyuki Kitazawa<sup>2</sup>, OGUCHI, Chiaki T.<sup>1</sup>, TAMURA, Toshikazu<sup>2</sup>

<sup>1</sup>Geosphere Research Institute of Saitama University, <sup>2</sup>Rissho University

The 2011 Off Pacific Coast of Tohoku earthquake of Mw9, which recorded a seismic intensity of JMA scale 6 in central Kanto, induced liquefaction at the northwestern part of the Watarase flood-retarding basin in the central part of the Kanto basin. The area is located in a former pond into which floodwater of the Watarase river and a few tributaries flew frequently. We collected boiled sand and carried out boring investigation to loosely-deposited sand and mud alternation at four sites (sites A-D) to identify the layers which caused liquefaction. At site D, we had a 500cm deep core sample. We observed some layers; 0-30cm: artificial ground, 30-70cm: silt, 70-250cm: medium or fine sand, 250-400cm: clay, 400-500cm: medium sand. Ground water level was 200cm deep. Bowling sites A, B and C were almost similar to site D. Grading and mineral analyses carried out by liquefaction deposits and core samples. From the ground water level and grading and mineral analyses, we considered that liquefaction layer was the medium and fine sand of around 200cm deep. In comparison of granulometry and mineral composition of boiled sand with those of borehole-core samples below watertable, we identified the layers which were liquefied as follows: site A- medium and fine sand (134-157cm deep) and medium sand (187-232cm deep), site B-coarse or medium sand (160-195cm deep), site C- fine sand (193-255cm deep), site D-fine sand (210-245cm deep) and fine sand (399-422cm deep). All the liquefied sandy layers are correlated to the uppermost members of the Holocene deposits which were interpreted to have been formed during recent 2000years.

Keywords: The 2011 Off Pacific Coast of Tohoku earthquake, liquefaction, grading analysis, mineral analysis, central part of the Kanto basin, Watarase flood-retarding basin