(May 19-24 2013 at Makuhari, Chiba, Japan)

©2013. Japan Geoscience Union. All Rights Reserved.

SCG63-01

Room:104



Time:May 22 16:15-16:30

#### An interpretation of dehydration process in the subduction zone beneath Kyushu Island, Northwestern Japan

Shun Handa<sup>1</sup>, Maki Hata<sup>2</sup>, Dapeng Zhao<sup>3</sup>, Junichi Nakajima<sup>3</sup>, Masahiro Ichiki<sup>3\*</sup>, Kiyoshi Fuji-ta<sup>4</sup>

<sup>1</sup>Faculty of Agriculture, Saga University, <sup>2</sup>Graduate School of Science, Kyoto University, <sup>3</sup>Graduate School of Science, Tohoku University, <sup>4</sup>Center for Promotion International Exchange, Saga University

The Japan Island Arc has different subduction settings; the young Philippine Sea plate (10-50 Ma) subducts beneath Kyushu Island in the southewestern Japan with dipping angles of about 60 degrees, while the Pacific plate older than 100 Ma subducts beneath Tohoku district in the northeastern Japan with dipping angles of about 45 degrees. It has been considered that these different subduction settings cause different volcanic activities and dehydration processes between Kyushu and Tohoku districts (e.g. Iwamori, 2007; Ichiki et al., 2009). In this study, we compiled the electrical conductivity (Handa et al., 1992; Handa et al., 1999; Ichiki et al., 2000; Hata et al., 2012) and seismic wave velocity (Nakajima et al., 2007; Zhao et al., 2012) models beneath Kyushu Island, and interpreted that dehydration process from subducting slabs and fluid transport process were consistent with each other between Kyushu Island and Tohoku district. The interpretation is 1) fluids dehydrated from subducting slab are absorbed in peridotites at the bottom of the mantle wedge. The hydrous minerals are dragged into the deeper part and dehydrated in the deeper mantle beneath the backarc region. 2) The fluids dehydrated from the hydrous peridotite indicate Rayleigh-Taylor instability in the upwelling process. This results in the volcanic and non-volcanic areas along the volcanic front of Kyushu Island.

An obvious negative free-air and/or Bouguer gravity anomaly is observed in the forearc region of Kyushu Island (Kono and Furuse, 1989; Shichi, 1997; cf. Nakada et al., 2002). The Vp/Vs and electrical conductivity values at ca. 40 km depth beneath the forearc region show higher than 2.0 (Saiga et al., 2010) and 0.02 S/m (Ichiki et al., 2000), respectively. These suggest that serpentine diapir underlies beneath the forearc region of Kyushu Island. However, these features have not yet been observed beneath the forearc region of Tohoku district. More observations focusing on the forearc region are required in the Tohoku district.

Keywords: Electrical conductivity, Seismic wave velocity, Subduction zone, Dehydration, Backarc, Serpentine

(May 19-24 2013 at Makuhari, Chiba, Japan)

©2013. Japan Geoscience Union. All Rights Reserved.



SCG63-02

```
Room:104
```

### Slab-fluids: saline fluids in fore arc regions and supercritical fluids under volcanic arcs

Tatsuhiko Kawamoto<sup>1\*</sup>, yoshitaka kumagai<sup>1</sup>

<sup>1</sup>Inst Geotherm Sci, Grad School Sci, Kyoto Univ

Chemical features of slab-fluids are essential to understand the geo processes in subduction zones. We studied the amphibole and phlogopite bearing harzburgite xenolith collected from the Pinatubo 1991 eruption. The harzburgite has coarse olivine having many fluid inclusions. The fluid inclusions are composed of  $H_2O-CO_2$ -Cl fluids with 5.1 +/- 1 wt% NaCl.. The Pinatubo volcano is located at the volcanic front of the Luzon arc subducted by South China Sea plate. We suggest that such CO<sub>2</sub> bearing saline fluids are infiltrated in the forearc mantle. We also studied plagioclase lherzolite xenoliths collected from the Ichinomegata volcano, Notheast Japan arc. The xenoliths have orthopyroxene grains having many CO<sub>2</sub>-H<sub>2</sub>O-Cl-S fluid inclusions with 3.7 +/- 0.8 wt% NaCl. We suggest that such fluids can be formed through degassing of arc magmas. We estimate that slab-fluids to produce the arc magmas have 1.1 ? 1.4 wt% NaCl with assumption of Cl partitioning between basaltic magmas and aqueous fluids.

The origin of such saline fluids remains unanswered at this moment. If the slab-fluids are saline fluids, their percolation processes may differ from pure  $H_2O$  fluids. Pressure-temperature conditions of critical endpoints between magmas and fluids may be different from those in the pure  $H_2O$  systems. There still remains to be investigated to answer for those questions. The chemical analyses of fluid inclusions in mantle rocks and melt inclusions in volcanic rocks should be conducted in more localities with more elements. And high-pressure and high-temperature experiments using saline solutions should be conducted to understand the role of saline fluids in subduction-zone processes.

Keywords: subduction zone, magma, fluid inclusion, mantle wedge, dehydration, chlorine

(May 19-24 2013 at Makuhari, Chiba, Japan)

©2013. Japan Geoscience Union. All Rights Reserved.

SCG63-03

Room:104



Time:May 22 16:45-17:00

## The maximum depth of the hydrothermal-convection zone in the crust controlled by the precipitation of silica minerals

Hanae Saishu<sup>1\*</sup>, Atsushi Okamoto<sup>1</sup>, Noriyoshi Tsuchiya<sup>1</sup>

<sup>1</sup>Tohoku University

Precipitation of silica minerals ubiquitously occur in crustal environments. Quartz is the most stable phase of silica. Metastable silica polymorphs, such as amorphous silica, cristobalite, and chalcedony, also form in the surface and subsurface silica deposits. The dissolution-precipitation of silica minerals has a significant effect on both mechanical and hydrological properties of the Earth's crust. However, the structure of the crust has been studied mostly in geophysics, not in geochemistry.

Here we interpret the maximum depth of the hydrothermal-convection zone at Kakkonda geothermal field, Japan, on the dissolution-precipitation of silica minerals. The drilling of the well WD-1a at Kakkonda encountered the temperature exceeding the hydrostatic boiling-point curve, over 500 C at 3729 m depth (Doi et al., 1998). The boundary between the hydrothermal-convection zone and the heat-conduction zone was found at 3100 m depth because of the critical change of permeability.

First we calculated the quartz solubility along the P-T conditions of the WD-1a (Ikeuchi et al., 1998). The quartz solubility had the local minimum value at 3100 m depth which coincided with The boundary between the hydrothermal-convection zone and the heat-conduction zone, suggesting that quartz could precipitate from both upflow and downflow fluid at the boundary.

Next we conducted the hydrothermal flow-through experiments to investigate the temperature dependence of the precipitation of silica minerals. The P-T conditions for precipitation were from 170 to 430 C and 24 MPa. Any rock/mineral substrates were not used in the precipitation vessel. The initial solution was made by dissolution of granite at 350 C and 24 MPa. The Si concentration in the input solution, from 330 to 350 ppm, rapidly decreased to the quartz solubility at over 400 C. The experimental results indicated that quartz precipitation associated with nucleation occur dominantly at high temperature whereas it associated with quartz growth on quartz surfaces only occur at low temperature.

A large amount of quartz precipitate is expected to seal the fractures and to block the downflow fluid efficiently. The maximum depth of the hydrothermal-convection zone in the geothermal fields may reflect the significant precipitation of quartz at high temperature.

References) Doi, N., Kato, O., Ikeuchi, K., Komatsu, R., Miyazaki, S., Akaku, K., and Uchida, T., Geothermics, 27, 663-690, 1998.; Ikeuchi, K., Doi, N., Sakagawa, Y., Kamenosono, H., and Uchida, T., Geothermics, 27, 591?607, 1998.

Keywords: Silica minerals, Precipitation, Hydrothermal experiment, Geothermal field

(May 19-24 2013 at Makuhari, Chiba, Japan)

©2013. Japan Geoscience Union. All Rights Reserved.

SCG63-04

Room:104



Time:May 22 17:00-17:15

#### Clay mineral characteristics of the plate-boundary fault at the Japan Trench

Jun Kameda<sup>1\*</sup>, Kohtaro Ujiie<sup>2</sup>, Takehiro Hirose<sup>3</sup>, Matt Ikari<sup>4</sup>, Francesca Remitti<sup>5</sup>, Mayuko Shimizu<sup>1</sup>, Yohei Hamada<sup>3</sup>, Gaku Kimura<sup>1</sup>, Frederick Chester<sup>8</sup>, James Mori<sup>8</sup>, Nobu Eguchi<sup>3</sup>, Sean Toczko<sup>3</sup>, Exp 343 Scientists<sup>6</sup>

<sup>1</sup>The University of Tokyo, <sup>2</sup>Tsukuba University, <sup>3</sup>JAMSTEC, <sup>4</sup>University of Bremen, <sup>5</sup>Universita' di Modena e Reggio Emilia, <sup>6</sup>Texas A&M University, <sup>7</sup>Kyoto University, <sup>8</sup>Exp 343

The 2011 Tohoku-oki earthquake (Mw9.0) rupture propagated along the plate-boundary megathrust and caused a huge tsunami. One anomalous aspect of this earthquake is that the seismic slip broke through the up-dip limit of the seismogenic zone, with slip propagating as far as the trench axis. In order to elucidate the physical mechanisms responsible for such unexpected behavior of the shallow fault, the IODP Ex 343 The Japan Trench Fast Drilling Project (JFAST) was carried out one year after the earthquake. It succeeded in recovery of material from within the plate boundary shear zone. Our data illustrate how mineralogical properties vary through a depth-section including the plate boundary fault rock, and we discuss the mechanical significance.

At the drilling site (C0019E) where the largest fault slip (>50m) occurred, a plate boundary shear zone was identified around 820 mbsf. X-ray diffraction (XRD) analysis of clay-fraction samples reveals that relative abundance of smectite is markedly higher at the fault (74-94 wt.%) than in the surrounding host rocks. Bulk-XRD results indicate the absolute smectite abundance in the fault rock reaches more than 70 wt.%, suggesting (by correlation with previous experimental studies of smectitic clays) the shear zone material had low intrinsic friction coefficient.

Because it has such a high smectite content, the shear zone is also expected to be influenced by physico-chemical interactions between smectite and interstitial water. In particular, the swelling behavior of smectite will affect the in-situ mechanical state of the fault. We estimated osmotic swelling forces the shear zone rock could cause by applying the Gouy-Chapman theory of diffuse double layer states under the restricted swelling strain condition. Based on measurements of exchangeable cation content, cation exchange capacity and BET surface area for some bulk rock samples (including 2 fault rocks), the theoretical estimate suggests osmotic repulsive forces of the order of ~5MPa could act between the smectite particles within the fault. Thus, in addition to its contribution to a low friction coefficient, the swelling behavior of smectite might further reduce effective pressure (and therefore shear strength) of the plate-boundary fault, and help to promote localized slip on it.

Keywords: 2011 Tohoku-oki earthquake, JFAST, smectite

(May 19-24 2013 at Makuhari, Chiba, Japan)

©2013. Japan Geoscience Union. All Rights Reserved.



SCG63-05

Room:104

# Relationship of intra-plate earthquake and dehydrated fluid -Example of the analysis of serpentinite body in Mt.Shiraga-

Seiya Fukumura<sup>1\*</sup>, Kazuaki Okamoto<sup>2</sup>

<sup>1</sup>Department of Science Education, Saitama University, <sup>2</sup>Faculty of Education, Saitama University, <sup>3</sup>Graduate School, Tokyo Gakugei University

None

(May 19-24 2013 at Makuhari, Chiba, Japan)

©2013. Japan Geoscience Union. All Rights Reserved.

SCG63-06

Room:104



Time:May 23 09:00-09:30

### Influence of dehydration to Cl isotopic fractionations: implication for behavior of hydrophilic Cl during subduction

Masaaki Musashi1\*

<sup>1</sup>Department of Chemistry, Tokyo Metropolitan University

Chlorine, which is known as a hydrophilic element, has been used for elucidating mechanisms of the oceanic materials recycling during subduction (Philippot et al., 1998). Since Cl-bearing minerals sush as NaCl are highly dissociative in solution, chloride can be a sensitive proxy for fluid mobility in crustal and subduction-related environments (Barnes et al., 2008).

Chlorine isotopic ratio ( $d^{37}$ Cl/permil vs. SMOC, standard mean ocean chloride) varies in a range of +-10permil. The highly positive  $d^{37}$ Cl values were found in the MORB while the negative  $d^{37}$ Cl values were seen in subduction-zone pore fluids. Serpentinized ultramafic rocks from ODP sites showed negative  $d^{37}$ Cl, indicating that a result of hydration of the ultramafic rock by infiltrating<sup>35</sup>Cl-enriched pore fluids from the overlying sediments (Barnes and Sharp, 2006). The pore fluids having strongly negative  $d^{37}$ Cl values (Ransom et al., 1995) are also consistent with preferential retention or fixation of  $d^{37}$ Cl in silicates.

However, the mechanism of Cl isotopic fractionation between two phases occurring phase separation along dehydration and recrystallization at subduction related environments has not been described well. To elucidate an influence of water to the Cl isotope fractionation, we have conducted anion exchange chromatographic experiments. The results showed the heavier isotope,<sup>37</sup>Cl, enriched into liquid phase while the lighter,<sup>35</sup>Cl, enriched into anion-exchange resin phase (Musashi et al., 2007).

The trend of the heavier isotopic enrichment into liquid phase by the chromatography was agreeable to the theoretical and experimental studies on Li isotope effect: dehydration of the Li hydrate influenced on<sup>7</sup>Li enrichment into the liquid phase (Oi et al., 1991). Controversially, Schauble et al. (2003) theoretically estimated the lighter isotope, <sup>35</sup>Cl, enriched into liquid phase by the Cl isotope equilibrium of the anhydrates.

To understand the Cl isotopic fractionation factor (S) experimentally obtained, the reduced partition function ratios (named f value) of several Cl-hydrates were computed after geometrical structures of the Cl-hydrates were optimized by ab initio molecular orbital calculation. Remarkably, the Cl-hydrates were not optimized until hydration number being more than 100, although the number of the primary hydration sphere around a Cl- in aqueous solution was seven. This implied that the extremely dissociative Cl- was negatively hydrous and the hydration structure was unstable. The f value of the Cl-(H2O)n was calculated and 1000\*ln f(100) =1.658 (n=100) (Oi, private comm.). The S value is expressed by the theory of two phases'separation as follows:  $\ln S = \ln F(m) - \ln f(n)$  (Eq.1), where F(m) is a RPFR of Cl-(H2O)m adsorbing to resin with the hydration number of m, and f(n) is that of Cl-(H2O)n dissolved in solution with the number of n. Since the m becomes less than the n by dehydration, symmetry of the molecular structure of the former F(m) is less than that of the latter f(100). We speculate that F(m)<f(100), implying that<sup>37</sup>Cl preferably can be enriched into solution phase by dehydration effect.

When we summarize from the above-mentioned things, the thermo-dynamical stability of the primary hydration sphere around Cl- ion is an important factor controlling the tendency of Cl isotope fractionation between liquid and solid phases of geochemical interests. Assuming an anion exchange resin as oceanic sediment, we may say that<sup>35</sup>Cl preferentially enriches into the sediment phase while<sup>37</sup>Cl enriches into the subduction-zone pore fluid phase. However, only if Cl- incorporated into the solid phase such as oceanic sediment is stable thermo-dynamically, as F(m) > f(n) (Schauble et al., 2003), the <sup>37</sup>Cl may enrich into the sediment phase rather than the pore fluid phase. Similarly, in case of the ultimate dehydration such as recrystallization of NaCl from the saturated solution, the<sup>37</sup>Cl may enrich into crystal phase (Eggenkamp et al., 1995).

Keywords: chlorine isotope fractionation, hydrophilic, hydration structure, subduction-zone pore fluid, molecular orbital calculation, anion exchange equilibrium

(May 19-24 2013 at Makuhari, Chiba, Japan)

©2013. Japan Geoscience Union. All Rights Reserved.



Room:104



Time:May 23 09:30-09:45

#### A numerical simulation of brine-rock interaction

Yuika Morita<sup>1\*</sup>, Kenichi Hoshino<sup>2</sup>

<sup>1</sup>Dept. Earth and Planet. Sci., Hiroshima Univ., <sup>2</sup>Grad. Sch. Sci., Hiroshima Univ.

The thermodynamic database, SUPCRT92 (Johnson et al., 1992) has been widely used for analyses of water-rock interactions. However, since it gives thermodynamic data of solutes in pure water solvents, they cannot be applied to solutes in mixed solvents as common geological fluids.

According to Hoshino et al. (2009), the dielectric constant is a key parameter characterizing chemical properties of solvents. Within the framework of electrostatic approach to predict thermodynamic properties of aqueous fluids taken in SUPCRT92, a chemical potential of a certain solute can be divided to the structural non solvation and solvation terms (Akinfiev and Zotov, 1999). The latter is expressed by the Born equation with the Born parameter of the solute and the dielectric constant of the solvent. Hence, if we can estimate the dielectric constants of brines, we may calculate the chemical potentials of solutes in the brines from those in pure water solvents given by SUPCRT92. They also tried to estimate the constants of 1 molal NaCl solutions from quartz solubilities in brines measured in previous experiments. The estimated constants are higher than those of water below 400 C at 100 MPa and abruptly increase with decreasing temperatures at around 400 C. However, they estimated the constants from quite rough inter- and/or extrapolations of solubility data of experiments under various temperature and pressure conditions with different salinities.

Therefore, we carried out solubility measurements for the assemblage of quartz and wollastonite in 1 molal NaCl solutions at 400 and 300 C at 100 MPa by using Dr. HIP (internally heated pressure vessel) of the Institute for Study of the Earth's Interior, Okayama University. Small amounts of quartz and wollastonite crystals were sealed with 1 molal NaCl solutions in gold capsules. Each capsule was hung by Mo wire in the hot spot of a Mo furnace within the pressure vessel, and held for 91 and 64 hours at 300 and 400 C, respectively. At the end of the run, the hanging wire was broken with a surging current, thereby letting the capsule fall into the cold bottom of the vessel, resulting in quenching the capsule.

Since Si is dissolved in the brines mainly as SiO2(aq), while Ca is CaCl+ in the experimental conditions, the solubilities of the both minerals, i.e., concentrations of Si and Ca saturated with the minerals, are used for the consistency check of estimated dielectric constants and thermodynamic data for neutral and charged species.

The dielectric constants of the brines estimated from concentrations of Si, 15.83 for 400 C and 27.84 for 300 C, were, however, different from those estimated from Ca concentrations, 19.32 for 400 C and 34.38 for 300 C, probably due to analytical errors during concentration measurements. Another possibility is that the solutions continued to react with the minerals slightly after the ends of runs. Then, we estimated the quench temperatures where unique dielectric constants could be obtained for the both Si and Ca concentrations. The resultant temperatures are 385 C with the constant of 20.14 and 290 C with 34.51 for the 400 and 300 C runs, respectively. The constants are almost consistent with those estimated from Ca concentrations at 400 and 300 C. It should be emphasized that the born parameter of Ca2+ is about one order of magnitude larger than that of SiO2(aq), resulting in the larger effect of a difference in the dielectric constant on Ca concentrations than the effect on Si concentrations, and that a dilution rate of the solutions for concentration measurements of Si is 10 times larger than those from Si concentrations.

Results of numerical simulations of brine-rock interactions using the above estimated dielectric constants will be shown in the presentation.

Keywords: dielectric constant, H2O-NaCl solution, solubility, SUPCRT92, geological fluid

(May 19-24 2013 at Makuhari, Chiba, Japan)

©2013. Japan Geoscience Union. All Rights Reserved.

SCG63-08

Room:104



Time:May 23 09:45-10:00

### Coupling of serpentinization reactions and silica diffusion

Atsushi Okamoto<sup>1\*</sup>, Yuichi Ogasawara<sup>1</sup>, Oyanagi Ryosuke<sup>1</sup>, Noriyoshi Tsuchiya<sup>1</sup>

<sup>1</sup>Graduate School of Environmental Studies, Tohoku University

Silica activity is considered to be one of the key factors in controlling reaction paths and rates of serpentinization (e.g., Frost and Beard, 2007; Klein et al., 2009). There are many experimental studies on serpentinization during mantle peridotites and water interaction, focusing on extent of serpentinization, evolution of fluid chemistry and generation of hydrogen and hydrocarbons. However, all of these studies focused on bulk solid materials and solutions within the reaction vessel, and local changes of products and silica concentration gradient have not been clarified; therefore, the role of silica transport on progress of serpentinization is still unclear. In this study, we conducted hydrothermal experiments in the olivine (Ol)?orthopyroxene (Opx)?H2O system at 250 degreeC and at a vapor-saturated pressure of 3.98 MPa to explore the role of silica diffusion in aqueous fluids during serpentinization. Olivine (Fo91), orthopyroxene (En92), or their composite powders (with Ol/Opx/Ol zones) were set in tube-in-tube vessels, and solution chemistry and the extent of serpentinization were analyzed in detail.

In the Ol?H2O experiments, the product changed from serpentine + magnetite to serpentine + brucite + magnetite, accompanied by a Si-drop in the solutions, that is similar to the results of our previous observations (Okamoto et al., 2011). Serpentinization proceeded uniformly throughout the reaction tube, indicating that the supply of water was not the rate-determining process. In the Opx?H2O experiments, orthopyroxenes were dissolved along the cleavages, and a small amount of serpentine + talc was formed. The silica activity of the solutions in the Opx?H2O experiments was at the level coexisting serpentine + talc, that is 1?3 orders higher than in the Ol?H2O experiments.

In the Ol?Opx?H2O experiments, serpentinization proceeded in both the Ol and Opx zones, and white-colored reaction zone (2 mm thick) was developed at the boundary of the Ol and Opx zones. In the Opx zone, the extent of serpentinization was nearly constant, and mixture of serpentine + talc was formed. In the Ol zone, the total amount of H2O revealed by thermogravimetry and SEM observations was most extensive along the boundary between the Ol and Opx zones, and it decreased gradually away from the boundary. Based on the Mg/Si values of the products, the ratio of talc in the products (Mtalc/Mtalc+Msrp) is highest in the Opx zone, and decreased steeply in the boundary zone, and talc was absent away from the boundary. The silica concentration in the bulk solution is lower than the stability field of talc, indicating the high Si gradient within the cm scale reaction tube.

Serpentinization in the Ol?Opx?H2O experiments was modeled simply by coupled processes involving silica diffusion and three reactions: (1) a silica?consuming reaction after olivine, (2) a silica-releasing reaction after orthopyroxene and (3) talc-forming reaction after serpentine. We will discuss the kinetic model explain the reaction progress and evolution of solution chemistry, and the role of silica on the rate of serpentinization. Our experimental results represent an analogue of serpentinization in natural hydrothermal systems with a high porosity, and we suggest that the spatial variation of serpentine as a function of the distance from a source of silica could be a useful indicator of the relative magnitudes of reaction, mass transport, fluid flow as well as temperature during hydrothermal alteration of oceanic lithosphere.

Okamoto, A., Ogasawara, Y., Ogawa, Y., Tsuchiya N., 2011. Chemical Geol., 289, 245-255.

Frost, B.R., and Beard, J.S., 2007. J. Petrol, 48, 1351-1368.

Klein, F., Bach, W., Jons N., McCollom T., Moskowitz B., Berquo, T. 2009. Geochim. Cosmochim. Act., 73, 6868-6893.

Keywords: serpentinization, silica diffusion, rate-dermining process, olivine-orthopyroxene-H2O

(May 19-24 2013 at Makuhari, Chiba, Japan)

©2013. Japan Geoscience Union. All Rights Reserved.



Room:104



Time:May 23 10:00-10:15

### Influence of Si-metasomatism on slab-mantle interface rheology

Ken-ichi Hirauchi<sup>1\*</sup>, Sabine den Hartog<sup>2</sup>, Christopher Spiers<sup>2</sup>

<sup>1</sup>Graduate School of Human and Environmental Studies, Kyoto University, <sup>2</sup>Faculty of Geosciences, Utrecht University

Aqueous fluids liberated during dehydration of the subducting slab cause hydration of the overlying forearc mantle wedge, changing the mechanical properties of the slab-mantle interface. Antigorite, a high-temperature serpentine mineral, is expected to be the main hydrous mineral present in the forearc wedge, while slab-derived fluids are likely to contain significant amounts of dissolved silica, leading to Si-metasomatism and replacement of antigorite by talc. However, it remains unclear how the strength and internal structure of antigorite-rich rocks evolve in the presence of reacting silica-rich fluids.

To determine the effect of Si-metasomatism on the rheological properties of antigorite, we performed a series of frictional sliding experiments on 100% antigorite, 100% talc and antigorite (70%) plus quartz (30%) gouges under hydrothermal conditions, using a ring shear machine. The pure antigorite and talc gouges showed steady-state shearing at a friction coefficient of 0.63 and 0.21, respectively. In contrast, the antigorite/quartz (atg/qtz) gouges exhibited a peak friction coefficient of 0.40-0.62 followed by strain weakening towards a quasi-steady-state strength with the friction coefficient of 0.25-0.47. The degree of weakening of atg/qtz relative to pure antigorite increased with increasing temperature and decreasing sliding velocity. The weakening was mainly due to the development of through-going, talc-bearing boundary shears, which widened until the steady-state sliding was attained.

Our experiments indicate that in the lowermost part of the forearc wedge, where silica-saturated fluids infiltrate from the dehydrating slab, metasomatically produced talc slip surfaces or shear bands will form in the intensely sheared plate interface, causing a much larger weakening effect than expected for antigorite, even if the total amount of talc formed is minor (<10 vol%).

Keywords: antigorite, fluids, mantle wedge, metasomatism, subduction zone, talc

(May 19-24 2013 at Makuhari, Chiba, Japan)

©2013. Japan Geoscience Union. All Rights Reserved.

SCG63-10

Room:104



Time:May 23 10:15-10:30

### Geochemical variations in the Sangihe arc: Fluid and melt slab fluxes in response to slab temperature

Takeshi Hanyu<sup>1\*</sup>, James B. Gill<sup>2</sup>, Yoshiyuki Tatsumi<sup>3</sup>, Jun-Ichi Kimura<sup>1</sup>, Keiko Sato<sup>1</sup>, Chang Qing<sup>1</sup>, Ryoko Senda<sup>1</sup>, Takashi Miyazaki<sup>1</sup>, Yuka Hirahara<sup>1</sup>, Toshiro Takahashi<sup>1</sup>, Iskandar Zulkarnain<sup>4</sup>

<sup>1</sup>Japan Agency for Marine-Earth Science and Technology, <sup>2</sup>University of California at Santa Cruz, <sup>3</sup>Kobe University, <sup>4</sup>Indonesian Institute of Science

The Sangihe arc, northeastern Indonesia, is an oceanic arc situated in unique tectonic settings where the active arc-arc collision is ongoing in the northern arc sector. The compositional diversity of lavas from south to north in the arc should reflect influx from subducted slab in response to slab components and P-T conditions in the sub-arc mantle. To elucidate magma genesis and slab thermal structure in such a setting, we have obtained new geochemical data for lavas from the entire Sangihe arc. In the southern arc where is away from the collision zone, the across-arc geochemical variation demonstrates that slab component changes in character from low-temperature fluid, through high-temperature fluid, to partial melt from the volcanic front to the rear arc. The geochemical systematics, the estimated mass fraction of the slab component, and the inferred stability of accessory rutile, zircon, and phengite in the slab are all similar to other oceanic arcs, such as Izu arc, indicating that the thermal structure of the slab is not affected by impending collision. In contrast, volcanic front lavas from the dormant northern Sangihe arc are systematically more enriched in fluid-immobile elements than the southern volcanic front lavas. This may be related to advanced collision in the northern arc that could have slowed the subduction rate and heated the slab in the Pliocene followed by cessation of volcanic activity in the Quaternary.

Keywords: subduction zone, slab dehydration, slab melting, Sangihe arc, arc collision

(May 19-24 2013 at Makuhari, Chiba, Japan)

©2013. Japan Geoscience Union. All Rights Reserved.

SCG63-11

Room:104



Time:May 23 10:30-10:45

### Lateral variation of trace element of volcanic rocks from East Java, Sunda arc: estimation of slab fluid contributions

Esti Handini<sup>1\*</sup>, Toshiaki Hasenaka<sup>1</sup>, Haryo Edi Wibowo<sup>4</sup>, Tomoyuki Shibata<sup>2</sup>, Yasushi Mori<sup>3</sup>, Agung Harijoko<sup>4</sup>

<sup>1</sup>Graduate School of Science and Technology, Kumamoto University, <sup>2</sup>Beppu Geothermal Research Laboratory, Kyoto University, <sup>3</sup>Kitakyushu Museum of Natural and Human History, <sup>4</sup>Department of Geological Engineering, Gadjah Mada University

We analyzed volcanic rocks from eastern part of Java island in order to estimate the influence of slab-derived fluid across the arc. Such lateral variation of slab-derived fluid contributions, from both sediment (SED) and altered oceanic crust (AOC), to arc magmas has been documented in central and western sections of Java island. The ratios of fluid-mobile elements to HFS (High Field Strength) elements (e.g. Ba/Nb, Ba/Zr, Ba/La) were examined as well to reveal the lateral variation of subduction components. We also evaluate the mantle source variability across this arc magmas by using Nb/HFSE (e.g. Nb/Ta, Nb/Zr) ratios.

Volcanic rocks from eastern part of Java island show general enrichment of LILE and LREE, and negative anomaly of Nb and Ti, in both the frontal-arc and back-arc regions. These arc magma's characteristics are also well observed in the volcanic rocks from central and western parts of Java island. The increasing ratios of Nb/HFSE in the back-arc region of eastern part of Java imply particular mantle source enrichment in this part. Subduction components, as represented by Ba/HFSE, are well observed all across the arc. These ratios decrease from volcanic front toward back arc, which suggests a recognizable influence of slab-derived fluid in this particular part of Java island. The back-arc alkaline volcanoes, such as Ringgit-Beser, are low in terms of Ba/HFSE ratios, suggesting the small input of subduction components. In terms of across-arc variation of slab-derived fluid, volcanic rocks from East Java show similar decreasing pattern, which is also shown by magmas from Central Java. However, the appearance of back-arc alkaline volcanism at 220 km depth of Wadati-Benioff zone, which is much shallower compared to 370 km in central part of Java, raises a question of different controls on back-arc volcano formation in Java island.

The decreasing patterns of slab-derived fluid across the eastern part of Java, which is recognized in Central Java as well, suggest the distinct contributions of slab-derived fluid into arc magmas in Sunda arc. In addition, this finding implies that subduction signature is observed not only in the frontal arc region, but also in the back-arc region of both East and Central parts of Java island.

Keywords: East Java, Sunda arc, slab fluid, lateral variation, trace elements

(May 19-24 2013 at Makuhari, Chiba, Japan)

©2013. Japan Geoscience Union. All Rights Reserved.

SCG63-12

Room:104

Time:May 23 11:00-11:15

# Electrical Conductivity of Highly Concentrated Salt Solution at Elevated Temperature and Pressure

Hiroshi Sakuma<sup>1\*</sup>, Masahiro Ichiki<sup>2</sup>, Katsuyuki KAWAMURA<sup>3</sup>, Kiyoshi Fuji-ta<sup>4</sup>

<sup>1</sup>Tokyo Institute of Technology, <sup>2</sup>Tohoku University, <sup>3</sup>Okayama University, <sup>4</sup>Saga University

Introduction: Aqueous fluids in the Earth's crust would have large effect on the occurrence of earthquake and volcanic eruptions. To understand the effect of aqueous fluids, it is necessary to delineate their distribution in the Earth's crust. The distribution of the fluids has been expected to be revealed by electromagnetic observation, e.g. magnetotellurics. Electrical conductivity distribution in the crust is considered to roughly correspond to the fluids distribution because of the high electrical conductivity of fluids relative to solids. To develop a plausible model of the fluids distribution to explain the electromagnetic observations, we have to construct a database of the electrical conductivities of fluids over a range of pressure (p), temperature (T), and electrolyte concentrations (c). Classical molecular dynamics (MD) simulations are useful to obtain the physical properties of fluids at a range of p, T and c and to understand the underlying atomic-scale mechanism of the electrical conduction. Liquid and spuercritical phases of water and aqueous NaCl solutions are dominant at the p-T conditions of the Earth's crust. The aims of this study are (1) to develop a database of electrical conductivity of aqueous NaCl solution at a range of temperature, pressure, and salt concentrations and (2) to understand the physics and chemistry of the electrical conductivity of NaCl solution at extremely supercritical conditions.

Computational Methods: We used a flexible and induced point charge (FIPC) water model [1]. The point charges are fluctuated during the MD simulations. The MD simulations were performed using the code MXDORTO with some modifications. The database of electrical conductivity was developed for NaCl solution at T < 2000 K, p < 2 GPa, and c < 9.5 wt%

Results and Discussion: The electrical conductivity was almost constant at T > 673 K, p > 0.5 GPa, and low salt concentration c = 0.6 wt%. This is because the association of ions canceled out the mobility of ions at these conditions. At the salt concentration c = 3.3 wt%, which corresponds to the concentration of sea water, the electrical conductivity showed large temperature and pressure dependences at T > 1000 K and p < 1.0 GPa. The values were a function of temperature and density of the solution. The maximum conductivity was ~25 S/m. The behavior of highly concentrated salt solution c = 9.5 wt%, which is a few times higher than the sea water, will be discussed in the presentation. In this study, we explain the underlying mechanism of the change of the electrical conductivity of aqueous NaCl solution in the supercritical phase.

[1] Sakuma, H., Ichiki, M., Kawamura, K., and Fuji-ta, K., under revision.

Keywords: NaCl, geofluid, MT, static dielectric constant, water, viscosity

(May 19-24 2013 at Makuhari, Chiba, Japan)

©2013. Japan Geoscience Union. All Rights Reserved.

SCG63-13

Room:104



Time:May 23 11:15-11:30

### 3-D Channeling Flow through Rock Fracture Networks in Field-scale

Takuya Ishibashi<sup>1\*</sup>, Noriaki Watanabe<sup>1</sup>, Keisuke Sakurai<sup>1</sup>, Nobuo Hirano<sup>1</sup>, Atsushi Okamoto<sup>1</sup>, Noriyoshi Tsuchiya<sup>1</sup>

<sup>1</sup>Graduate School of Environmental Studies, Tohoku University

Rock fractures are recognized as the predominant pathways of fluid in the Earth's crust, because fractures usually have much greater permeability than the matrix permeability. Fluid flow through rock fractures is characterized by formation of preferential flow path (i.e. channeling flow) due to the heterogeneous aperture distribution created by the rough surfaces contacting, in part, each other.

In understanding the fluid migration within Earth's crust, discrete fracture network (DFN) model is one of the most powerful techniques to incorporate geometrical properties in fractures (fracture size, location, orientation, and density), and can account explicitly for the contribution of individual fractures on fluid flow. However, in the conventional DFN models, individual fractures were characterized by a single aperture value despite the fact that the real fractures had heterogeneous aperture distributions, and as a result the formation of 3-D preferential flow paths thorough fracture network were neglected. Therefore, the authors have developed GeoFlow, a novel DFN model simulator, where fractures are characterized by aperture distribution [Ishibashi et al., 2012]. In order to utilize GeoFlow for a field scale problems, the authors also developed a prediction method of fluid flow within multi-scaled fractures under confining stress [Ishibashi et al., 2012].

In the present study, we challenged to construct the precise fracture network with heterogeneous aperture distribution in fieldscale. The Yufutsu oil/gas field in Hokkaido, Japan is well known as fractured type of reservoir, and selected as the subject for study. This is because reliable DFN models can be developed based on 3-D seismic data, acoustic emission data, in-situ stress measurement, and well logging for this field [Tamagawa et al., 2010]. The modeling domain is 1,050 (East-West) x 1,050 (North-South) x 1,050 (Depth) m3, and fractures are represented by squares of 50-390 m on a side. Aperture distributions are numerically determined by contacting a pair of fractal fracture surfaces to have the lab-scale non-scale-dependent contact area, and considered for the critically stressed fractures, which have high permeability due to shear dilation. Constructed DFN models are, then, converted into equivalent permeability continua that reflected contributions of both the matrix and fracture permeabilities. For the equivalent permeability continua, steady-state laminar flow of a viscous, incompressible fluid is simulated by GeoFlow under the unidirectional flow geometry.

The simulation results by GeoFlow show that the localization of flow paths in the fracture networks is much more remarkable than that simulated by conventional DFN models due to the 3-D channeling flow. Subsequently, percentage of total area of flow paths to total area of the fracture plane (flow area) is calculated for quantitative evaluation of flow path localization. As a result, the actual flow area is estimated to be around 20-50% of the flow area predicted by conventional DFN models. This finding implicates the followings: the reactive fields where water-rock interaction takes place are limited to narrower area than predicted by conventional DFN models, or 3-D channeling flow have a significant impact on well productivity of fractured type of reservoirs. In understanding the reality of the fluid migration within Earth's crust, 3-D channeling flow is one of the key phenomenon, and the suggested method in this presentation enables us to address this phenomenon.

Keywords: rock fracture, network model, channeling flow, heterogeneous aperture distribution, field-scale

(May 19-24 2013 at Makuhari, Chiba, Japan)

©2013. Japan Geoscience Union. All Rights Reserved.



Room:104

Time:May 23 11:30-11:45

#### Fluid fraction dependence of elastic wave velocity and electrical conductivity of a watersaturated rock

Akiyoshi Higuchi<sup>1\*</sup>, Tohru Watanabe<sup>1</sup>

<sup>1</sup>Gradudate School of Science and Engineering, University of Toyama

Fluid-filled cracks must be dominant conduction paths at the mid-crustal depth. Electrical conductivity must strongly depend on the connectivity of cracks. What amount of crack is required to form an interconnected network? How does its connectivity change with its amount? In order to solve these problems, we are experimentally studying electrical conductivity of watersaturated rocks with various amounts of crack. The amount of crack is changed by confining pressure, and evaluated via elastic wave velocity.

A cylindrical sample (D=25 mm, L=30 mm) of Aji granite (Kagawa pref., Japan) was saturated with KCl aqueous solution (0.01 mol/L). The porosity is 0.68%, and the density 2.656 g/cm<sup>3</sup>. Electrical conductivity was measured with the two-electrode method (Ag-AgCl electrodes, f=1 Hz-100 kHz), and elastic wave velocity the pulse transmission technique (PZT transducers, f=2 MHz). Measurements have been made using a 200 MPa hydrostatic pressure vessel, in which confining and pore-fluid pressures can be separately controlled. The confining pressure was increased up to 125 MPa, keeping the pore-fluid pressure 0.1 MPa. It took one day or longer for the electrical conductivity to become stationary after increasing the confining pressure.

The electrical conductivity decreased by an order of magnitude as the confining pressure increased from 0.1 MPa to 25 MPa. It decreased by only 1% with the increase of confining pressure from 25 MPa to 125 MPa. Elastic wave velocity increased by 5% as the confining pressure increased from 0.1 MPa to 25 MPa. It showed 2% increase with increasing confining pressure from 25 MPa to 125 MPa.

These changes in electrical conductivity and elastic wave velocities must be caused by the closure of cracks. Based on elastic stiffness of Aji granite at 180 MPa, we can estimate the aspect ratio of a crack which closes at a given confining pressure. The aspect ratio is  $3.6 \times 10^{-4}$  for the closure pressure of 25 MPa, and  $1.8 \times 10^{-3}$  for 125 MPa. The large decrease in conductivity, which was observed below 25 MPa, is caused by the closure of cracks with the aspect ratio less than  $3.6 \times 10^{-4}$ . Cracks with the aspect ratio from  $3.6 \times 10^{-4}$  to  $1.8 \times 10^{-3}$  closed as the confining pressure increased from 25 MPa to 125 MPa, leading to only a slight decrease in conductivity. The connectivity of fluid is still maintained by cracks with the aspect ratio lager than  $1.8 \times 10^{-3}$ . Two groups of crack dominate the change in electrical conductivity up to 125 MPa.

Keywords: water-saturated rock, elastic wave velocity, electrical conductivity, fluid fraction, aspect ratio of crack

(May 19-24 2013 at Makuhari, Chiba, Japan)

©2013. Japan Geoscience Union. All Rights Reserved.

SCG63-15

Room:104



Time:May 23 11:45-12:00

### Sedimentary pore fluid-like halogens and noble gases in mantle peridotites from the Western-Pacific subduction zones

Masahiro Kobayashi<sup>1\*</sup>, Hirochika Sumino<sup>1</sup>, Takehiko Saito<sup>1</sup>, Keisuke Nagao<sup>1</sup>, Satoko Ishimaru<sup>2</sup>, Shoji Arai<sup>3</sup>, Masako Yoshikawa<sup>4</sup>, Tatsuhiko Kawamoto<sup>4</sup>, Yoshitaka Kumagai<sup>4</sup>, Tetsuo Kobayashi<sup>5</sup>, Ray Burgess<sup>6</sup>, Chris J. Ballentine<sup>6</sup>

<sup>1</sup>GCRC, Univ. of Tokyo, <sup>2</sup>Dept. of Earth Environ. Sci., Kumamoto Univ., <sup>3</sup>Dept. of Earth Sci., Kanazawa Univ., <sup>4</sup>Inst. Geothermal Sci., Kyoto Univ., <sup>5</sup>Earth and Environ. Sci., Kagoshima Univ., <sup>6</sup>Univ. of Manchester, UK

Halogen and noble gas compositions can provide complementary information as tracers on origins and behaviors of  $H_2O$  in the mantle. This is because both groups of elements are strongly partitioned into fluids and have distinct elemental and/or isotopic compositions depending on their origins. Elementally fractionated atmospheric noble gases in the convecting mantle can be explained by subduction of seawater or sedimentary pore fluids [1]. A pioneer work suggests that halogens in a mantle wedge peridotite just above a subducting slab show a signature suggesting its origin involving sedimentary pore fluids [2]. Halogens and noble gases in pore fluids may be incorporated into serpentine minerals in oceanic plates, and then carried into the deeper mantle through the subduction [2,3]. Here, we present halogen and noble gas compositions of mantle peridotites from the Western-Pacific subduction zones to put a better constraint on how far the influence of subducted pore fluids extends in the mantle.

We apply the "noble gas method" to samples, in which halogens (Cl, Br and I) and other elements (K, Ca, Se, Te, Ba and U) are converted to isotopes of Ar, Kr and Xe by neutron irradiation in a nuclear reactor [4]. This method has superior detection limits, two to five orders of magnitude lower than those by other methods, and can determine low halogen concentrations in mantle peridotites.

Samples studied in the present work are harzburgitic xenoliths from the Avacha volcano in Kamchatka, Russia and the Pinatubo volcano in the Philippines, and alpine-type peridotites from the Horoman massif in Hokkaido, Japan. H<sub>2</sub>O-rich fluid inclusions have been described in minerals of those peridotites [5,6,7]. The Br/Cl and I/Cl values show heavy enrichments in I, suggesting a contribution of subducted fluids [2] to halogens in a mantle-like component [7] with various proportions, which have unique values in each locality. Slab-derived atmospheric noble gases are also dominated in these samples as previously reported [9,10].

The features of subducted halogens and noble gases in the mantle peridotites demonstrate that sedimentary pore fluids are carried beneath the island arcs through subduction and survive in the mantle wedge.

References: [1] Holland and Ballentine (2006) Nature 441, 186-191. [2] Sumino et al. (2010) Earth Planet. Sci. Lett. 294, 163-172. [3] Kendrick et al. (2011) Nature Geosci. 4, 807-812. [4] Bohlke and Irwin (1992) Geochim. Cosmochim. Acta 56, 203-225. [5] Ishimaru et al. (2007) J. Petrol. 48, 395-433. [6] Kumagai et al. (2011) JpGU Meeting 2011, SCG060-P07. [7] Hirai and Arai (1987) Earth Planet. Sci. Lett. 85, 311-318. [8] Johnson et al. (2000) Geochim. Cosmochim. Acta 64, 717-732. [9] Hopp and Ionov (2010) Earth Planet. Sci. Lett. 302, 121-131. [10] Matsumoto et al. (2001) Earth Planet. Sci. Lett. 185, 35-47.

Keywords: halogen, noble gas, peridotite, mantle, subduction zone, pore fluid

(May 19-24 2013 at Makuhari, Chiba, Japan)

©2013. Japan Geoscience Union. All Rights Reserved.



Room:104



Time:May 23 12:00-12:15

# Slab-mantle coupling condition beneath northeastern Japan estimated from distribution of serpentinite

Kazuhiko Ishii<sup>1\*</sup>

<sup>1</sup>Graduate School of Sceiences, Osaka Prefecture University

Seismic evidences (Kawakatsu & Watada, 2007; Tusji et al., 2008) shows a serpentinite layer in the mantle wedge just above the Pacific slab at depth 90-130 km beneath northeastern Japan. This is inconsistent with the hypothesis of common depths (about 80km) of slab-mantle decoupling among subduction zones (Wada & Wang, 2009). Numerical models show that at the transition depth from the decoupling to coupling, slab surface temperature increase abruptly so that serpentine become unstable at deeper depth. I examined several different coupling conditions in numerical models. The model assuming slab-mantle coupling at 130 km and gradual upward decoupling shows temperature distribution consistent with geophysical evidences. This result suggests that the decoupling depth is controlled by temperature distribution and varies among subduction zones.

Keywords: subduction zone, serpentinite, mantle wedge, thermal structure

(May 19-24 2013 at Makuhari, Chiba, Japan)

©2013. Japan Geoscience Union. All Rights Reserved.



Room:104



Time:May 23 12:15-12:30

### Intermediate-depth earthquakes: Role of geofluids and stresses

Junichi Nakajima<sup>1\*</sup>, Keisuke Yoshida<sup>1</sup>, Akira Hasegawa<sup>1</sup>

<sup>1</sup>Graduate School of Science, Tohoku University

Generation of intermediate-depth earthquakes is an ongoing enigma because high lithostatic pressures render ordinary dry frictional failure unlikely. Earthquakes in oceanic crust have been linked to the transformation of basalt to eclogite and concomitant dehydration (e.g., Kirby et al., 1996), and earthquakes in the oceanic mantle have been discussed in terms of dehydration of serpentine minerals (e.g., Yamasaki and Seno, 1996). Here we perform waveform analyses of two small seismic clusters in the crust and mantle of the downgoing oceanic lithosphere and show seismic evidence for fluid-related embrittlement for both crustal and mantle earthquakes. The observations presented in this study show the role of volume-change related stresses and fluid-related embrittlement as viable processes for nucleating earthquakes in downgoing oceanic lithosphere.

Eclogitization of the basaltic and gabbroic layer in the oceanic crust involves a volume reduction of 10%?15%. One consequence of the negative volume change is the formation of a paired stress field as a result of strain compatibility across the reaction front. Waveform analysis of an isolated seismic cluster reveals that tensional earthquakes lie 1 km above compressional earthquakes, and earthquakes with highly similar waveforms lie on well-defined planes with complementary rupture areas. The tensional stress is probably caused by the dimensional mismatch between crust transformed to eclogite and underlying untransformed crust, and the earthquakes are probably facilitated by reactivation of fossil faults extant in the subducting plate (Nakajima et al., Geology, 2013).

For mantle earthquakes, we focus on a seismic cluster that was activated in the Philippine Sea slab, 8 months after the megathrust Tohoku-oki earthquake (Mw9.0) on March 11, 2011. The seismic sequence started with an M 4.1 normal-fault event at the deepest part of the cluster, and subsequent earthquakes migrated upward along a conduit-like zone that dips northward. The tensional stress due to the co-seismic slip promoted the efficient upward migration of fluids from the underlying Pacific plate, producing overpressurized conditions at the tip of the fluid migration paths. The enhanced pore-fluid pressures and the resultant reduced effective normal stress weakened the strength of the faults sufficiently to bring the system into the brittle regime under the enhanced deviatoric stress. The gap of 8 months may represent the time needed for the increases in pore-fluid pressures to become sufficient to overcome the lithostatic pressure.

Keywords: Intraslab earthquakes, fluids, dehydration

(May 19-24 2013 at Makuhari, Chiba, Japan)

©2013. Japan Geoscience Union. All Rights Reserved.

SCG63-P01



Time:May 22 18:15-19:30

### Spectroscopic properties of sub- and supercritical fluid( $H_2O - (CO_2) - X$ )

Chizu Sekiguchi<sup>1\*</sup>, Nobuo Hirano<sup>1</sup>, Atsushi Okamoto<sup>1</sup>, Noriyoshi Tsuchiya<sup>1</sup>

<sup>1</sup>Graduate School of Environmental Studies Tohoku University

Physicochemical states of H2O are divided into three phases, solid, liquid and vapor. Especially, the vapor-liquid phase boundary is called the saturated steam pressure curve. The terminated point of this curve is called the critical point. Liquid density becomes equal to gas density at that point. The fluid's state above the critical point is called supercritical fluid (water). Supercritical fluids exist near the deep-sea hydrothermal vent or in the deep earth's crust.

Supercritical fluid has a characteristic property that chemical reactivity, solubility and/or ion product. It is very important for the understandings of fluid/crustal rocks interaction. Therefore, decision of supercritical point of crustal fluid and characterization of fluid's state is very important.

The fluid near the critical point has intense density fluctuation, so, it is considered that the optical transmissivity is very low.

In present study, spectroscopic measurements for pure H2O, CO2 and C2H5OH fluids under high temperatures and high pressures up to 400 °C/30 MPa were carried out by using visible-type autoclave. It was observed the state of the optical property of the fluid near the critical point. In addition, it was considered a method for the critical point determination of multicomponent fluid by the spectral measurement of the transmitted light through the fluid. On the critical point, intensity of transmitted light though each fluid became low drastically. The minimum intensity of transmitted light was corresponded to critical temperature and pressure of each fluid. Differences between experimentally determined critical temperature and reference data in literature of pure fluids were within about 1.6 °C, and pressure differences were less than 0.3 MPa. It is practically well coincide and it is possible to evaluate critical temperature and pressure of multicomponent geofluids by using spectroscopic measurement under hydrothermal conditions.

Intensity between about 940 and 960 nm of H2O and of C2H5OH was always dark through entire temperature range in both cases of heating and cooling stages. Those absorptions in near-infrared region were corresponded to a combination of fundamental vibrations of -OH. It indicates that spectral measurement of multicomponent fluid will also lead to a further understanding of the fluid composition and the molecular structure.

Keywords: critical point, supercritical fluid, spectroscopic measurement

(May 19-24 2013 at Makuhari, Chiba, Japan)

©2013. Japan Geoscience Union. All Rights Reserved.

SCG63-P02

Room:Convention Hall



Time:May 22 18:15-19:30

## Development of solubility measurement technique of rare earth element (Ce) in super critical aqueous fluids

Takeyasu Abe1\*, NAKAMURA, Michihiko1, SASAKI, Osamu2, OGAWA, Yasumasa3, YAMADA, Ryoichi1

<sup>1</sup>Tohoku University, Earth Science, <sup>2</sup>Tohoku University, Museum, <sup>3</sup>Tohoku University, Environmental Studies

Mineral solubility in supercritical aqueous fluids has been determined mainly with "single crystal weight-loss method" (e.g. Manning, 1994). The detection limit of the weight loss (typically 10 micro gram) produces relatively large errors for nominally insoluble minerals (e.g. Antignano and Manning, 2008). In this study, we have been developing two different methods for measuring the solubility of Ce-monazite in aqueous fluids in the lower crustal conditions.

Firstly, synthetic fluid inclusion method was tested. We synthesized fluid inclusions in a gem-quality quartz single crystal at 0.8-1.2 GPa and 700-900 degC using a piston cylinder apparatus. The volume fractions of synthesized fluid inclusions were determined by using X-ray CT. The quartz crystals were dissolved with HF acid and the solution was analyzed with ICP-MS. The concentration of the fluid inclusion was then calculated by subtracting the amount of Ce in the background quartz.

Secondly, we conducted direct analyses of solute recovered from runs at 1 GPa and 800 degC. In order to separate the fluid from the starting material, we put CePO<sub>4</sub> powder with deionized distilled water into a gold inner capsule with one end welded shut and the crimped lightly. The fluid was expected to be equilibrated diffusively during the run duration (24 hours). The weight of water in the outer capsule was measured after quenching and the quenched crystals only in the outer capsule were dissolved with HNO<sub>3</sub> acid for ICP-MS analyses.

In the synthetic fluid inclusion method, solubility in the  $SiO_2$ -saturated system was determined, but the minimum Ce concentration that can be determined with this method is large due to small volume fraction of the synthetic fluid inclusions. The preliminary results obtained with the direct solute analyses method were consistent with the result reported by a previous study (Tropper et al., 2011).

Keywords: weight loss method, synthetic fluid inclusion method, solute trap method

(May 19-24 2013 at Makuhari, Chiba, Japan)

©2013. Japan Geoscience Union. All Rights Reserved.

SCG63-P03

Room:Convention Hall

Time:May 22 18:15-19:30

### Evolution of aperture distribution and permeability change during fracture sealing by silica minerals

Ryo Yamada<sup>1\*</sup>, Atsushi Okamoto<sup>1</sup>, Hanae Saishu<sup>1</sup>, Michihiko Nakamura<sup>2</sup>, Satoshi Okumura<sup>2</sup>, Osamu Sasaki<sup>3</sup>, Noriyoshi Tsuchiya<sup>1</sup>

<sup>1</sup>Touhoku University, <sup>2</sup>Tohoku university, <sup>3</sup>The Tohoku university museum

Fractures are dominant fluid pathways in the upper crusts. Ubiquitous occurrences of quartz veins suggest that precipitation of quartz provides significant effects on the hydrological and mechanical properties of crustal environments. For example, a model has been proposed that fracture sealing processes control the change of pore fluid pressure and thus earthquake cycle. Previous studies on quartz veins have focused on the P-T conditions, stress and strain fields and fluid compositions; however, details of dynamics of fluid flow and how fractures are sealed during vein formation are still unclear. In this study, we carried out the hydrothermal experiments to synthesis quartz veins, and observed the aperture structures by using X-ray CT. The purpose of this study is to clarify how aperture structures evolve by quartz precipitation in fractures and to understand the behavior of permeability evolution during vein formation.

We conducted the hydrothermal flow-through experiments for quartz precipitation from Si-supersaturated solutions at 430C and 30 MPa (supercritical region). The experimental apparatus consists of two vessels for preparation of the Si-supersaturated solution and for precipitation, respectively. The precipitation vessel has double-structure: the main flow path was the inner alumina tube, and the outer SUS tube was filled with static solutions connected with the flow path. A granite core (Westerly granite, diameter=3.6mm, length=50mm) with a slit of 300 micro-meter width was placed in the alumina tube. Inner and outer pressure of the inner tube was almost same (31MPa). Precipitation occurred preferentially within the alumina tube (mainly in the slit of granite), and alumina tube was broken when fracture was sealed and upstream fluid pressure was raised toward ~35 MPa. The fluid pressure was recorded by the second to calculate the change of the permeability during run. The advantage of this system is that we can take out the non-destructive sample. We observed the aperture sizes of fractures before and after of run by computer tomography.

The mineralogy and aperture structures changes systematically along the fluid flow path. Near the inlet of the precipitation vessel, only amorphous silica precipitated predominantly. From the inlet to 35mm of fracture, nucleation and growth of quartz predominantly occurred, regardless of vein wall minerals. In this region, precipitation of quartz occurred preferentially on top wall rather than bottom wall, indicating the effects of the gravity on the density fluctuation of supercritical water. From 35mm to outlet of fracture, silica precipitates occurred as epitaxial overgrowth from quartz crystal. The wavelength of aperture structures is controlled by distribution and grain size of quartz of the host granite. Accordingly, fractures are not sealed homogeneously, but complex 3D flow pathways are evolved during vein formation.

Keywords: Hydrothermal experiments, Quartz vein, aperture

(May 19-24 2013 at Makuhari, Chiba, Japan)

©2013. Japan Geoscience Union. All Rights Reserved.

SCG63-P04

Room:Convention Hall

Time:May 22 18:15-19:30

### Distribution of C-H-O fluids deduced from fluid inclusions from the Shimanto belt in the Muroto area, SW Japan

Michimasa Musha<sup>1\*</sup>, Noriyoshi Tsuchiya<sup>1</sup>, Atsushi Okamoto<sup>1</sup>

#### <sup>1</sup>Tohoku University

Geofluids have compositions in C-H-O system, mainly composed of H2O, CO2 and CH4, and the compositional variation of fluids within the Earth's interior is of special importance for understanding the global carbon cycle. In this study, we characterized the C-H-O fluids in the ancient subduction zone, that were trapped in mineral veins as fluid inclusions within the accretionary complex, Shimanto belt, SW Japan. Although calcite-bearing veins commonly occur in the Shimanto belt, it is known that fluid inclusions were mainly composed of H2O and CH4; therefore it is unclear why calcite precipitated from the fluids in absence of CO2.

The Muroto Peninsula belongs to the Tertiary (Paleogene and Neogene system) Shimanto belt, and it is mainly composed of sandstones, mudstones and conglomerates with small amount of basalt. The ages of accretion become younger toward the south, and maximal temperature evaluated from the vitrinite reflectance increased from north(214C) to south(278C) in this area (DiTullio, 1993). Mineral veins were mainly composed of quartz, with small amount of calcite. We collected the mineral veins from the 9 outcrops along the coast, W1 to W5 in the western side, and E1 to E4 from the eastern side from Paleogene system. Lewis (2000) reported the fluid inclusions of CH4 and CO2 mixture at the locality W5, but the regional distribution of CO2 fluids is not clear.

The mole fraction of CH4 and CO2 gasses in the two-phase fluid inclusions in quartz veins and carbonic(one-phase) fluid inclusions in quartz and calcite were measured by the Laser Raman Spectroscopy (HoloLab, KAISER OPTICAL SYSTEMS Co.) with thin sections of veins. Homogenization temperatures of water-rich inclusions were measured by microthermometric techniques.

Two-phase fluid inclusions in the mineral veins in the Muroto area show the following features: (1) The gas phase of fluid inclusions are composed of pure CH4, or CO2-CH4 mixture, with various XCO2(=nCO2/nCO2+nCH4) values ranging from 0 to 0.8. Fluid inclusions with pure CH4 gas were found in the northern parts of the Muroto area (W1 - W4 and E1 - E3). (2) The average XCO2 values increased toward south, and the most southern points W5 and E4 shows XCO2 of 0.3~0.8. (3) The XCO2 values are various within individual veins; fluids including CO2 (XCO2 > 0) were located only close to vein walls, whereas gas phase of fluid inclusions composed only CH4 were located in the center of the vein. Even in a single quartz crystals in mineral vein, the XCO2 values are scattered, 0.18~0.88.

One-phase carbonic fluid inclusions were composed of CH4. Calcite veins also contain this type of CH4 one-phase inclusion. Primary fluid inclusions were composed of CO2 and CH4 mixture as mentioned above, but gas phase of secondary inclusions were all composed of only CH4 in the whole Muroto area. The average homogenization temperature of W1 and W5, are 216 C at W1, and 226 C at W5, respectively.

The increase of CO2 gas with increasing temperature (W1 to W5) and occurrence of CO2-bearing inclusions near vein wall imply that CO2 fluids were generated by diagenetic processes of carboniferous materials in host rocks. We will discuss the timing and controlling factor to produce variation in C-H-O fluid inclusions both in regional and local scales.

Referances:DiTullio L., Laughland M. M., Byrne T., Thermal maturity and constraints on deformation from illite crystallinity and vitrinite reflectance in the shallow levels of an accretionary prism: Eocene-Oligocene Shimanto Belt, southwest Japan, Geological Society of America, special paper (1993), 273, 63-82

Lewis J. C., Byrne T. B., J.D.Pasteris, (2000) Early Tertiary fluid flow and pressure-temperature conditions in the Shimanto accretionary complex of south-west Japan: constraints from fluid inclusions, J. metamorphic Geol., 2000, 18, 319-333

Keywords: fluid inclusions, calcite, accretinary complex, mineral veins

(May 19-24 2013 at Makuhari, Chiba, Japan)

©2013. Japan Geoscience Union. All Rights Reserved.

SCG63-P05

Room:Convention Hall

Time:May 22 18:15-19:30

## In-situ observation of dehydration and incongruent dissolution of antigorite into aqueous fluids

Ryo Nishizaki<sup>1\*</sup>, Tatsuhiko Kawamoto<sup>1</sup>

<sup>1</sup>Graduate School of Science, Kyoto univ

It is considered that dehydration of serpentine in slab or mantle wedge causes seismicity (Yamasaki and Seno(2003 J. Geophys. Res.)). We performed an in situ observation of serpentine dehydration using Basset-type externally heated diamond anvil cell (W.A.Bassett et al. 1993 Rev. Sci. Instrum. ).

We placed antigorite( $Mg_{48}Si_{34}O_{85}(OH)_{62}$ ) in water along with an air babble in the cell. Before the heating, we confirmed there was no forsterite in the cell by Raman spectroscopic investigation. With Raman spectrum data of antigorite, we compared with Enami(2006 Gansekikoubutsukagagu in Japanese). On the heating, we observed, when antigorite dehydrate in water, antigorite melted in water and then forsterite formed and separated from water at 550-600 C and 0.2-0.7 GPa. The forsterite grew to about 30micrometer size in an hour.

The stability of antigorite suspected from this experiment isn't in contradiction Evans et al. (1976 Schweiz. Mineral. Petrogr. Mitt. ).

Takahashi et al. (2011 J. Geophys. Res.) suggests dehydration of antigorite causes strengthening and embrittlement of the gouge by shear-sliding test. We got the result of supporting this suggestion. We didn't observe talc after the heating, so we considered that talc melted in water.

Keywords: antigorite, dehydration, in situ observation, high temperature and high pressure, sesmicity, incongruent dissolution

(May 19-24 2013 at Makuhari, Chiba, Japan)

©2013. Japan Geoscience Union. All Rights Reserved.

SCG63-P06

Room:Convention Hall

Time:May 22 18:15-19:30

### In situ X-ray diffraction analysis of the experimental dehydration of chlorite at high pressure

#### Hideki Suenami<sup>1\*</sup>, Toru Inoue<sup>2</sup>

<sup>1</sup>Graduate School of Science and Engineering, Ehime University, <sup>2</sup>Geodynamics Research Center, Ehime University

#### 1. Introduction

Water in hydrous minerals is transported to deep Earth by subducting slab, which dehydrate at certain pressure and temperature. Exist of deep Earth's water affect the physical properties of Earth's minerals such as melting point, viscosity, elastic velocity, and so on. Therefore it is important to study the effect of water for the subducting slab materials. Moreover determination of the stability region of hydrous minerals is important to understand the mechanism of transport of water.

Serpentine  $(Mg_6Si_4O_{10}(OH)_8)$  is major hydrous mineral in subducting slab. There are many experimental reports for serpentine under high pressure. The stability field has already determined by in situ X-ray diffraction experiments. Chlorite  $((Mg,Al)_6(Si,Al)_4O_{10}(OH)_8)$  should be also an important hydrous mineral in the subducted slab, because Al is included in slab materials. However there are few experimental reports for chlorite under high pressure.

So in this study, the dehydration reactions of chlorite have been studied by time-resolved X-ray diffraction analysis under high pressure and temperature.

2. Experimental

Time-resolved dehydration experiments of chlorite were conduced by in situ X-ray diffraction using the high-pressure apparatus MAX80 at PF-AR, KEK. Natural chlorite was used as a starting material, and sealed by Au caps plus diamond sleeve. Temperature was measured by W-Re thermocouple, and pressure was calculated by equation of state of NaCl and Au. Experiments were conduced between 3 to 8 GPa and up to 900 deg C. Time-resolved X-ray diffraction was measured at intervals of 50 deg C with checking diffraction change. When dehydration occurred at each pressure, it kept a few hours, and quenched. The quenched sample was analyzed by scanning electron microscope.

3. Results and discussion

In all experiments, chlorite was quickly dehydrated to forsterite + pyrope + fluid within 1 hour. Dehydration boundaries of chlorite were determined at 3 to 8 GPa, with compared with the previous works. The boundary has negative P/T slope at 5 to 8 GPa. Chlorite was stable at  $\sim$  800 deg C below 4 GPa. The dehydration boundary in the present study is consistent with previous phase equilibrium boundary by quench experiment. This means that, chlorite become to equilibrium state rapidly when slab cross the dehydration boundary.

The dehydration boundaries of chlorite and serpentine are compared. Pressure range of dehydration of chlorite is narrower than that of serpentine, which means that dehydration depth of chlorite does not change so much compared to serpentine by temperature profile of slab.

Keywords: Chlorite, Dehydration, High pressure phase relation, In situ X-ray diffraction

(May 19-24 2013 at Makuhari, Chiba, Japan)

©2013. Japan Geoscience Union. All Rights Reserved.

SCG63-P07

Room:Convention Hall

Time:May 22 18:15-19:30

### Elastic-wave velocity of serpentinites under high pore-fluid pressure

Yuya Harada<sup>1</sup>, Ikuo Katayama<sup>1\*</sup>, Yoshio Kono<sup>2</sup>

<sup>1</sup>Department of Earth and Planetary Systems Science, Hiroshima University, <sup>2</sup>Geophysical Laboratory, Carnegie Institution of Washington

Serpentine is one of the candidates to explain low-velocity anomaly and high Poisson ratio in subduction zones. However, extremely high Poisson ratio found beneath Kanto and southwest Japan requires the presence of aqueous fluid in addition to the serpentinites. In this study, we investigated the effect of pore fluid pressure on elastic-wave velocity of antigorite using intravessel apparatus at Pc = 10-200 MPa, Pp = 10-100 MPa and room temperature. Compressional and shear-wave velocities under dry condition increase with increasing confining pressure, and Vp/Vs increases slightly. At wet conditions, elastic velocities decrease with increasing pore fluid pressure, and Vp/Vs increases slightly. However, the effect of pore pressure is rather weak, in which Vp/Vs = 1.804 at Pp = 10 MPa shifted to Vp/Vs = 1.811 at Pp = 100 MPa. This indicates that the relatively low-porosity serpentinites can not explain the observed high Poisson ratio, even in high fluid pressure; consequently, much higher porosity due to fracturing is required to increase Poisson ratio at the plate boundary.

Keywords: Elastic-wave velocity, pore-fluid pressure, Vp/Vs, serpentinite

(May 19-24 2013 at Makuhari, Chiba, Japan)

©2013. Japan Geoscience Union. All Rights Reserved.

SCG63-P08

Room:Convention Hall

Time:May 22 18:15-19:30

### Dihedral angle of garnet-H2O fluid in eclogite: Implication for low S-wave velocity regions at lowermost upper mantle

Mika Hashimoto<sup>1\*</sup>, Kyoko N. Matsukage<sup>2</sup>

<sup>1</sup>Department of Earth Sciences, Ehime University, <sup>2</sup>Geodynamics Research Center, Ehime University

Seismology have observed low shear-wave velocity region at depth of 300-400km in some of wedge mantle, where mantle rock is considered to contain small amount of aqueous fluid (or hydrous melt) in the grain boundary of minerals [e.g., 1]. Seismic behavior of fluid bearing system is highly influenced by a connectivity of fluid [e.g., 2]. The connectivity of aqueous fluid in a rock under mantle conditions is controlled by dihedral angle (= h), what is defined by the solid-liquid interfacial energy. A small amount of fluid can connect in grain boundaries and migrate if a value of h is less than 60 degree. To investigate connectivity of aqueous fluid in garnet-rich rocks, we measure the h for the garnet-aqueous fluid in eclogite bulk composition at upper mantle condition, and then, discuss the behavior of aqueous fluid in wedge mantle.

The target composition of starting material was MORB + 3.5 wt% of H2O, which prepared by mixing of JB-2 and Mg(OH)2. High-pressure experiments were performed using the multi-anvil apparatus (ORANGE1000) at pressure of 4 to 13 GPa at constant temperature of 1000 degree C. Run duration was 24 hour. Au/Pt double capsule was used as sample containers to eliminate the Fe-loss. To control oxygen fugacity, NiO + Ni + Ni(OH)2 powder was stuffed the space between Au and Pt capsules. Dihedral angle measurements were made from secondary-electron images at >5000\* taken by field emission scanning electron microscope (FE-SEM). In a large population of over 200, measurements were carried out for each sample in the random cross section, using Scion Image software of NIH. A true dihedral angle was adopted as the median of apparent angles on the polished section. Mineral chemistry was analyzed by using scanning electron microscope with energy dispersive spectrometer (SEM-EDS).

At lower pressure (4-8 GPa), there are garnet, pyroxene, coesite, and rutile. At high pressure (10-13 GPa), majorite component in garnet increase with increasing pressure, and modal composition of pyroxene amount decrease. More than 10 GPa, FeTi-hydroxide is observed instead of rutile. In all run products, we observed quench crystal, quench glass and pore at garnet grain boundaries. Below 8 GPa, part of fluid separate from coexisting minerals to high temperature side in sample capsule. The fluid form connected network at garnet rich part. This connected network cannot observe pyroxene-pyroxene grain boundary. Therefore we regard as h > 60 degree at pyroxene-H2O fluid. Over 10 GPa, fluid does not separate in sample capsule. It suggests that fluid network does not connect in the higher pressure. It has possibility that the fluid contains silicate components because it was observed large amount of quench crystal. The h of garnet-fluid is 45 degree at 4 GPa. It increases with increasing pressure, and is maximum (h = ~66 degree) at about 10 GPa. It suggested that garnet rich rocks are possible to trap fluid in a rock at ~10 GPa (= ~300 km in deep). We also pointed out that the dihedral angle of clinopyroxene should be larger than garnet. Therefore we conclude that shear wave velocity possible to decrease and attenuate at lowermost upper mantle, if garnet and pyroxene rich rocks exist at there.

[1]Revenaugh & Sipkin(1994), Nature , 369, 9
[2]Takei(2005), JGR, 110
[3]Yoshino et al. (2007), EPSL,256, 466

[4]Mibe et al. (2003), JGR,108

[5]Ono et al. (2002), EPSL,203, 895

Keywords: Dihedral angle, H2O-fluid, seismic low velocity zone, garnet, wedge mantle, connectivity

(May 19-24 2013 at Makuhari, Chiba, Japan)

©2013. Japan Geoscience Union. All Rights Reserved.

SCG63-P09

Room:Convention Hall

Time:May 22 18:15-19:30

# Determination of the reaction boundary $MgCO_3 + SiO_2 = MgSiO_3 + CO_3$ in the upper mantle conditions

Sho Kakizawa<sup>1\*</sup>, Toru Inoue<sup>2</sup>, Akihiro Yamada<sup>2</sup>, Hideki Suenami<sup>3</sup>

<sup>1</sup>Earth Planetary Science Course, Super Science Special Course, Ehime University, <sup>2</sup>Geodynamics Research Center, Ehime University, <sup>3</sup>Graduate School of Science and Engineering, Ehime University

Subducting slab consists of three layers; marine sediment, MORB and peridotite. The carbonates exist marine sediment, which transport  $CO_2$  to Earth interior. It is important to clarify the stability and decarbonation conditions of carbonates under high pressure. Previous studies indicate that magnesite is only stable carbonate mineral in the mantle above ~5 GPa, because the following reactions should occur with increasing pressure,  $2CaCO_3 + 2MgSiO_3 = CaMg[CO_3]_2 + CaMg[SiO_3]_2$ , and then  $CaMg[CO_3]_2 + MgSiO_3 + MgCO_3 + CaMg[SiO_3]_2$ . Still more, Isshiki et al. (2003) determined that magnesite would be stable in the mantle up to core-mantle boundary condition. However, there are few studies for the reaction of carbonate and silicate under high pressure. Here, we determined the reaction boundary;  $MgCO_3$  (magnesite) + SiO\_2 (coesite) = MgSiO\_3 (enstatite) + CO\_2 between 4-9 GPa. This reaction indicates that carbon is transported by slab in carbonate minerals. On the other hand, magnesite reacts with coesite in the ascending hot plume at upper mantle conditions. The details of the experimental results will be presented.

Keywords: magnesite, decarbonation, carbon cycle, deep Earth

(May 19-24 2013 at Makuhari, Chiba, Japan)

©2013. Japan Geoscience Union. All Rights Reserved.

SCG63-P10

Room:Convention Hall



Time:May 22 18:15-19:30

### Development of "Geofluid Map" in the Naruko district, NE Japan

Takashi Hoshide<sup>1\*</sup>, Michihiko Nakamura<sup>1</sup>

<sup>1</sup>Tohoku University

We recently address the development of the "Geofluid Map" that represents fluid distribution in the crust of Japan arc. In this presentation, we present the method of the development of the map about Naruko district, NE Japan.

Presumption of rock type from seismic tomography

First, we selected possible rock types by review of geologic maps and crustal sections deduced from studies of mantle xenolith (e.g., Takahashi, 1978). Measurement data of elastic wave velocity of these rock types in high temperature and pressure (e.g., Kern et al., 2002; Wang et al., 2005) were plotted on the Vp-poisson's ratio diagram. In NE Japan, rock types on the diagram can be divide into 3 groups mainly by the difference of Vp (C1: Granitic rocks, C2: Gabbroic rocks & Amphibolites, M1: Peridotites & Pyroxenites). By plotting recent data of seismic tomography in Naruko district (Okada et al., inpress) on the diagram, we deduced the distribution of rock types in crustal section of Naruko district.

#### Estimation of fluid distribution in crust

There are some studies about estimation of fluid content and distribution in crust (Ueshima, 2005; Mishina, 2006). Effective electrical conductivities of natural rocks depend on kind of rocks, content of fluid, connection of pore fluid and salt concentration in pore fluid. In consideration of the distribution of rock types deduced above, we estimated fluid content and distribution in crustal section of Naruko district using the recent data of electrical conductivity obtained by magnetotelluric observation in this area (Ogawa, personal communication).

(May 19-24 2013 at Makuhari, Chiba, Japan)

©2013. Japan Geoscience Union. All Rights Reserved.

SCG63-P11

Room:Convention Hall

Time:May 22 18:15-19:30

## Water distribution in the upper mantle beneath Kyushu, Japan, as derived from receiver function analyses

Yuki Abe<sup>1\*</sup>, Takahiro Ohkura<sup>1</sup>, Kazuro Hirahara<sup>1</sup>, Takuo Shibutani<sup>2</sup>

<sup>1</sup>Graduate School of Science, Kyoto Univ., <sup>2</sup>DPRI, Kyoto University

The Kyushu district, Japan, where the Philippine Sea (PHS) plate subducts, has several active volcanoes. In Kyushu, volcanoes are not distributed at regular intervals on the volcanic front and volcanic rocks have various chemical properties. To reveal the causes of the distribution of volcanoes and the chemical variation in volcanic rocks and to understand the process of magma genesis, we should reveal the water transportation by the PHS slab.

We investigated the seismic velocity discontinuities in the upper mantle beneath Kyushu, with seismic waveform data from stations of Hi-net, which are established by National Research Institute for Earth Science and Disaster Prevention, and stations of the J-array, which are established by Japan Meteorological Agency, Kyushu University, Kagoshima University and Kyoto University. We used receiver function analyses developed especially for discontinuities with high dipping angles (Abe et al., 2011, GJI). We obtained the geometry and velocity contrasts of the continental Moho, the oceanic Moho, and the upper boundary of the PHS slab.

We detected a discontinuity corresponding to the oceanic Moho and interpreted that the oceanic crust of the PHS slab has a low S-wave velocity and is hydrated down to 70 km beneath south Kyushu, down to 80-90 km beneath central Kyushu, and down to less than 50 km beneath north Kyushu.

We revealed from the detected velocity contrast at the continental Moho that the forearc mantle beneath central Kyushu has a low velocity region (Vs=2.8-3.5 km/s) that can be composed of hydrated materials and free aqueous fluid. Such a low velocity forearc mantle does not exist beneath north and south Kyushu. Beneath north Kyushu, the oceanic crust would not convey much water to the mantle wedge. Beneath south Kyushu, water dehydrated from the slab would move to the backarc side and cause arc volcanism, while it would move to the forearc side and cause a gap in volcanism and serpentinization of the forearc mantle. The low velocity forearc mantle exists only near the edge of the mantle wedge beneath the southern part of central Kyushu while it spreads more widely beneath the northern part of central Kyushu. Geochemical studies indicated that volcanic rocks that were and were not influenced by slab-derived fluid coexist in north Kyushu and the northern part of central Kyushu (Kita et al., 2001, JVGR; Miyoshi et al., 2008, JVGR). Wide distribution of the hydrated materials in the forearc mantle and mantle upwelling may cause such coexistence.

Keywords: Kyushu, Philippine Sea slab, receiver function, subduction zone, water transportatio, volcanism

(May 19-24 2013 at Makuhari, Chiba, Japan)

©2013. Japan Geoscience Union. All Rights Reserved.

SCG63-P12

Room:Convention Hall

Time:May 22 18:15-19:30

#### Detectability of crustal change accompanied with shallower slow earthquakes

Keisuke Ariyoshi<sup>1\*</sup>, Ryoko Nakata<sup>1</sup>, Toru Matsuzawa<sup>2</sup>, Takane Hori<sup>1</sup>, Ryota Hino<sup>2</sup>, Akira Hasegawa<sup>2</sup>, Yoshiyuki Kaneda<sup>1</sup>

<sup>1</sup>JAMSTEC, Earthquake and Tsunami Research Project for Disaster Prevention, <sup>2</sup>RCPEV, Graduate School of Science, Tohoku University

Owing to developing dense network of inland seismic observations, deeper slow earthquakes have been observed at the depth of about 30 km in southwestern Japan [e.g., Obara, 2002, Science]. More recently, shallower slow earthquakes have been also confirmed by ocean-seafloor seismograms [Sugioka et al., 2012, Nature Geosci.]. Since the shallower slow earthquakes have been also observed around the source region of the 2011 Tohoku earthquake [Matsuzawa et al., 2012, SSJ-FM], it is important for us to robustly detect shallower slow earthquake from seismic and geodetic observations in order to estimate the spatial distribution of seismic coupling for megathrust earthquake [Ariyoshi et al. 2012, SSJ-FM].

From August 2011, Dense Ocean-floor Network system for Earthquake and Tsunamis (DONET) has been operating steadily until now. The DONET has observation cable extending from land-based Owase city to the trench off Kumano-nada, which covers shallower part of source region of the Tonankai earthquake. Since shor-term slow slip events accompanied with tremor episodes have been observed by tiltmeters in deeper part of subduction zones [e.g., Hirose and Obara, 2006, GRL], crustal deformation driven by shallower slow earthquake is expected to be detected by ocean-floor hydraulic gauges. In the Japan subduction zone, episodic slow slip events had been observed by hydraulic gauge before the 2011 Tohoku-Oki earthquake [Ito et al., 2013, Tectonophys., in press]. In this study, we try to investigate the detectability from an earthquake cycle simulation based on rate- and state-dependent friction law.

As a study of modeling shallower slow earthquakes, Ariyoshi et al. [2012, SSJ-FM] reproduced shallower slow earthquake by assuming frictional property similar to deeper one, which occurs along-strike migration only for deeper slow earthquake with shallower slow earthquake inactive in inter-seismic stage of megathrust earthquake. In this study, we estimate crustal deformation at DONET observation points by applying the reproduced model to the Tonankai area.

In the pre-seismic stage, numerical simulation shows that the rate of vertical displacement is increased and enough to be detectable by hydraulic gauges because of higher rate of moment release for the shallower slow earthquakes. In addition, since the shallower slow earthquake becomes more active in pre-seismic stage, these results indicate that slip events detectable by DONET is expected to be more frequent toward the occurrence of megathrust earthquakes. On the other hand, DONET could not detect the shallower slow earthquakes because of lower rate of moment release.

These results suggest that monitoring slow earthquake by ocean-floor hydraulic gauges in addition to seismometers is expected to play an important role in detecting the generation process of megathrust earthquakes.

Keywords: slow earthquake, ocean-floor network observation, hydraulic pressure, megathrust earthquake cycle simulation, role of geofluid in subduction plate, friction law