

南西諸島における強震動シミュレーションのための3次元地下構造モデル Three-dimensional structure model for modeling strong motion around the Ryukyu arc

藤岡 慧¹; 竹中 博士^{2*}; 山田 伸之³; 中村 武史⁴; 岡元 太郎⁵; 藤原 広行⁶

FUJIOKA, Akira¹; TAKENAKA, Hiroshi^{2*}; YAMADA, Nobuyuki³; NAKAMURA, Takeshi⁴; OKAMOTO, Taro⁵; FUJIWARA, Hiroyuki⁶

¹九州大学, ²岡山大学, ³福岡教育大学, ⁴海洋研究開発機構, ⁵東京工業大学, ⁶防災科学技術研究所

¹Kyushu Univ., ²Okayama Univ., ³Kyushu Univ. of Education, ⁴JAMSTEC, ⁵Tokyo Institute of Technology, ⁶NIED

The Ryukyu Islands have frequently been damaged by large earthquakes and tsunamis since ancient times. For instance, in 1771, gigantic tsunamis are occurred from an earthquake and more than 12000 people died in Yaeyama Islands. From the point of view of disaster prevention, it is also important to improve the precision of strong ground motion prediction. Here we build a 3D numerical structure model for modeling of strong ground motion, which includes land and ocean-bottom topographies and a seawater layer as well as subsurface structures of the arc side and the PHS slab, partially based on the J-SHIS model for near-surface structure (NIED) and a slab-top depth model of the PHS (Headquarters for Earthquake Research Promotion, Japan). We then try to improve the near-surface structure model in the islands using our original microtremor surveys. We also conduct numerical simulations of seismic motions for three sub-oceanic earthquakes occurring near the Amami Islands, Okinawa Island and Miyako Island to confirm the applicability of the constructed structure model and to check the improvement of the near-surface model.

キーワード: 南西諸島, 強震動, シミュレーション

Keywords: Ryukyu arc, strong motion, simulation