

## 地震発生に先行する断層強度低下の地震波モニタリング可能性の検討 Feasibility of acoustic monitoring of strength drop precursory to earthquake occurrence

亀 伸樹<sup>1\*</sup>; 永田 広平<sup>2</sup>; 中谷 正生<sup>1</sup>; 日下部 哲也<sup>1</sup>  
KAME, Nobuki<sup>1\*</sup>; NAGATA, Kohei<sup>2</sup>; NAKATANI, Masao<sup>1</sup>; KUSAKABE, Tetsuya<sup>1</sup>

<sup>1</sup> 東京大学地震研究所, <sup>2</sup> 文部科学省

<sup>1</sup>Earthquake Res. Inst., Univ. of Tokyo, <sup>2</sup>Ministry of Education, Culture, Sports, Science and Technology

Rate- and state-dependent friction law (RSF), proposed on the basis of laboratory experiments, has been extensively applied to modeling of earthquake stick-slip cycles. A simple spring-slider model obeying RSF predicts a significant decrease of the frictional strength  $\Phi$  (the state of contact) that is localized within a few years preceding the earthquake occurrence. On the other hand, recent laboratory experiments successfully monitored the history of the strength by simultaneously measuring P-wave transmissivity  $|T|$  across the frictional interface using a 1MHz transducer. This suggests a possibility of earthquake forecast by monitoring the strength of a natural fault by acoustic methods.

The present paper explores the feasibility of such monitoring in the field on the basis of the physics of RSF combined with the linear slip model (LSM) employed in the classical acoustic methodology for monitoring an imperfectly welded interface. The characteristic frequency  $f_c$ , around which  $|T|$  (or reflectivity  $|R|$ ) has a good sensitivity to the interface strength, is shown to be proportional to the strength and inversely proportional to the representative scale of real contacts. For natural faults  $f_c$  is estimated to be 1 to 100Hz, which is practicable in the field. The changes of  $|T|$  and  $|R|$  depend on the ratio of the strength drop to the absolute strength level, the latter of which is not constrained by RSF simulations. Expected changes in wave amplitude in the preslip period would be several percent for strong faults and several tens percent for weak faults, which may be detectable by acoustic methods such as seismic reflection surveys.

キーワード: 断層強度, 地震サイクル, 速度・状態依存摩擦則, 地震先行現象, 線形すべりモデル, 地震波モニタリング  
Keywords: fault strength, earthquake cycle, rate- and state-dependent friction, precursor, linear slip model, acoustic monitoring