

沿岸海底地形学および関係諸科学のための高解像度マルチビーム測深調査 High-resolution multibeam bathymetric survey for coastal seafloor geomorphology and related sciences

菅 浩伸^{1*}; 長尾 正之²; 渡久地 健³; 堀 信行⁴; 浦田 健作⁵; 藤田 和彦³; 横山 祐典⁶; 中島 洋典⁷; 長谷川 均⁸; 中井 達郎⁸; 後藤 和久⁹; 片桐 千亜紀¹⁰; 小野 林太郎¹¹; Sinniger Frederic¹²; Prasetia Rian³; 波利井 佐紀³; 井口 亮¹³; 鈴木 淳²
KAN, Hironobu^{1*}; NAGAO, Masayuki²; TOGUCHI, Ken³; HORI, Nobuyuki⁴; URATA, Kensaku⁵; FUJITA, Kazuhiko³; YOKOYAMA, Yusuke⁶; NAKASHIMA, Yosuke⁷; HASEGAWA, Hitoshi⁸; NAKAI, Tatsuro⁸; GOTO, Kazuhisa⁹; KATAGIRI, Chiaki¹⁰; ONO, Rintaro¹¹; SINNIGER, Frederic¹²; PRASETIA, Rian³; HARII, Saki³; IGUCHI, Akira¹³; SUZUKI, Atsushi²

¹九州大学地球社会統合科学府, ²産総研地質情報, ³琉球大学, ⁴奈良大学, ⁵大阪経済法科大学, ⁶東京大学大気海洋研究所, ⁷有明高専, ⁸国土館大学, ⁹東北大学災害科学国際研究所, ¹⁰沖縄県立博物館美術館, ¹¹東海大学, ¹²海洋研究開発機構, ¹³沖縄高専

¹Graduate School of Integrated Sciences for Global Society, Kyushu University, ²Institute of Geology and Geoinformation, AIST, ³University of the Ryukyus, ⁴Nara University, ⁵Osaka University of Economics and Law, ⁶AORI, University of Tokyo, ⁷Ariake National College of Technology, ⁸Kokushikan University, ⁹IRIDeS, Tohoku University, ¹⁰Okinawa Prefectural Museum and Art Museum, ¹¹Tokai University, ¹²JAMSTEC, ¹³Okinawa National College of Technology

The geomorphology of shallow coastal regions has been modulated by repeated subaerial and submarine processes during glacio-eustatic sea-level change. However, in contrast to the vast knowledge that has been accumulated regarding terrestrial landforms, few previous studies have dealt with shallow seafloor landforms, which represent former terrestrial landscapes modified by present marine processes, from a geomorphological perspective.

A broadband multibeam echosounder (Sonic 2022, R2 Sonic, LLC) and its accessory system were introduced to H. Kan's laboratory in 2010 using JSPS Grant-in-Aid for Scientific Research A. We have carried out our bathymetric survey in Kume, Ishigaki, Kikai Islands and the southeastern and northwestern coasts of Okinawa Island in the Ryukyus, southwestern Japan since 2010.

The Sonic 2022 has a variable ultrasonic frequency of 200 to 400 kHz, 256 ultrasonic beams and selectable swath coverage of 10 to 160 degrees. The typical ultrasonic beam widths parallel and orthogonal to the direction of travel are within one degree of each other when an ultrasonic frequency of 400 kHz is selected. We used a VS111 GPS compass system with A20 and A30 antennas (Hemisphere Inc.) combined with a dynamic motion sensor (DMS-10, Teledyne TSS Ltd.), a sea surface sound velocity sensor (miniSVS, Valeport Ltd.), a sound velocity profiler (MicroSVP, AML Oceanographic Ltd.). Overlap of at least ~20% (typically ~50%) was implemented throughout the bathymetric survey to ensure 100% coverage of the surveyed area. The minimum and maximum depth was 1m and 400m, respectively. The HYPACK2010 software was used for both hydrographic survey and data processing. IVS3D Fledermaus was used for three-dimensional visualization.

We conducted geomorphological studies of the coastal seafloor in the coral reef areas of the Ryukyu Islands based on our high-resolution bathymetric map with a grid size of 1 m combined with SCUBA diving observations. For example, the submerged tropical karst features were discovered in Nagura Bay, Ishigaki Island (Kan *et al.* 2015). This is the first description of submerged humid tropical karst using multibeam bathymetry. Along with the geomorphological studies, we have also started biological and archeological studies in our bathymetric areas to promote interdisciplinary researches which link natural and human sciences.

Keywords: multibeam ecosounder, coastal seafloor geomorphology, biology, archaeology, coral reefs, Ryukyu Islands