

GOSAT-2 FTS SWIR 設計結果に基づく感度解析初期結果

Preliminary sensitivity study of the GOSAT-2 FTS SWIR retrievals based on the designed specifications

*吉田 幸生¹、亀井 秋秀¹、森野 勇¹、齊藤 誠¹、野田 響¹、松永 恒雄¹

*Yukio Yoshida¹, Akihide Kamei¹, Isamu Morino¹, Makoto Saito¹, Hibiki Noda¹, Tsuneo Matsunaga¹

1. 国立環境研究所

1. NIES

The Greenhouse gases Observing SATellite (GOSAT) was launched in January 2009 and observed global distribution of the column-averaged dry air mole fractions of carbon dioxide and methane (XCO_2 and XCH_4) for about seven years. As a successor mission to the GOSAT, GOSAT-2 is planned to be launched in early 2018, and its critical design review (CDR) was completed. GOSAT-2 also has a Fourier transform spectrometer (FTS) like GOSAT to obtain short-wavelength infrared (SWIR) light reflected from the earth's surface and thermal infrared (TIR) radiation emitted from the ground and atmosphere. According to the current design of the FTS-2 (FTS onboard the GOSAT-2), its SNR is higher than or almost equal to that onboard the GOSAT, and it covers the 2.3 μm carbon monoxide (CO) band as well as the 1.6 and 2.0 μm CO_2 bands and 1.67 μm CH_4 band. Our preliminary sensitivity test shows that the SNR improvement in SWIR bands reduces the retrieval random error (precision) about 15% for XCO_2 and 35% for XCH_4 than those of GOSAT.

キーワード：温室効果ガス観測技術衛星2型、二酸化炭素カラム平均濃度、メタンカラム平均濃度

Keywords: GOSAT-2, XCO_2 , XCH_4