

スリランカ3種混合試料による透水性及び吸着特性

Adsorption characteristic and permeability for three mixed materials in Sri Lanka

*齋藤 瑠緯¹、斎藤 健志¹、川本 健¹、Ganila Paranavithana¹

*Rui Saito¹, Takeshi Saito¹, Ken Kawamoto¹, Ganila N Paranavithana¹

1. 埼玉大学大学院理工学研究科

1. Graduate School of Science and Engineering, Saitama University, Japan

In developing countries including Sri Lanka, municipal solid waste is often dumped directly without incineration or any other treatments, resulting in groundwater contamination by leachate originated from the dumped waste inside. Because the leachate contains harmful chemical compounds such as heavy metals, it is important to treat the groundwater contaminated by leachate with low-cost and maintenance free systems. Permeable reactive barrier (PRB) system is suitable as in-situ remediation technique for the contaminated groundwater. In this study, adsorption (for Cd and Pb) and permeability characteristics were evaluated for locally available and low-cost materials (soil, coconuts shell biochar, and crushed brick) obtained from Sri Lanka as filling materials in the PRB system. In the experiments, the mixed materials with different ratios were used. Maximum adsorption capacity for both Cd and Pb was the highest observed in biochar 100%. For the permeability characteristics, hydraulic conductivity for the mixed materials generally increased with decreasing degree of compaction. The mixed material, soil 25% + biochar 25% + brick 50%, showed the highest hydraulic conductivity at degree of compaction with around 75%, showing more than 10^{-3} cm/s.

キーワード：浸出水、反応性浸透壁、吸着特性、透水係数、締固め度

Keywords: Leachate, Permeable reactive barrier (PRB), Adsorption Characteristic, Hydraulic Conductivity, Degree of compaction