

# Large surface wave of Sumatra earthquake captured by the long baseline kinematic analysis of 1-Hz GPS data

# Yusaku Ohta[1]; Irwan Meilano[2]; Fumiaki Kimata[3]; Kazuro Hirahara[4]; Takeshi Sagiya[4]

[1] Env.Studies Nagoya Univ.; [2] Earth and Planetary Sci.,Nagoya Univ.; [3] Res. Center Seis. & Volcanology, Graduate school of Environ., Nagoya Univ.; [4] Environmental Studies, Nagoya Univ.

We investigated directivity of large seismic wave caused by 2004 Sumatra earthquake based on high frequency GPS data.

The 26 December 2004 moment magnitude 9.0 west coast of northern Sumatra earthquake generated large Tsunami, more than 160,000 people were killed by these disasters [USGS., 2005]. Yagi [2004] investigated rupture model of this earthquake based on teleseismic bodywave (P-waves) inversion method with ABIC (e.g.Yagi et al., 2003). He divided rupture process into two stages and pointed out the second rupture generated ultra long (several hundred seconds) period seismic wave. Larson et al., (2004) found a good agreement between strong ground-motion records integrated to displacement and 1-Hz Global Positioning System (GPS) position estimates collected more than several hundred kilometers from 2002 Denali earthquake epicenter.

In these backgrounds, we processed GPS data using 1-Hz kinematic analysis. International GPS Service (IGS) operated more than 200 GPS stations in all around world for the earth science research (IGS 2004, see <http://igsceb.jpl.nasa.gov/>). Most IGS sites record measurements at 0.033 Hz, however, several sites record with 1-Hz sampling. We selected 5 GPS sites (YOGY, IISC, DGAR, BAN2, MEDN) for the kinematic GPS analysis around rupture area in this earthquake. Due to the limited number of 1-Hz GPS stations, however, we found directivity of rupture process in this earthquakes based on the high-frequency GPS data.