

AGE030-P17

会場:コンベンションホール

時間: 5月26日17:15-18:30

## 水平型及び垂直型拡散実験による岩石間隙水中拡散係数の評価

### Evaluation of diffusion coefficients in rock pore water by means of horizontal and vertical through-diffusion experiment

桐野 裕介<sup>1\*</sup>, 横山 正<sup>1</sup>, 中嶋 悟<sup>1</sup>

Yusuke Kirino<sup>1\*</sup>, Tadashi Yokoyama<sup>1</sup>, Satoru Nakashima<sup>1</sup>

<sup>1</sup>大阪大学大学院理学研究科宇宙地球科学専攻

<sup>1</sup>Osaka University

Diffusion is one of the main mechanisms of solute transport in pore water of geologic media. Relations between diffusion coefficients and porosities of rocks have been evaluated by several previous studies. However, the effect of density-driven flow in through-diffusion experiments has not been considered, and the diffusivity-porosity relationships proposed in the literature might be changed.

Therefore, the degree of density-driven flow in the horizontal diffusion cell, which has been conventionally used for diffusivity measurements, is evaluated quantitatively. The diffusion experiment using Fontainebleau sandstone was conducted for KCl and KI aqueous solutions with various concentrations (densities). The results show overestimation of the diffusion coefficient due to the density-driven flow, and are explained by a theoretical model using a diffusion-advection equation. Based on this theory, a diagram to evaluate the condition at which the measured diffusion coefficient does not include the effect of density-driven flow is presented.

Then, the vertical diffusion cell has been constructed for the precise determination of diffusion coefficients without the effect of density-driven flow, even for highly permeable rocks.

The relationships between diffusion coefficients and porosities are finally reconsidered by eliminations of data including the effect of density-driven flow and additions of data measured by the vertical diffusion cell.

キーワード:実効拡散係数,有効間隙率,密度流

Keywords: effective diffusion coefficient, effective porosity, density-driven flow