

PCG040-P15

Room: Convention Hall

Time: May 27 17:15-18:45

## Development of a camera using DMD as an occulting mask for observations of faint emission around planets (3)

Yasuyuki Obuchi<sup>1\*</sup>, Takeshi Sakanoi<sup>2</sup>, Masato Kagitani<sup>2</sup>, Norihide Takeyama<sup>1</sup>, Akito Enokuchi<sup>1</sup>, Shoichi Okano<sup>2</sup>

<sup>1</sup>Genesia corporation, <sup>2</sup>Tohoku University

We have developed a camera using an innovative occulting mask for the observation of planets. When we observe faint emission close to a bright source like a planet, stray light due to scattering in the telescope deteriorates the S/N ratio of the faint object. In order to prevent such an effect, a dense filter is usually placed in order to occult a bright source. When we make observation of the Io plasma torus (IPT), we use a filter to occult the Io disk. However, the Io disk still disturbs observation of IPT, especially in a region close to Io, since Io moves relative to Jupiter during observation. Therefore, a mask that can be variable in its position and also in its shape in the FOV is strongly required.

In order to realize this requirement, we have developed a camera using an occulting mask that employed a DMD (Digital Micromirror Device). A DMD is a device which can select the light incident on it dynamically by flipping tiny mirrors (Flipping angle is +/- 12 degrees relative to the array surface). The size of each mirror is 13um x 13um, and they are arranged in an array of 1024 x 768. Each tiny mirror element can be independently controlled by a computer. Based on preliminary experiments, unwanted light could be reduced to 10-3 - 10-4 relative to a bright object, and we expect this to be sufficient for observation of IPT. Diffracted light from the DMD surface and scattered light from the edge of each mirror of the DMD are obstructed by a physical stop on an exit pupil of a camera.

By using such an innovative DMD mask, we will be able to observe not only IPT mentioned above, but also the inner planets, like Mercury. In addition, various observations are expected when a camera system using a DMD mask is onboard space vehicles.

The optical performance of the product including DMD and the first result of the observation by the camera will be presented.

Keywords: Planet, observation, camera, development