

PEM022-09

会場: 201A

時間:5月23日14:15-14:30

二波長高速撮像による微細オーロラ変動

Small-scale auroral dynamics based on dual-spectral high-speed imaging data

坂野井 健^{1*}, 八重樫 あゆみ¹, 片岡 龍峰², 浅村 和史³, 佐藤 光輝⁴, 小岩 綾¹, 三好 由純⁵, 塩川 和夫⁵, 海老原 祐輔⁶, 岡野 章一¹

Takeshi Sakanoi^{1*}, Ayumi Yaegashi¹, Ryuho Kataoka², Kazushi Asamura³, Mitsuteru Sato⁴, Aya Koiwa¹, Yoshizumi Miyoshi⁵, Kazuo Shiokawa⁵, Yusuke Ebihara⁶, Shoichi Okano¹

¹東北大学大学院理学研究科,²東京工業大学,³宇宙航空研究開発機構宇宙科学研究本部, ⁴北海道大学大学院理学研究院,⁵名古屋大学太陽地球環境研究所,⁶名古屋大学高等研究院

¹Grad. Sch. of Science, Tohoku University, ²Tokyo Institute of Technolog, ³JAXA/ISAS, ⁴Dep.of Cosmoscience, Hokkaido University, ⁵STEL, Nagoya University, ⁶Inst. for Advanced Res., Nagoya Univ

The spatial structure and temporal variation of optical aurora are useful to investigate the magnetosphere-ionosphere coupling process, and provide us information on the characteristics of precipitating electrons, acceleration processes, wave-particle interactions, and so on. Past groundbased optical data showed the small-scale feature of auroral arc (< 100 m) showing curls and folds, as well as the temporal variation in flickering and pulsating auroras. Some models explained these features based on field-aligned acceleration processes with double layer, inertial Alfven waves, EMIC etc. However, these models assume the 1-D system along a magnetic field line, and therefore, 2-D and 3-D structures of small-scale aurora are not understood. We carried out high-speed imaging measurements with a monochromatic camera at Toolik field station and Poker Flat Research Range, Alaska, during the winter period of 2009/2010. The optical system consists of ANDOR iXon DU-897 EMCCD camera, objective lens (Nikon f=50mm,F 1.2), and an interference filter optimized for N2 1PG aurora at 670 nm. It achieved 100 Hz sampling imaging with the field-of-view (FOV) of 9.3 deg, bin numbers of 64 x 64, and spatial resolution mapping at 110 km altitude of 280 m. At Poker Flat Research Range, the Hamamatsu EMCCD camera was additionally operated to make high-speed imaging measurements at two different wavelengths. The specifications of Hamamatsu EMCCD camera are mostly the same as ANDOR camera, except for an auroral emission at O 845 nm aurora which is responsible for a soft electron precipitation, sampling rate of 110 Hz and bin numbers of 128 x 128. Therefore, the ratio of N2/O auroral intensities gives us the characteristic energy of precipitating electrons. Further, we installed the search coil magnetometers obtained with 400 Hz sampling to observe magnetic variations due to inertial Alfven wave and EMIC. Initial results of small-scale auroras concerning on arcs, pulsating and flickering auroras will be reported in this presentation.

キーワード:オーロラ,高速撮像,加速,フリッカリング,パルセーティング Keywords: aurora, high-speed imaging, acceleration, flickering, pulsating