

PPS003-P32

会場:コンベンションホール

時間:5月24日17:15-18:45

次期月探査計画セレーネ2のための月面眺望画像分光カメラ(ALIS) 開発の現状と科学目的

Advanced Lunar Imaging Spectrometer (ALIS) for SELENE-2: Present Status and Science Objectives

佐伯 和人^{1*},諸田 智克², 大嶽 久志², 岡田 達明², 大竹 真紀子², 杉原 孝充³, 本田 親寿⁴, ALIS検討グループ¹

Kazuto Saiki^{1*}, Tomokatsu Morota², Hisashi Otake², Tatsuaki Okada², Makiko Ohtake², Takamitsu Sugihara³, Chikatoshi Honda⁴, ALIS Working Group¹

¹大阪大学 大学院理学研究科,²宇宙航空研究開発機構 宇宙科学研究本部,³海洋研究開発機構,⁴会津大学

¹Graduate School of Science, Osaka Univ., ²ISAS/JAXA, ³JAMSTEC, ⁴Univ. of Aizu

A future lunar landing mission SELENE-2 is being planned by Japan Aerospace Exploration Agency (JAXA). In the present design, SELENE-2 consists of a lander, a rover, and a communication relay orbiter, but de-tailed configuration - landing site(s), mission life etc. - is now under investigation. Advanced Lunar Imaging Spectrometer (ALIS) is an imaging spectrometer which we are developing for SELENE-2 lander.

Scientific objectives of ALIS are geological investigation around the landing site by VIS/NIR (Visible and Near Infra-red light) spectroscopy, making of the photometric model of the lunar surface by repeated observation with various photometric conditions, and production of an operation map for the rover to access sampling targets, for example ejecta from central peaks. ALIS is composed of a monitor camera and two spectrometers; Visible system (VIS:380-1050 nm with 5 nm resolution) and Near Infrared system (NIR:1000-2450nm with 10 nm resolution). Each spectrometer is composed of an imaging sensor and a grism unit. These spectrometers take '1-line spatial resolution' x 'wavelength resolution' image as one shot. Line images are assembled by scanning image on a slit of the spectrometer with rotating ALIS body. We conducted so far the concept design of ALIS and computed its thermal model and optical model to confirm its feasibility.

キーワード:次期月探査,月,着陸機,リモートセンシング, SELENE-2 Keywords: SELENE-2, moon, lander, remotesensing