

MSD030-P02

会場:コンベンションホール

時間: 5月27日17:15-18:45

JEM-GLIMS搭載フォトメタの開発

Development of filter photometers onboard the JEM-GLIMS

吉田 健悟1*, 佐藤 光輝², 高橋 幸弘², 吉田 和哉³, 坂本 祐二³, 鈴木 睦⁴, 牛尾 知雄⁵

Kengo Yoshita^{1*}, Mitsuteru Sato², Yukihiro Takahashi², Kazuya Yoshida³, Yuji Sakamoto³, Makoto Suzuki⁴, Tomoo Ushio⁵

¹北海道大学宇宙理学専攻,²北海道大学大学院理学研究院,³東北大学大学院工学研究科航空宇宙工学専攻, ⁴宇宙航空研究開発機構宇宙科学研究本部,⁵大阪大学大学院工学研究科情報通信工学部門

¹Cosmosciences, Hokkaido University, ²Cosmoscience, Hokkaido University, ³Tohoku University, ⁴ISAS/JAXA, ⁵Osaka University

Lightning-associated transit luminous events (TLEs), sucah as sprites, elves, and blue jets, are discovered in 1990s. As a generation mechanism of sprites quasi-electrostatic field model (QE model) is proposed and is a most supported model. However, most of observational characteristics can not be explained by the QE model perfectly. Recently it is suggested that horizontal lightning currents will play important role in the generation mechanism. In order to identify the generation mechanism, nadir observation of spatial distribution and temporal evolution of sprites is essential. Terrestrial gamma-ray flashes (TGFs) have been discovered in 1994. Since the occurrence distribution of TGFs is highly correlated with that of lightning discharge, it is suggested that TGFs is excited by lightning discharge. However, it is not clear that which lightning discharge process generate TGFs.

In order to solve these problems, JEM-GLIMS (Global Lightning and sprIte MeasurementS on JEM-EF) has been planned. JEM-GLIMS is a space mission to observe TLEs and TGFs. Optical and electromagnetic observation of JEM-GLIMS will be carried out at the Exposure Facility (EF) of the Japanese Experiment Module (JEM) at International Space Station (ISS) in 2011. We are developing photometers onboard JEM-GLIMS. The photometers consist of six channels, which have each band-pass to measure absolute intensity of lightning and sprites. In order to fix the detailed design of proto-flight model of photometers, we have carried out mainly three experiments; (1) sensitivity calibration, (2) drift characteristics measurements, and (3) health check test under the high temperature. For these experiments, we used bread board model (BBM) which has be developed already. Based on the results of these experiments, we have changed the BBM design slightly to fulfill the requirements for the photometer and have fixed the final design of the proto-flight model of the photometer. We have finished the fabrication of the photometer and started the performance check tests. We will present preliminal results of the experiments mode in detail.

キーワード:雷放電,高高度放電発光現象,スプライト,フォトメタ,開発,地球ガンマ線

Keywords: lightning, transient luminous events, terrestrial gamma-ray flashes, development, observation, photometer