

MSD030-P03

会場:コンベンションホール

時間: 5月27日17:15-18:45

JEM-GLIMS ミッションのミッションステータスと光学観測機器の開発状況

Development Status of Optical Instruments onboard JEM-GLIMS

佐藤 光輝^{1*}, 牛尾 知雄², 森本 健志², 鈴木 睦³, 山崎 敦³, 石田 良平⁴, 高橋 幸弘¹,
芳原 容英⁵, 坂本 祐二⁶, 吉田 健悟¹

Mitsuteru Sato^{1*}, Tomoo Ushio², Takeshi Morimoto², Makoto Suzuki³, Atsushi Yamazaki³,
Ryohei Ishida⁴, Yukihiro Takahashi¹, Yasuhide Hobara⁵, Yuji Sakamoto⁶, Kengo Yoshita¹

¹北海道大学, ²大阪大学, ³宇宙科学研究本部, ⁴大阪府立大学, ⁵電気通信大学, ⁶東北大学

¹Hokkaido University, ²Osaka University, ³ISAS/JAXA, ⁴Osaka Pref. University,
⁵University of Electro-Communication, ⁶Tohoku University

In order to study the generation mechanism of Transient Luminous Events (TLEs), global occurrence rates and distributions of lightning and TLEs, and the relationship between lightning, TLEs and Terrestrial Gamma-ray Flashes (TGFs), we will carry out the lightning and TLE observation at Exposed Facility of Japanese Experiment Module (JEM-EF) of International Space Station (ISS). In this mission named JEM-GLIMS (Global Lightning and sprItE Measurements on JEM-EF) two kinds of optical instruments and two sets of radio receivers will be integrated into the Multi mission Consolidated Equipment (MCE) which is the bus system and will be installed at JEM-EF finally. The optical instruments consist of two wide FOV CMOS cameras and six wide FOV photometers, and all these optical instruments are pointed to the nadir direction. CMOS cameras named LSI (Lightning and Sprite Imager) use the STAR-250 device as a detector, which has 512x512 pixels and 25x25 um pixel size, and have 28.3x28.3 deg. FOV. One CMOS camera with a wide band filter (730-830 nm) mainly measures lightning emission, while another camera with a narrowband filter (766+/-6 nm) mainly measures TLE emission. Five of six photometers named as PH have 42.7 deg. FOV and use photomultiplier tube (PMT) as a photon detector. They equip band-pass filters (150-280 nm, 316+/-5 nm, 337+/-5 nm, 392+/-5 nm, and 762+/-5 nm) for the absolute intensity measurement of the TLE emission. One of six photometers equips a wide-band filter (600-900 nm) to detect lightning occurring within 86.8 deg. FOV. These output signals will be recorded with the sampling frequency of 20 kHz with a 12-bit resolution. JEM-GIMS will be launched in 2011. We have passed the critical design review (CDR) on January and February and have started the fabrication of the proto-flight model. We will present the development status of the JEM-GLISM optical instruments and discuss the scientific outputs derived from this mission more in detail.

キーワード:雷放電,スプライト,国際宇宙ステーション

Keywords: Lightning, Sprite, International Space Station