

SSS013-P03

会場:コンベンションホール

時間: 5月25日17:15-18:45

## 二次余震が大森宇津公式のp値に与える影響：速度および状態依存摩擦構成則によるモデリング

### Effect of secondary aftershocks on the p-value in the Omori-Utsu formula with the rate- and state-friction model

岩田 貴樹<sup>1\*</sup>

Takaki Iwata<sup>1\*</sup>

<sup>1</sup>早稲田大学

<sup>1</sup>Waseda University

To explain the temporal evolution of an aftershock sequence, a model based on the rate- and state-dependent constitutive law [Dieterich, 1994, JGR] seems attractive and is frequently used in present studies. As well known, an aftershock activity decays following an inverse power law (Omori-Utsu formula) [Utsu, 1961, Geophys. Mag.], and the Dieterich model successfully reproduce such decay.

In an usual application of the Dieterich model, we simply assume that a stressing rate is constant in time. Under this simple assumption, the temporal decay of an aftershock sequence derived from the Dieterich model is asymptotically close to the special case of the Omori-Utsu formula; its p-value is limited to 1 (i.e., the original Omori formula). Variation of the p-value is observed in real aftershock sequences. Hence, to fit comprehensively an earthquake sequence derived from the Dieterich model with general aftershock sequences, incorporating an inconstant stressing rate is suggested by several studies [e.g., Dieterich, 1994, JGR; Helmstetter and Shaw, 2009, JGR].

Dieterich [1994, JGR] suggests another idea to generate an aftershock decay with  $p \neq 1$ . The occurrence of a (large) aftershock causes a stepwise stress increase in an aftershock area, and an expected seismicity rate derived from the Dieterich model also increases abruptly. Multiple increase of the seismicity rate in the decay of aftershock activity could make an apparent p-value variable (see Figure 7 of Dieterich [1994, JGR]). In this study, this idea that the effect of secondary aftershocks provides the variation of the p-value is examined.

The aftershock sequence of the 1995 Kobe earthquake during a four-year period after the occurrence of the mainshock is analyzed. Hypocentral information of each of the aftershocks is determined by Japan Meteorological Agency. Considering the detection capability of the aftershocks, we analyze those of which magnitude (M) is 2.5 or larger; the number of analyzed events is 1590.

We suppose that the amount of stress step ( $\Delta CFF$ ) caused by the aftershock is proportional to an exponential function of its magnitude:  $\Delta CFF = a \cdot \exp(bM)$ . With an incorporation of the stress changes caused by the aftershocks, we apply the Dieterich model to the observed aftershock sequence. The parameters a and b and other parameters involved in the original Dieterich model are estimated by the maximum log-likelihood method through a point process analysis. As a result

of the application of this model, the slope of the aftershock decay slightly increases and the p-value is estimated at 1.05. Using AIC we compare the goodness-of-fit of this model with that of a model without stress changes given by the aftershocks, and find that the former model is significantly better than the latter; the difference of the AICs is 122.46. However, the p-value estimated from the Omori-Utsu law is 1.20. Only a consideration of the secondary aftershock effect is inadequate to explain the wide variation of the p-value observed in real aftershock sequences.

キーワード:余震活動,大森宇津公式, p値,速度および状態依存摩擦構成則,点過程解析,統計地震学

Keywords: aftershock activity, Omori-Utsu formula, p-value, rate- and state-dependent friction law, point process analysis, statistical seismology