

STT073-06

会場: 101

時間:5月27日16:45-17:00

極限環境における観測をめざしたレーザー干渉式広帯域地震計の開発

Development of a Laser-interferometric broadband seismometer for the observation in extreme environments

堀 輝人^{1*}, 新谷 昌人¹, 小林 直樹², 白石 浩章², 岡田 達明², 佐藤 毅彦², 鹿熊 英昭³, 村上 英記⁴

Teruhito Hori^{1*}, Akito Araya¹, Naoki Kobayashi², Hiroaki Shiraishi², Tatsuaki Okada², Takehiko Satoh², Hideaki Kakuma³, Hideki Murakami⁴

1東大地震研, 2宇宙研, 3地震予知振興会, 4高知大

¹ERI, Univ. Tokyo, ²ISAS/JAXA, ³ADEP, ⁴Kochi Univ.

We have developed a Laser-interferometric broadband seismometer for observations in extreme environments.

As such environments, the seafloor (ocean bottom borehole) and the planet (Mars investigation etc.) are so important sites from the viewpoint of seismology.

The seismic observation in ocean bottom boreholes in subduction zones is a critical way to get better comprehension of earthquake generation process and the prediction.

Also, the seismic observation on a planet (earthquakes, free oscillation) is so effective way to reveal its internal structure.

To perform valuable observations for such purpose, many superior specifications are simultaneously required for the seismometer, such as high sensitivity, broadband, maintenance-free, robustness, low noise, compact size (borehole/hand size), durability in high/low temperature, and radiation durability (cosmic ray).

As there are no seismometers on the market that have these specs, we have originally developed a laser-interferometric type broadband seismometer.

This seismometer consists of 3 sections: a laser intereferometer, a long-term pendulum, and a feedback servo electronics.

Until now, we have made each elements and performed the vibration test, temperature test, for the confirmation of the durability.

In this presentation, we will show the details of these performance tests, the entire structure of the seismometer, and the prospects for the development.

キーワード:広帯域地震計,レーザー,海底ボアホール,惑星探査,極限環境,自由振動

Keywords: broadband seismometer, laser, ocean bottom borehole, planet investigation, extreme environment, free oscillation