

APE031-20

会場:104

時間:5月26日 09:15-09:30

テフラを伴う阿蘇溶結凝灰岩から得た絶対古地磁気強度： 相対古地磁気強度変動曲線の較正点

Absolute paleointensities for the Aso welded tuffs extruded with tephras: Calibration points for relative paleointensity

丸内 亮¹, 望月 伸竜^{2*}, 山本 裕二³, 渋谷 秀敏¹

Toru Maruuchi¹, Nobutatsu Mochizuki^{2*}, Yuhji Yamamoto³, Hidetoshi Shibuya¹

¹ 熊本大学自然科学研究科, ² 熊本大学大学院先導機構, ³ 高知大学海洋コア総合研究センター

¹Kumamoto University, ²Kumamoto University, ³Kochi University

Paleointensities of the geomagnetic field determined by welded tuffs can be used as calibration points in relative paleointensity curves if widespread tephras which were extruded with the welded tuffs have been recognized in sediments and dated on the basis of oxygen isotope records (Takai et al., 2002). In order to provide calibration points of virtually no error in age for relative paleointensity, we have conducted absolute paleointensity measurements of four welded tuffs of 90-270 ka (Aso-1, 2, 3, and 4) which were extruded with widespread tephras.

Using these welded tuffs containing volcanic glasses, we can carry out paleointensity experiments on both glassy and rocky parts of them. Thermal and alternating-field demagnetizations indicate that blocking-temperature and coercivity of the glassy parts show narrower distribution than those of the rocky parts. These data suggest that magnetic minerals of the glassy parts are relatively uniform in size and/or titanium content compared to those of the rocky parts.

The low-temperature demagnetization (LTD)-double heating test (DHT) Shaw paleointensity method was applied to 31 glassy and 72 rocky samples, respectively. From 15 successful results of glassy samples, mean paleointensities were obtained as 19.5±3.0, 20.2±2.0, 27.7±4.0, and 32.7±3.7 micro-T for the Aso-1, 2, 3, and 4 welded tuffs, respectively. From 33 successful results of rocky samples, mean paleointensities were obtained as 20.9±4.4, 23.9±2.5, 30.3±7.9, and 33.5±5.2 micro-T for the Aso-1, 2, 3, and 4 welded tuffs, respectively. The agreements between paleointensity values from different materials indicate that the paleointensities determined in this study are reliable. Therefore, these paleointensities can be used as calibration points for relative paleointensity curves.

キーワード: 溶結凝灰岩, テフラ, 古地磁気強度, LTD-DHT ショー法

Keywords: welded tuff, tephra, paleointensity, LTD-DHT Shaw method