

MG1032-05

会場:102

時間:5月23日 17:30-17:45

地上磁場と GPS TEC の同時観測データを用いるプラズマ圏密度分布推定手法 Method for estimating the plasmaspheric density distribution from the ground magnetic field and GPS TEC

河野 英昭^{1*}, 才田 聡子², 上野 玄太³, 樋口 知之³, 中野 慎也³, 湯元 清文⁴

Hideaki Kawano^{1*}, Satoko Saita², Genta Ueno³, Tomoyuki Higuchi³, Shin'ya Nakano³, Kiyohumi Yumoto⁴

¹九州大学大学院理学研究院地球惑星科学部門, ²情報・システム機構新領域融合研究センター, ³情報・システム研究機構統計数理研究所, ⁴九州大学 宙空環境研究センター

¹Kyushu University, ²Transdis. Res. Integr. Center, ³The Institute of Statistical Mathematics, ⁴Kyushu University

The plasmasphere is the region in space, close to the Earth. It is a part of the magnetosphere (region filled with the Earth-origin magnetic field). The plasmasphere is filled with ionosphere-origin plasma, and the shape of the plasmasphere changes in response to the activity of the magnetosphere. It is important to monitor three-dimensional plasma distribution in and near the plasmasphere; for example, the plasmasphere can affect the progress of magnetic storms via plasmasphere-ring current interactions (the ring current is another region in which strong electric currents, carried by plasma there, flow in the shape of a ring surrounding the Earth).

Measures to monitor the three-dimensional density distribution in and near the plasmasphere includes ground magnetometers and GPS satellites, as follows. From ground magnetometer data one can identify the eigenfrequency of the field line running through the magnetometer. From thus identified frequency (so-called FLR frequency, where FLR stands for "field line resonance"), one can guess the plasma mass density distribution along the field line. Ground coverage by magnetometers is getting thicker day by day toward two-dimensional ground coverage, from which one can guess three-dimensional plasma density in the region threaded by the field lines running through the ground surface.

Each GPS satellite provides TEC (total electron contents) along the line of sight from the satellite to a ground GPS receiver; from the TEC one can guess the electron density distribution along the line of sight. There are 24 GPS satellites, and the ground coverage by GPS receivers is getting thicker day by day, from which one can guess three-dimensional electron plasma density in the region covered by the line of sights from the GPS satellites to the ground GPS receivers.

In this paper we invent a method to evaluate the ground-magnetometer information and the GPS-TEC information at the same time and obtain a unified plasmaspheric plasma density distribution. In essence, the method calculates the differences between the observations and the corresponding quantities calculated from the estimated plasma distribution, and minimizes the sum of the differences for the two types of observations. Details will be given at the presentation. We first realize this method in an iterative manner by using the quasi-Newton method. We have so far tested it with simulated data; we will show the results at the meeting. Further tests with sample data are ongoing.