

MSD004-11

会場:301A

時間:5月27日 17:00-17:15

TARANIS 小型衛星：科学目標と開発の現状 TARANIS Micro-Satellite: Science Objective and Current Status

佐藤 光輝^{1*}, 高橋 幸弘¹, 鈴木 睦²
Mitsuteru Sato^{1*}, Yukihiro Takahashi¹, Makoto Suzuki²

¹ 北海道大学, ² 宇宙科学研究所

¹Hokkaido Univ., ²ISAS/JAXA

In the past 20 years, various new phenomena associated with lightning discharges were discovered. One of these phenomena is transient luminous events (TLEs), such as sprites, elves and blue jets. These transient optical flashes are generated by the strong cloud-to-ground discharges whose charge moment or peak current is extremely large. The other is terrestrial gamma-ray flashes (TLFs), which are first discovered by BATSE onboard the CGRO satellite in 1994. The most likely models for the generation of TGFs involve the production of runaway electron beams accelerated in an avalanche process by thundercloud associated with strong electric fields. However, fundamental issues regarding the association of TLEs or lightning with TGFs and the nature of the source of penetrating radiation itself remain a mystery.

In order to study the occurrence condition and mechanisms of TLEs and the generation region and mechanism of TGFs, and in order to identify the relationship between TLEs and TGFs, simultaneous space measurements of lightning, TLEs and TGFs are essential. For these purposes a micro satellite mission named TARANIS (Tool for the Analysis of RAdiations from lightNings and Sprites) is under way. The scientific payload consists of two cameras, three photometers, one hard X-ray/gamma-ray detector, one energetic electron detector, and electric/magnetic field sensors. The orbit of the satellite will be polar sun-synchronous with an altitude of 700 km, and the local time of ascending node is required to be 22 LT with a slow drift of the order of 2 LT/year. Our group has joined the TARANIS mission as co-investigators, and started development of the photometers (MCP-PH: Micro Cameras and Photometers-PHOTometer). MCP-PH consists of four channels: one wide-FOV (42.7 deg.) photometer with wide-band filter (150-280 nm) named as PH1, two wide-FOV (42.7 deg.) photometers with narrowband filter (337±5 nm, 762.5±5 nm) named as PH2 and PH3, and one wide-FOV (86.8 deg.) with wideband filter (600-800 nm) named as PH4. As the optical detector of these photometers, metal-package photomultiplier tubes (PMTs) will be used for PH1-PH3. For PH4 a photodiode with 10x10 mm² size will be used. As the optics of the photometers, telecentric dioptrics system is adopted. The dimension (LxDxH) and mass of the photometers is 12x19x14 cm and 1.6 kg, respectively. We have developed breadboard model and finished the experiments for the performance check. Based on these results, we started designing of the engineering model (EM) of the photometers.

Current status of the TARANIS mission is just at the start line of Phase-C/D, which is the development of EM and fabrication of flight model (FM). Final deliver of FM is planned in 2014, and the launch of TARNIS is planned in 2015. At the presentation, we will discuss the science goal and current mission status more in detail.

キーワード: 雷, スプライト, 地球ガンマ線

Keywords: lightning, sprite, terrestrial gamma-ray flash