

SCG066-P02

会場:コンベンションホール

時間:5月22日14:00-16:30

断層帯のジルコン熱年代学[~]跡津川断層系茂住祐延断層を例として[~] Zircon thermochronology of fault zones:Case study of the Mozumi-Sukenobu fault, central Japan

郁芳 隨徹 ¹*, 長谷部 徳子 ², 山田 国見 ⁴, 末岡 茂 ¹, 村上 雅紀 ¹, 田上 高広 ¹, 渡邊 裕美子 ¹, 山田 隆二 ³, 荒井 章司 ² Zuitetsu Ikuho¹*, Noriko Hasebe², Kunimi Yamada⁴, Shigeru Sueoka¹, Masaki Murakami¹, Takahiro Tagami¹, Yumiko Watanabe¹, Ryuji Yamada³, Shoji Arai²

¹ 京都大,² 金沢大,³ 防災科研,⁴ 日本原子力機構 ¹Kyoto University, ²Kanazawa University, ³NIED, ⁴JAEA

Quantitatively understanding of heat generation and transformation associated with faulting is a key to understand not only dynamics of faults but also heat budget, temperature structure and range records. To understand thermal history along faults, geologic thermometers such as thermochronometers, homogenization temperatures of fluid inclusions and vitrinite reflectances have been used. Zircon fission-track thermochronology has been one of the most powerful tools to reveal thermal history along faults (e.g., Murakami et al., 2004; Tagami and Murakami, 2007). Zircon fission-track thermochronology has advantages as below: (1) fission tracks are annealed only by heating, (2) zircon is physically robust and chemically stable and can occurs along fracture zones, and (3) short-term annealing kinetics of zircon fission tracks is well understood based on laboratory experiments.

In the Mozumi-Sukenobu fault, the strongest thermal anomalies were detected between two fracture zones identified in the tunnel by using zircon fission track methods. This secondary heating is attributed to ore deposit water probably sourced from the Kamioka mine on the basis of spatial distribution of ZFT and ZHe ages, numerical calculations using the 1-D thermal diffusion equation, geological observations and ZFT inversion calculations.

キーワード: 熱年代学, 断層, 跡津川断層系

Keywords: thermochronology, fault, Atotsugawa fault group