

STT056-P04

Room:Convention Hall

Time:May 26 16:15-18:45

## Evaluation of developed precise magnetic exploration tools with using the AUV Urashima and deep-tow systems

Makoto Harada<sup>1\*</sup>, Keizo Sayanagi<sup>1</sup>, Nobuhiro Isezaki<sup>1</sup>, Takafumi Kasaya<sup>2</sup>, Jun Matsuo<sup>3</sup>, Takao Sawa<sup>2</sup>, Hisatoshi Baba<sup>4</sup>, Nobuhito Onishi<sup>5</sup>

<sup>1</sup>Inst. of Oceanic R&D, Tokai Univ., <sup>2</sup>JAMSTEC, <sup>3</sup>OYO International Co., <sup>4</sup>School of Marine Sci.&Tech. Tokai Univ., <sup>5</sup>Tierra Technica

We have developed new precise exploration tools for the seafloor hydrothermal deposits by magnetic method in order to estimate abundance of metallic resources (e.g. Sayanagi et al., 2009). Developed tools are assumed to be used with the underwater platforms such as deep-tow (DT) and autonomous underwater vehicle (AUV).

Since 2009, we have carried out several technical tests and performances by using the helicopter and research vessels. In this session, we introduce the results of the performance tests of following three research cruises.

### 1) Yokosuka YK09-09 Cruise (19-29 July, 2009; Kumano-Basin)

We carried out AUV Urashima and YKDT (Yokosuka Deep-Tow) dives in Kumano-nada (depth at 2,050m). To inspect the efficiency of equipments, we used a magnetic target which is consisted of 50 neodymium magnets. Four flux-gate (FG) and one Overhauser (OH) magnetometers were set up in the AUV and two FG and one OH magnetometers were used in the DT surveys (Harada et al., 2010a, 2010b). We could obtain the three-component magnetic field and gyro data in the whole processes of AUV and DT experiments. After the effects of permanent and induced magnetization of platform were eliminated (Isezaki, 1986), magnetic anomaly generated from the magnetic target was clearly visualized.

### 2) Bosei-maru (Tokai Univ) Cruise (30 May - 05 Jun., 2010; Bayonnaise Knoll)

We carried out the DT survey in the inside and outside of Bayonnaise caldera (E139.75,N31.55). One FG sensor was set at the tail of the titan frame. The frame including the magnetic exploration system was towed by 50 m non-magnetized cable after the metallic wire along east-west track line at the depth between 500-550 m, which crosses just above the hydrothermal area known as Hakurei deposit.

### 3) Yokosuka YK10-17 Cruise (9-19 Dec., 2010; Bayonnaise Knoll)

We carried out the AUV (Urashima) surveys in the inside and outside of the Bayonnaise caldera. Three FG sensors were installed in the payload space of AUV, and one OH sensor was towed from the rear side of AUV by 25 m cable. In those dives, we used both optical fiber gyro set up in the payload space and INS (Inertial Navigation System) of AUV. The AUV was navigated at the altitude of some tens of meters and the depth of 500m to make three-dimensional models of hydrothermal deposit of Bayonnaise caldera.

From above cruises, we could understand the efficiency of our system, restrictions of navigation and their suitable operation, and the facts to be improved which are related to some kinds of noise components and combination of plural signals.

### Acknowledgement:

We are grateful to the crews of R/V Yokosuka (Captains Mr. E. Ukekura in YK09-09, and Mr. K. Sameshima in YK10-17) and Bosei-maru (Captain Mr. H. Kawachi), who made our difficult trials in the navigation possible by their professional skill. We also thank to all scientific participants, marine crew, support staff, and technical experts of private companies for overall support. This project has been supported by the Ministry of Education, Culture, Sports, Science & Technology (MEXT) - Japan.

### References:

- Sayanagi et al. (2009) Proc. The 9th SEGJ Intern'l. Sympo. Imaging and Interpretation, 2009.
- Harada et al. (2010a) J. School of Marine Sci. Tech., Tokai Univ., 8 (2), 23-40, 2010.
- Harada et al. (2010b) Abstracts in Fall Meeting of SGPSS, 2010.
- Isezaki et al. (1986) Geophysics, 51, 1992-1998, 1986.

Keywords: hydrothermal deposit, magnetic exploration, ocean bottom resources, autonomous underwater vehicle, deep-tow system, performance evaluation