

Japan Geoscience Union Meeting 2011

(May 22-27 2011 at Makuhari, Chiba, Japan)

©2011. Japan Geoscience Union. All Rights Reserved.



STT054-01

Room:105

Time:May 24 16:30-16:45

Recent development of airborne surveys of the Earth

Shigeo Okuma^{1*}, Toru Mogi², Jiro Segawa³

¹Geological Survey of Japan, AIST, ²Hokkaido University, ³Tokyo Univ. of Marine Science & Tech.

This presentation summarizes the recent development of airborne surveys and monitoring of the Earth.

Keywords: airborne geophysics, airborne gravity survey, airborne magnetic survey, airborne electromagnetic survey, airborne radiometric survey, airborne thermal infrared survey

STT054-02

Room:105

Time:May 24 16:45-17:00

Observation at Sakurajima volcano using an unmanned autonomous helicopter

Takao Ohminato^{1*}, Takayuki Kaneko¹, Takao Koyama¹, Atsushi Yasuda¹, Minoru Takeo¹, Atsushi Watanabe¹, Yoshiaki Honda², Masato Iguchi³, Takatoshi Yanagisawa⁴

¹Earthquake Research Institute, ²CEReS, Chiba University, ³Sakurajima Volcano Research Center, DPRI, ⁴JAMSTEC

Observations in the vicinity of summit area of active volcanoes are important in understanding volcanic processes. However, it is challenging to install observation sensors near the active vent because of the danger of sudden eruptions, and thus the summit area of active volcanoes are often left blank from the observational point of view. We are developing a risk-free observation system based on an unmanned autonomous helicopter (UAV) combined with various types of observation devices. The UAV has been already used for the aeromagnetic surveys in Izu-Oshima, and succeeded in detecting fine scale geomagnetic anomalies. In addition to the aeromagnetic survey, we aim at developing various types of volcano-observation tools based on the UAV such as installing seismometers and GPS modules, sampling volcanic ash in the vicinity of active vents, and obtaining both infrared and visible images from onboard cameras. In this presentation, we will present an outlines of the installation of seismic modules at Sakurajima volcano, Japan conducted in fall of 2009 and 2010.

We used the UAV, model RMAX-G1 developed by Yamaha-Motor Co., Ltd. The payload of the helicopter is approximately 10kg, including the fuel and attached equipments. The autonomous aviation is available within 5km from the base station with meter accuracy using kinematic-differential GPS. This high positional accuracy makes it possible to conduct repeated observation at exactly the same place. Real-time images taken from the onboard cameras are transmitted to the base station. This facility is a great advantage in remote installation of sensors.

We developed an earthquake observation module (EOM) and a winch system both are designed exclusively for the UAV. Since the payload of the helicopter includes not only the weight of the EOM but also the weight of the onboard winch, onboard camera, and fuel, we had to limit the EOM's weight around 5kg. In order to realize such light weight, we had to newly develop light-weight solar panels. The EOM is carried by the helicopter to just above the target point for installation, being hanged at the tip of the wire of the onboard winch. Then, by sending out the wire gradually from the winch, the EOM is dropped slowly and is installed on the ground without strong shock. The EOM is solar powered, and is equipped with GPS for timing. Data are transmitted over the cellular-phone network. Since it is also difficult to level the sensors, a triaxial accelerometer is adopted as a seismic sensor.

Sakurajima is one of the most active volcanoes in Japan. Since the reopening of the Showa crater at the eastern flank in 2006, eruptions continue at the Showa crater, and the recent annual number of explosive eruptions is record-breaking. Entering the area within 2 km from the summit craters is prohibited, and thus there is no observation station in the restricted area. Seismic sensors in this area will significantly improve the data quality. From November 2nd to 12th in 2009 and 2010, we installed the EOMs in the summit area of Sakurajima within 2km from the active vent. We carefully investigated geographical maps and high resolution aerial photographs beforehand in order to decide potential target positions for installation of EOMs. In the experiment in 2009, we could successfully install three modules at the planned positions. In the experiment in 2010, we not only could install EOMs at 4 places, but also could retrieve three EOMs installed in the previous year. Although the EOMs installed in 2009 could not work properly due to trouble of the EOMs main board, the EOMs installed in 2010 are still arrive and are sending seismic signals at the time of this abstract submission. Although the recorded waveforms of the explosive eruptions are contaminated by the modules mechanical resonance noise above 30 Hz or more, waveforms in general are good in the frequency band lower than that frequency.

Keywords: Unmanned helicopter, volcano observation

Japan Geoscience Union Meeting 2011

(May 22-27 2011 at Makuhari, Chiba, Japan)

©2011. Japan Geoscience Union. All Rights Reserved.



STT054-03

Room:105

Time:May 24 17:00-17:15

A Basic for Gravity Measurement Performance of Simple Gravimeter Using a Force-Balanced-Type Accelerometer on a Carrier

Hiroko Matsuo¹, Satoshi Tokue¹, Hitoshi Morikawa^{1*}, Shigeo Matsuda²

¹Tokyo Institute of Technology, ²Clover tech. Inc.

The gravity survey is applied often to model a ground structure. For this purpose, a spring-type relative gravimeter is usually used. Though this type of gravimeter can provide very accurate data, it is very expensive and difficult to handle. In the engineering field, especially, for the estimation of earthquake ground motion, a model of ground structure is needed for large area. This means that a simple and inexpensive sensor to measure the gravity is required. For this, we began to develop a new gravimeter using a force-balanced-type accelerometer. In this study, we examine basic performance of same sensors. Firstly, we develop a preliminary system and calibrate it. Then, a simple measurements was carried out using a Ferris wheel, and some other carriers.

Keywords: gravity survey, force-balanced-type accelerometer, mobile carrier, Independent Component Analysis

STT054-04

Room:105

Time:May 24 17:15-17:30

The use of Geonet combined with RTK-GPS on board the air/sea moving platform and its results

Jiro Segawa^{1*}

¹Department of Marine Engineering, TUMST

In gravity measurement on board aeroplane or ship the accuracy of positioning has as significant effect on the accuracy of gravity as the sensitivity and stability of gravity sensor and precision of levelling. In gravity measurement using aeroplane or ship the GPS receiver installed on board the moving vehicle is compared with the GPS receiver installed on land base station, and interferometric positioning is conducted using the paired signals. By this method we can obtain the position of the moving platform with the cm order accuracy. However, this sort of positioning is likely to be subject to the refraction of radio wave from satellites so that the interferometric positioning yields large errors as the distance of base line increases. The order of magnitude of such effect is about 1cm as long as the base length is shorter than 10km. If it is longer than 50km, the error reaches 10cm. In 2009, however, we experienced the least ionospheric refraction case when the error of positioning was smaller than 5cm whereas the base length was larger than 50km. We knew later that in 2009 the solar activity was minimum so that the effect from the ionosphere was minimum.

In case of gravity measurement on moving vessels it is something to build a base station over the area of survey. It may be necessary to keep a person at each GPS base station, which is a work not light to execute.

From January to March we got a chance to get on board the Shioji-Maru belonging to TUMST. We installed two GPS receivers on this ship, and measured the position of the ship. These GPS receivers are compared to GEONET receivers distributed near-by. Since Geonet bases are located

at about 10km spacings it is expected that a few cm accuracy in positioning is reached and demonstrated by our present researches.

Keywords: Positioning of cm accuracy, RTK-GPS, Accuracy of positioning of moving platform, GEONET, Base distance, Accuracy of gravity measurement

STT054-05

Room:105

Time:May 24 17:30-17:45

Magnetic anomaly change of Usu Volcano 2000-2010 detected by repeated aeromagnetic surveys

Tadashi Nakatsuka^{1*}, Shigeo Okuma¹, Takeshi Hashimoto², Mitsuru Utsugi³, Wataru Kanda⁴, Takao Koyama⁵, Joint Group for Usu Volcano Airborne Magnetic Survey⁶

¹Geological Survey of Japan, AIST, ²Hokkaido Univ., ³Kyoto Univ., ⁴Tokyo Inst. Tech., ⁵Univ. Tokyo, ⁶-

Aeromagnetic survey is expected to contribute to the elucidation of the volcanic structure and the change of its activity. However, the track lines of repeated surveys cannot be the same, and the inspection to the repeatability and the spatial alias effect of magnetic anomaly pattern is quite important to acquire valid information of the activity. To overcome this difficulty, we applied the generalized mis-tie control method (Nakatsuka and Okuma, 2006; Nakatsuka et al., 2009).

Usu Volcano 2010 aeromagnetic survey was conducted by the Usu Volcano Aeromagnetic Study Group, in September, 2010 (Hashimoto et al., 2011). The existing reference data is the survey by the Geological Survey of Japan in June 2000 (Okuma et al., 2003, 2010). Both data were processed together with the generalized mis-tie control method to yield total-force magnetic anomaly change between two epochs. The result revealed increases of magnetic force at Nishiyama-Kompira crater activity areas, the area of Gin-numa crater, and Showa-shinzan dome, and a relative decrease zone along northern somma. The comparison of the result with other studies' observation and the interpretation is to be presented in another paper (Hashimoto et al., 2011).

Although the track lines were fixed by the post-flight differential process of GPS system in both surveys, the altitude fix in 2000 survey might not be accurate enough because of insufficient accuracy signal from a few satellites among GPS satellites. As 2000 survey flights were equipped with a radio-altimeter, the altitudes difference between GPS and radio-altimeter data was examined in detail, with the help of Volcanic DEM (10m mesh) by the Geographical Survey Institute. Considering that the data of radio-altimeter reflect artificial buildings and constructions, the slant radio-wave reflection from sideward topography, and the existence of thick surface vegetation, the GPS altitude data is proven to be generally well determined. Nevertheless, GPS altitude in 2000 survey may have occasional shift of 20-30 m, and also the unreasonable difference (< 10m) against radio-altimeter over the Lake Toya was revealed. As a whole the altitude accuracy of 2000 survey data is not minimal enough. If we consider this altitude accuracy, finer variations in the results above should be carefully interpreted, although the principal characteristics of the analysis results above are still reliable.

Keywords: Usu Volcano, aeromagnetic survey, magnetic anomaly change, generalized mis-tie control, volcanic activity, helicopter

STT054-06

Room:105

Time:May 24 17:45-18:00

Accuracy improvement of tunnel geological features evaluation by helicopter-borne EM and magnetic survey

Kenji Okazaki^{1*}, Yoshihiko Ito¹

¹CERI, PWRI

1. Introduction

For long tunnels, however, surveys must cover a wide range of areas, placing a limit on the feasible improvement in accuracy, as adequately grasping the geological conditions of the entire tunnel ground as well as depth properties incur significant labor and costs. Geophysical explorations making use of helicopters are applied in civil engineering geological fields, such as long tunnels and of large scale landslides, have recently been on the increase. This method enables the simultaneous conduction of more than one exploration at a time with electromagnetic soundings and magnetic prospecting from the air. Capable of rapidly and broadly measuring the characteristic values of the underground, this method allows the gathering of three-dimensional geological information.

2. Outline and Method

The authors were carried out HEM (helicopter-borne electromagnetic method) and the HMS (helicopter-borne magnetic survey) on a planned mountain tunnel with a total length of 4.1 km and 0.9 km long tunnel in the accretionary complex areas of Hokkaido, Japan. Records and survey results of constructed tunnels were also examined. Moreover, the pilot boring core, which had been conducted at all lines of the tunnel, was analyzed, shedding light on lithofacies distributed throughout the aforementioned areas. In the area surrounding the survey site, the Nikoro Group of the Tokoro belt is distributed. The Nikoro Group mainly consists of greenstone, pyroclastic sedimentary rock and hyaloclastite, and is mixed with pillow lava, chert and limestone. Many faults are formed in the area around the survey site due to tectonic movements at the time of formation of the accretionary complex and after that. The authors describe the feasibility and effectiveness of helicopter borne surveys tunnel construction to detect the distribution of geological property in the accretionary complex area by comparing them with other geological data and observation results.

3. Results

As the results, apparent electrical resistivity by HEM, it was found to reflect the lithofacies and the degree of weathering, deterioration and frequency of shear and fracture of the underground. According to data of seismic refraction, it was confirmed that the low velocity layer corresponded to a low apparent electrical resistivity part. Several low resistivity zones, mottled or relatively steep gradient parts of resistivity were recognized. These area or zones were correlated with actual lithofacies and actual geotechnical problems encountered by the tunnel excavation. As for the magnetic intensity by HMS, it was showed high value in basalt area, and low value in hyaloclastite area respectively. These tendencies correspond to the distribution of geological property observed by horizontal pilot boring core ahead of the tunnel excavation. Thus, the distribution of geological property will be indicated not only by the apparent electrical resistivity but also by the magnetic intensity. By these two combinations, the geotechnical condition is estimated briefly without decreasing its accuracy.

Keywords: helicopter-borne EM, helicopter-borne magnetic survey, tunnel

STT054-07

Room:105

Time:May 24 18:00-18:15

Response characteristics of GREATEM system considering a half-space model

Saurabh K. Verma¹, Toru Mogi², Sabry Abd Allah^{2*}

¹NGRI,Hyderabad, India, ²ISV, Faculty of Science, Hokkaido Univ

ABSTRACT

The GRounded Electrical source Airborne Transient EM (GREATEM) system employs a cable transmitter on the ground and an airborne receiver coil flown below a helicopter. In comparison to other helicopter borne TEM (heli-TEM) systems, the main advantage of the GREATEM system is that it does not fly a large transmitter loop that makes the payload heavier and the survey logistics more rigorous, and expensive. The possibility to apply a large source moment (long cable and high amplitude current) facilitates recording good S/N ratios even at relatively higher flight altitudes (>100m). Also, the long duration pulses (1 cycle lasting 1.6 sec) and all time measurements make it possible to obtain reliable late time (> 20 msec) signals to probe greater depths. We have studied the response characteristics of the GREATEM system considering a half-space model.

The resistivity of the half-space is varied over a wide range to represent various types of geological terrains and rock types. The study reveals the range of resistivity values (resistivity aperture) which can be resolved well by the GREATEM system. The influence of varying the flight height and the distance of the source cable is also studied. Due to the deployment of grounded source, the GREATEM survey area is confined to a few tens of square km in the vicinity of the source cable. However, comparisons with other heli-TEM and ground TEM systems clearly bring out several advantages of the GREATEM system.

Keywords: Helicopter borne TEM (Heli-TEM), Deep penetration Heli-TEM, Grounded source Heli-TEM, Helicopter borne LOTEM

Japan Geoscience Union Meeting 2011

(May 22-27 2011 at Makuhari, Chiba, Japan)

©2011. Japan Geoscience Union. All Rights Reserved.



STT054-08

Room:105

Time:May 24 18:15-18:30

Applicability of airborne electromagnetics to coastal areas: Kujoyukuri case

Hisatoshi Ito^{1*}, Kazuhiro Tsukuda¹, Kenzo Kiho¹, Hideshi Kaieda¹, Koichi Suzuki¹, Toru Mogi², Abd Allah Sabry², Akira Jomori³, Youichi Yuuki⁴

¹CRIEPI, ²Hokkaido Univ., ³NeoScience Co., ⁴Oyo Co.

Understanding hydrogeological character in coastal areas is an issue of paramount importance considering that most people live and work while catastrophic natural disasters occasionally happen. It is also important to delineate the distribution of fresh and saline water to maintain sustainable development in coastal areas and also for siting of geological disposal of nuclear wastes. Nonetheless limited information has been acquired to this day for the lack of suitable survey method. Airborne electromagnetics (AEM) is a method to survey underground by means of electrical resistivity. It has a merit to survey both land and sea simultaneously. While conventional AEM can reveal resistivity only to a depth of ~300 m on land, we succeeded to increase the survey depth to ~1000 m by employing grounded electrical source airborne transient electromagnetics, or GREATEM. Here, we applied GREATEM to a coastal area for the first time. The Kujoyukuri coastal plain, Boso Peninsula, was selected for our study. This area is suitable because shallow seawater develops and enough resistivity data are available by grounded electromagnetic survey on land, electrical resistivity measurements at sea, and borehole logging. As a result, it was found that GREATEM can reveal resistivity structure in the coastal area to a depth of 300-350 m within ~1 km offshore.

Keywords: Airborne electromagnetics, Coastal area, Kujoyukuri

STT054-P01

Room:Convention Hall

Time:May 24 14:00-16:30

Magnetic constraints on the shallow subsurface structure of the Fukui Plain

Shigeo Okuma^{1*}, Masahiko Makino¹, Tadashi Nakatsuka¹

¹Geological Survey of Japan, AIST

The Geological Survey of Japan (GSJ) conducted a helicopter-borne high-resolution aeromagnetic survey over the Fukui Plain, central Japan, to better understand concealed faults associated with the 1948 Fukui Earthquake (June 28, 1948, $M_j = 7.1$) that caused tremendous damage to this area. The survey was flown with a Cesium vapor magnetometer and a differential GPS along east-west and N10W flight lines at an altitude of 150m above terrain and spaced 300m and 3,000 m apart, respectively. The observed magnetic data have been processed and total magnetic intensity anomalies were compiled on a smoothed observed surface. The reduction to the pole anomalies were also calculated from the total magnetic intensity anomalies on the surface. Next, 3-D magnetic imaging has been applied to the magnetic anomalies to better understand the subsurface structure of the area. The characteristics of the results of the imaging are summarized as follows:

(1) Magnetization highs of 2.0 A/m lie south of the Awara Hot Spring in the western part of the plain, implying the existence of a past volcanic center and/or intrusions associated with the hot spring.

(2) A broad high-magnetization area which includes the local highs south of the Awara Hot Spring occupies the western part of the plain, suggesting buried volcanic rocks trapped inside the Neogene basin inferred from seismic and gravity surveys.

(3) The broad high-magnetization area is bounded by the Fukui Earthquake Fault to the east. Whereas, magnetization lows are dominant in the eastern part of the plain.

(4) Negative magnetizations are dominant along the coastline of the Sea of Japan north of the Kaetsu Plateau, suggesting the existence of reversely magnetized volcanic rocks which may outcrop along the coastline.

(5) On the basis of these results, it is suggested that the 1948 Fukui Earthquake occurred along the boundary of the old basement structure.

Keywords: aeromagnetic survey, high-resolution aeromagnetic survey, magnetic anomaly, magnetic structure, Fukui Plain, Fukui earthquake faults

STT054-P02

Room:Convention Hall

Time:May 24 14:00-16:30

Three dimensional resistivity modeling for the GREATEM survey data

Sabry Abd Allah^{1*}, Toru Mogi¹, Akira Jomori², Elena Fomenko³

¹Faculty of science, hokkaido university, ²NeoScience Co,Osaka 594-1157, Japan., ³Lomonosov Moscow state university,Russia

ABSTRACT

The Ground Electrical source Airborne Transit Electro Magnetic (GREATEM) system uses a grounded electrical dipole source of nearly 2 to 3 km length as a transmitter and a three-component magnetometer in the towed bird as a detector. With a grounded source, a large-moment source can be applied and a long transmitter-receiver distance used, yielding a greater depth of investigation but limiting the survey area. Other advantages include a smaller effect of flight altitude and the possibility of higher-altitude measurements.

A series of data processing are used to obtain the transient response curves in the end from GREATEM field survey data, these steps include (1) movement correction: which made by subtracting predicted magnetic field variations, as derived by the response function based on the movement measured by the gyro, from the observed magnetic field variations, to yield moving-noise-free data. (2) Coordinate transformation: to transfer magnetic field components from bird-based coordinates to geographical coordinates that based on directional sensor data. (3) Removing local noise: magnetic field data obtained from the ground magnetometer were used to remove natural and artificial noise. (4) Data stacking: as GREATEM data is affected by the horizontal resistivity structure change, to over come this issue a stacking of data is need. (5) Signal portion extraction: search for 0-level, the partial signal (transient) was extracted.

We are going to make a 3D resistivity model for GREATEM data based on 1D resistivity structures inverted from GREATEM field survey data as initial model. The 3D EM forward modeling scheme based on finite difference (FD) staggered grid method (Fomenko and Mogi, 2002) used to calculate the response of 3D resistivity model at each corresponding survey line. Convolution is carried out in frequency domain to add the frequency characteristic response of field survey instrument to forward model synthetic data of EM transit response in order to compare it with field survey data transit response obtained after data processing.

In current work, we have developed 3D stacking of data in each grid, and employed this method practically on the data of GREATEM filed survey at the Kujukuri beach that has been conducted to test the GREATEM survey system and clarify the subsurface structure in coast line area such as the Kujukuri beach which located on the east coast of the Boso peninsula in Chiba Prefecture, Japan.

Keywords: GREATEM 3D resistivity model, GREATEM survey at cost line

STT054-P03

Room:Convention Hall

Time:May 24 14:00-16:30

Application of the airborne electromagnetic survey in landslide survey

Youichi Yuuki^{1*}, Fumiya Nakayama¹, yasuhiko fujisawa¹

¹oyo corporation

The airborne electromagnetic survey can survey underground three-dimensional resistivity structure from the air in a short time. The analysis method draws resistivity structure from the measurement data on a survey line, and presumes geological structure from resistivity structure. Many airborne electromagnetic survey methods have been developed recently. The frequency domain airborne electromagnetic survey method and the ground source type TIMEDOMAIN airborne electromagnetic survey method (GREATEM) are used according to the investigation purpose.

This announcement reports the enforcement example of a frequency domain airborne electromagnetic survey method.

Landslide survey was conducted by Minamishimabara of Nagasaki Prefecture. Northern Nagasaki is a national leading landslide zone. The area which surveyed is a landslide frequent occurrence zone which is equal to northern Nagasaki. Nagasaki Prefecture specifies the survey area as the landslide prevention zone. Survey was conducted for two years, in order to obtain the fundamental data of landslide preventive measures. The adjoining land of the survey area carried out measure construction in the previous year. The established construction place also investigated simultaneously. As a result, it turned out that an airborne electromagnetic survey is effective in the construction plan of landslide preventive measures. Moreover, it can carry out the effect judging of the area which carried out prevention construction of the measure against a landslide.

Keywords: airborne electromagnetic survey, landslide, airborne geophysics, resistivity

Japan Geoscience Union Meeting 2011

(May 22-27 2011 at Makuhari, Chiba, Japan)

©2011. Japan Geoscience Union. All Rights Reserved.



STT054-P04

Room:Convention Hall

Time:May 24 14:00-16:30

Coseismic Displacement Measurement of The 2010 El Mayor, Mexico Earthquake Using Satellite Optical Images

Masashi Matsuoka^{1*}, Shinsuke Kodama¹

¹AIST

This paper performed to measure the ground deformation of the fault rupture due to the 2010 El Mayor, Mexico earthquake by the sub-pixel correlation technique to pre- and post-event satellite orthorectified images. The Terra/ASTER and ALOS/PRISM images processed by the GEO Grid system were used for this examination. The maximum displacement interpreted from the image analysis was few meters of right-lateral strike slip. The results will be validated in comparison with field survey and other sensors' data.

Keywords: subpixel correlation, crustal displacement, satellite optical sensor, Terra/ASTER, ALOS/PRISM, the 2010 Baja California earthquake

Japan Geoscience Union Meeting 2011

(May 22-27 2011 at Makuhari, Chiba, Japan)

©2011. Japan Geoscience Union. All Rights Reserved.



STT054-P05

Room:Convention Hall

Time:May 24 14:00-16:30

Observations of temperature distributions in Sakurajima volcano crater using airborne hyperspectral scanner

Tetsuya Jitsufuchi^{1*}

¹NIED

Brightness temperature distributions in Sakurajima Volcano were acquired by using airborne hyperspectral scanners (ARTS). They revealed a significant temporal change of geothermal activity in the Sakurajima Volcano crater from Nov. 2008 to Nov. 2010. ARTS images were acquired over the Sakurajima Volcano crater on 8 April 2008, 26 November 2008, and 21 November 2010. ARTS was flown on a clear day at 4,000m ASL (8 April 2008, 26 November 2008) and at 5,000m ASL (21 November 2010). Brightness temperature distributions in the Sakurajima Volcano crater were acquired with a spatial resolution of 3.6 to 4.8m. The geo-corrected image was calculated directly using the data from the GPS/IMU system. We could detect the geothermal activities of Sakurajima crater (Minamidake A-crater and Showa crater) from these data. We calculated the heat flux at the Sakurajima Volcano crater from the Sekioka equation. The estimated heat flux at the Minamidake A-crater was 16.4MW at 1518 (UTC+9) 26 Nov. 2008 and 0.8MW at 1126 (UTC+9) 21 Nov. 2010. The estimated heat flux at the Showa crater was 4.2MW at 1518 (UTC+9) 26 Nov. 2008 and 57.3MW at 1126 (UTC+9) 21 Nov. 2010. These results indicated both the increase of geothermal activity of the Showa crater and the decrease of the geothermal activity of the Minamidake A-crater from Nov. 2008 to Nov. 2010.

Keywords: hyperspectral sensor, airborne, geothermal distribution