

# Japan Geoscience Union Meeting 2011

(May 22-27 2011 at Makuhari, Chiba, Japan)

©2011. Japan Geoscience Union. All Rights Reserved.



SCG066-01

Room:201A

Time:May 22 10:45-11:00

## Ubiquitous gas monitoring system observed gases in the Atotsugawa fault

Masaki Murakami<sup>1\*</sup>, Fumiaki Tsunomori<sup>2</sup>, Masaaki Sugimoto<sup>2</sup>, Hidemi Tanaka<sup>2</sup>

<sup>1</sup>Kyoto University, <sup>2</sup>University of Tokyo

Attempts of monitoring generated gases due to faulting have been performed by e.g. Sugisaki (1978). 30 years after the study performed, we developed a Quadrupole Mass Spectrometer into a GRowndWater Data Analyzing System (GROWDAS) in order to measure gasses under ground continuously. We started to observe nitrogen, oxygen, argon, carbon dioxide, methane and helium gasses by the GROWDAS at the Atotsugawa fault, Gifu prefecture on December 2010. In this study, we show results of the gas observation.

# Japan Geoscience Union Meeting 2011

(May 22-27 2011 at Makuhari, Chiba, Japan)

©2011. Japan Geoscience Union. All Rights Reserved.



SCG066-02

Room:201A

Time:May 22 11:00-11:15

## Generating process of intraplate earthquakes and roles of crustal fluids

Yoshihisa Iio<sup>1\*</sup>

<sup>1</sup>DPRI, Kyoto Univ.

The generating process intraplate earthquakes has not been fully understood yet. Recently, roles of the weak zone in the lower crust are noted, since aseismic deformation of the weak zone can generate stress concentration on the seismogenic fault above it. The existence of the weak zone is estimated as low velocity and/or low resistivity anomalies in the lower crust detected by tomographic studies. Furthermore, the stress concentration that is thought to be generated by the deformation of the weak zone was detected around the seismogenic faults in Japan. The weak zone is thought to be weakened by water in the lower crust. In fact, low velocity and/or low resistivity anomalies are estimated between the weak zone and the subducting slab beneath it.

Keywords: intraplate earthquake, lower crust, stress accumulation process, Niigata-Kobe tectonic zone, crustal fluid

# Japan Geoscience Union Meeting 2011

(May 22-27 2011 at Makuhari, Chiba, Japan)

©2011. Japan Geoscience Union. All Rights Reserved.



SCG066-03

Room:201A

Time:May 22 11:15-11:30

## Radon and Discharge Water Observations in Wari-ishi Hot Spring, Gifu Prefecture

Shigeki Tasaka<sup>1\*</sup>, Masaya Matsubara<sup>1</sup>, Norio Matsumoto<sup>2</sup>, Akito Araya<sup>3</sup>, Fumiaki Tsunomori<sup>4</sup>, SEISHO SATO<sup>5</sup>

<sup>1</sup>IMC, Gifu Univ, <sup>2</sup>Geological Survey of Japan, AIST, <sup>3</sup>ERI, Univ. Tokyo, <sup>4</sup>GCRC, Univ. Tokyo, <sup>5</sup>The Institute of Statistical Mathematics

The continuation observation of Radon and water flow rate was carried out at the Gifu Hida Kamioka, Wari-ishi hot spring, in Gifu University. The amount of water flow from 850m below ground was measured in the 10 minute interval from 1998 to 2004, and at intervals of 1 second from 2004, by using the Radon detector and electromagnetic flux meter with the accuracy of 0.25%.

The observation result of water change is related to the crust distortion accompanying the earth tide or the occurrence of an earthquake through change of the pore pressure of a stagnant water layer.

The purpose of this research is to clarify relation of water change, and seismic waves and crust distortion, and to clarify the relation of the occurrence of groundwater and an earthquake from a viewpoint of earthquake prediction. Analysis of water flow was performed in the following four viewpoints, 1) hypocentral distance of the earthquake and magnitude, 2) earth tide, 3) seismic waves, 4) crust distortion at the time of the occurrence of earthquakes.

Keywords: Radon, Hot Spring, Earth Quake Prediction, Discharge Underground Water, Tidal Response

# Japan Geoscience Union Meeting 2011

(May 22-27 2011 at Makuhari, Chiba, Japan)

©2011. Japan Geoscience Union. All Rights Reserved.



SCG066-04

Room:201A

Time:May 22 11:30-11:45

## A continuous and long term monitoring of hydraulic conductivity at Kamakura

Fumiaki Tsunomori<sup>1\*</sup>

<sup>1</sup>University of Tokyo

We will discuss results of a continuous monitoring of the hydraulic conductivity at Kamakura observatory.

The radon concentration anomaly related to earthquakes is governed by both rocks and the structure of an aquifer. The most important parameter of the structure of the aquifer is the porosity, which is directly connected to the hydraulic conductivity. It is therefore essential to establish a monitoring method of the hydraulic conductivity with the radon concentration for understanding such preseismic phenomena.

Groundwater level recovery, which is caused by an intermittent water sampling with 1 hour interval, was recorded automatically every 10 seconds for 1 year. The time constants of the water level recovery were calculated by Wylie's equation. Finally, the apparent hydraulic conductivities were calculated from the recovery constants with the structural parameters of the well.

We will focus attention on the characteristics of the time series of the apparent hydraulic conductivity.

Keywords: Groundwater, Hydraulic Conductivity, Continuous Monitoring

SCG066-05

Room:201A

Time:May 22 11:45-12:00

## 2000 western Tottori earthquake triggered by latent magmatism: variations in the $^3\text{He}/^4\text{He}$ ratios in the source region

Koji Umeda<sup>1\*</sup>, Koichi Asamori<sup>1</sup>

<sup>1</sup>Japan Atomic Energy Agency

A magnitude (M<sub>j</sub>) 7.3 intraplate earthquake occurred in the western Tottori area, southwest Japan, on 6 October 2000, where there was no apparent pre-faulting subsurface indication of the source fault of the 2000 earthquake. Magnetotelluric soundings were taken in and around the aftershocks occurred in order to image three-dimensional electrical resistivity structure at depths of up to 40 km, which could indicate an anomalously conductive body in the middle crust to the upper mantle on the southwest side of the source fault. Free gas and dissolved gases collected from groundwater wells around the seismic source region are characterized by  $^3\text{He}/^4\text{He}$  ratios several times higher than the atmospheric value; the highest value of 5.1 RA is similar to those of typical arc-related volcanic gases. Although alkali basalts of early Pleistocene age are sparsely distributed in the western Tottori area, the observed  $^3\text{He}/^4\text{He}$  ratios are higher than the calculated  $^3\text{He}/^4\text{He}$  ratio derived from the ancient magmatism, considering post-extrusive radiogenic ingrowth of  $^4\text{He}$  by decay of U and Th included in the magma. Therefore, it is concluded that the geophysical anomaly imaged to the southwest of the source fault is attributed to latent magmatism in the present-day subduction system. Aqueous fluids separated from the cooling crustal magma could cause deep low-frequency earthquakes around the Moho discontinuity and migrate into the brittle upper crust. In addition, the presence of aqueous fluid is expected to weaken the crustal materials. Locally anelastic deformation, implying notable compressive deformation in the E-W direction, was observed in the region where aftershocks were distributed. Under overpressure conditions, the existing fault could serve as a pathway for aqueous fluids expelled from magma with high  $^3\text{He}/^4\text{He}$  ratios, so that the upwelling of overpressurized fluids toward the Earth's surface results in the emanation of groundwaters with high  $^3\text{He}/^4\text{He}$  ratios along the trace of the source fault segments.

Keywords: 2000 western Tottori earthquake, helium isotope, latent magmatism

SCG066-06

Room:201A

Time:May 22 12:00-12:15

## Experimental evidence for pressure solution of quartz aggregate with small effective stress (0.5 MPa) at 25 - 45C

Kazuya Miyakawa<sup>1\*</sup>, Tianshi Yang<sup>1</sup>, Iwao Kawabe<sup>1</sup>

<sup>1</sup>Nagoya University

Dissolution rates of pressure solution (PS) of quartz sand in 0.002 M NaHCO<sub>3</sub> solution were experimentally determined at low temperatures (25? to 45?C) and low effective stresses (0.32 to 0.51 MPa) under conditions far from equilibrium. They were  $1.5\pm 0.4 \times 10^{-15}$  (25?C),  $2.1\pm 0.3 \times 10^{-15}$  (35?C) and  $2.7\pm 0.7 \times 10^{-15}$  (45?C) (Si mol/cm<sup>2</sup>/sec), respectively. The ratios of the dissolution rates of PS to those of quartz sand at zero effective stress were 4.0 $\pm$ 1.2 (25?C), 3.0 $\pm$ 0.6 (35?C) and 2.4 $\pm$ 0.6 (45?C), respectively. In response to a step-like increase of applied uniaxial loads, the dissolution rates of PS increased definitely at first, but the dissolution rate decreased gradually in the course of keeping the effective stress constant. After the effective stress was removed, there was a tendency that the dissolution rate increases more or less again. The apparent activation energy of our PS experiments was calculated to be approximately 24 kJ/mol, and this value is smaller than that of dissolution reaction of quartz sand at effective stress = 0. Our results clearly show that even at such low temperatures and low effective stresses, Si release into solution as a result of PS can be detected. Actually, when the stress is applied to a cracked granitic medium involving a groundwater flow system, the Si concentration in groundwater may be increased as a result of PS. This is interesting if there are available monitoring data as to dissolved Si in the groundwater for the purpose of earthquake prediction. We suggest that our study would help formulate a new method for the geochemical earthquake prediction study on the basis of pressure solution of SiO<sub>2</sub>.

Keywords: pressure solution, quartz dissolution, earthquake prediction

## ESR thermochronological studies on frictional heating events in the Taiwan Chelungpu fault drilling project Hole B cores

Tatsuro Fukuchi<sup>1\*</sup>, Noboru Imai<sup>2</sup>, Wonn Soh<sup>3</sup>, Sheng-Rong Song<sup>4</sup>

<sup>1</sup>Yamaguchi University, <sup>2</sup>AIST, <sup>3</sup>JAMSTEC, <sup>4</sup>National Taiwan University

The Taiwan Chelungpu Fault Drilling Project (TCDP) was launched in 2002 after the 1999 Chi-Chi earthquake to elucidate the rupture process caused in a subduction seismogenic zone, and continuous drill cores were collected from two main boreholes (Holes A and B) penetrating through the Chelungpu fault plane at depths [Ma et al., 2006]. In the Hole B cores, there exist three major fault zones at about 1136 m, 1194 m and 1243 m depths [Hirono et al., 2007]. As a result of the close investigations using various analytical methods, the black fault gouge zone distributed at about 1136 m depth (BGZ1136) is considered to have been most likely active in the Chi-Chi earthquake. Some preceding studies reported that high magnetic susceptibility and low inorganic-carbon content detected from the BGZ1136 may have been caused by coseismic frictional heating [Ikehara et al., 2007; Hirono et al., 2007]. On the other hand, X-ray diffraction analytical data clearly indicated that smectites, chlorites and illites exist in the BGZ1136 [Hashimoto et al., 2008; Hirono et al., 2008]. Especially the content of illites has been extremely increased as compared with that in the surrounding fault rocks, implying the occurrence of smectite-illitization in the BGZ1136 [Hirono et al., 2008]. However, since frictional heating is considered to cause an instantaneously dry state, hydrothermal reaction under a state of thermal equilibrium like smectite-illitization cannot occur at the same time as frictional heating. Thus, we carried out thermal analyses of the 1136m major fault zone in the Hole B cores using the electron spin resonance (ESR) technique. As a result, we obtained no evidence of the striking generation of frictional heat such as the anomaly of ferrimagnetic resonance (FMR) signal from the BGZ1136. Instead, we detected small FMR signal of maghemite from it. Magnetic analyses indicated that the black gouge has much higher coercive force than the surrounding fault rocks, suggesting the transformation of maghemite produced by ancient frictional heating into hematite due to hydrothermal reaction.

We have newly carried out thermochronological studies using the  $E_1'$  center, which is a paramagnetic signal associated with unpaired electrons trapped at vacancies in quartz [Fukuchi & Imai, 2001]. According to our step-by-step (5 minutes) heating experiments, the  $E_1'$  center commonly grows at 200-300 degree C, is saturated at 300-350 degree C and is almost annihilated at 450 degree C. The  $E_1'$  center in the BGZ1136 has been strikingly decreased, compared with those in the surrounding fault rocks, so that the black gouge may have been subjected to heat over 400 degree C. The only heat source is most probably frictional heating, because no igneous or metamorphic rock exists around the 1136m major fault zone. On the other hand, the  $E_1'$  center in the black gouge strikingly increases by heating at 250 degree C or more and has a maximum intensity at about 350 degree C. This means that the BGZ1136 was not subjected to heat over the heating for 5 minutes at 250 degree C in the Chi-Chi earthquake. This conclusion from the  $E_1'$  center is consistent with that from the FMR signal of maghemite. The  $E_1'$  center exactly suggests that frictional heat over 400 degree C detected from the BGZ1136 may have been generated earlier than the Chi-Chi earthquake. Moreover, thermochronological analyses using the  $E_1'$  center reveal that the black gouge may have been produced by ancient frictional heating older than 50 ka. The ESR thermochronology may allow us to identify coseismic frictional heating events of ~1 ka in deep drill cores.

### [References]

- Fukuchi, T. & Imai, N., 2001, *Island Arc*, 10, 467-478.  
Hashimoto, Y. et al., 2008, *eEarth*, 3, 1-6.  
Hirono, T. et al., 2007, *JGR*, 112, B07404, doi:10.1029/2006JB004738.  
Hirono, T. et al., 2008, *GRL*, 35, L16303, doi:10.1029/2008GL034476.  
Ikehara, M. et al., 2007, *Geochem. J.*, 41, 391-396.  
Ma, K.-F. et al., 2006, *Nature*, 444, 473-476, doi:10.1038/nature05253.

Keywords: electron spin resonance,  $E_1'$  center, Chelungpu fault, fault gouge, frictional heat, thermochronology