

SCG010-P01

会場:コンベンションホール

時間:5月25日 10:30-13:00

ARCHAEOGEOPHYSICAL STUDIES CONDUCTED ON SINOP MITRIDATES PALACE (BALATLAR CHURCH) ARCHAEOGEOPHYSICAL STUDIES CONDUCTED ON SINOP MITRIDATES PALACE (BALATLAR CHURCH)

Fethi Ahmet YUKSEL¹, Nihan HOSKAN^{2*}, Gulgun KOROGLU³
Fethi Ahmet YUKSEL¹, Nihan HOSKAN^{2*}, Gulgun KOROGLU³

¹I. U. Eng. Fac.Dpt. of Geophysical Eng., ²I. U. Eng. Fac.Dpt. of Geophysical Eng., ³M.S.U. of Fine Arts, D. of Hist. of Art
¹I. U. Eng. Fac.Dpt. of Geophysical Eng., ²I. U. Eng. Fac.Dpt. of Geophysical Eng., ³M.S.U. of Fine Arts, D. of Hist. of Art

Sinop, Turkey was founded at the tip of Cape Boztepe on Sinop Peninsula on the most northern edge of the Black Sea coast. The Balat Church complex in Sinop houses a stratigraphic structure stretching from Roman times to the Ottoman period. These structures include an area that has been systematically used for long periods from the Romans to the Ottoman State on the Black Sea coast of Anatolia.

From the early period to the present day since Sinop was built on the same location, it is not easy to discern the urban fabric of different periods. Within the city, the most important archeological finding involving the late Roman and early Byzantium periods, and known in scientific journals and colloquially, is the Balatlar Church or the Mitridates Palace. This site is a cross planned large structure and although there are no remains of the roof of the structure, the 5 to 6 m height walls have remained intact to this day and consist of what may be defined as triangular planned chambers that are inter-connected to each other. Despite the fact that only the outer walls remain standing, remnants or traces of carriers or the grounds of the inner sections of the area surrounded by the walls are not present. The remains of a cistern of four sections attached to each other that is triangularly planned and that is covered with barrel vaults are assumed to be related to this structure.

The building complex known as Balatlar Church is surrounded by chambers with high walls that are connected to each other. This large complex considered as an important structure when first built was used for different purposes in later periods. Various views on the function of the structure are as follows: It is thought that the name Balat comes from the Latin Palatium and that it was a palace dating back to the late Roman-early Byzantium period. Historical sources indicate the existence of large silos that stored grains arriving from the northern Black Sea to Sinop during the Byzantium Empire. Since a large part of the remnants of the structure are in the shape of large chambers, it is assumed by researchers that these chambers were used to store grains. Another hypothesis is that the structure might be a section of well-known gymnasium of Sinop bath (Thermae) complex dating back to the Roman period. The fact that large cisterns are located nearby and that layout of the plan recalls the monumental baths of Roma increases the likelihood that this hypothesis is correct. It is also assumed that the structure was used as a monastery at a later time.

Given historical past of Sinop, the Pontos inscriptions on the walls and being known as a palace, the debate on what the function of the Balat Church complex is still continues. The Palace has been considered as a grain silo, as a gymnasium bath (bearing in mind its scale) or as a monastery. However, the common view of researchers is that it is not possible to know the period the structure was built, its phases and its functions until excavation work is conducted on the site.

In planning the excavation work on the Balat Church complex, geophysical work was conducted in identifying the existence of the architectural remains of the well-known gymnasium bath complex of Sinop dating back to Roman times: the Pistina (pool), Apoditerium (the changing room section), Caldarium (the hottest section of the baths), Hypocaust (the heating installations section) and the Tepidarium (the tepid section of the baths). Using a proton magnetometer, a measurement of the vertical gradient was taken of the site. With the magnetic maps obtained, the magnetic anomalies attributed to the architectural remains of the underground heating installation made up of brick or stone columns where hot air could freely circulate from the hearth or furnace of the Roman bath were identified.

キーワード: Sinop-Mitridates Palace, Archaeogeophysics, Magnetometer, Balatlar Church, Gymnasium, Roma Bath
Keywords: Sinop-Mitridates Palace, Archaeogeophysics, Magnetometer, Balatlar Church, Gymnasium, Roma Bath

SCG010-P02

会場:コンベンションホール

時間:5月25日 10:30-13:00

Reconnaissance Geophysical Survey of groundwater aquifer at Ayun Musa Hot Springs, Egypt Reconnaissance Geophysical Survey of groundwater aquifer at Ayun Musa Hot Springs, Egypt

gad el-qady^{1*}
gad el-qady^{1*}

¹Nat. Res. Inst. astronomy & Geophysics

¹Nat. Res. Inst. astronomy & Geophysics

Since the beginning of the history, Sinai Peninsula is one of the main geographic units of Egypt. It lies at the crossroads of the continents of Africa and Asia, and actually represents the Asiatic part of Egypt. It had always been evident that Sinai region has a great economic development. Now, Sinai is moving rapidly towards huge investments in development. Groundwater is one of the main resources for such development projects. One of the targeted areas for development is Ayun Musa area.

Ayun Musa area lies on the Eastern side of the Gulf of Suez. Generally, the area is flat, but includes a few minor topographic highs occurring at different localities in the central and eastern parts of the studied area. The geological succession at Ayun Musa area starts by the Miocene rocks represented by Marl, sandstone, and limestone at other parts with thickness up to 150 m. This is, uncomfortably, followed by lower Cretaceous Nubian sandstone. The Nubian series in the area is differentiated mainly into marine formations of upper Jurassic and Lower Cretaceous age with dominant thickness succession of clays and Limestone containing intercalated water-bearing sandstone with thickness up to 150 meters. This unit is followed by upper Jurassic rocks of Marl, sandy limestone interbeds with total thickness of 110meters.

Structurally, the Gulf of Suez depression is one of the most intensively faulted area in Egypt. Many tectonic movements have taken place in the area since early times of Precambrian. During the early cretaceous to late Miocene period, there was vertical uplifting of the earth's crust, together with the effect of the complicated tectonics that arose from anticlockwise rotation of Arabian relative to African plates during that period. Locally at Ayun Musa area, there is a major uplifting system extending ENE-WSW direction.

The geophysical investigation described in this work was carried out by DC resistivity survey utilizing Schlumberger array of electrode separation. Nineteen Vertical electrical sounding stations (VES) were measured in the area. The electrode separation started with $AB/2 = 2$ up to 1000 meters in successive steps. The distance between stations varies between 300 and 500 meter as to be more or less in grid pattern. However, some considerations had been taken into the account such as the land surface slope might not be more than 30 degree along the spread. Such points imply the basis and the applicability of the Schlumberger array. Altogether hindered us to make all the stations with the same spread direction.

キーワード: DC resistivity, groundwater, Sinai, Egypt

Keywords: DC resistivity, groundwater, Sinai, Egypt

SCG010-P03

会場:コンベンションホール

時間:5月25日 10:30-13:00

Tracing a buried pipeline using multi frequency Electromagnetic Tracing a buried pipeline using multi frequency Electromagnetic

gad el-qady^{1*}, Mohamed Ismail²

gad el-qady^{1*}, Mohamed Ismail²

¹Nat. Res. Inst. astronomy & Geophysics, ²Soil, Water and Env. Res. Ins., Egypt

¹Nat. Res. Inst. astronomy & Geophysics, ²Soil, Water and Env. Res. Ins., Egypt

In this paper I describe the application of multi frequency broadband electromagnetic techniques to locate buried pipelines. At desert or arid areas, regular geophysical surveys usually are difficult to carry out. EM techniques could be the best among geophysical techniques to be used for this target. The EM survey was performed using a Geophysical Survey Systems, Inc. GEM-300 multi-frequency electromagnetic profiler. It is a handheld electromagnetic induction-type instrument that measures in-phase and quadrature terrain conductivity without electrodes or direct soil contact. 6 different frequencies have been used simultaneously. The slice maps for conductivity distribution at each frequency could help to trace the extension of the pipeline.

Two pipelines were traced successfully with 20 meters spacing of each others.

キーワード: EM, conductivity, pipelines

Keywords: EM, conductivity, pipelines

SCG010-P04

会場:コンベンションホール

時間:5月25日 10:30-13:00

Inversion of self potential anomaly using particle swarm optimization method- A MATLAB environment

Inversion of self potential anomaly using particle swarm optimization method- A MATLAB environment

Yogesh Arora^{1*}, Deepak Kumar Gupta¹, Upendra K. Singh¹

Yogesh Arora^{1*}, Deepak Kumar Gupta¹, Upendra K. Singh¹

¹Indian School of Mines-Dhanbad (INDIA)

¹Indian School of Mines-Dhanbad (INDIA)

The paper deals with a novel method based on Particle Swarm Optimization (PSO) of the inversion of geoelectrical single and multiple self potential (SP) data anomaly of idealized body. The PSO algorithm is inspired from the observations of the social behavior of animals, such as bird flocking or fish schooling. PSO is also a population based optimization algorithm like other evolutionary algorithms. In this method, members of the population are called as the swarm and each individual within the swarm is called as the particle. During the solution process, each particle in the swarm explores the search space through their current positions and physical property of earth. The PSO based algorithm is developed in MATLAB environment that made users friendly and runs the algorithm to produce the results more efficiently with optimal error. This also gives advantages over other conventional environment. In order to check the stability and accuracy of the algorithm, the developed algorithm is implemented and tested on synthetic SP data and finally applied to three field data from Bakreshwar thermal region and Surda region of India and Vilarehlo da Raia region of Portugal. The performances by PSO are compared with previous results and these results are well correlated with standard squared error. In general it is observed that the PSO method is faster and its performance is better compared to previous squared error without any initial assumptions of SP anomaly

キーワード: SP data, Inversion, PSO, MATLAB

Keywords: SP data, Inversion, PSO, MATLAB

SCG010-P05

会場:コンベンションホール

時間:5月25日 10:30-13:00

Characteristics of Offshore Microseism Excitations Revealed by Noise Correlations Characteristics of Offshore Microseism Excitations Revealed by Noise Correlations

Ying-Nien Chen^{1*}, Yuancheng Gung², Tzu-Ying Huang², Ling-Yun Chiao¹, Junkee Rhie³
Ying-Nien Chen^{1*}, Yuancheng Gung², Tzu-Ying Huang², Ling-Yun Chiao¹, Junkee Rhie³

¹Institute of Oceanography, NTU, ²Department of Geosciences, NTU, ³SEES, SNU

¹Institute of Oceanography, NTU, ²Department of Geosciences, NTU, ³SEES, SNU

Taking advantage of a unique opportunity provided by a dense array of coastal short-period seismic stations and the diverse bathymetry around Taiwan, we examine how the long-range coherent ambient noises are influenced by surrounding ocean settings using the cross-correlation functions (CCFs) between pairs of stations. The effective energy of the CCFs derived from three components of short-period seismometer data falls within the frequency range of the short period secondary microseism (SPSM). The spatial variations mapped from the amplitude asymmetry of CCFs and source migration images evidently demonstrate that the SPSM strengths are closely linked to the drastic changes in offshore ocean characteristics and result in much stronger SPSM in the shallow and narrow Taiwan Strait than in deep open seas of eastern Taiwan. The temporal variations of the CCF strengths exhibit very good correlations with the wind speeds and wave heights, explicitly indicating the observed SPSM is dominated by local sources generated from wind-driven ocean waves around offshore Taiwan. We also look into the long-period microseism excitations from the continuous data recorded by broad-band stations in Taiwan, Japan and Korea. We present the preliminary results on how the microseism excitations of different frequency bands are influenced by the nearby offshore settings.

キーワード: short period secondary microseism, noise correlation, microseism excitations

Keywords: short period secondary microseism, noise correlation, microseism excitations

SCG010-P06

会場:コンベンションホール

時間:5月25日 10:30-13:00

Estimation of bedrock depth in Beijing, China, using microtremor array analysis Estimation of bedrock depth in Beijing, China, using microtremor array analysis

Peifen Xu^{1*}, Suqun Ling³, Weiyan Ran³, Qingxiao Liu³

Peifen Xu^{1*}, Suqun Ling³, Weiyan Ran³, Qingxiao Liu³

¹Institute of Geology and Geophysics, CAS, ²Geo-Analysis Institute Co. Ltd, Japan, ³Beijing Bureau of Geology

¹Institute of Geology and Geophysics, CAS, ²Geo-Analysis Institute Co. Ltd, Japan, ³Beijing Bureau of Geology

In order to draw the bedrock geological map in plain area of Beijing, we conducted array measurements of microtremors at eight sites in city Beijing and its adjacent area to estimate deep S-wave structures and obtained their pre-Cenozoic bedrock depth.

We use three aperture arrays with different radii between 40 to 300m at each observation site to collect the microtremor data and estimate the phase velocities of the fundamental mode of the Rayleigh waves from the vertical components at each site by using the SPAC (Spatial Auto-Correlation) method (Aki, 1957). The estimated frequency ranges for the phase velocities were about 0.3~3.9Hz. The 1-D structure models down to a depth of about 3 km were estimated by fitting of the observed and the theoretical phase velocities through a nonlinear inversion using a genetic algorithm (GA) (Cho et al., 1999).

The results reveal that the deepest bedrock located in Beijing rift, the depth is 1510 m, and the shallowest depth is only 170 m, located in Laiguangying uplift. The difference of the pre-Cenozoic bedrock depth between eight sites in plain area of Beijing is about 1300 m. The depth of the bedrock surface has changed dramatically, related to different tectonic units. Since the deep S-wave velocity structure of Beijing City and its adjacent area had been basically unknown, we delineate it for the first time in this article using array measurement of microtremors.

キーワード: bedrock depth, array measurements of microtremors, spatial auto-correlation method, estimate deep S-wave structures, plain area of Beijing, China

Keywords: bedrock depth, array measurements of microtremors, spatial auto-correlation method, estimate deep S-wave structures, plain area of Beijing, China

SCG010-P07

会場:コンベンションホール

時間:5月25日 10:30-13:00

2008年岩手宮城内陸地震時荒砥沢ダムで観測された段波形成のメカニズム The surging of the liquefied lateral flow in the Aratosawa reservoir at the initiation of huge landslide masses trigger

齊藤 隆志^{1*}, 松波孝治¹

Takashi Saito^{1*}, Koji MATSUNAMI¹

¹ 京都大学防災研究所

¹ DPRI, Kyoto Univ.

The Iwate-Miyagi Nairiku Earthquake in 2008 had triggered the huge landslides in the upper reach of Aratosawa reservoir. The initiation of these landslides are closely related to the strong ground motion, the geological setting, the spatial distribution of the old landslide masses, the liquefaction of the ground, and the rise-up of the groundwater after the dam construction. These particular conditions results in a chain of instabilities of mass in the watershed. The initiations of the rapid removal of the valley sediment were the liquefaction and lateral flows of the valleys which resulted in the prompt removals or disappearances of valley sediments. And the instabilities of the foot part of the slope had triggered the huge landslides in the upper reach. The Aratosawa reservoir was constructed and filled up in the year of 1998, this earthquake was the first terrible shaking of foot of the slopes with the 20 meters of groundwater rise-up. These processes were analyzed by the use of the archived observation results of water level of Aratosawa reservoir which had been missing because of power cut just after the main shock. The prompt first rise-up of the water level suggests the propagation of the hydraulic bore generated by the rush-in of the liquefied lateral flow in the reservoir, and the second slow rise-up of the water level corresponds to the creeping intrusion of the huge landslide masses into the reservoir. The density and the velocity of the first liquefied lateral flow were large enough to crash the bridge in upper reach of the Shitsumukukisawa valley.

キーワード: 岩手宮城内陸地震, 荒砥沢ダム, 段波, 液状化, 地すべり

Keywords: Iwate-Miyagi Nairiku Earthquake, Aratosawa Reservoir, hydraulic bore, liquefaction, landslide

SCG010-P08

会場:コンベンションホール

時間:5月25日 10:30-13:00

Earthquakes induced landslides reflected by DC resistivity and high frequency electromagnetic data Earthquakes induced landslides reflected by DC resistivity and high frequency electromagnetic data

Dragos Armand Stanica^{1*}

Dragos Armand Stanica^{1*}

¹Inst. of Geodynamics, Romanian Academy

¹Inst. of Geodynamics, Romanian Academy

The main objective of this paper is to present the DC resistivity and high frequency electromagnetic (HFEM) monitoring system that may provide in near real-time the landslide hazard level related to the intermediate depth earthquakes occurred in the seismic active Vrancea zone (Romania). Thus, the specific methodology and software packages have been applied for obtaining all the important HFEM parameters and to point out their anomalous behavior versus the specific pattern pre-established in non geodynamic conditions. Consequently, by analyzing the data carried out at the Provita de Sus landslide (test-site), placed in Subcarpathians area, at about 100 km far away of epicenter zone, it was possible to assign the increase of the landslide motion related to the local active fault which has been reactivated by the earthquakes of magnitude higher than 4, triggered in the Vrancea zone in a span of two years (2009 and 2010). There were three more important aspects that became the major selection criteria of this landslide as test site: (i) it is an earthquake triggered landslide followed by post seismic slow slipping ground motion that can be monitored; (ii) it is situated nearby Provita de Sus locality and can endanger life and property, owing to a high probability of flood, which might be produced by damming Provita river due to rock falls into the watercourse; (iii) the existence of logistic base (Geodynamic Observatory Provita de Sus) able to supply optimal monitoring conditions and wireless connection with the Center of Bucharest. In the end, this paper illustrates the stage of the monitoring system implementation and the results highlight the utility of merging the electric (DC resistivity) and electromagnetic precursory parameters (normalised function Bzn, anisotropy, skewness and strike) with different 2D tomographic images associated with post seismic landslide processes. Subsequently, in the Provita de Sus test site, it was possible to provide information regarding the both specific ground motion produced by the interference between seismic triggered factors with local geotectonic conditions and landslide hazard level.

キーワード: EM data, earthquakes, landslides

Keywords: EM data, earthquakes, landslides

SCG010-P09

会場:コンベンションホール

時間:5月25日 10:30-13:00

2008年岩手宮城内陸地震時荒砥沢ダム上流で発生した地すべり移動の三次元的検討 The 3D analyses of the huge landslide mass movements triggered by the Iwate-Miyagi nairiku Earthquake in the upper reach

齊藤 隆志^{1*}, 松波 孝治¹

Takashi Saito^{1*}, Koji Matsunami¹

¹ 齊藤隆志

¹ Takashi SAITO

The Iwate-Miyagi Nairiku Earthquake in 2008 had triggered the huge landslides in the upper reach of Aratosawa reservoir. The huge mass movements had occurred on the adjacent slopes of the upper reach of the reservoir. The initiation of the huge mass was directly the strong ground motion of the main shock. The following liquefaction had occurred in the valley bottom of the slopes, and valley bottom sediments run out from valley. Several parts or masses had triggered to move to down slope after the rush-in of the lateral flow from the valleys. The cross sectional explanations of the landslide mass movements were reported by The Japan Landslide Society(2009). The behaviors of huge landslide masses were too complicate to discuss in two dimensions with single cross section. Then 3D analyses were tried to clarify the movements of the huge landslide masses using DEMs.

キーワード: 岩手宮城内陸地震, 荒砥沢ダム, 地すべり, 三次元的検討

Keywords: Iwate-Miyagi Nairiku Earthquake, Aratosawa Reservoir, landslide, 3D analyses

SCG010-P10

会場:コンベンションホール

時間:5月25日 10:30-13:00

荒砥沢巨大地すべり山塊の地震に誘発された傾斜、上昇・下降運動 Earthquake-triggered tilts, up and down motions of a huge mass in the Aratozawa Land-slide Area

松波 孝治^{1*}, 森井 互¹, 齊藤隆志¹

Koji Matsunami^{1*}, Wataru MORII¹, Takashi SAITO¹

¹ 京都大学防災研究所

¹Disast. Prev. Res. Inst. of Kyoto Univ.

The 2008 Iwate-Miyagi Nairiku Earthquake induced a huge landslide at the upper reaches of Aratozawa reservoir. The movement of a huge mass that is 600m*500m in size reached to about 340m in distance. We performed aftershock observations in the Aratozawa area using broad-band strong-motion seismometers. We detected transient long-period horizontal and vertical ground motions in aftershock seismograms. The long-period horizontal and vertical ground motions are due to tilts and up/ down motions of the ground triggered by aftershocks, respectively. Site amplification characteristics for the mass show a significant peak at around 1 Hz, suggesting a resonant vibration of the mass due to the incidence of seismic waves. The results obtained in this study indicate instability of the huge mass that has experienced a large landslide.

キーワード: 地すべり, 荒砥沢, 岩手宮城内陸地震, 地震応答, 地盤傾斜, 地盤上昇下降

Keywords: landslide, Aratosawa Reservoir, Iwate-Miyagi Nairiku Earthquake, seismic response, ground tilting, ground rising and descending