

5線熱パルスセンサーを用いた飽和・不飽和水分フラックスの推定 Estimation of Water Flux in Variably Saturated Soil with a Penta-Needle Heat Pulse Probe

坂井 勝^{1*}, 加藤 薫², スコット ジョーンズ³
SAKAI, Masaru^{1*}, KATO, Kaoru², JONES, Scott B.³

¹ 三重大学大学院生物資源学研究科, ² 三重大学生物資源学部, ³ ユタ州立大学 植物・土壌・気象学科

¹Graduate school of Bioresources, Mie University, ²Faculty of Bioresources, Mie University, ³Department of Plants, Soils and Climate

The penta-needle heat pulse probe (PHPP) employs a central heater needle surrounded by an orthogonal arrangement of four thermistor needles. By inversely fitting an analytical solution for two-dimensional heat transport with an infinite line source, both components of the flux in a plane normal to the axis of the PHPP needles, J_x and J_y , thermal conductivity, and thermal diffusivity can be estimated. Using estimated J_x and J_y , water flux magnitude and direction can also be calculated. In this study, the applicability of PHPP estimations was tested in both of saturated and unsaturated water flows in sand. Laboratory column experiments under steady-state saturated (flux range of 180-430 cm/d) and unsaturated (1.9-130 cm/d) water flow conditions were conducted. Two PHPPs were installed with orientations to yield water flow directions of 30° and 45°. In case of saturated flow condition, estimated J_x and J_y agreed well with measured water fluxes (less than 25 % relative errors), resulting in good estimations of water flow magnitudes and directions. In case of unsaturated flow condition, water fluxes estimated by PHPP with 30° agreed well with measured flux. However, one component (J_x) from PHPP with 45° showed a constant discrepancy (-55 cm/d) in any flow rates. This result indicates that differences of constant resistance between sand and needle, heterogeneity of the sand-water-air system, and heterogeneity of microscopic unsaturated flow in measurement area resulting from water content changes (0.38 cm³/cm³ for saturated flow to 0.10 cm³/cm³ for unsaturated flow) affect PHPP estimations.