Japan Geoscience Union Meeting 2012

(May 20-25 2012 at Makuhari, Chiba, Japan)

©2012. Japan Geoscience Union. All Rights Reserved.



HGM02-08

会場:301A

## ナノライムや樹脂を用いた岩石の強化実験 -大谷石、琉球石灰岩、安山岩を中心に-Experimental study of rock strengthening tuff, limestone, and andesite by using nanolime and other consolidants

宋 苑瑞  $1^*$ , アンドラス モルゴス  $2^2$  SONG, Wonsuh  $1^*$ , MORGOS, Andras  $2^2$ 

## 1 筑波大学陸域環境研究センター, 2 東京芸術大学大学院美術研究科

<sup>1</sup>Terrestrial Environment Research Center, University of Tsukuba, <sup>2</sup>Graduate school of Conservation, Tokyo University of the Arts

This study is focussing to the efficiency and evaluation of up-to-date consolidants (a non-aquaeous collodial nanolime (Ca(OH)2) suspension, a well-known oligomeric tetraethoxysilane product (Wacker SILRESR BS OH 100), an extremely low viscous epoxy resin (Araldite 2020) and for cultural heritage the most frequently used thermoplastic acrylic resin (ParaloidTM B-72 or also called AcryloidTM B-72) which is known from its good durability, high transparency and non-yellowing film-properties for the consolidation of Oya-tuff. The consolidation effect of nanolime particles were also studied on Ryukyu-limestone and Indonesian basaltic andesite.

The actuality of this study is given by the fact, that degradation (corrosion) of the rocks is incredible speeded up in the last decades by the increased air-pollution e.g. acid rain etc. This makes the stone buildings, objects and sites much more vulnerable. The stone material weakens and looses its original binder to a considerable depth. Consecutively many stone historical constructions require consolidation, conservation and restoration in recent days.

The consolidants were tested by the measurement of tensile strength, Equotip surface hardness, p-wave velocity.

キーワード: 岩石強化, ナノライム, 樹脂, 凝灰岩, 石灰岩, 安山岩 Keywords: Rock strengthening, nanolime, resin, tuff, limestone, andesite