

JEM-GLIMS ミッションにおける運用計画とデータ処理システム Operation Plan and Data Processing System of JEM-GLIMS Mission

佐藤 光輝^{1*}, 牛尾 知雄², 森本 健志², 山崎 敦³, 鈴木 睦³, 菊池 雅行⁴, 芳原 容英⁵

SATO, Mitsuteru^{1*}, USHIO, Tomoo², MORIMOTO, Takeshi², YAMAZAKI, Atsushi³, SUZUKI, Makoto³, Masayuki Kikuchi⁴, HOBARA, Yasuhide⁵

¹ 北海道大学大学院理学研究院, ² 大阪大学大学院工学研究科, ³ 宇宙科学研究所, ⁴ 国立極地研究所, ⁵ 電気通信大学情報・通信工学科

¹Faculty of Science, Hokkaido University, ²Graduate School of Engineering, Osaka University, ³ISAS/JAXA, ⁴NIPR, ⁵Faculty of Electro-Communications, The University of Electro-Communications

In order to study the occurrence conditions and generation mechanisms of Transient Luminous Events (TLEs), lightning and TLE observations named JEM-GLIMS (Global Lightning and sprIte MeasurementS on JEM-EF) will start this year. JEM-GLIMS instruments will be launched by H-IIB rocket with HTV carrier and installed at Exposed Facility of Japanese Experiment Module (JEM-EF) of International Space Station (ISS). In this mission two kinds of optical instruments and two sets of radio receivers are employed. After the installation, JEM-GLIMS instruments will be checked their health during the initial operation phase, which is planned to take a few months. After the initial operation, nominal operation phase will start. In this nominal operation, JEM-GLIMS instruments will be operated by TLE mode mainly, which is the observation mode of lightning and TLEs when ISS located night-side. All science data acquired by optical and electromagnetic instruments are continuously transmitted to the ground with a 5.8 kbps telemetry speed, which enables to obtain 53 optically transient events. All these level-0 data are stored in JAXA data server and transmitted to ISAS/JAXA data processing system. After these level-0 data are converted into level-1 data, they will be distributed to the JEM-GLIMS mission members. We will present the mission schedule, operation mode and data processing system more in detail at the presentation.

キーワード: 雷放電, スプライト, JEM-GLIMS, 国際宇宙ステーション, 運用, データ処理

Keywords: lightning, sprite, JEM-GLIMS, ISS, Operation, Data Processing

航空機観測によるスプライトストリーマの立体構造 Three-dimensional Structure of Sprite Streamers by Aircraft observation

小林 縫^{1*}, 佐藤光輝¹, 高橋幸弘¹, 工藤剛史¹, 三宮佑介¹, 山田大志¹, NHK 宇宙の渚プロジェクト², H. C. Stenbaek-Nielsen³, Matthew G. Mcharg⁴, Ryan Haaland⁵, KAMMAE Takeshi³, Steve A. Cummer⁶, Yoav Yair⁷, Walter Lyons⁸
KOBAYASHI, Nui^{1*}, SATO Mitsuteru¹, TAKAHASHI Yukihiro¹, KUDO Takeshi¹, SANMIYA Yusuke¹, YAMADA Taishi¹, NHK Cosmic Shore Project², STENBAEK-NIELSEN, Hans C.³, MCHARG, Matthew G.⁴, HAALAND Ryan⁵, KAMMAE Takeshi³, CUMMER, Steve A.⁶, YAIR yoav⁷, LYONS Walter⁸

¹北海道大学理学部地球惑星科学科, ²NHK 制作局 科学環境番組部, ³Univ. of Alaska, Fairbanks, AK, United States, ⁴US Airforce Academy, Colorado Springs, CO, United States, ⁵Fort Lewis College, Durango, CO, United States, ⁶Duke University, Durham, NC, United States, ⁷Open University of Israel, Ra'anana, Israel, ⁸FMA Research, Ft Collins, CO, United States
¹Dept. of CosmoSciences, Hokkaido Univ., ²NHK, ³Univ. of Alaska, Fairbanks, AK, United States, ⁴US Airforce Academy, Colorado Springs, CO, United States, ⁵Fort Lewis College, Durango, CO, United States, ⁶Duke University, Durham, NC, United States, ⁷Open University of Israel, Ra'anana, Israel, ⁸FMA Research, Ft Collins, CO, United States

The spatial distributions and the three-dimensional structures of sprite streamers are the key parameters to reveal the occurrence conditions and the development mechanisms of them. However the three-dimensional structures of sprite streamers have never been identified, because it is difficult to capture images from multiple ground-based observation sites simultaneously. Moreover, since the time constant of sprite emissions is about a few milliseconds, it is difficult to capture detailed spatial and time evolution of sprite streamer without using high-speed cameras.

In this study, we study the characteristic of the spatial and time evolution of sprite streamers, especially three-dimensional structures which have never been revealed, by analyzing the data of sprite images observed by high-speed cameras from jet aircraft.

On November 28 and December 3, 2010 in winter Japan, we have carried out optical observations using a high-speed camera and a high-vision CCD camera from a jet aircraft under collaboration between Japan Broadcasting Corporation (NHK) and Hokkaido University. Using the high-speed camera, it is possible to capture images with a sampling rate of 8,300 frames per second (fps). Using the high-vision CCD camera, it is possible to capture true color images of sprites with a sampling rate of 30 fps. During the two observation flights, we have succeeded to capture 28 sprite events. We have analyzed a columniform sprite observed at 13:12:35UT on November 28, 2010 and revealed the spatial and time evolution of the sprite streamers. This sprite consists of 4 distinct sprite elements. Each element begins as a bead between 66 and 78 km altitude and moved downward with a speed of 0.8×10^7 - 1.1×10^7 m/s and a remnant emission stayed at the region where the bead passed through. The altitudes of upper and lower edge of columns are estimated to be 85-90 km and 65-70 km, respectively. It is found that these results are comparable with previous results derived from the sprite observations in North America.

On the other hand, we have carried out simultaneous optical observations using the high-speed cameras and high-vision cameras and WATEC CCD cameras from two jet aircrafts in summer US. In the period of June 27-July 10, 2011, aircraft observations were conducted in 8 nights totally, and succeeded to capture sprite images for over 40 events by the high-speed cameras in each aircraft simultaneously. Using these images, we have performed triangulation analysis for two sprite events observed at 05:20:49UT on July 3, 2011 and at 08:54:13UT on July 5, 2011, and estimated the spatial distributions. It was found that sprites were occurred with a horizontal shift from the location of the parent CG discharge with distance from 60 to 80 km. This result may suggest that there are certain occurrence conditions produced by not only a vertical current of the parent CG discharge but also other factors such as horizontal lightning currents, atmospheric gravity waves and micro meteors. We also studied a columniform sprite with upward streamers observed at 05:20:49UT from July 3, 2011 and performed triangulated analysis to identify the three-dimensional structures. It was found that upward streamers grew radially from a bottom part of the downward streamer. It was also found that the altitudes of upper and lower edge of upward streamers are 76-78 km and 72-73 km, respectively, and that diameter and the velocity of the upward streamers are about 0.3 km and 5.5×10^6 - 5.6×10^6 m/s. On the other hand, the altitude of upper and lower edge of downward streamer is estimated to be 81 km and 71 km, respectively. The diameter and the velocity of downward streamer were estimated to be about 0.7 km and 4.7×10^6 m/s, respectively.

At the presentation, we will show the characteristic of the spatial and time evolution of sprite streamers observed in winter Japan and in summer US more in detail.

キーワード: スプライト, スプライトストリーマの立体構造, スプライトの水平空間分布

Keywords: sprite, Three-dimensional structure of sprite streamers, spatial distributions of sprite