

ドイツ Ketzin CCS 実証試験サイトにおける地震波アクロスと地震計アレーによる タイムラプスのシミュレーション Time-lapse simulation for the Ketzin (Germany) CCS site assuming a single seismic ACROSS and multi-seismic receivers

笠原 順三^{1*}, 高梨 将², 加藤 文人², 羽佐田 葉子³, ステファン ルース⁴, クリストファー ジュリン⁵
Junzo Kasahara^{1*}, Mamoru Takanashi², Ayato Kato², Yoko Hasada³, Stefan Lueth⁴, Christopher Juhlin⁵

¹ 東京海洋大学, ² 石油天然ガス・金属鉱物資源機構, ³ 大和探査(株), ⁴ GFZ, ドイツ, ⁵ ウプサラ大学

¹Tokyo University of Marine Science and Technology, ²JOGMEC, ³Daiwa Exploration and Consulting Co. Ltd., ⁴GFZ, Germany, ⁵Uppsala University

Time-lapse-studies of the physical state of the injection zones or fractured zones is a key component in the CCS, CO₂-EOR and shale-gas development. Monitoring systems using the seismic-ACROSS can be one of the most suitable methods for these purposes. We have made simulations assuming a single ACROSS source and a multi-seismometer- array installed at the Ketzin pilot site for CO₂ storage in Germany. At Ketzin, CO₂ has been injected since July, 2008. About 62 ktons of super-critical CO₂ have been injected to date at about 630-650 m depth, and injection will continue into 2013. To monitor how the injected CO₂ behaves after injection is extremely important for studying the long term behavior of a storage site. The objectives of this study are to find the most suitable locations for an ACROSS-source and receivers at the Ketzin site given infrastructure constraints. Preliminary results using the velocity-density structure site model shows that a rectangular injection zone 200 m wide and 10 m thick at 665 m depth is well imaged. This result encourages us to plan for using an ACROSS-source for time-lapse-studies to monitor the migration of injected CO₂ at Ketzin, even after injection has finished.

キーワード: タイムラプス, CCS, アクロス, モニタリング, 地震波, タイムリバーサル法

Keywords: Time lapse, CCS, ACROSS, monitoring, seismic waves, timerevesal method