

CO₂ 地中貯留における流体流動-岩石力学連成解析：ナチュラル・アナログ研究としての松代事象への適用 Coupled fluid flow and geomechanical modeling in geological CO₂ storage: Application to Matsushiro phenomena

船津 貴弘^{1*}, 奥山 康子¹, 雷 興林¹, 中尾 信典¹
Takahiro Funatsu^{1*}, Yasuko Okuyama¹, Xinglin Lei¹, Shinsuke Nakao¹

¹(独) 産業技術総合研究所地圏資源環境研究部門

¹Institute of Geo-Resources and Environment, AIST

The mechanical responses of CO₂ reservoir and the caprock around the storage region become crucial for Japanese geological CO₂ storage (GCS) after the M9.0 East Japan earthquake on March 11, 2011. The CCS Research Committee, METI (Ministry of Economy, Trade and Industry), recommended to screen out areas having a large-scale faults in the process of selection of storage site for 105t-scale demonstration (2009). Although the site for the planned demonstration adequately selected, we do not exclude fully at present the possibility of GCS reservoir failure and/or leakage of stored CO₂ from GCS site(s) elsewhere in Japan caused by geomechanical motions.

The examples of such phenomena are the re-activation of pre-existing faults, induced seismicity, reservoir failure and unintended uplift and so on, some of which are observed in an actual demonstration site (Mathieson et al., 2009; Vasco et al., 2010; Onuma et al., 2011).

The unintended phenomena listed above are essentially connected with stress field changes due to the increase in pore pressure, around the area of GCS, which is inevitable as GCS injects pressurized CO₂ into an underground reservoir. The rise in pore pressure reduces an effective confining stress to modify the conditions toward the critical failure line of Mohr-Coulomb law. The change in pore pressure is most probably cause micro-scale (or, pore-scale) deformations within the rocks, which will give rise to the changes in rock permeability. The permeability change probably cause a change in fluid flow underground in the next step, which will promote further rock deformation and then change in fluid flow. The sequence of process can be analyzed by a coupled analysis using fluid flows simulator for rock media and that calculating the geomechanical process under the changing pore pressures. The TOUGH-FLAC code is a good and working example of this coupled simulator, being applied to follow the CO₂ motion within faulted and tectonically active formations (Rudqvist et al., 2007, 2008).

We consider that the coupled simulation of fluid flow and geomechanics, exemplified by TOUGH-FLAC simulation collaborating with LBNL, is the most important tool in developing the scheme to assess the fluid-mechanical conditions around the underground storage regions of CO₂.

As not enough data such as rock deformation related to fluid flow is available from GCS site for evaluation of TOUGH-FLAC code applicability to Japanese geological condition, we investigate the Matsushiro field, Nagano, central Japan is selected for our natural analogue study. The Matsushiro field is famous for the earthquake swarm associated with the CO₂-rich fluid upwelling during the period of 1965-1967. The Matsushiro phenomena was previously studied by using TOUGH-FLAC (Cappa et al., 2009), however, the geological model was simplified very much, so it is afraid that the possibly important geological features can be missed.

In this study, we modified their model based on the various field and laboratory data and re-constructed the geological model with three layered strata according to P-wave velocity profile.

TOUGH-FLAC simulation has been conducted using updated geological model. The simulation results indicated the ground uplift due to fluid injection and the magnitude of the ground uplift is reasonably agree with actual observation in Matsushiro field during the swarm.

キーワード: 流体流動-岩石力学連成解析, 岩石力学, CO₂ 地中貯留, ナチュラル・アナログ研究, 松代事象

Keywords: Coupled fluid flow geomechanical modelling, Geomechanics, Geological CO₂ storage, Natural analogue, Matsushiro phenomena