

V_p-V_sによるCO₂挙動モニタリングについて実験的手法に基づく検討 The potential of V_p and V_s monitoring for MVA program of offshore CCS project

北村 圭吾^{1*}, 薛 自求²
Keigo Kitamura^{1*}, Ziqiu XUE²

¹九州大学 WPI-I²CNER, ²地球環境産業技術研究機構

¹WPI-I²CNER Kyushu University, ²Research Institute of Innovative Technology for the Earth

For the safe operation of CCS, we are required to monitor the CO₂ behavior and to accurately account for the storage volume of CO₂ in deep reservoirs. It is well-known that the P-wave velocity measurements (V_p) can be used for monitoring the CO₂ behavior in deep reservoirs. However, it is difficult to accurately estimate the storage volume of CO₂ by only using V_p. Takahashi (2000) indicated the potential of S-wave velocity for monitoring of fluid behavior and accounting for the storage volume of natural gas in deep reservoirs. S-wave monitoring can be achieved by deploying a permanent ocean bottom cable(OBC) system at the off-shore CCS sites. In our own study, we conducted a simultaneous measurement of V_p and V_s of porous sandstone by injecting various types of fluids under set in-situ pressure and temperature conditions. For this study, we use the Tako sandstone, which is an early Miocene marine sandstone, mainly composed of quartz and plagioclase. Tako sandstone has near 10mDarcy of permeability and almost 24% porosity. The sample was cut into a column shape (5cm in diameter and 10cm in length), and polished on both ends (1PV=47 ml). In this study, we tried to estimate CO₂ saturation, and to monitor the CO₂ behavior in porous sandstone by measuring V_p and V_s. First, we injected near 1.3PV water into the vacuumed specimen (Water injection). After this process, over 2.2PV CO₂ is injected into the water saturated specimen (Drainage). Finally, CO₂-saturated water over 2.3 PV is re-injected into the CO₂-injected specimen (Imbibition). We illustrated the V_p-V_s relationships of all the processes. This V_p-V_s relationship diagram clearly illustrates the obvious differences between water injection and drainage. On the other hand, drainage and imbibition show the similar tendency of V_p-V_s change with injecting CO₂ and CO₂-saturated water. These changes indicate the changes of CO₂ saturation during drainage and imbibition stage. This result suggests the potential to estimate CO₂ saturation by using the V_p-V_s relationship. Additionally, V_p does not recover to pre-drainage levels after end of imbibition process. This V_p difference is considered to be the effect of residual trapped CO₂. This result also indicates the potential of monitoring the residual trapped CO₂ from seismic wave velocities.

キーワード: P 波速度, S 波速度, 多孔質砂岩, CO₂ 飽和度, MVA

Keywords: P-wave velocity, S-wave velocity, Porous sandstone, CO₂ saturation, MVA