Japan Geoscience Union Meeting 2013

(May 19-24 2013 at Makuhari, Chiba, Japan)

©2013. Japan Geoscience Union. All Rights Reserved.



MIS31-P01

会場:コンベンションホール

時間:5月19日18:15-19:30

Al-SiO 系彗星状粒子成長に関する研究 Comet-like particle growth in Al-SiO

鈴木 仁志^{1*} Hitoshi Suzuki^{1*}

1 東北学院大学工学部電子工学科

¹Department of Electronic Engineering, Tohoku Gakuin University

When a metal was evaporated in an inert gas atmosphere, a vapor of the metal cooled and formed nanoparticles by collision with the inert gas molecules. The nanoparticles grow by coalescence growth and rise on a convection flow of the gas like a smoke. The nanoparticle production method is called a gas evaporation method.

SiO consists of Si and SiO₂. Metal nanoparticles covered with an amorphous SiO layer can be produced by evaporating a mixture powder of the SiO and a metal. However, comet-like particles were grown in the rising smoke using a few kinds of metals¹⁾. In the case of Cr-SiO particle produced by the gas evaporation method, Si was dissolved in a Cr drop at a high temperature region in a smoke. The Si dissolved in the Cr drop was crystallized by supersaturation on cooling process. The Si crystal grew like a tail and the Cr drop became $CrSi_2$ crystal like a core of come-like particle. The comet-like particle grew around the eutectic point between Si and $CrSi_2$. Thus, the comet-like particle grew like a VLS mechanism.

Since Al has a eutectic point with Si, the comet-like particle growth was expected using a mixture powder of Al and SiO. Production of the comet-like particles was tried by the gas evaporation method.

Comet like-particles were produced by evaporation of Al and SiO mixture powder in Ar gas $1.0*10^4$ Pa. The particles were observed by TEM, and analyzed by EDS. It was found that a core part of the comet-like particle consisted of Al or Al and Si, a tail part consisted of Al and O by EDS analysis. ED patterns of the particles indicated that structure of the core part was Si and Al crystals, and the tail part was Al₂O₃ single crystal. Composition of Al and Si in the core part depended on the ratio of Al and Si in the mixture powder. The tail part structure was always Al₂O₃ in every composition. The comet-like particles were grown like a VLS mechanism with SiO2 reduction and Al oxidation.

1) C. Kaito et.al, J. Crystal Growth 200 (1999) 271.

キーワード: ナノ粒子, ひげ結晶, アルミ, シリコン, アルミナ, 透過型電子顕微鏡法 Keywords: Nanoparticle, Whisker, Al, Si, Al₂O₃, TEM