

ハイスピードカメラ観測によるスプライトストリーマの分岐条件 Split Condition of Sprite Streamer Tips Derived From High-Speed Camera Observations

三原 正大^{1*}, 佐藤 光輝¹, 小林 縫¹, 高橋 幸弘¹, 井上 智広², H. Stenbaek-Nielsen³, M. McHarg⁴, R. Haaland⁵, Takeshi Kammae³, Yoav Yair⁶, W. Lyons⁷, S. Cummer⁸, NHK 宇宙の渚プロジェクト²

Mihara Masahiro^{1*}, Mitsuteru Sato¹, Nui Kobayashi¹, Yukihiro Takahashi¹, T. Inoue², H. Stenbaek-Nielsen³, M. McHarg⁴, R. Haaland⁵, Takeshi Kammae³, Yoav Yair⁶, W. Lyons⁷, S. Cummer⁸, NHK Cosmic Shore Project²

¹ 北海道大学 大学院理学院 宇宙理学専攻, ² 日本放送協会, ³ アラスカ大学フェアバンクス校, ⁴ アメリカ空軍士官学校, ⁵ フォートルイス大学, ⁶ オープン大学, ⁷ FMA Research, ⁸ デューク大学

¹Department of Cosmospice, Graduate School of science, Hokkaido University, ²Japan Broadcasting Corp, ³University of Alaska Fairbanks, ⁴US Air Force Academy, ⁵Fort Lewis College, ⁶Open University, ⁷FMA Research, ⁸Duke University

In order to clarify the split condition of sprite streamer tips, the detailed spatial and temporal development of sprite streamers are the key physical properties. According to the previous ground-based observations using high-speed cameras, it was found that streamer tips usually appear at around ~80 km at the initial stage of the sprite development and propagate downward with an accelerated and expanded motions. After they reach ~70 km altitude, they tend to start splitting. However, detailed splitting mechanism of streamer tips is not fully understood yet since it is difficult to capture the detailed development and fine structures of the splitting streamer tips. In order to specify the detailed spatiotemporal evolution of sprite streamers and to identify the physical parameters determining the splitting condition of streamer tips, we have analyzed image data obtained by high-speed cameras onboard two jet aircrafts.

In the period from June 27 to July 10, 2011, we have succeeded in capturing 12 sprite events over the Great Plains in summer US, where the multiple splits of streamer tips are clearly measured by high-speed cameras with a sampling rate of 8300 fps. It was found that streamer tips initiated from approximately 75 km altitude propagate downward with an exponential increase of the brightness before they start splitting first. We estimated brightness changes of streamer tips at each frame of image data recorded by the high-speed cameras, and we also estimated the ratio of the streamer tip brightness just after the tip splits to that just before the tip reaches next split. It is found that the ratio of the brightness at the streamer tip initiation to the brightness just before the first split becomes greater than 1.0. However, it is found that the ratio of the brightness of 1st (2nd) split to 2nd (3rd) split becomes about 1.0. At the presentation, we will show more detailed results.