

## K-Ar年代その場計測装置の開発状況 Development of an in-situ K-Ar dating instrument

長 勇一郎<sup>1\*</sup>, 三浦 弥生<sup>2</sup>, 諸田 智克<sup>3</sup>, 亀田 真吾<sup>4</sup>, 吉岡 和夫<sup>5</sup>, 岡崎 隆司<sup>6</sup>, 並木 則行<sup>7</sup>, 石橋 高<sup>7</sup>, 大野 宗祐<sup>7</sup>, 小林 正規<sup>7</sup>, 荒井 朋子<sup>7</sup>, 千秋 博紀<sup>7</sup>, 和田 浩二<sup>7</sup>, 杉田 精司<sup>8</sup>

Yuichiro Cho<sup>1\*</sup>, Yayoi N. Miura<sup>2</sup>, Tomokatsu Morota<sup>3</sup>, Shingo Kameda<sup>4</sup>, Kazuo Yoshioka<sup>5</sup>, Ryuji Okazaki<sup>6</sup>, Noriyuki Namiki<sup>7</sup>, Ko Ishibashi<sup>7</sup>, Sohsoke Ohno<sup>7</sup>, Masanori Kobayashi<sup>7</sup>, Tomoko Arai<sup>7</sup>, Hiroki Senshu<sup>7</sup>, Koji Wada<sup>7</sup>, Seiji Sugita<sup>8</sup>

<sup>1</sup> 東京大学 理学系研究科 地球惑星科学専攻, <sup>2</sup> 東京大学 地震研究所, <sup>3</sup> 名古屋大学, <sup>4</sup> 立教大学, <sup>5</sup> 宇宙航空研究開発機構 宇宙科学研究所, <sup>6</sup> 九州大学, <sup>7</sup> 千葉工業大学 惑星探査研究センター, <sup>8</sup> 東京大学 新領域創成科学研究科 複雑理工学専攻

<sup>1</sup>Dept. Earth & Planetary Science, Univ. Tokyo, <sup>2</sup>Earthquake Research Institute, Univ. Tokyo, <sup>3</sup>Nagoya University, <sup>4</sup>Rikkyo University, <sup>5</sup>ISAS/JAXA, <sup>6</sup>Kyushu University, <sup>7</sup>PERC, Chiba Institute of Technology, <sup>8</sup>Dept. Complexity Science and Engineering, Univ. Tokyo

We have been developing an in-situ dating method based on the K-Ar system for future planetary landing missions. The K-Ar dating method employs radiometric decay of  $^{40}\text{K}$  into  $^{40}\text{Ar}$  with half-life of 1.25 Gyr [Steiger & Jager, 1977]. Our system measures K and Ar with two techniques at the same laser irradiation spot on a sample: laser-induced breakdown spectroscopy (LIBS) and quadrupole mass spectrometry (QMS), respectively (LIBS-QMS system). Potassium and argon are extracted from a sample simultaneously by the laser ablation, in which the sample is vaporized by a series of intense ( $> 1\text{GW}/\text{cm}^2$ ) laser pulses. We used a Nd:YAG laser with 6 ns of pulse width and 1064 nm of wavelength (Surelite I, Continuum). The laser energy was set at 100 mJ and the spot diameter was  $\sim 500$  micron. The pulse repetition rate was 2 Hz. We used a small spectrometer with a charge couple device (CCD) (HR 2000+, Ocean Photonics Inc.), to simulate a small and simple spectrometer for the spacecraft missions. The light emission from plasma was collected by a lens and transmitted through an optical fiber to the entrance slit of the spectrometer. The spectral acquisition time was 1 ms and the shutter was opened before the laser pulses reached the sample; time-integrated plasma emission was observed to simulate a non-gated operations on the planetary missions. The intensity of the K line at 769 nm was normalized by that of the O emission line at 777 nm in order to reduce signal fluctuations.

The gas extracted from the sample was purified with a Ti-Zr getter. The purified Ar gas was trapped on the charcoal trap cooled by liquid nitrogen. The Ar isotopes,  $^{36}\text{Ar}$ ,  $^{38}\text{Ar}$  and  $^{40}\text{Ar}$ , are measured with the quadrupole mass spectrometer. Blank mass spectra were also acquired and subtracted from the main data. Finally, the volume of laser ablation pit was measured with a laser microscope to obtain the concentration of  $^{40}\text{Ar}$  within the pit.

In order to construct a calibration curve for  $\text{K}_2\text{O}$ , 24 geologic samples with known  $\text{K}_2\text{O}$  concentration were measured with our LIBS system. The calibration line can be fitted by a power law:  $I=0.11C^{0.55}-0.00686$ , where I and C are the signal intensity and  $\text{K}_2\text{O}$  concentration (wt%). The detection limit and the quantification limit of our LIBS system were 300 ppm and 1 wt%, respectively. Also the detection limits of  $^{36}\text{Ar}$  and  $^{40}\text{Ar}$  were measured to be  $2 \times 10^{-12}$  and  $2 \times 10^{-11}$  [cm<sup>3</sup> STP], respectively, in this study. As a result, if a rover encounters a rock with  $\text{K}_2\text{O}=1$  wt%, as Mars Exploration Rover found at Gusev crater, our instrument is expected to measure K and Ar from a rock sample; i.e., the error in LIBS measurement would be  $<20\%$  and the S/N for QMS signals would be sufficient ( $\sim 200$ ).

Using our instrument, we measured three samples whose K concentrations and ages have been measured previously with flame photometry and a sector mass spectrometer: a hornblende ( $\text{K}_2\text{O}=1.12$  wt%, 1.75 Ga), a biotite ( $\text{K}_2\text{O}=8.44$  wt%, 1.79 Ga), and a plagioclase ( $\text{K}_2\text{O}=1.42$  wt%, 1.77 Ga) [Nagao, unpublished data]. We obtained the model ages of  $2.1 \pm 0.3$ ,  $1.8 \pm 0.2$ , and  $2.0 \pm 0.3$  Ga, respectively.

Since the three samples have similar ages and different K concentrations, we should be able to construct a "virtual" isochron by plotting the concentrations of K and  $^{40}\text{Ar}_{rad}$ . The slope of the isochron simulated with our experimental data yields 1.34 Ga of age. The data with known values yields 1.79 Ga. Such underestimation probably results from both overestimation for K and underestimation for  $^{40}\text{Ar}$  in the biotite data, which have large weight for the regression. Nevertheless, a positive correlation between [K] and  $[^{40}\text{Ar}_{rad}]$  is obvious. Although further improvement in the accuracy of our measurements is necessary, the data obtained in this study demonstrate that our LIBS-QMS method can reproduce the trend essential for quantitative isochron-based age measurements.

キーワード: 来る 10 年機器提案, その場年代計測装置, 固体惑星着陸探査, K-Ar 年代

Keywords: Decadal Survey, In-situ age measurements, Planetary landing missions, K-Ar dating