

## 浅間山山頂域電磁気構造探查序報 Preliminary report of wide band MT survey in the summit area of Mt. Asama, Japan

小山 崇夫<sup>1\*</sup>, 相澤 広記<sup>2</sup>, 辻 浩<sup>1</sup>, 神田 径<sup>3</sup>, 長谷 英彰<sup>1</sup>, 山谷 祐介<sup>4</sup>, 渡邊 篤志<sup>1</sup>, 橋本 武志<sup>5</sup>, 田中 良<sup>5</sup>, 高倉 伸一<sup>4</sup>, 小川 康雄<sup>3</sup>, 上嶋 誠<sup>1</sup>, 長竹 宏之<sup>1</sup>, 吉村 令慧<sup>6</sup>, 武尾 実<sup>1</sup>  
Takao Koyama<sup>1\*</sup>, Koki Aizawa<sup>2</sup>, Hiroshi Tsuji<sup>1</sup>, Wataru Kanda<sup>3</sup>, Hideaki Hase<sup>1</sup>, Yusuke Yamaya<sup>4</sup>, Atsushi Watanabe<sup>1</sup>, Takeshi Hashimoto<sup>5</sup>, Ryo Tanaka<sup>5</sup>, Shinichi Takakura<sup>4</sup>, Yasuo Ogawa<sup>3</sup>, Makoto Uyeshima<sup>1</sup>, hiroyuki nagatake<sup>1</sup>, Ryohei Yoshimura<sup>6</sup>, Minoru Takeo<sup>1</sup>

<sup>1</sup> 東京大学地震研究所, <sup>2</sup> 九州大学大学院理学研究院附属・地震火山観測研究センター, <sup>3</sup> 東京工業大学火山流体研究センター, <sup>4</sup> 産業技術総合研究所, <sup>5</sup> 北海道大学大学院理学研究院附属地震火山研究観測センター, <sup>6</sup> 京都大学防災研究所地震防災研究部門

<sup>1</sup>Earthquake Reserach Institute, Univ. Tokyo, <sup>2</sup>Volcano Research Center, Earthquake Research Institute, University of Tokyo, <sup>3</sup>Volcanic Fluid Research Center, Tokyo Institute of Technology, <sup>4</sup>National Institute of Advanced Industrial Science and Technology, <sup>5</sup>Institute of Seismology and Volcanology, Graduate School of Science, Hokkaido University, <sup>6</sup>Earthquake Hazards Division, Disaster Prevention Research Institute, Kyoto University

We conducted MT and AMT surveys in the summit area of Mt. Asama in September 2012 in order to elucidate the shallow structure beneath the crater summit including its conduit. The electromagnetic measurements were performed at 27 sites, the spacing of which is as short as about several hundred meters to detect the highly resolved structure.

The AMT measurements were conducted at all the 27 sites for several hours, and MT measurements were conducted at 9 sites for several days. The five-component MT and AMT data were collected using the Phoenix MTU system and the Metronix ADU system. However only telluric measurements were carried out at some sites because the summit area is very rocky and the surface is too hard to dig halls and install large magnetic sensors.

By estimating MT impedance tensors at some sites, the following facts were found:

- 1) At higher frequency as several hundred Hz, the sites at eastern side of the crater show low apparent resistivity as several ohm-m, while other sites show higher apparent resistivity beyond 100 ohm-m.
- 2) Low resistivity parts move to the center of the summit at middle range of frequency as 1 Hz, although the data error is relatively large due to the dead band of the EM source.
- 3) The center and western parts of the summit show the low apparent resistivity at lower frequency as 0.01 Hz.

The preliminary results will be shown in this presentation.

キーワード: 浅間山, 電磁気探查, 見かけ比抵抗

Keywords: Mt. Asama, MT survey, apparent resistivity