

断層の浸透性と粒度組成について - メタンハイドレート堆積層の浸透性評価を目的として -
Permeability of fault and grain size distribution -Evaluation for the permeability of methane-hydrate bearing layers-

木村 匠^{1*}, 金子広明¹, 皆川秀紀¹
Sho Kimura^{1*}, Hiroaki Kaneko¹, Hideki Minagawa¹

¹ 独立行政法人産業技術総合研究所メタンハイドレート研究センター

¹ Methane Hydrate Research Center, National Institute of Advanced Industrial Science and Technology

Permeability of sediments is important factors for production of natural gas from natural gas hydrate bearing layers. Methane-hydrate is regarded as one of the potential resources of natural gas. As results of coring and logging, the existence of a large amount of methane-hydrate are estimated in the Nankai Trough, offshore central Japan, where has a lot of faults. For the purpose of a rational evaluation of permeability of methane-hydrate layers, it is important to understand properties of fault zone because of different condition from other layers due to large displacement shear. In this study, we investigated the permeability of a specimen formed artificial fault in ring-shear test. Moreover, under high and low normal stresses the difference in grain size distribution of shear zone and other zones were discussed. This study is financially supported by METI and Research Consortium for Methane Hydrate Resources in Japan (the MH21 Research Consortium).

キーワード: 断層, 浸透性, 粒度組成

Keywords: Fault, Permeability, Grain size distribution