

JEM-GLIMS による雷・TLE の天底観測 : ISUAL リム観測との比較

Nadir observation of lightning and TLEs by JEM-GLIMS: Comparison with ISUAL limb observation

足立 透^{1*}, 佐藤 光輝², 牛尾 知雄³, 森本 健志⁴, 山崎 敦⁵, 鈴木 睦⁵, 菊池 雅行⁶, 高橋 幸弘², INAN, Umran⁷, LINSKOTT, Ivan⁷, 芳原 容英⁸
Toru Adachi^{1*}, Mitsuteru Sato², Tomoo Ushio³, Takeshi Morimoto⁴, Atsushi Yamazaki⁵, Makoto Suzuki⁵, Masayuki Kikuchi⁶, Yukihiro Takahashi², Umran Inan⁷, Ivan Linscott⁷, Yasuhide Hobara⁸

¹ 早稲田大学 高等研究所, ² 北海道大学 大学院理学研究院, ³ 大阪大学 大学院工学研究科, ⁴ 近畿大学 理工学部, ⁵ 宇宙航空研究開発機構 宇宙科学研究所, ⁶ 国立極地研究所 研究教育系, ⁷ Electrical Engineering Department, Stanford University, ⁸ 電気通信大学 大学院情報理工学研究科

¹ WIAS, Waseda University, ² Department of Cosmospice, Hokkaido University, ³ Information and Communication Engineering Department, Osaka University, ⁴ Faculty of Science and Engineering, Kinki University, ⁵ Institute of Space and Astronautical Science, JAXA, ⁶ Division for Research and Education, NIPR, ⁷ Electrical Engineering Department, Stanford University, ⁸ Graduate School of Information and Engineering, The University of Electro-Communications

The present study analyzes the optical data of lightning and TLEs obtained by JEM-GLIMS on the International Space Station. In contrast to former studies based on the ISUAL limb observation, JEM-GLIMS is pointed toward nadir and, thereby, provides an innovative way to clarify the horizontal structures of lightning and TLEs, which are one of the most crucial issues to improve our understanding of atmospheric discharge physics and electrodynamic coupling between the troposphere and the ionosphere. A difficult point, however, is that careful analyses are required to separate the optical emissions of lightning and TLEs which spatially overlap in the field-of-view in the case of nadir-looking geometry.

The main data analyzed here are those obtained by GLIMS dual-color imager (LSI) and six-color spectrophotometer (PH). One LSI channel is equipped with a 762-nm filter to selectively detect high-altitude TLE emissions by minimizing contamination from low-altitude lightning emissions by deep O₂ atmospheric absorption while the other LSI channel has a broadband red filter to equally measure both phenomena. PH detects time-resolved emission intensity at a sampling rate of 20 kHz with six channels measuring at 150-280, 337, 762, 600-900, 316 and 392 nm, respectively. These spatiotemporally- and spectrally-resolved optical data are analyzed in comparison with well-calibrated results obtained by the ISUAL limb observation of lightning and TLEs.

The goal of this study is to separately identify the signatures of lightning and TLEs from GLIMS data and precisely clarify their spectral and spatiotemporal characteristics.

キーワード: 雷, スプライト, 大気電気, GLIMS, ISS, 宇宙機

Keywords: lightning, sprites, atmospheric electricity, GLIMS, ISS, Spacecraft