

Multi-site infrasound observation around Syowa station, Antarctica

KAKINAMI, Yoshihiro^{1*} ; OKADA, Kazumi⁶ ; YAMAMOTO, Masa-yuki¹ ; KANAO, Masaki² ; MURAYAMA, Takahiko³ ; MATSUSHIMA, Takeshi⁴ ; ISHIHARA, Yoshiaki⁵

¹Kochi University of Technology, ²National Institute of Polar Research, ³Japan Weather Association, ⁴Institute of Seismology and Volcanology, Faculty of Sciences, Kyushu University, ⁵JAXA Space Exploration Center, Japan Aerospace Exploration Agency, ⁶Institute of Seismology and Volcanology, Faculty of Science, Hokkaido University

Infrasound is one of the frontier fields in geophysics to observe atmospheric events. World wide infrasound observing network has been constructed as the CTBTO (Comprehensive Nuclear-Test-Ban Treaty Organization) to detect infrasound signal from huge artificial explosions, however, the CTBTO infrasound observing stations usually catch the natural infrasonic waves generated by many geophysical events, like volcanic eruptions, earthquakes, tsunamis, etc. For example, when a huge meteorite fall was observed near Chelyabinsk, Russia in 2012, the induced infrasonic waves reached to many distant CTBTO stations more than 10,000 km apart from. In the polar region, there exists local infrasound sources generated mainly by the ice sheets on ground, ice field, and glacier motions. Icequakes have been frequently monitored by seismic stations in polar region, however, monitoring of induced atmospheric infrasonic waves through lithosphere-atmosphere coupling is still in progress. We installed an infrasound sensor at Syowa station, Antarctica in 2008 during IPY (International Polar Year) period by JARE (Japanese Antarctic Research Expedition) 49 mission. However, the direction-finding of the infrasonic waves is significant to study the comparison between the seismic data, thus, 2 sensors were added on Syowa to make a triangle sensor array in 2013 by JARE 54. In addition, 5 more sensors were installed at 5 locations around Syowa in 2013 (Murayama et al., 2013).

The infrasound data observed at Syowa can be transferred to Japan via satellite connection, however, the data recorded by data logger at the stations near Syowa cannot be obtained without visiting there. In JARE 55 mission, we obtained one-year infrasound observation data recorded at several stations around Syowa and will return them back to Japan in March 2014. In this paper, we will introduce some preliminary results obtained in Antarctica as the first multi-site infrasound observation at the frozen continent.

Keywords: ifrasound, Antarctica, multi-site observation, JARE, ice quake

Characteristic features of infrasound waves observed at Antarctica

KANAO, Masaki^{1*} ; MURAYAMA, Takahiko² ; YAMAMOTO, Masa-yuki³ ; ISHIHARA, Yoshiaki⁴ ; KAKINAMI, Yoshihiro³ ; OKADA, Kazumi⁵ ; MATSUSHIMA, Takeshi⁶

¹National Institute of Polar Research, ²Japan Weather Association, ³Kochi University of Technology, ⁴Japan Aerospace Exploration Agency, ⁵Hokkaido University, ⁶Kyushu University

Characteristic features of infrasound waves observed at Antarctica reveal the physical interaction involving surface environmental variations in the continent and surrounding Southern Oceans. A single infrasound sensor has been continuously recorded since 2008 at Syowa Station (SYO; 39E, 69S), the Lutzow-Holm Bay (LHB), East Antarctica. The continuously recording data clearly represent a contamination of the background oceanic signals (microbaroms) during whole seasons. In austral summer in 2013, several field stations by infrasound sensors are established along the coast of the LHB. Two infrasound arrays with different diameter size are installed at both SYO (by 100 m spacing triangle) and S16 area on continental ice sheet (by 1000 m spacing triangle). Besides these arrays, two isolated single stations are deployed at two outcrops in LHB. These newly established arrays clearly detected the propagating directions and frequency contents of the microbaroms from Southern Ocean. Microbaroms measurements are a useful tool for characterizing ocean wave climate, complementing other oceanographic and geophysical data in the Antarctic. Moreover, several kind of remarkable infrasound signals are demonstrated, such as regional earthquakes, together with a detection of the airburst shock waves generated from meteorite injection at the Russian Republic on 15 February 2013. Detail and continuous measurements of the infrasound waves in Antarctica could be a new proxy for monitoring a regional environmental change as well as temporal climate variations in high southern latitude.

Keywords: infrasound, array observations, Lutzow-Holm Bay, East Antarctica, microbaroms, surface environment

Monitoring snow avalanches by using infrasound with an object of establishing remote detection system of snow avalanches

ARAI, Nobuo¹ ; MURAYAMA, Takahiko^{1*} ; IWAKUNI, Makiko¹ ; TANIMOTO, Saki² ; TAKAHASHI, Daisuke² ; KURIHARA, Yasushi² ; ARAKI, Keiji² ; YAMAMOTO, Masa-yuki³

¹Japan Weather Association, ²Railway Technical Research, ³Kochi University of Technology

It has been demonstrated that avalanches produce strong infrasonic vibrations in air during their movement (Bedard, 1988^[1], Hejda, 1995^[2]). These infrasonic vibrations propagate great distances and can follow the natural relief. This fact shows that it is possible to monitor remotely the snow avalanche by using infrasound detection system.

We aim to establishing remote detection system of snow avalanches. In order to study the feature of the signal associated with snow avalanches, as a first step, we carried out trial infrasound observation simultaneously with the video monitoring and the meteorological observation at mountainous region in Niigata Prefecture from January to April 2013. During the trial observation, some infrasound signals generated by snow avalanches were recorded. We analyzed these data and attempted to extract features from infrasound signals.

[References]

[1] Bedard, A. J. et al. 1988. On the feasibility and value of detecting and characterizing avalanches remotely by monitoring radiated sub-audible atmospheric sound at long distances. Proc. A Multidisciplinary Approach to Snow Engineering, Santa Barbara, CA.

[2] Hejda, D. 1995. Caracterisation de l'emission acoustique des avalanches, (These de diplome, E. P. F. Lausanne, Suisse.)

Keywords: Infrasound, Snow avalanches, Avalanche monitoring

Micro-barometric variation associated with rainfall

IYEMORI, Toshihiko¹ ; SANO, Yasuharu^{2*} ; HAYASHI, Taiichi³ ; ODAGI, Yoko¹ ; AOYAMA, Tadashi¹ ; NAKANISHI, Kunihito¹

¹Graduate School of Science, Kyoto University, ²Asahi University, ³DPRI, Kyoto University

A sudden rainfall (shower) is often preceded by a micro-barometric variation. To examine quantitative relationships between them, we conducted observations of micro-barometric, rainfall and absorption of BS broadcasting radio waves and recorded the data with one second resolution.

As a result, we often observed the events where a pressure increase starts about one minute before a strong rainfall. Just after the start of the rainfall, micro-barometric variation with period about a few minutes were also observed. These results suggest that the dynamic pressure associated with the falling rain drops pushes the air and observed as a gradual increase of the pressure on the ground. If this is the case, a rarefaction waves may propagate upward over the rain cloud. In this paper, we will show the results obtained from many events.

Keywords: micro-barometric variation, gravity wave, rainfall, acoustic gravity wave

Ionospheric disturbances by volcanic explosions: Observations with GNSS

NAKASHIMA, Yuki^{1*} ; HEKI, Kosuke¹

¹Dept. Natural history sciences, Graduate school of science, Hokkaido Univ.

There have been numbers of reports that atmospheric waves, e.g. internal gravity waves and acoustic waves, excited by various natural or artificial phenomena on the ground, shake up the ionospheric F layer as high as 300 km [Calais et al., 1998 GJI; Heki and Ping, 2005 EPSL]. Acoustic waves from volcanic eruptions are observed as infrasound in near fields, but they also propagate upward and cause ionospheric disturbances [Heki, 2007 GRL]. We try to reveal the characteristics of ionospheric disturbances caused by volcanic explosions using Total Electron Content (TEC) data derived at the dense array of ~1240 Global Navigation Satellite System (GNSS) stations in the Japanese GEONET.

Heki [2006] detected TEC changes of ~0.1 TECU in the region to the south - southeast of the volcano ~10 minutes after the explosion of the Asama Volcano, central Japan, on Sep. 1, 2004, at 11:02 UT. He estimated the atmospheric wave energy from the amplitude of TEC disturbances, and inferred the explosion energy by comparing the TEC change amplitudes with those caused by an artificial explosion with known energy [Calais et al., 1998]. Later, Dautermann et al. [2009 JGR] performed a similar study for the 2003 explosion of the volcano in the Montserrat Island, West Indies.

Here we report on the TEC disturbances caused by the explosion of the Kirishima-Shinmoe volcano, southern Kyushu, Jan. 31 2011, 22:54 UT. According to the JMA documents issued in 2011 January, this explosion induced the infrasound of ~458 Pa, which blasted some window glasses in Kirishima-city, Kagoshima. We also detected 0.2-0.3 TECU peak-to-peak amplitude disturbances after the 2009 October explosion of the Sakurajima volcano, southern Kyushu. They appeared 10 minutes after the explosion and propagated southward with a sound speed at the F layer height. In contrast to the period of ~4 minutes of typical coseismic ionospheric disturbances, TEC changes by volcanic explosions were found to have periods of ~2 minutes or shorter.

In the presentation, we will compare new examples of ionospheric disturbances by volcanic explosions, such as the 2011 Shinmoe and 2009 Sakurajima cases, with older cases such as the 2004 Asama case.

Keywords: GPS, GNSS, infrasound, acoustic wave, volcanic explosion, ionosphere

Simulation of ionospheric variations caused by acoustic waves generated in the lower atmosphere

SHINAGAWA, Hiroyuki^{1*}

¹NICT

In the lower atmosphere of the earth, acoustic-gravity waves are generated by various kinds of natural and artificial sources, such as cumulus clouds, tornados, typhoons, earthquakes, tsunamis, volcanic eruptions, meteor impacts, nuclear explosions, rocket launches, etc. Previous theoretical and observational studies have suggested that acoustic-gravity waves induced by such sources can propagate up to the upper atmosphere, producing temporal and spatial variations in the thermosphere and in the ionosphere. However, specific mechanisms of upper atmospheric variations caused by the acoustic-gravity waves have not yet been fully understood because the atmosphere-ionosphere system is an extremely complicated and nonlinear, and it is easily disturbed by many other sources in the atmosphere and in space. In order to quantitatively study the ionospheric variations caused by tsunami-driven acoustic-gravity waves of the 2004 Sumatra earthquake and 2011 Tohoku-oki earthquake, we developed a nonhydrostatic compressible atmosphere-ionosphere model. The model successfully reproduced atmospheric waves and large-scale electron density variations that are caused by tsunami-driven acoustic-gravity waves. We are now developing an atmosphere-ionosphere model with higher spatial resolution and more realistic parameters. We expect that the model is able to reproduce atmospheric-ionospheric phenomena associated with infrasonic and gravity waves produced by various kinds of phenomena. We will report previous results and future prospects.

Keywords: acoustic wave, lower atmosphere, upper atmosphere, ionosphere, simulation, model

Low-frequency atmospheric pressure waves associated with the outer-rise earthquake on Oct. 25, 2013, 17:10 UTC.

ARAI, Nobuo^{1*} ; IWAKUNI, Makiko¹ ; MURAYAMA, Takahiko¹ ; NOGAMI, Mami¹

¹Japan Weather Association

Sensitive microbarographs in and around Japan recorded unequivocal signals associated with the 2011 Off the Pacific Coast of Tohoku, Japan earthquake ($M_w = 9.0$) (Arai *et al.*, 2011).

These signals retained the original shape of the tsunami and traveled in the atmosphere significantly faster than the tsunami waves in the ocean, therefore, we think that an establishment of a network of infrasound observation along the coast line facing the subduction zone would improve the tsunami warning system.

According to this idea, we deployed three (3) microbarograph stations in Ofunato City, Iwate last July as the first step of the establishment of a network of infrasound observation and are trying to observe atmospheric pressure changes continuously.

The outer-rise earthquake occurred off the Fukushima region on Oct. 25, 2013, 17:10 UTC and the tsunami waves with few tens centimeter heights observed at coastal area of Tohoku region. And some curious atmospheric pressure waves detected at our Ofunato sites. The characteristics of the observed signals are consistent with the features of the tsunami source produced by the outer-rise earthquake.

Reference:

Arai *et al.* , Atmospheric boundary waves excited by the tsunami generation related to the 2011 great Tohoku-Oki earthquake, *Geophysical Research Letters*, Vol. 38, L00G18, doi:10.1029/2011GL049146.

Keywords: Infrasound, atmospheric pressure change, outer-rise earthquake, detection of tsunami

Examination on Numerical Simulation of Tsunami-Induced Extremely Low Frequency Sound Waves with Geospatial Information

OKUBO, Kan^{1*} ; KAWASHIMA, Ken¹ ; OSHIMA, Takuya² ; TAKEUCHI, Nobunao³

¹Graduate School of System Design, Tokyo Metropolitan University, ²Faculty of Engineering, Niigata University, ³Graduate School of Science, Tohoku University

Air pressure changes associated with earthquakes and/or tsunami have been investigated previously. As for air pressure changes associated with tsunami, some observation results have been reported (T. Mikumo (1964), T. Mikumo, et al. (2008) and William L. Donn and Eric S. Posmentier (1964), Y. Tamura (2011), N. Arai, et al. (2011)).

We have measured the air pressure in the terrestrial atmosphere with other meteorological parameters (temperature, humidity, etc.) continuously at Hosokura outdoor observation station (HSK) in Miyagi Prefecture, Japan. The extremely low frequency sound waves (so-called micro barometric waves) are also detected as large changes of air pressure in the 2011 off the Pacific coast of Tohoku Earthquake (M 9.0, origin time;14:46.18JST) (K. Okubo, et al. (2011)).

Although the power failure was caused by the earthquake occurrence, our observation system had been maintained by the UPS system and the private power generation. Therefore, in this earthquake, our observation system successfully observed extremely low frequency sound waves induced by tsunami. The waves were detectable at the observation point on the ground surface sufficiently early before the arrival of tsunami waves at coastal areas, because sound waves propagate faster than ocean waves (tsunami).

These results can encourage early tsunami detection (S. Iwasaki (1992), T. Izumiya (1994)) using multi-site observation and arrival time difference method. That is, detection of tsunamis might be possible by monitoring extremely low frequency sound waves at ground surface observation sites and/or sea-level observation at relatively low cost. It is important to obtain information of tsunami as soon as possible; arrival time, area and scale.

In this study we present a fundamental examination on analysis and visualization of extremely low frequency sound waves caused by tsunami using numeral approach. We employ the numerical simulation using the Finite-Difference method in Time-Domain (FDTD method) (Yee, 1966) with geospatial information for the large-scale sound wave propagation. As an elementary study, it is applied to the estimation of extremely low frequency sound waves' propagation and time-series analysis of sound pressure.

Through our study, we show the numerical results of sound pressure distribution and estimate the propagation phenomena of sound waves, compared with the observed data at HSK. This examination may help the development of the design of early tsunami detection system. In the future, further efforts can suggest new systems for early warning of destructive tsunami using a combination of other measurements.

We are grateful to Hosokura Metal Mining Co. for the maintenance of our site. This research was partially supported by a Grant-in-Aid for Scientific Research from the Japan Society for the Promotion of Science.

Keywords: Numerical Simulation, tsunami, sound field change, microbarometric wave, infrasound, numerical visualization

Atmospheric Gravity Waves from the 2010 Maule, Chile earthquake (Mw8.8)

MIKUMO, Takeshi^{1*} ; IWAKUNI, Makiko² ; ARAI, Nobuo²

¹Kyoto University, ²Japan Weather Service, ³Japan Weather Service

Atmospheric pressure waves were recorded after the 2010 Maule, Chile earthquake (Mw=8.8) by microbarographs at seven International Monitoring System (IMS) stations in the distance range up to 7,680 km. By applying bandpass-filtering, we extracted low frequency gravity waves, removing atmospheric noise and higher-frequency acoustic modes, and then estimated their phase velocities around 332-341 m/s. To compare with these observations, we constructed synthetic waveforms, referring to the source dimension and coseismic vertical ground displacements based on geodetic measurements (Moreno et al., 2012), and incorporating a standard atmospheric sound velocity structure up to a height of 220 km. The comparison between the observed and synthetic waveforms provides generally satisfactory agreement, and suggests the time constant of ground displacements between 2 and 3 min in the northern and southern segments of the entire source region extending for about 500 km..

Keywords: 2010Maule, Chile earthquake, Mw=8.8, low-frequency, Atmospheric gravity waves

High resolution barometer array in Palau, Western Pacific

ISHIHARA, Yasushi^{1*} ; FUKAO, Yoshio¹ ; SHITO, Azusa² ; OBAYASHI, Masayuki¹ ; SHIROOKA, Ryuichi¹

¹JAMSTEC, ²Institute for Geothermal Sciences, Kyoto University

The Variety of waves is propagating in the atmosphere, ocean and solid earth. And there are interacting between each layer. For total and integrated understanding, multi parametric measurement over different field is required. We target Palau islands, western Pacific for multi parametric measurement. We are operating broadband seismic station in a station of Pacific Geophysical Network (OHP network). And another seismic station is also under operation due to removing of seismic station. Meteorology group of JAMSTEC has their station including meteorological radar. We think that Palau is fine condition to construct integrated geophysical measurement field. So that we deployed high resolution barometric small array in Palau.

Palau locates tropical zone and its daily weather condition is similar and relative more stable than middle latitude zone and polar area that have some day's variation and passing of front. In our research, one of main focuses is very low frequency band of barometric variation; the ambient condition has merit to get accurate detection of signal.

As for observation system, sensor is quartz oscillation type high resolution barometer and recorder is Linux Box via serial communication. We set to be sampling of 2 sps to get high resolution data. We installed Five(5) stations in Palau whose station interval is about 20km. Two stations of them locate at seismic stations and another station is same area with weather station. The array is operating from August, 2013 and is under operation.

The tentative data review shows atmospheric gravity wave is frequently recorded in longer period of 200sec. Sometimes event pulse-like signals are detected. Apparent velocity of these waves is 20 ? 30 m/s and direction of propagation varies daily. Most signal arrives from outside of this array. We report character of these wave and relation with meteorological condition.

Keywords: atmospheric gravity wave, micro seism

Improvement and evaluation of optical-type infrasound sensor for multi-site observation

IKEHARA, Kousuke^{1*} ; YAMAMOTO, Masa-yuki¹ ; KAKINAMI, Yoshihiro¹ ; ISHIHARA, Yoshiaki²

¹Kochi University of Technology, ²JAXA Space Exploration Center, Japan Aerospace Exploration Agency

Infrasound is applicable for remote-sensing methods for detecting geophysical phenomena in the atmosphere. There have been developed and used many types of infrasound sensors, however, typically used infrasound sensors are almost developed by foreign countries, resulting high cost situation in Japan. If we can develop low cost infrasound sensors, multi-site arrayed observation will be realized in near future.

Recently, infrasound signal generated by tsunami was clearly detected by many CTBTO infrasound stations (Arai et al., 2011), suggesting a new era for establishing a dense infrasound sensor network in every prefecture of Japan for preventing or reducing catastrophic disasters. Because the nature of pressure waves with large wavelength, amplitude of infrasound generated by tsunami might be proportional to the size of the disasters. Combination with sensor networks of seismometers on ground and ocean floor, GPS-buoy type wave recorders, and water manometers on ocean floor, establishing a dense network of infrasound sensors with arrayed configuration is desired.

Since 2006, we have been developing new sensing method of infrasound by using piezo film and PSD (Position Sensitive Detectors), achieving frequency range between 0.001 Hz and 10 Hz as well as minimum pressure level of 0.01 Pa (Yamamoto and Ishihara, 2009). In 2013, we tried downsizing the PSD type infrasound sensor developed in 2008 into a size of 0.15 m x 0.15 m x 0.25 m height with calibrating it by using space chamber (0.8 m length x 0.58 m diameter) as an accurate volume pressure reservoir (Manabe et al., 2013). Here, we improved the PSD optical-type infrasound sensor by using 3D printer technology to make many tiny parts designed with 3D CAD software.

By pushing and pulling a small amount of air by a small syringe, calibrating pressure waves with extremely weak amplitude (10 Pa to 0.01 Pa) can be generated in the space chamber, precise measurement of artificially generated infrasonic signals could be realized. The waves were measured by both of the developed PSD sensor and Chaparral Model-2.5 infrasound sensor at the same time. Comparison with output signals by two types of sensors, the downsized PSD type infrasound sensor was carefully studied. In this paper, we will introduce the new design and obtained calibrating datasets.

Keywords: infrasound, multi-site observation, sensor development, optics, measurement, low-cost

Pressure sensors detected wind noise produced in wind tunnel

IWAKUNI, Makiko^{1*} ; YAMAMOTO, Masa-yuki² ; TANIMOTO, Saki³ ; KAKINAMI, Yoshihiro² ; IKEHARA, Kosuke² ; OKADA, Kazumi⁴ ; ARAKI, Keiji³ ; KURIHARA, Yasushi³ ; ARAI, Nobuo¹ ; MURAYAMA, Takahiko¹ ; NOGAMI, Mami¹

¹Japan Weather Association, ²Department of systems engineering, Kochi University of Technology, ³Railway Technical Research Institute, ⁴Institute of Seismology and Volcanology, Hokkaido University

As infrasound and pressure disturbance induced by local wind around infrasound sensors are partially in the same frequency range, amplitude of the infrasound signal is sometimes lower than that of pressure disturbance by strong wind. Thus, obtaining the infrasound signal by analyzing software from the observation data with such wind noises is one of the technical objectives to solve. Usually, some porous pipes connected with the infrasound sensors have been used in order to reduce such local wind disturbances.

To evaluate such system for wind noise reduction, we conducted experimental study by using a wind tunnel with wind speed up to 60 m/s. We used nano-resolution pressure transducer (6000-16B manufactured by Paroscientific Inc., USA) and microphone type infrasound sensors

(Chaparral physics, Model25 manufactured by Univ. of Alaska Fairbanks) in the wind tunnel of the Railway Technical Research Institute (RTRI), Japan. In this presentation, we will show the relationship between the wind speed and porous pipe configuration installed in the wind tunnel.

In this presentation, we show the relation between wind speed and pipe direction.

Keywords: Infrasound, wind noise reduction, pipe reduction system, wind tunnel