

Gravity observation using a superconducting gravimeter at Ishigakijima, Japan (part 3)

IMANISHI, Yuichi^{1*} ; NAWA, Kazunari² ; TAMURA, Yoshiaki³ ; IKEDA, Hiroshi⁴ ; MIYAJI, Takeshi³ ; TANAKA, Yoshiyuki¹

¹ERI, The University of Tokyo, ²AIST, ³NAOJ, ⁴University of Tsukuba

About two years have passed since we started gravity observation by means of a superconducting gravimeter at the VERA Ishigakijima Station, National Astronomical Observatory Japan in 2012, with the main purpose of detecting possible gravity changes associated with the long-term slow slip events beneath the Yaeyama Islands. Up to now, we have experienced three times of events, which took place in May 2012, December 2012 and July 2013. For the two events in 2012, gravity changes possibly associated with the slow slip events were recorded. The July 2013 event was not well recorded because of the damages by the typhoon. In addition, an earthquake swarm near the Yaeyama Islands in April 2013 may have also influenced the observed gravity. The next slow event is expected to take place around February 2014. Modeling and interpretation of the data will be presented in the paper.

Keywords: superconducting gravimeter, slow slip, Ishigakijima

Various drift rates of gPhone gravimeters obtained from short-term observations at geothermal fields

NAWA, Kazunari^{1*} ; MIYAKAWA, Ayumu¹ ; SUGIHARA, Mituhiko¹

¹Geological Survey of Japan, AIST

We carried out short-term but continuous gravity observations using gPhone (spring type) gravimeters at geothermal fields. At hot spring area of Hachijojima, we obtained 1-4 months gravity data using several gPhone gravimeters at different sites and situations of the period between February 2011 and December 2012. Using the obtained data, we calculated and compared temporal variations of the drift rate. As a result, drift rates of gravimeters showed various characteristics according to location and elapsed time from installation. In many cases, it took about a month until initial drift stabilized, that is, drift rate became quasi-constant. Even after stabilized, drift rate of gPhone gravimeters remained a few microGal/day (on the other hand, the nominal drift rate of iGrav superconducting gravimeter is 0.5 microGal/month), although the magnitude of the drift rates were considerably smaller than several hundred microGal/day of CG-3M gravimeters. We will show the result of gPhone-133 replaced from Hachijojima to a geothermal power plant at Kyushu District in March 2013.

Keywords: relative gravimeter, temporal gravity change, Hachijojima, on-land observation

Gravimetric vertical array observation -the 2013 fiscal year-

TANAKA, Toshiyuki^{1*} ; HONDA, Ryo¹

¹TRIES, ADEP

A vertical array of gravimeters (Mizunami Underground Laboratory; MIU) is quite rare in the world, and this method that suppresses rainfall responses and stacks signal from deep part of the crust can contribute to leveling up the potential of gravimetry (Tanaka et al., EPS, 2013). This time (Nov. 2013~Jan. 2014), we have succeeded in getting higher quality data than before with almost same configuration; namely, using two gPhone gravimeters (#130 on the ground, #90 at 300m under the ground). Though blasting for construction works had performed frequently during last year, we can detect sub-microGal responses of rainfall this time in the frequency band from hourly to daily. In the longer band, the sensor temperature of #130 is still shifting slightly, which can affect drifting rate. Here, we describe the four time-series data: data of belowground, (1); data on the ground, (2); sum of the two, (3); difference between the two, (4). We have finally got residual gravity values without tidal and atmospheric responses by using the BAYTAP-G (Tamura et al., 1991), with assuming of linear drift. When it rains, (1) should show gravity decrease, (2) should show gravity increase, (3) should offset the response, and (4) should superimpose the response. Because, only the main part of the Akeyo formation, which overlies an impervious layer from the surface to approximately 80m depth, responds to precipitation (e.g. Tanaka et al., Gcubed, 2006). Actually, we have observed such responses of rainfall. These depend on the way of rainfall; however, it seems that the amplitude of the response of (1) is slightly larger than (2). If so, the infinite slab assumption of a groundwater layer caused by rainfall is unsuitable for this gravimeter layout. On atmospheric correction, (1) and (2) should be almost same, (3) should superimpose, and (4) should offset the response. Actually, we have observed such responses and confirmed that (4) is one-tenth the atmospheric response of that of (1) or (2).

In the future, we will aim to accumulate high quality data, survey the habit of these two gravimeters (i.e. sensor drift, sensor temperature, and tilt response), and finally construct a vertical array including an absolute gravimeter.

Acknowledgements: This work is supported by a promotion grant for the establishment of the underground research facility of the Agency for Natural Resources and Energy, Minister of Economy, Trade and Industry. We thank the JAEA for the cooperation of observations (especially Mr. Y. Horiuchi) and our colleagues.

Keywords: continuous gravity measurement, gravimeter, inland water, rainfall, atmospheric correction, measuring method

Huge uplift event of Iwoto: Estimation of gravity change based on the result of gravimeter calibration in Sapporo-Naha

OZAWA, Taku^{1*} ; MIYAGI, Yosuke¹ ; UEDA, Hideki¹ ; NAGAI, Masashi¹ ; FUJITA, Eisuke¹

¹National Research Institute for Earth Science and Disaster Prevention

Ogasawara-Iwoto is the volcanic island located to 1200km south of Tokyo. It has a caldera with the diameter of 10km, and its central and southwestern part appears on the sea surface. One of characteristics for its volcanic activity is to have the large uplift rate, and National Research Institute for Earth Science and Disaster Prevention (NIED) has revealed occasional occurrence of huge uplift events and distribution of its crustal deformation (Ukawa et al., 2006). NIED started gravity survey from 1996, and Ukawa (2006) suggested involvement of magma in a huge uplift event. Though continuous subsidence had been observed from early 2003, it rapidly changed to uplift in mid-2006. Its uplift decelerated with time after 2007, but it rapidly re-accelerated in Feb. 2011. According to GNSS observation by NIED and GSI, the amount of uplift from re-acceleration to Apr. 2012 reached 2m. In late April of 2012, discolored water was found around Iwoto, and uplift activity slowed down after that. To investigate crustal deformation and gravity change associated with this event, we carried out GNSS campaign observation and gravity survey. We presented the result of GNSS campaign observation in fall meetings of the geodetic society of Japan and the volcanological society of Japan. We also presented preliminary result for gravity survey, but there was a problem on uncertainty for temporal change of scale factors of used gravimeters (Scintrex CG-3M #284 and #371). To estimate scale factors of their gravimeters, we carried out gravity survey between Sapporo and Naha. In this presentation, we show temporal change of scale factors revealed from this calibration and gravity change of Iwoto estimated using its result.

In gravimeter calibration, we measured gravities at NIED (Bosai-BS), GSI (Tsukuba-GS and Tsukuba-FGS), Haneda airport (Haneda-GS), Chitose airport (Chitose-GS), Hokkaido University (Sapporo-GS), and Okinawa Meteorological Observatory (Naha-GS and Naha-FGS). In estimation of relative gravity, we assumed that the drift rate was constant, and estimated gravities and the drift rate simultaneously. Then we estimated scale factors so that estimated gravities corresponded to those of JGSN96 (Geospatial Information Authority of Japan, Geodetic department, 1997). Since Sapporo-GS was moved to new benchmark, we used gravity measured by GSI. Estimated changes of scale factors from those in 2006 were $+2 \times 10^{-5}$ and -1×10^{-4} for #284 and #371, respectively. Temporal changes of scale factors are not orderly, and then obtained scale factor is different significantly from estimated value by the linear approximation. Therefore it indicates that consideration of temporal change of scale factor is important in survey of large gravity difference.

Estimating gravity at the benchmark in Iwoto (IWO101), estimated gravities from #284 and #371 were consistent within 0.027mGal, and its average was decrease of 0.734mGal from that in 2006. Uplift in this period was 3.05m, and then gravity change rate with respect to uplift was -0.241mGal/m. This gravity change rate is in good agreement with that for the 2001-2002 huge uplift event by Ukawa et al. (2006). This result suggests that the huge uplift event from 2006 has been caused by the magma with the similar density to that in the 2001-2002 event.

Acknowledgements. GNSS and gravity surveys were supported by JSDF. A part of survey and analysis for Iwoto was carried out by Ohba Co. Ltd. Gravity calibration was supported by GSI, Hokkaido University, and Okinawa Meteorological Observatory.

Keywords: Iwoto, gravity, scale factor, magma

Absolute gravity measurements near the Sor-Rondane Mountains, Antarctica

FUKUDA, Yoichi^{1*} ; AOYAMA, Yuichi² ; SUGANUMA, Yusuke² ; OKADA, Masaki² ; DOI, Koichiro²

¹Graduate School of Science, Kyoto University, ²National Institute of Polar Research

In order to detect the gravity changes due to ice sheet mass changes, Glacial Isostatic Adjustment (GIA) and other effects, we have conducted absolute gravity measurements at Princess Elisabeth Station (PES) near the Sor-Rondane Mountains, Antarctica, as part of the 55th Japanese Antarctic Research Expedition (JARE-55). In addition, the first absolute gravity measurements using a field absolute gravimeter have also been conducted on the Seal rock near the Asuka station, where the gravity reference point (No.26-01) established by JARE-26 is located.

The absolute gravimeters employed were FG5#210 and A10#017, and a relative gravimeter LaCoste #805 was also used for dg/dz measurements and gravity connections. Using DROMLAN (Dronning Maud Land Air Network), we moved to PES with the instruments via Novolazarevskaya from Cape Town in South Africa. The length of our stay in PES was for 18 days from Nov. 29 to Dec. 16, 2013. Belgian researchers have already conducted absolute gravity measurements using a FG5 in North Shelter (NS), a small observation hut built on an outcrop a few hundred meters apart from the main base of PES. One of the main purposes of this project is to monitor long-term gravity changes by means of successive absolute gravity measurements at the same gravity point in NS. Since NS has not enough space for adjusting the gravimeters before measurements, we borrow a room in the main base for the purpose and test measurements as well. We established a tentative gravity point in the room and compared the gravity values measured by A10 and FG5. The result showed the discrepancy was within 2 micro-Gals. This means that A10 was well calibrated. Unfortunately a crucial fault arose in the dropping chamber of the FG5, and it could not be recovered to the last. For this reason, the measurements in NS were carried out using A10. The gravity value on the reference point was calculated to be 982302155.21 micro-Gals with the measured dg/dz of -4.4529 micro-Gals/cm. Although the exact comparisons with the gravity values obtained by the Belgian team have not been completed yet, the gravity values seem to be in agreement within several micro-Gals. Therefore the temporal gravity change would be very small, even if it existed.

The gravity measurements on the Seal rock have been conducted on Dec. 5th and 6th. Since No.26-01 is located near the summit of the Seal rock, where strong wind blows constantly, it is very difficult to conduct absolute gravity measurements even using A10. Therefore a tentative gravity point was set up at the foot of Seal rock, and measurements with A10 were conducted at the point. Then gravity connection to No.26-01 was conducted with the LaCoste gravimeter. The gravity value thus obtained at No.26-01 was 982406.109 mgal with the accuracy of about 15 micro-Gals including the errors due to the gravity connection.

The gravity values of No.26-01 so far obtained were 982405.33mgal by JARE-26 (GSI, 2002), and 982402.817mgal by JARE-27 (Fukuda, 1986). The new value is 0.779 mgal and 3.292 mgal larger than those of JARE-26 and JARE-27, respectively. In JARE-27, two sets of LaCoste gravimeters were employed for the gravity connection between Seal rock and Syowa Station. Since a large discrepancy between the values obtained by two gravimeters was found, Fukuda (1986) applied a step correction of 3.765mGals to the suspected gravimeter. However, judging from the present result, the correction could be applied to the wrong gravimeter. If the correction was applied to the other gravimeter, the difference of 3.292 mgal was set to about 0.5mGals, and it would be likely as the accuracy of the gravity connection. The gravity value of No.26-01 has been used as a reference value for the gravity surveys so far conducted in the Sor-Rondane area. Therefore the revisions of those values should be required from now on.

Keywords: absolute gravity measurement, Sor-Rondane, Antarctica, ice sheet movement, gravity changes, gravity reference point

Performance of the recoil-compensation mechanism used for a throw-up type absolute gravimeter

SAKAI, Hiroataka^{1*} ; ARAYA, Akito¹ ; TSUBOKAWA, Tsuneya² ; EMANUELE, Biolcati³

¹Earthquake Research Institute, University of Tokyo, ²Shin-ei keisoku, ³L'Istituto Nazionale di Ricerca Metrologica

Absolute gravimeters can measure gravity acceleration in the accuracy of 8 to 9 digits. They are accurate and useful for many applications, however the apparatus is too bulky and heavy. Therefore, in the field observation, their installation site is limited. As a result, for volcanic observations, a gravity value is usually measured by an absolute gravimeter at a reference point of foot, and then a gravity value of an observation point can be obtained from the gravity difference between a reference point and an observation point measured with a relative gravimeter; such a method is laborious, and requires long time. Furthermore it is hazardous to approach the observation points when the volcano is active. This study is to minimize absolute gravimeter in order to improve these situations. The original point of our new apparatus is to incorporate a recoil-compensation mechanism to improve the measurement accuracy.

In the absolute gravity measurements, we adopted a rise-and-fall method, while conventional absolute gravimeters usually adopt a simple free-fall method. The simple free-fall method has several problems such as bulky mechanism to lift up a test mass, repeated measurements, and long time to take for the preparation. Hence, we developed a throw-up equipment that had no need for lifting up a test mass and could measure repeatedly. This enabled to minimize one of the biggest parts in the absolute gravimeter.

The equipment which we developed this time can throw up the test mass by 3mm in height simply by applying the signal to a piezoelectric element which is incorporated in the expansion mechanism. When the test mass was thrown up, it rotated by an anchoring effect and it may cause the error in the gravity measurement. We applied other piezoelectric elements which separate the stage from the test mass just before the test mass leaves the stage to cut off the anchoring force. At the end of 2012, we carried out a performance test of the throw-up equipment at Esashi Earth Tidal Station in Iwate. At Esashi, we replaced the free fall equipment of the existing absolute gravimeter with the throw-up equipment. As a result, the throw-up equipment was able to detect a gravity change of earth tides. The resolution of the gravity measurement δg was estimated to be $40\mu\text{gal}$. However, the absolute gravity deviated from the value expected from the past measurements up to $\Delta g = 3\text{mgal}$. This big error was inferred from the recoil effect at the time of throw that induces vibration to the interferometer.

We developed the recoil compensation mechanism of the throw-up equipment to improve the measurement accuracy Δg . Specifically, we put the same piezoelectric element and the expansion mechanism on the other side of the baseplate to which the throw-up mechanism is attached. These expansion mechanisms move symmetric by applying the same signal to the piezos. When the test mass is thrown up, the counter mass fixed by springs is launched downward at the same time to compensate the recoil effect. We could observe the recoil reduction as much as 2.7% of peak acceleration without the compensation mechanism. After performing fine adjustment of the equipment, we plan to conduct gravity measurement by the same method to 2012, and the result and the development status will be reported.

Keywords: absolute gravimeter, throw-up equipment, miniaturization, recoil effect, compensation mechanism, gravity measurement

Development of a laser-interferometric gravity-gradiometer and its trial operation on the volcanic island of Sakurajima

SHIOMI, Sachie^{1*} ; KAGIYAMA, Tsuneomi¹

¹Aso Volcanological Laboratory, Kyoto University

We have been developing a laser-interferometric gravity-gradiometer for volcanological studies. The gravity gradiometer measures differential accelerations between two test masses that are in free fall at different heights. Because its detection principle is based on the differential measurements, measured values are insensitive to the motions of observation points. That is to say, the gravity gradiometer is expected to have a good resolution even when it were used on an accelerating vehicle, such as an airship, or in an active volcanic area. Therefore, the gravity gradiometer could be useful for, for example, resource explorations and studies on volcanic activities.

The gravity gradiometer, to be used on an airship, had been developed at the Institute for Cosmic Ray Research (ICRR) of the Tokyo University from 2009 to 2012. A prototype of the gravity gradiometer was built up and tested at the ICRR. Their laboratory test showed that its resolution of measuring vertical gravity gradients was about a few $\mu\text{Gal}/\text{m}$ in two second measurements. However, large unexplained disturbances were observed in longer term measurements. In order to understand the sources of the disturbances, the prototype was moved to the Aso Volcanological Laboratory (AVL) of the Kyoto University in July 2012. Since then, its further development, to be used at an observatory in a volcanic area, has been carried out at the AVL.

We will report the current status of the development for volcanological studies and results of trial measurements performed at the Sakurajima Volcanological Laboratory of the Kyoto University, on the volcanic island of Sakurajima, Kyusyu, Japan.

Keywords: gravity gradients

The two components of postseismic gravity changes and their mechanisms

TANAKA, Yusaku^{1*} ; HEKI, Kosuke¹

¹Graduate School of Science, Hokkaido University

The time series analysis of the gravity changes of the three Mw9-class mega-thrust earthquakes (2004 Sumatra-Andaman earthquake; 2010 Chile (Maule) earthquake; and 2011 Tohoku-oki earthquake) gives the strong possibility that the gravity observation separates postseismic phenomena. There are three sensors for earthquake observations: the first sensor is seismographs, the second sensor is GNSS (Global Navigation Satellite System) or SAR (Synthetic Aperture Rader), and the third sensor is the gravity observation. Seismographs cannot be used to catch the signal of postseismic phenomena because they do not shake the ground. GNSS like GPS (Global Positioning System) and SAR catch the signal of postseismic phenomena but they cannot separate those phenomena because the phenomena move the ground with the same polarities. However, the polarities to gravity changes of postseismic phenomena can be different each other. This suggests that the gravity can become the first sensor to catch the separated signals of postseismic phenomena.

GRACE (Gravity Recovery And Climate Experiment), which is the twin satellites launched in 2002 by NASA and keeps on observing the gravity field of the earth, gives the two-dimensional gravity data and the insight into phenomena under the ground when and after earthquakes occur. The results of time series analysis of postseismic gravity changes with GRACE data show that the gravity which decreases coseismically keeps on decreasing for a few months and increases for a longer period; the postseismic gravity changes have two components (short- and long-term gravity changes). This is a new discovery and this also suggests that the gravity observation gets the different postseismic phenomena with different polarities.

The mechanisms of coseismic gravity changes are well known but those of short- and long-term postseismic gravity changes are not clear completely. They are explained with afterslip and viscoelastic mantle relaxation to some extent but each of them has each problem.

Although the mechanisms of postseismic gravity changes have rooms to be discussed, the gravity observation can do what the seismographs, GNSS and SAR cannot do; the gravity observation separates the postseismic phenomena.

High resolution mapping of ice mass trend in Greenland using GRACE GFZ solution

MATSUO, Koji^{1*} ; FUKUDA, Yoichi¹

¹Graduate school of Science, Kyoto University

The gravity satellite mission GRACE has been measuring monthly variations of the Earth's gravity field since its launch in 2002. The GRACE data has updated from RL04 to RL05 in May 2012, and have been provided in the form of spherical harmonic (Stokes') coefficients with degree and order up to 60 (d/o60) from CSR and JPL. In addition, GFZ has provided Stokes coefficients with d/o90 as RL05a product in December 2013. In this study, we examine the measurement error of GFZ RL05a product (d/o90). Then we attempt to delineate a high resolution map of ice mass trend in Greenland by making use of the full Stokes' coefficients.

First, we examine the measurement error. Following the method of Wahr et al. (2006), we derive temporal and spatial variation of the measurement error from error variance matrix of GRACE data. The global average of RL05a error is about 100cm in equivalent water thickness. Because RL04 error is about 300cm, RL05a achieves triple the precision improvement. The temporal variation of error in global average is about 200 cm from January 2003 to July 2003, and reduces to about 100cm afterwards. The spatial distribution shows large error in equatorial region (about 130cm) and small error in polar region (about 40cm). Considering these results, it can be said that the quality of RL05a is especially high in polar region after August 2003.

Next, we derive ice mass trend in Greenland from GFZ RL05a (d/o90) product. Here we apply de-stripping filter (Swenson and Wahr, 2006) to alleviate the noise. In addition, we employ spherical Slepian Basis (Harig and Simons, 2012) to extract ice mass trend in Greenland effectively. In doing so, we can successfully delineate a clear ice mass trend map with about 200 km spatial resolution, which is 1.5 times as high as before. We confirmed very good agreement with ICESat result.

Keywords: Satellite gravimetry, Greenland, Ice sheet mass variation, Space geodesy, GRACE, ICESat

Establishment of GSIGEO2011 (Japanese geoid model)

KODAMA, Tokuro^{1*} ; MIYAHARA, Basara¹ ; KAWAWA, Hiroshi¹ ; KUROISHI, Yuki¹

¹GSI of Japan

Geospatial Information Authority of Japan (GSI) established Japanese geoid model "GSIGEO2000". The model has enabled a translation from ellipsoidal heights to orthometric heights in GNSS survey for triangulation points, which are positional reference for surveys in Japan. As a result, the model greatly has contributed to realize efficient control point survey. In order to expand utilization field of geoid model to height determination of third-order benchmarks by GNSS satellite positioning, GSI has established new Japanese geoid model "GSIGEO2011" and reported here.

GSIGEO2011 has established as a hybrid geoid model of a gravity geoid model and observed geoid height data. New Japanese gravity geoid model, JGEOID2008 (Kuroishi, 2009), is adopted as the base model, and least square collocation method is adopted to fit the model to observed geoid height data obtained at over 750 GNSS-based control stations all over Japan. In order to utilize for height determination of third-order benchmarks, residuals between the model and input observed geoid heights are set to 2cm in standard deviation. JGEOID2008 is greatly improved at reduction of local systematic errors which are contained in older gravity geoid models. Therefore, short wavelength components in geoid are well described and fit to observed data, and as a result, the accuracy of the hybrid model is improved.

The 2011 off the Pacific coast of Tohoku Earthquake caused huge crustal deformation in an wide area around eastern Japan. GSI urgently conducted control point surveys for restoration and opened the result for eastern Japan. GSI also conducted geoid surveys for GNSS-based control points which is located in an area experienced huge crustal deformation, and the results have been utilized for the input geoid heights data of GSIGEO2011. Therefore, GSIGEO2011 is consistent with the revised survey results in eastern Japan.

GSI has published newly established GSIGEO2011 and tired to realize height determination of third-order benchmarks by GNSS survey referring GNSS-based control points which have orthometric heights. This challenge is expected to drive further improvement in efficiency of survey procedure in Japan.

Keywords: GSIGEO2011, Geoid model, survey results

The Japan Gravity Standardization Net 2013 (JGSN2013)

YOSHIDA, Kenji^{1*}

¹GSI of Japan

Geospatial Information Authority of Japan (GSI) have established new gravity standardization net, the Japan Gravity Standardization Net 2013 (JGSN2013), from the latest absolute and relative land gravity data which covers Japanese islands. GSI already established and published the Japan Gravity Standardization Net 1975 (JGSN75), which is consistent with the International Gravity Standardization Net 1971 (IGSN71). JGSN75 have been officially referred as Japanese gravity standard.

JGSN2013 have been established by combining gravity data obtained from primary-order absolute gravity survey and first-order relative gravity survey. In Tohoku area, at least one gravity survey was done for each gravity benchmark after the 2013 off the Pacific coast of Tohoku Earthquake. Therefore, the gravity survey data include gravity change caused by the earthquake.

JGSN2013, which is the second Japanese gravity standard net established by GSI, have achieved great improvement in accuracy and special coverage by adopting FG5 absolute gravity meter as an instrument, updating station coordinates to ITRF2008 and modifying tidal correction procedure to more consistent manner through all process. As a result, JGSN2013 have a capacity not only to contribute to monitoring of earth gravity field, which is promoting by GGOS, but also to be registered to international absolute gravity database (AGrav), which is operated as a joint project by IAG IC-WG2.1 and IGFS. The establishment of JGSN2013 is reported in the paper.

Keywords: The Gravity Standardization Net, JGSN75, JGSN2013

Calibration of the superconducting gravimeter iGrav10 by parallel observation with the absolute gravimeter FG5 #217

SUGIHARA, Mituhiko^{1*} ; NAWA, Kazunari¹ ; MIYAKAWA, Ayumu¹

¹AIST

An iGrav superconducting gravimeter (SG) was re-installed in the Farnsworth field, TX for the purpose of studying the effects of CO₂ injection at an enhanced oil recovery (EOR) site in December 2013. Usually the iGrav SG has an ultra-low drift of less than 0.5 microGal / month and a virtually constant scale factor. Empirically, the drift rate looks negligible using the TSoft program. However observed trend contains the drift-like component which is about 0.4 microGal / day. Strictly it is difficult to distinguish real gravity changes from time-varying instrumental drift. We made co-located measurements with the FG5 absolute gravimeter (AG) in middle of December 2013 and middle of January 2014. The gravity differences between the two periods was determined to be +1 +/-2 microGal by the AG measurements, whereas -12 microGal by the SG measurements. The observed drift of the SG was much larger than the specified value, so that the SG was determined to be reset and is improved. Generally it takes at least six months to evaluate such low drift of less than 0.5 microGal / month using co-located measurements with AG. Another choice is parallel SG and SG measurements located in close proximity. We are planning such measurements at the Farnsworth site in 2014. This research is funded and supported by Ministry of Economy, Trade and Industry (METI).

Keywords: Superconducting gravimeter, iGrav, absolute gravimeter, FG5, parallel observation

Densed gravity survey on the southeastern Kego fault system

NISHIJIMA, Jun^{1*} ; FUJIMITSU, Yasuhiro¹

¹Faculty of Engineering, Kyushu University

The Kego fault system is one of the active fault located in Fukuoka city, southwestern Japan. We have conducted densed gravity survey on the southeastern Kego fault systems. One of the purposes of the survey is to reveal the location and detailed shape of the active fault syatem. We have measured gravity value at 721 points using Scintrex CG-3+ and CG-5 gravimeter. The measurement point interval was arranged as about several tens to hundreds meters. The measured gravity values were processed with a series of correction (height, drift, tidal, the free-air, the Bouguer and terrain) in order to obtain a gravity anomaly map. We determined the Bouguer density of 2.47 g/cm³ using an objective Bayesian approach (Murata, 1993).

According to the gravity anomaly map of the Fukuoka City area that consists of not only our gravity data but also the gravity data of other institutions, the gravitational basement, which has a high density and affects to the gravity anomaly, is thought as Paleozoic Sangun metamorphic rocks and Cretaceous plutonic rocks (Sawara Granite, etc.) (Karakida et al., 1994). And a clear low gravity anomaly extension that has a strike of NW-SE is detected and coincides with the location of Kego Fault confirmed by a trenching survey (Shimoyama et al., 2005).

We will report the result of a three-dimensional analysis using GRAV3D ver. 3.0 (Li and Oldenburg, 1998).

Keywords: Densed gravity survey, active fault, gravity anomaly

Crustal thickness deduced from a three-dimensional gravity modeling with seismic survey results

FUJIOKA, Yukari^{1*} ; ISHIHARA, Takemi² ; OIKAWA, Mitsuhiro¹ ; KANEDA, Kentaro¹ ; NISHIZAWA, Azusa¹

¹Hydrographic and Oceanographic Department, Japan Coast Guard, ²National Institute of Advanced Science and Technology

The Japan Coast Guard (JCG) has conducted multichannel seismic reflection and refraction surveys as part of the Continental Shelf Survey from 1983 through 2008 in the area from the northwest part of the Pacific plate to the Philippine Sea plate. On the other hand, it has also conducted marine gravity surveys in the same area and possesses enormous amount of gravity data. We calculate crustal density distribution by applying the three-dimensional gravity inversion method (Ishihara and Koda, 2007) using these data.

This method has performed in the following procedures: First, an initial density structure model constituting of seawater, sediment, crust and mantle is made by interpolation of seismic survey results with reference to a gravity distribution. Second, gravity anomalies are calculated using the initial model. Mantle Bouguer anomalies are calculated by subtracting a constant, which depends on the regional structure, from the differences between observed and calculated gravity anomalies. Finally, the Moho depths are obtained by inversion analysis to minimize the mantle Bouguer anomalies. We can estimate the crustal thickness distribution in this way.

It confirmed that the above method improves the initial model with the Moho depths due to velocity structure from refraction surveys, and that a more appropriate density structure model can be obtained.

In addition, it is necessary that whole structure depending on a sea area with the effects given by structure, such as a density and/or a thickness of sediment and/or lithosphere, should be considered if the effects of them are large. For example, in the case of the northwest part of Philippine plate, we found that the thickness of the lithosphere depending on its age strongly affects the result of the inversion. Therefore, we used the calculated gravity data after removal of variation for wave length than or equal to 400 km in order to remove effect given by the structure under crust.

We will report these revisions and the crustal thickness distribution in several sea areas. It is expected that gravity determination of the crustal thickness distribution in large sea area gives important clues on tectonic evolution of crust.

Keywords: gravity

Estimation of the density structure beneath the Kanto District, Japan, by 3-D gravity inversion

EDO, Tatsumi^{1*} ; YAMAMOTO, Akihiko¹

¹Graduate School of Science and Engineering, Ehime University

We applied an improved gravity inversion technique by Bear et al. (1995) to rapidly invert Bouguer gravity data in Kanto District, Japan, for a 3-D density distribution as a source of the observed field. The technique estimates the density distribution within the source volume using a least-squares inverse solution that is obtained iteratively by singular value decomposition using orthogonal decomposition of matrices with sequential Householder transformations. The source volume is subdivided into a series of right rectangular prisms of specified size but of unknown density. This discretization allows the construction of a system of linear equations relating the observed gravity field to the unknown density distribution. Convergence of the solution to the system is tightly controlled by a damping parameter which may be varied at each iteration. Application to a gravity data set from Kanto District, Japan, has yielded a geologically reasonable result that agrees with published models derived from interpretation of gravity, magnetic, seismic, and drilling data.