

## Creating future of solid Earth science with high performance computing (HPC): Introduction

HORI, Takane<sup>1\*</sup> ; HINO, Ryota<sup>2</sup> ; HONKURA, Yoshimori<sup>3</sup> ; KANEDA, Yoshiyuki<sup>1</sup> ; ARIKAWA, Taro<sup>4</sup> ; ICHIMURA, Tsuyoshi<sup>5</sup> ; TODORIKI, Masaru<sup>5</sup>

<sup>1</sup>JAMSTEC, <sup>2</sup>Tohoku University, <sup>3</sup>Tokyo Institute of Technology, <sup>4</sup>Port and Airport Research Institute, <sup>5</sup>University of Tokyo

In Japan, high performance computing (HPC) had been driven by computer science community (HPC developer). However, recently, computational science community (HPC user) has been expected to contribute to the planning and development of the next generation HPC showing the scientific and/or social issues to be solved for the next 10-20 years using HPC. In various fields of science using HPC, scientists have started to discuss scientific and/or social issues to be solved in each field. Hence, in this session, we aim to examine such issues in solid Earth science, which HPC can contribute to solve. For social issues, we will focus on earthquake and tsunami disaster mitigation. For scientific issues, we would like to discuss construction of the next generation of solid Earth model based on the big data of seismic waves and crustal deformation obtained by high-density observation networks. We will introduce the contents of the "white paper" of the future plans for computer science in various fields including solid Earth science.

Keywords: HPC, hazard mitigation

## The K Computer and Japan Plan for Exascale

HIRAO, Kimihiko<sup>1\*</sup>

<sup>1</sup>AICS RIKEN

At the end of September 2012, official operation of the Kcomputer has started. Already in many areas we see many great results. Users of K are actually very much impressed having experienced using K. The K is Japanese supercomputer jointly developed by Fujitsu and Riken and everything is made in Japan. The K computer won the top position on TOP500 in 2011 achieving a LINPACK benchmark performance of 10 petaflops - becoming the first supercomputer ever to reach this milestone. The K fell behind China and US machines on the latest TOP500. We believe that the K is still one of the most powerful and user-friendly machine in the world. K demonstrates an extraordinary level of stability. K is capable of sustained performance of 1 PF on real applications in a wide range of science. K is the strong science machine.

Computer simulation is becoming more and more important for contemporary science and engineering. Nobel Prizes 2013 in chemistry and physics show how computing is changing every field of research. Particularly simulations performed on the supercomputer will drive progress in science and technology and play an important role in solving difficult problems that we face as a society. There are very critical issues that need to be solved - global warming, alternative energy, disaster mitigation, new materials, healthcare, security, etc. The role of simulations will become increasingly larger, and the results that they provide will undoubtedly greatly affect society. The new frontiers opened up by the K computer will be presented.

The post K project will be lauced from April 2014. MEXT selected RIKEN AICS to develop a new exascale supercomputer by 2020. The post K is 100 times faster than the current K computer. Architecture is hybrid of general-purpose plus accelerator components. We will push the state of the art in power efficiency, scalability & reliability. Power consumption is limited in the range of 30-40MW.Total project cost is ca. JPY140 billion with about JPY 110 billion coming from the government's budget (JPY 1.2 billion for 2014)

Computer simulation will dramatically increase our ability to understand the world around us. With exascale computing, we are reaching a tipping point in predictive science. Its success will have lasting impact on the planet and people all around the world and for generations into the future. With a planned deployment in 2020, the new system is expected to keep Japan at the leading edge of computing science and technology.

## The application of simulation studies using HPC to disaster management: current status and future.

YOKOTA, Takashi<sup>1\*</sup> ; TAIRA, Yutaro<sup>1</sup>

<sup>1</sup>Cabinet Office

In Central Disaster Management Council, estimations of damage by anticipated earthquakes have been conducted to plan measures for disaster management(preparedness, emergency response and recovery). Also, when a large earthquake occurs early assessments of the damage have been carried out immediately to grasp the situation of the disaster and to support decision-making for emergency response operations in central government. These estimations and assessments require high accuracy to develop more effective measures and to decide more appropriate operations.

It is indisputable that the sophistication of forecasting techniques of natural phenomena is necessary to mitigate human damage by encouraging residents to evacuate.

In this presentation, we will introduce our approaches described above, and would like to talk about what to expect from the application of simulation studies using High Performance Computing to the disaster management of earthquakes and tsunamis in particular.

Keywords: disaster managent, damege estimation, HPC

## Development of Integrated Earthquake Simulator on K-computer

ICHIMURA, Tsuyoshi<sup>1\*</sup> ; HORI, Muneeo<sup>1</sup>

<sup>1</sup>Earthquake Research Institute, The University of Tokyo

Earthquake simulation with high-resolution and high-accuracy could have significant contribution on making rational and effective counter measures against earthquake disaster. Such earthquake simulation must consider whole process from a fault rupture to city responses, since each process has significant effects on the resulting responses. We are now developing such earthquake simulation system on K-computer, which is called Integrated Earthquake Simulator (IES). IES combines spatial data and earthquake simulation with a high-fidelity model to simulate the whole process. The target domain of earthquake simulation is typically very large, making it difficult to prepare sufficient data to construct a high-fidelity model. Even if a high-fidelity model can be constructed, it is difficult to resolve the computational expense due to the discretization of such models. Thus, simplified analyses or analytical methods are typically used in earthquake simulation. However, the construction of high-fidelity models has become popular with recent increases in available spatial data, and a considerable volume of data from high-density observation networks is now available for checking their validity. The realization of analyses using high-fidelity models is desirable. Several examples of analyses using such models can currently be found on the K-class supercomputer, although the resolution is not yet adequate. In this presentation, we discuss the following earthquake simulations (parts of IES) on the K computer, together with problems to be solved: non-linear wave simulation with high resolution, crust deformation analysis with island-scale and the seismic response analysis of soil-structures system.

Keywords: earthquake simulation, high performance computing, high fidelity, high resolution and accuracy

## Consideration to the resiliency of protective structures against tsunami by using High Performance Computer

ARIKAWA, Taro<sup>1\*</sup> ; OIE, Takayuki<sup>1</sup> ; TOMITA, Takashi<sup>1</sup>

<sup>1</sup>Port and Airport Research Institute

The Committee for Technical Investigation on Countermeasures for Earthquakes and Tsunami Based on the Lessons Learned from the "Great East Japan Earthquake" (2011) of the Central Disaster Management Council has responded to the Great East Japan Earthquake by proposing that basically, two levels of tsunami must be hypothesized to build future tsunami countermeasures. One is a tsunami hypothesized to build comprehensive disaster prevention countermeasures centered on evacuation of residents. It is set based on a survey of tsunami deposits formed over an ultra-long period and observations of crustal movement, and it is a maximum class tsunami which, although it occurs extremely rarely, causes devastating damage when it does occur. One more is a tsunami which is hypothesized to build coastal protection facilities such as breakwaters and other structures which prevent tsunami from inundating inland regions. It is a tsunami which occurs more often than the maximum class tsunami, and although it is a low type of tsunami, it causes severe damage. At such times, technological development of structures which are capable of resiliently providing effects even under tsunami height which is the object of the design must continue for coastal protection facilities etc. to be improved. So, in this research, the protective effectiveness is considered by using STOC-CADMAS(Arikawa and Tomita, 2005).

## Determination of Earth structure using waveform inversion and Spectral-Element Method

TSUBOI, Seiji<sup>1\*</sup> ; MIYOSHI, Takayuki<sup>1</sup> ; OBAYASHI, Masayuki<sup>1</sup> ; TONO, Yoko<sup>1</sup>

<sup>1</sup>JAMSTEC

Recent progress in large scale computing by using Spectral-Element Method and the Earth Simulator has demonstrated possibilities to perform full-waveform inversion of three dimensional (3D) seismic velocity structure inside the Earth. Specifically Liu and Tromp (2006) have shown that it becomes feasible to compute finite frequency kernel for seismic velocity structure based on adjoint method. We apply their method to obtain 3D velocity structure beneath East Asia. We take one chunk from global mesh of Spectral-Element Method and compute synthetic seismograms with accuracy of about 10 second. We use GAP-P2 mantle tomography model (Obayashi et al., 2009) as an initial 3D model and try to use as many broadband seismic stations available in this region as possible to perform inversion. We then use the time windows for body waves and surface waves to compute adjoint sources and calculate adjoint kernels for seismic velocity structure. We use the earthquakes, which occurred in East Asia since 2001, with magnitude greater than 5.5 and selected 161 events for this inversion. One iteration of the waveform inversion using 256 cores of massively parallel supercomputer, such as K-computer, requires 0.1 million CPU hours. We have performed several iteration and obtained improved 3D velocity structure beneath East Asia. The result demonstrates that waveform misfits between observed and theoretical seismograms improves with the iteration proceeds and it now becomes feasible to perform waveform inversion within practical computational time. We will use much shorter period in our synthetic waveform computation and will try to obtain seismic velocity structure for basin scale model in our future study.

Acknowledgements: We used F-net seismograms of the National Research Institute for Earth Science and Disaster Prevention. This study was supported by the strategic Programs for Innovative Research "Field 3" Advanced prediction Researches for Natural Disaster Prevention and Reduction.

Keywords: Earth structure, Seismic tomography, Synthetic seismogram, Spectral Element Method

## Mantle convection simulations on HPC: past, present and future

KAMEYAMA, Masanori<sup>1\*</sup> ; MIYAGOSHI, Takehiro<sup>2</sup> ; FURUICHI, Mikito<sup>2</sup> ; NAKAGAWA, Takashi<sup>2</sup> ; YANAGISAWA, Takatoshi<sup>2</sup> ; NAKAKUKI, Tomoeiki<sup>3</sup> ; OGAWA, Masaki<sup>4</sup>

<sup>1</sup>GRC, Ehime University, <sup>2</sup>JAMSTEC, <sup>3</sup>Hiroshima University, <sup>4</sup>University of Tokyo

In this presentation, we will discuss (a rather personal view of) the possible directions of the advanced numerical studies of mantle dynamics in concert with the progress of high-performance computing in the next era. We will start with a brief overview of the research targets and outcrops of the numerical modelings of mantle convection to date from a viewpoint of geosciences. Then we will discuss the scientific goals which the mantle dynamics researchers are to tackle with in coming years, together with the technical issues in terms of both software and hardware developments.

Keywords: mantle convection, numerical simulation

## Cloud Services to Release Techniques of Data Assimilation

NAGAO, Hiromichi<sup>1\*</sup> ; HIGUCHI, Tomoyuki<sup>2</sup>

<sup>1</sup>Earthquake Research Institute, The University of Tokyo, <sup>2</sup>The Institute of Statistical Mathematics

Data assimilation (DA) is a fundamental technique to integrate numerical simulations and observation data in the framework of the Bayesian statistics. The purpose of DA is to provide an assimilation model that enables us to predict the future state and/or to determine parameters in the given simulation model. A sequential Bayesian filter, e.g., Kalman filter and particle filter, alternatively estimates probability density functions of one-step-ahead prediction and filtering, which respectively mean the states conditionally given the past observation data and given both past and present observation data. DA seems to be hard to implement due to complex programming of the procedure and needed numerous computation, which essentially requires High Performance Computing (HPC). Cloud service (CS) can be a solution for this through an implementation of the DA procedure on a parallel computing environment.

We have developed and released several CSs related to DA such as CloCK-TiME (Cloud Computing Kernel for Time-series Modeling Engine) and DA system for seismoacoustic waves. CloCK-TiME enables us to carry out a multivariate time-series analysis using the particle filter through the Internet. Users can, via the user interface, construct observation and system models, and specify optional parameters to control the analysis in detail. DA system for seismoacoustic waves enables us to determine hypocentric parameters through DA based on a numerical simulation related to seismoacoustic wave propagation using the normal model summation and observed infrasound data obtained at Shionomisaki and Sugadaira.

We will discuss the importance and availability of CS for DA researches through introduction of CSs we have developed.

Keywords: cloud computing, data assimilation, time-series analysis, seismoacoustic wave, multivariate analysis



## Techniques of Big-Data Processing on the NICT Science Cloud

MURATA, Ken T.<sup>1\*</sup>; WATANABE, Hidenobu<sup>1</sup>; UKAWA, Kentaro<sup>2</sup>; MURANAGA, Kazuya<sup>2</sup>; YUTAKA, Suzuki<sup>2</sup>; TATEBE, Osamu<sup>3</sup>; TANAKA, Masahiro<sup>3</sup>; KIMURA, Eizen<sup>4</sup>

<sup>1</sup>NICT, <sup>2</sup>Systems Engineering Consultants Co., LTD., <sup>3</sup>University of Tsukuba, <sup>4</sup>Ehime University

This paper is to propose a cloud system for science, which has been developed at NICT (National Institute of Information and Communications Technology), Japan. The NICT science cloud is an open cloud system for scientists who are going to carry out their informatics studies for their own science.

The NICT science cloud is not for simple uses. Many functions are expected to the science cloud; such as data standardization, data collection and crawling, large and distributed data storage system, security and reliability, database and meta-database, data stewardship, long-term data preservation, data rescue and preservation, data mining, parallel processing, data publication and provision, semantic web, 3D and 4D visualization, out-reach and in-reach, and capacity buildings.

In the present study, we examine performance of parallelization of I/O on the NICT Science Cloud system. We examine an I/O performance of data file system; distributed file system (Gfarm). The Gfarm file system shows a tremendous fast I/O, as fast as 23 GB/sec using only 30 servers. We should pay attention to this I/O speed (23GB/sec is 184 Gbps) from the viewpoint of network speed. We also discuss that the distributed file system shows high scalability: Parallelization efficiency in the present examination is higher than 90% in case of parallel file system. We finally discuss high-performance data processing on the NICT Science Cloud. We have already archived several examples using our technique for both Earth and Space observation data and simulation data. The speed up of the data processing is more than 60 times for scientific big-data.

## Creating future of solid Earth science with high performance computing (HPC): Discussion

HINO, Ryota<sup>1\*</sup> ; HORI, Takane<sup>2</sup> ; HONKURA, Yoshimori<sup>3</sup> ; KANEDA, Yoshiyuki<sup>2</sup> ; ARIKAWA, Taro<sup>4</sup> ; ICHIMURA, Tsuyoshi<sup>5</sup> ; TODORIKI, Masaru<sup>5</sup>

<sup>1</sup>Tohoku University, <sup>2</sup>JAMSTEC, <sup>3</sup>Tokyo Institute of Technology, <sup>4</sup>Port and Airport Research Institute, <sup>5</sup>University of Tokyo

How the evolution of High Performance Computing (HPC) contributes to progress in earth sciences? We will develop a perspective in the next 10 to 20 years based on comprehensive discussion provided in the session including invited talks. Especially, we will discuss what is necessary for solving the social issues such as improvement of hazard maps, tsunami warning system, long-term forecast, etc. The aim of the concluding discussion is to integrate the opinions of attendees, both speakers and non-speakers, into a proposal for development of next generation HPC as a solution to important problems in terms of scientific breakthrough and social relevance.