

断層における浸透率と粒子破碎の関係ーメタンハイドレート貯留層特性評価を目的としてー

Relationship of permeability and particle breakage of experimental fault -Evaluation for the methane-hydrate reservoir-

木村 匠^{1*}; 金子 広明¹; 伊藤 拓馬¹; 皆川 秀紀¹
KIMURA, Sho^{1*}; KANEKO, Hiroaki¹; ITO, Takuma¹; MINAGAWA, Hideki¹

¹ 産業技術総合研究所メタンハイドレート研究センター貯留層特性解析チーム
¹Reservoir Modeling Team, Methane Hydrate Research Center, AIST

Methane hydrate is expected to be an energy resource in the future. As results of coring and logging, the existence of a large amount of methane-hydrate is estimated in the east Nankai Trough, offshore central Japan, where many folds and faults have been observed. Permeability in methane hydrate-bearing sediment is important factors for estimating the efficiency of methane gas production. In this study, we use a ring-shear apparatus to examine the relationship between the permeability and grain size reduction of silica sand sample after large displacement shearing under tested effective normal stresses ranging from 0.5 MPa to 8.0 MPa. The grain size distribution in the shear zone of sand specimen after ring-shearing at each normal stress level is analyzed by laser particle analyzer. The permeability and grain size reduce with the increasing the effective normal stress due to particle breakage. The relationship between permeability and grain size distribution after ring-shearing is expressed well by a curve in each sand, silt and clay size content. In the first group, the sand size content is up to about 80 %, permeability drastically decreases by two orders of magnitude. In the second group, the sand size content is less than about 80 %, the permeability is almost constant. In the silt and clay size, the both contents are up to about 10 %, the permeability abruptly decreases, while, the permeability gradually decreases over about 10 %. The results are indicated that the grain size reduction and the effective normal stress during shearing are one of the controlling factors of the permeability in fault of sand. This study is financially supported by METI and Research Consortium for Methane Hydrate Resources in Japan (the MH21 Research Consortium).

キーワード: 断層, 粒子破碎, 浸透率, 粒度組成, リングせん断試験

Keywords: Fault, Particle breakage, Permeability, Grain size distribution, Ring-shear test