

## Relationship between sound velocity and density of liquid alloy under pressure

TERASAKI, Hidenori<sup>1\*</sup> ; NISHIDA, Keisuke<sup>2</sup> ; URAKAWA, Satoru<sup>3</sup> ; KUWABARA, Souma<sup>1</sup> ; TAKUBO, Yusaku<sup>1</sup> ; SHI-MOYAMA, Yuta<sup>1</sup> ; UESUGI, Kentaro<sup>4</sup> ; TAKEUCHI, Akihisa<sup>4</sup> ; SUZUKI, Yoshio<sup>4</sup> ; KONO, Yoshio<sup>5</sup> ; HIGO, Yuji<sup>4</sup> ; KONDO, Tadashi<sup>1</sup>

<sup>1</sup>Osaka Univ., <sup>2</sup>Univ. Tokyo, <sup>3</sup>Okayama Univ., <sup>4</sup>JASRI, <sup>5</sup>HPCAT

It is important to understand the relationship between sound velocity and density of liquid Fe-alloys under high pressure for obtaining a constraint of the composition of the molten outer core from observed seismic data. We have studied a relationship between sound velocity and density of liquid alloy based on simultaneous measurement of these properties under high pressure and high temperature. Sound velocity was measured using ultrasonic pulse-echo overlapping method and density was measured employing X-ray absorption method combined with X-ray tomography technique. The measured P-wave velocity and density of liquid Ni<sub>90</sub>S both increase with pressure. From these data, adiabatic bulk modulus ( $K_{S0}$ ) of the liquid sample can be well constrained to 29 GPa. It is note that the measured P-wave velocity is found to increase linearly with increasing density. This result provides an important issue in terms of Birch's law for liquid material.

Keywords: Sound velocity, density, liquid, high pressure