

Assessment of weathering grades for different chemical and geomechanical properties; A Sri Lankan case study

UDAGEDARA, Dashan T.^{1*} ; OGUCHI, Chiaki T.² ; GUNATILAKE, Jagath K.³

¹Uva Welassa University, Saitama University, ²Saitama University, ³University of Peradeniya

Having a better understanding of the weathering grade of rock materials is highly beneficial in the perspective of civil engineering and geology. The classification of weathering grades can be performed based on the chemical, physical, mineralogical, textural and strength properties of rocks. Among those, the use of chemical components to classify weathering grades is not very promising for all types of rocks. Based on the mobility of elements various chemical indices for weathering grades have been formulated. Most of those indices are based on experiments of weathered acidic igneous rocks under humid and well drained environments. There are only a few indices formulated for sedimentary and metamorphic rocks, so the use of chemical weathering indices for the classification of weathered metamorphic rocks would not be convincing. However, the use of physical and strength properties for the assessment of weathering grades is comparatively convenient. A better variation of those properties with respect to weathering grades is resultant irrespective to rock type. Therefore, this study focuses on assessing weathering indices using physical, strength and chemical properties of a selected metamorphic rock and evaluating the correlation among the indices derived from those properties.

Fresh and weathered rocks of garnet-sillimanite gneiss were selected from the Samanalawewa Hydropower Project. Weathering grades were visually assessed initially, then confirmed with physical and strength properties using tests on dry density, water content, ignition loss, point load strength and slake durability. Whole rock geochemical data were used to calculate weathering indices.

Physical and strength properties show a marked difference with weathering grades. However, chemical indices are not very convincing. Silica-Titania, Product index and Ruxton ratio show a gradual variation with weathering grades. Mobiles index also shows an acceptable variation. However, the modified weathering potential index, which was formulated for metamorphic rocks, Parker index, which was formulated for all types of rocks, do not show a gradual variation with weathering grades. Chemical index of alteration and weathering (CIA and CIW) do not show a recognizable variation with weathering grades. Physical and strength properties show good correlation with most of chemical indices. In addition, most chemical weathering indices show good correlation with each other. The Lixiviation index is the one shows weak correlation with most of other chemical weathering indices. The failure of some indices in showing a good correlation can be accounted for the heterogeneity of garnet-sillimanite gneiss.

Keywords: Weathering grades, Rock weathering, Chemical weathering index

Spheroidal weathering process of granite porphyry with columnar joints to form corestones covered with rindlets

HIRATA, Yasuto^{1*} ; CHIGIRA, Masahiro² ; CHEN, Youqing³

¹Graduate School of Science, Kyoto University, ²Disaster Prevention Research Institute, Kyoto University, ³Graduate School of Energy Science, Kyoto University

In the southeast mountainous region of the Kii peninsula, Japan, granite porphyry shows typical spheroidal weathering, in which 0.4-1.5 m diameter of corestones are made with scale-like rindlets. The rindlets are made by the exfoliation of surface parts of a corestone by mineral-chemical alteration and crack propagation, of which processes were poorly known. We made field investigation and made analyses and measurements for mineralogy, chemistry and physical properties of rock samples and found that the oxidation of colored minerals and iron precipitation creates micro-cracks, which separates rindlets from a corestone.

Fresh granite porphyry has almost vertical columnar joints with 2-6 m intervals and is intersected near the ground surface by the sheeting joints. At the beginning of the spheroidal weathering, an oxidation front is made along joint surfaces to form a brown band. Brown bands were 2.5-5 cm thick and individual rindlets were 3.5-5 cm thick regardless of radius of corestones, which suggests that the rindlet separation occurs when a brown band thickness reaches about 5 cm. Thin-section observation and XRD analyses indicated that pyrite is depleted, chlorite is transformed into vermiculite, and iron(III) hydroxides precipitate in the brown band. Microscopic observation of cut surfaces of rock samples impregnated with fluorescent resin showed that pores are filled with the precipitate and micro-cracks form subparallel to the oxidation front in the brown band. Cracks in the brown band or rindlets seem to converge at aggregates of iron(III) hydroxides and vermiculite, and cracks form a network subparallel to the oxidation front with 0.5-2 cm interval at a maximum. In the brown band, P-wave velocities increased up to 10%, but tensile strengths with fracture surface parallel to the oxidation front decreased in the brown band than those of fresh rock. These physical property changes are due to pore filling and crack development in the brown band. The mass balance calculation using densities and Ti concentrations of rock samples did not detect rock volume changes in the brown band and the inner rindlets, but suggested that rock volumes increased by 20% in the outer rindlets and by 80% in the saprolite from the fresh rock. Mass balance calculation also suggested that chemical components are leached out in the brown band, the rindlets, and the saprolite in a consistent way. A corestone is thus getting smaller with the exfoliation of rindlets from brown bands, which gradually migrates inside the corestone by the oxygen diffusion, then rindlets are finally disintegrated into saprolite.

Keywords: spheroidal weathering, weathering rind, granite porphyry, crack, oxidation, P-wave velocity

Regarding to the arguing issue; Bioweathering vs Bioprotection in stone historical buildings

SONG, Wonsuh^{1*}; WARAGAI, Tetsuya²; OGUCHI, Chiaki¹

¹Graduate School of Science and Engineering, Saitama University, ²Department of Geography, College of Humanities and Sciences, Nihon University

The Angkor complex is the one of the greatest cultural heritages in the world. It is constructed in the early 12th century, designated as a world cultural heritage by UNESCO in 1992. The temples at the Angkor complex are mainly made of sandstone and laterite. However, due to the tropical climate, plants, lichens and various microorganisms are growing well on the rock surface. Black crusts are also easily found on the stone surface. Biological factors are considered as a damage factors for the heritage. The studies suggested that how it can be removed without destroying the substrate efficiently.

We sampled Angkor sandstone covered by black crust at the Angkor Wat and Bayon temples, Angkor complex, and observed the section and the surface of the rock sample by using SEM. Surfaces of the samples are not polished in order to observe the original condition. The depth of the black crust is up to 1 mm. Many filamentous materials were found on the black crust. Average energy-dispersive X-ray spectroscopy data of the black crusts shows that over 70 % of the surface materials are compounds of carbon. And 15% of the mass are made of SiO₂. It seems that these materials are hyphae. The shape of the hypha is like a thread and its size is few μm in diameter and up to several centimeters in length. Black crusts are consisted of elements and compounds of carbon, Na, Mg, Al, Si, Cl, K, Ca, and Fe.

The answer of the controversy question "Do lichens on the historical building protect it or not?" is not fixed. It protects while weathers. It depends on the time scale and the surroundings. We have to focus on the timing of the lichen fall off. Under the lichen coverage, rocks may be protected. When the lichen fall off, it may have lower surface than lichen-free rock surface. Weathering is in progress and is a result of previous process under various facts, not only biological factors but wet-dry cycle, various salt and so on. This is the reason why it is hard to judge whether lichens should be removed or not. We have to check all the environmental data such as temperature, humidity, direction, insolation, rainfall frequency, human effect, weathering degree etc. and decide to remove or not. Therefore, field survey and evaluation standard are needed. Further research has to be continued to find out the better and proper way of conservation for the historical sites as Angkor monument.

Keywords: Angkor Wat, stone cultural heritage, conservation, lichen, biological weathering

Accumulation of radioactivity inside Yoshimi archeological heritage

RAJIB, Mohammad^{1*} ; KODAMA, Shogo¹ ; SONG, Wonsuh² ; OGUCHI, Chiaki T.²

¹Graduate School of Science and Engineering, Saitama University, ²Department of Civil and Environmental Engineering, Saitama University

The Hundred Caves of Yoshimi is a cluster of ancient grave caves dug on the cliff made of tuffaceous sandstone located in Yoshimi town, Saitama. It was designated as a national historic site on March 7, 1923. Built between late 6th century and late 7th century, the caves were initially made for only the blood royal and other big powerful families but later used for large scale of underground munition factory. At present, the area is used for tourist attraction. Continuous survey has revealed that the caves are heavily affected by salt weathering, mostly by gypsum. However, seasonal changes have also been observed in salt formation. As part of that survey, accumulation of natural radioactivity, significantly anomalous than background level, has been observed inside some of the caves of Yoshimi. The survey has been carried out to all accessible caves and radioactivity was measured by Horiba Radi PA-1000 radiation monitor within 2-5 cm of the wall. Radioactivity was found to be as high as 0.119 micro sievert per hour in some of the walls which is more than twice of the natural radioactivity found at the entrance of the area. This amount is marginally higher than the radiation dose limits for general public. Having similar rock type in all the caves, the reason of such accumulation of radioactivity is lichen formation in the inside walls which is a known bio-accumulator of radioactivity. Though studied walls are still out of reach of tourists visiting Yoshimi caves, spreading of lichen to other walls might increase the radioactivity risk. Such accumulation of radioactivity also needs to be considered if other caves are opened for tourists in future. Specific source of radioactivity also needs to be investigated through detail survey.

Keywords: Natural Radioactivity, Yoshimi caves, Weathering, Lichen, Bio-accumulator, Radiation dose

Formation processes of block stream in Mt. Maneo, South Korea

SETO, Masayuki^{1*} ; KIM, Song-hyun² ; TANAKA, Yukiya²

¹Fukushima University, ²Kyung Hee University

This study revealed that formation processes of slope deposits include block stream near Mt. Maneo, South Korea. Using a satellite image reading from Naver site (<http://www.naver.com/>) and a field survey, we studied the positional relationship between the Mt. Maneo block stream and its surrounding terrain, as well as the general shape of the block stream. The satellite image scale was about 1:5000, which had a resolution sufficient to identify the block stream. Next, we superimposed the interpreted satellite image on a 1:25000 topographic map, and read the contour lines over the location of the block stream. The plan view of the block stream on Mt. Maneo has a belt-like shape. The top end of the slope is the steepest, having an incline of around 20 degrees. On examining the contour lines crossing the block stream, the contour lines in the top section are found to be more or less straight and represent an even slope with no obvious ridges or valleys. In the central part of the block stream, the contour lines are convex in the upslope direction, indicating a wide valley. In the lower section of the block stream, the contour lines are convex in the downslope direction, indicating the presence of a ridge.

A cross-section of the block stream is visible in the central part of the out crop and can be split into two parts: a matrix of fine-grained materials on the northwestern side, and a matrix-free deposit on the other side. For the purpose of this study with respect to sedimentary facies, we counted the sections having matrix as part of the block stream. In the matrix-free deposit section, blocks with a larger diameter tend to be concentrated in the lower portion. The overall cross section has an upward convex shape.

We observed ground water flow and soil saturation by five tensiometers. All observation points were located at the top of block stream. Depth of the tensiometers were about 30cm. Tensiometers were inserted fine slope deposits at the upper part of the block stream. Observation period was Jul. 9, 2014 to Jul.14, 2014. We observed that slope deposits were rapidly saturated associating with rainfall event. Rain fall event was occurred in Jul. 13, 2014. Rainfall amount was 30mm/day. All tensiometers responded this rain fall event. Suction was decreased very rapidly at this rainfall event. This means that saturation of soil layer occurred at the head of block stream associating with rainfall event. Water was concentrated in the valley created by this landslide. We can recognize from observation of suction that the unconsolidated weathered fine-grained material forming the landslide block was washed out by this water flow, leaving only the core stones behind.

We believe that the area of the Mt. Maneo block stream is an old landslide site. This could have been a deep seated landslide that reached the deep weathering layer of the upper section of Mt. Maneo, and it is thought that a large section of the landslide block consisted of core stones and weathered fine-grained material.

Keywords: Block stream, Form processes, Landslide, Hydrological survey, South Korea, Mt. Maneo

Roles of alluvial cones in sediment budget in the wide valley floor of the Kamikochi valley, central Japan

SHIMAZU, Hiroshi^{1*}

¹Rissho University

The upper reaches of the River Azusa, flowing down in the Kamikochi valley in the Northern Japan Alps, central Japan, is surrounded by very steep mountain slopes and high mountains which elevation is higher than 2500m. There are many landslides on the steep mountain slopes, from which debris is supplied to the valleys of the tributaries of the upper River Azusa.

Alluvial cones are the most important features on the valley floor of the upper River Azusa. These are formed at each outlet of the tributaries. To clarify the roles of the alluvial cones in the sediment budgets of the upper Azusa basin, landforms of the alluvial cones were investigated and the sediment linkages between the tributaries and the main river were discussed.

Many debris flow lobes are distributed on the surfaces of the alluvial cones. This shows that the alluvial cones are formed by debris flow accumulation. Most of the alluvial cones have several levels of terraced surfaces. The cone of a tributary, Furuikezawa, has four levels of surfaces. Each surface is bordered by terrace cliffs of several meters high. While the most part of the lowest surface is covered with newly deposited gravels with pioneer trees younger than 70 years, the other surfaces are covered with mature forest, the age of some trees are hundreds of years, and dense forest floor vegetation. The channel of Furuikezawa directly connects with the lowest surface and the surface borders on the main river floodplain with dense riparian forest. The surface is not contact with the channel of the main river. The lower borders of the terraced surfaces are margined by terrace cliffs which stretch parallel with the direction of the valley of the River Azusa. Other alluvial cones in the Kamikochi Valley have such similar geomorphological characteristics.

These characteristics of the alluvial cone show the alternation of accumulation of debris flows on the cone surface and lateral erosion of the toe of the cones by the channel shift of the main river. The debris supplied from a tributary basin is stored as its alluvial cone deposits. When the channel of the River Azusa will be shifted to the alluvial cone, lateral erosion will occur at the lower end of it. As lowering of the base level the channel of the tributary begin downcutting and the alluvial cone surface becomes a terrace. Debris produced by the lateral erosion is transported downstream of the main stream.

During the time lag between debris supply to the cone and eroded away from the cone and transport downstream debris became easily breakable into fine materials.

Alluvial cones on a wide floodplain play important role on sediment transport link between mountain slope and valley floor. Produced debris from the mountain slopes is not transported directly downstream by the main river. That is an important factor in basin sediment budgets.

Keywords: debris transport process, alluvial cone, wide floodplain, sediment budget, Kamikochi, central Japan

Geomorphological evolution of Hashirikotan barrier spits resulting from seismotectonics along the southern Kuril Trench

NANAYAMA, Futoshi^{1*} ; SHIGENO, Kiyoyuki² ; WATANABE, Kazuaki¹ ; YOSHIKAWA, Hideki¹ ; HASEGAWA, Takeshi³ ; IKEDA, Yasuo⁴ ; ISHIWATA, Kazuto⁵ ; UCHIDA, Yasuhito⁶

¹Geological Survey of Japan, AIST, ²Meiji Consultant Co. Ltd., ³Ibaraki University, ⁴Hokkaido University of Education, ⁵Betsukai Museum, ⁶Geological Survey of Hokkaido, HRO

An active barrier system is developed in the Nemuro Bay area along the Okhotsk Sea in eastern Hokkaido, Japan. This presently rare feature consists of a lagoon (the Furen-ko lagoon), a flood tidal delta, a barrier, and a tidal inlet that opens into the outer sea of Nemuro Bay and the Sea of Okhotsk. The Hashirikotan barrier spits are active in the northeastern part of the Furen-ko lagoon, and five spit branches (BS1~BS5) can be observed clearly. Using geomorphological, sedimentological, and ground-penetrating radar methods, we analyzed Holocene sediments near the Furen-ko lowland. We dated them using radiocarbon and tephrochronological methods. The Furen-ko barrier system has been established since 5.5 ka. BS1, the youngest spit was formed after the 17th century, and BS2 was caused by the last seismic uplift in the 17th century. BS3 was uplifted in the 12~13th century, and BS4 was caused by seismic uplift in the 9th century. These great earthquakes (Mw8.5~9.1) have occurred at an approximate 500-year interval along the southern Kuril subduction zone. Coastal areas were raised by 1~2 m during or just after the earthquakes due to postseismic displacement. Conversely, land subsidence has been ongoing at a rate of about 1.0 mm/year since the 17th century. We conclude that the geomorphological evolution of the Furen-ko barrier system has been controlled by the seismotectonics along the Kuril subduction zone.

Keywords: geomorphological evolution, Hashirikotan barrier spit, seismotectonics, southern Kuril trench, eastern Hokkaido, northern Japan

Measurement of changes in wall surface morphology in Yoshimi-Hyakuana cave by terrestrial laser scanning

HAYAKAWA, Yuichi S.^{1*} ; OGUCHI, Chiaki T.² ; ARIGA, Natsuki³ ; AOKI, Hisashi³

¹Univ. Tokyo, ²Saitama Univ., ³Tokyo Gakugei Univ.

Detection and quantitative evaluation of changes in surface morphology of rocks are crucial issue for the understanding of processes of weathering. Using terrestrial laser scanning (TLS) approach, detailed topographic measurements of wall surface morphology were performed repeatedly at a test site of Yoshimi-Hyakuana cave in Saitama Prefecture, central Japan. Time series of point clouds and digital elevation models (DEMs) were compared to each other, revealing the locations of centimeter-scale changes in the wall surface, likely induced by salt weathering. The spatial distribution of such surficial changes will be further assessed by continuous measurements, with appropriate accuracy assessments.

Keywords: TLS, weathering, point cloud, digital elevation model

Arsenic contained in the pore water of the natural sediments in the northern part of the Nakagawa Lowland, Japan

HACHINOHE, Shoichi^{1*} ; HOSSAIN, Sushmita² ; ISHIYAMA, Takashi¹ ; HAMAMOTO, Hideki¹ ;
OGUCHI, Chiaki T.³

¹Center for Environmental Science in Saitama, ²Bangladesh Atomic Energy Commission, ³Graduate School of Science and Engineering, Saitama University

The Kanto Plain is the largest lowland in Japan. Marine sediments are found over a wide area here, even more than 50 km inland from the present shoreline, because of the global cyclic changes in sea levels. The dependence on groundwater to meet the water needs in this area is relatively high. In particular, groundwater is the source of approximately 40 % of the municipal water supplies. Arsenic levels, greater than those permitted by the environmental standards of Japan, have been detected in the groundwater of this area. Therefore, measurements were conducted to evaluate the occurrence of arsenic and other related elements in the pore water contained in the natural sediment layers. We measured the levels of various inorganic chemical substances, such as arsenic (As), iron (Fe), and sulfur (S), and major dissolved ions, such as sulfate (SO_4^{2-}), calcium (Ca^{2+}), and sodium (Na^+). The pore water was collected from sediment samples, obtained by drilling from the river bottom down to a depth of 44 m. The pore water samples were obtained immediately after the extraction of the sediments. The sedimentary facies shown in the vertical profile are continental, transitional, and marine, including two aquifers. The upper aquifer (15~20 m) contains fine to coarse sand, whereas the lower aquifer (37~44 m) contains fine to coarse sand and gravel. The concentration of arsenic and other inorganic elements was measured by an inductively coupled plasma mass spectrometer (ICP/MS) and an inductively coupled plasma atomic emission spectrometer (ICP/AES). The concentration of major dissolved ions was measured by an ion chromatograph analyzer. The total chemical element content was measured by X-ray fluorescence analysis, using solid sediment samples. We obtained the following results. The arsenic concentrations in the pore water of the marine silt and clay sediments (approximately 40 mg/L) were about five times higher than those in the continental sediments (approximately 8 mg/L). The highest concentration of arsenic (74 mg/L) was detected at a depth of 13 m, which is immediately above the upper aquifer. Visual observations confirmed oxidizing conditions for this level. Therefore, it points to arsenic being adsorbed to iron hydroxide in the sediments. In contrast, in the top part of the section, from the river bottom to a depth of approximately 3 m, the arsenic concentrations in the pore water were clearly high, and decreased gradually and continuously with depth. This is ascribed to the anthropogenic impact on the river.

Keywords: Heavy metal, Arsenic, Water-rock interaction, Pore water, Leaching, Pollution

A recursion model for calculating the original widths of narrow terraces and their lateral erosion rates on rock coasts.

UESAWA, Shimpei^{1*}

¹Shimpei Uesawa, ²Ayumu Miyakawa

This presentation presents a new and simple recursion model for calculating the erosion rates of flights of narrow terraces under conditions of regular uplift. The general equations developed are: $\Delta x_n = \Delta x'_n + \Delta x_{n-1} - \Delta z_{n-1}/\tan\theta$, and $\varepsilon_n = \Delta x_n/t_n - t_{n+1}$, where n is the number of narrow terraces, Δx_n is the original width of narrow terrace n , $\Delta x'_n$ is the observed width of narrow terrace n , Δx_{n-1} is the original width of narrow terrace $n-1$ (one step below terrace n), Δz is the height of the narrow terrace, θ is the gradient of the slope, ε is the lateral erosion rate, and t is the time uplifted. The model can be used to calculate the lateral erosion rate if the widths of the present shore platform and of the emerged narrow terraces can be obtained, and where chronological control is available. Lateral erosion rates on the Ashizuri, Boso, and Kii peninsulas in Japan, as well as the Huon Peninsula in Papua New Guinea, were calculated using the model to be approximately 0.001, 0.2-1.0, 0.009, and 0.002-0.014 m/yr, respectively. These calculated values are in agreement with the rates of lateral erosion determined in previous studies.

Keywords: rock coast, recursion model, lateral erosion rate

Adjustment processes of river longitudinal profile: laboratory experiment

GENNO, Reiko^{1*} ; ENDO, Noritaka¹

¹Department of Natural Science and Technology, Kanazawa University

It is generally recognized that longitudinal profiles of graded rivers take exponential curve shapes. Even in an uplift area, a river attains a stable state, i.e., dynamic equilibrium between uplift and fluvial erosion. The change or adjustment of a river profile, however, is not still understood well, especially for a bedrock river. We have conducted physical model experiments in which an initial slope of the mixture of sand and silt was set up and rivers developed by incision of the slope. A weir with a slit at the center was placed at the downstream end to prevent the base-level change due to uncontrolled sedimentation inside of the observed area. Constant rainfall was realized by very fine mist supplied from ten nozzles installed above the flume. The rate of tilting, the axis of which was sited at the shoreline (landward uplift), can be controlled. The parameters of the present study are the gradient of an initial flat slope and the uplift rate. Two types of experiment were conducted, Ex. (i): experiments to test the dependence on initial slope gradient with no uplift; Ex. (ii) to examine the effect of tilting uplift. Results are as follows: Ex. (i) showed that the trunk stream eroded the river bed through two stages. The first stage ended when the valley head erosion ceased. The second deepening started because of the development of tributaries and resultant increase of stream discharge. At the same time, knickpoints generated, which were caused by strong erosion near a junction owing to the difference of bed gradients between a trunk stream and its tributary. Ex. (ii) showed that rivers were more influenced by tilting than erosion at first, but erosion gradually increased to balance with uplift (dynamic equilibrium). The experiment in which the tilting rate was changed during the run also showed dynamic equilibrium topographies for each tilting rate, but a profile with a part of convex shape occurred during the transition. The present study suggests that knickpoints occurs during the process to toward a graded state, equilibrium state for both static and dynamic equilibrium states.

Keywords: river longitudinal profile, laboratory experiment, tilting uplift, graded river

Magnitude-frequency distribution of hummocks and its geomorphological significance

YOSHIDA, Hidetsugu^{1*}

¹Meiji Univ.

Hummocks are conically-shaped mounds formed on debris avalanche deposits after catastrophic sector collapse of mountain (often volcanic) body. The present study investigates the cumulative frequency distribution of hummocks, and discusses its geomorphological significance. Total of 17 debris avalanches are examined in this study. And the result shows a clear relationship between magnitude and cumulative frequency distribution given by (Yoshida, 2015),

$$\log_{10}N(x)=a-bx \quad (1)$$

where $N(x)$ is cumulative number of hummocks larger than and equal to x , x is the magnitude expressed by $\log_{10}A$, A is the area of a hummock, and a and b are constants. The constant b is peculiar to each avalanche, with a range of 1-2. When a volcanic mass collapses, it breaks up into numerous rock blocks during movement as a debris avalanche. Hummocks are basically composed from such rock masses, and generally become smaller with distance from the source. Previous studies have proposed simple models involving such progressive breaking up of hummocks (volcanic masses or debris avalanche blocks) due to avalanche spreading. From the above, therefore, the constant b becomes a significant value geomorphologically, reflecting the debris avalanche processes directly, because the values of b imply the rate of increases in frequency of hummocks (or debris avalanche blocks as core(s) of hummocks) with the decrease of magnitude, due to the succession of debris avalanche processes. The difference in the value of b may be controlled by the mobility of the debris avalanches. This is because when the debris avalanche is more mobile, the collapsed/sliding masses and the debris avalanches are more shattered and broken up during movement till emplacement, resulting in more frequent fragments of debris avalanche blocks (i.e. hummocks). A strong correlation between values of H/L (equivalent coefficient of friction as a representative of mobility of debris avalanches) and b supports the above speculation, which the higher H/L (less mobile) of avalanches yields the lower b value.

(References) Yoshida, H. (2015) AJG Meeting; Yoshida et al. (2012) *Geomorphology*, 136, 76-87.