

根尾谷断層水鳥断層崖における UAV を用いた DSM の RTK-GPS 測量による精度評価

Accuracy evaluation of UAV-measured DSM by RTK-GPS on Midori fault scarp of Neodani active fault, Gifu Prefecture, Japan

佐藤 浩^{1*}; 内山庄一郎²
SATO, Hiroshi, P.^{1*}; UCHIYAMA, Shoichiro²

¹ 日本大学文理学部, ² 防災科学技術研究所

¹College of Humanities and Sciences, Nihon Univ., ²National Research Institute for Earth Science and Disaster Prevention

樽見鉄道水鳥駅周辺の根尾谷断層による水鳥断層崖を対象に、リアルタイムキネマティック GPS によって平面位置が悪く見積もって 8 mm の精度をもつ基準点を 6 点設置し、その標高値を正解として、UAV の撮像画像から生成した DSM の標高の計測精度を評価した。その結果、崖上の 3 点でそれぞれ 3 cm, -8~-9 cm, -5~-7 cm の較差となった。また、崖下の 3 点でそれぞれ 40 cm 前後, -3~-4 cm, -0.6~-2 cm となった。崖下の 1 点を除けば、DSM は概ね 10 cm 未満の精度のあることが分かった。

謝辞

仮想基準点方式による RTK-GPS の測量結果は玉野総合コンサルタントから提供いただいた。

参考文献

内山ほか, 2014, 小型 UAV と SfM ソフトウェアを用いた断層変位地形把握の試みー根尾谷断層水鳥断層崖を例にー, 活断層研究, 40, 35-41.

キーワード: 断層, UAV, GPS, リアルタイムキネマティック, DSM, 仮想基準点

Keywords: fault, UAV, GPS, RTK, DSM, VRC

Structure from Motion および様々なカメラを用いた精度比較 Comparison of accuracy using various cameras and Structure from Motion

小林 勇介^{1*}; 石川 正樹²; 渡辺 悌二³

KOBAYASHI, Yuusuke^{1*}; ISHIKAWA, Masaki²; WATANABE, Teiji³

¹ 北海道大学環境科学院環境起学専攻, ² 北海道大学環境科学院環境起学専攻, ³ 北海道大学

¹Graduate School of Environment Hokkaido Univ., ²Graduate School of Environment Hokkaido Univ., ³Hokkaido University

Recently, the significance of Unmanned Aerial Vehicle (UAV) and Structure from Motion (SfM) has been increasing in geoscience field to understand geomorphological phenomena. These two new technologies can be used inexpensively, easily, rapidly and automatically in comparison to a traditional photogrammetry method, so that geomorphological changes that are caused by various agencies can be estimated at close interval. For these reasons, geomorphological information (e.g. DEM and Orthophotograph) can be made flexibly to suit researcher preferences. Most mountain national parks in Japan have been suffered from serious trail erosion for long time. Especially, some mountain trails in Daisetsuzan National Park in Hokkaido, northern Japan, have been eroded in a few meters in depth. This serious soil erosion bothers national park managers, mountain hikers and also alpine vegetation. It is important for park managers to accurately and easily understand that eroded soil volume and geomorphological changes. For the purpose of the management, this study demonstrated two new technologies and evaluated quality of DEMs and orthophotographs. This study aims: (1) to demonstrate two new technologies under various conditions, and (2) to understand differences of accuracy in some cameras and some software to make three-dimensional data.

This study used two methods to take photographs: (1) UAV (DJI Phantom2 +Vision) at 5 m, 10 m and 20 m flying height; and (2) a monopod at distance of 1.5 m and 3 m from the ground surface at 24 viewpoints. In order to compare difference of accuracy of cameras, Ricoh GR, Ricoh CapiroR7 and DJI camera were used with UAV; and Ricoh GR, Canon power shot SX150IS, NikonD90, Panasonic LUMIX DMC TZ-60, Ricoh CapiroR7, SONY Cyber-shot DSC-TX5, Ricoh GR, and Panasonic LUMIX DMC-GX1 camera were used with monopod. Sixty pictures were taken by the cameras on UAV, and 24 pictures were taken by the cameras on the monopod. Moreover the following software was used for making DEMs and orthophotographs: Visual SfM (free), Photo Scan Pro (commercial) and 123Dcatch (free). In place of the actual micro-topography, artificial sheet and blocks were placed on a flat ground for targets when taking photographs to evaluate absolute positional accuracy.

The analysis of the photographs taken with UAV by Photo Scan Pro shows that the average absolute positional error score was almost the same in Ricoh GR (0.001 cm) and Ricoh CapiroR7 (0.042 cm) at the 5-m flying height. But, at the 10-m flying height the average absolute positional error score was as large as 1.371 cm in Ricoh CapiroR7. On the other hand, the score for Ricoh GR was 0.039 cm. At the 20-m flying height, the score for Ricoh GR was 0.066 cm. In this flying height, Ricoh CapiroR7 was not suitable due to bad resolution. DJI camera was not suitable in all cases. When using a monopod, the average absolute positional error score was less than 1 mm in all cameras from distance of 1.5 m (Ricoh GR: 0.89 mm, Canon Power Shot SX150IS: 0.71 mm, Nikon D90: 0.68 mm, Panasonic LUMIX DMC TZ-60: 0.68 mm, SONY Cyber-Shot DSC-TX5: 0.65 mm, Ricoh CapiroR7: Not suitable). The results show that UAV-SfM is a useful method for national park managers and even mountain hikers to obtain high-resolution models by using inexpensive cameras to record trail conditions.

Keywords: Structure from Motion, UAV

**Tsunami-induced bedrock erosion and sediment deposition on uplifted coastal bench:
Cape Todogasaki, eastern Japan**
**Tsunami-induced bedrock erosion and sediment deposition on uplifted coastal bench:
Cape Todogasaki, eastern Japan**

早川 裕式^{1*}; 小花和 宏之²; Wassmer Patrick³; 齋藤 仁⁴; 小口 高¹
HAYAKAWA, Yuichi S.^{1*}; OBANAWA, Hiroyuki²; WASSMER, Patrick³; SAITO, Hitoshi⁴; OGUCHI, Takashi¹

¹Univ. Tokyo, ²Chiba Univ., ³Univ. Strasbourg, ⁴Kanto Gakuin Univ.

¹Univ. Tokyo, ²Chiba Univ., ³Univ. Strasbourg, ⁴Kanto Gakuin Univ.

An uplifted coastal bench at an elevation of ca. 20 m a.s.l. is located around Cape Todogasaki of the ria-type rocky coast in Sanriku, northeastern Japan. Tsunami waves induced by the 2011 Tohoku Earthquake were high enough to spread over the 20-m high terrace. To clarify the effects of tsunamis on the terrace surface micromorphology, we performed field measurements of structure-from-motion multi-view stereo (SfM-MVS) photogrammetry using an unmanned aerial system (UAS), composed of a digital camera mounted on a small unmanned aerial vehicle (sUAV), and terrestrial laser scanning (TLS). Global navigation satellite system (GNSS) rover was used to obtain geographical coordinates (centimeter accuracies) of ground control points for the georeferencing of the UAS and TLS data. Using digital elevation models (DEMs) with a 20-cm resolution generated from the point clouds of UAS and TLS, micromorphology of the terrace surface was analyzed. Despite limited basin area draining into the terrace, erosional features in the bedrock were identified. These features appear to be formed by the tsunami flow. Furthermore, sedimentological characteristics of small thin clasts and large (>2 m) boulders located on the terrace were examined in the field, revealing that the sediments are likely dislocated from in-situ bedrock at the terrace edge. Evidences of landward flow were also found from the sediment structure. We conclude that the uplifted terrace surface underwent erosion by not only the 2011 tsunami but also repeated significant tsunamis in the past, some of which could have been much larger than that in 2011.

キーワード: tsunami, UAS, TLS, erosion, sediments

Keywords: tsunami, UAS, TLS, erosion, sediments

沿岸海底地形学および関係諸科学のための高解像度マルチビーム測深調査 High-resolution multibeam bathymetric survey for coastal seafloor geomorphology and related sciences

菅浩伸^{1*}; 長尾正之²; 渡久地健³; 堀信行⁴; 浦田健作⁵; 藤田和彦³; 横山祐典⁶; 中島洋典⁷; 長谷川均⁸; 中井達郎⁸; 後藤和久⁹; 片桐千亜紀¹⁰; 小野林太郎¹¹; Sinniger Frederic¹²; Prasetia Rian³; 波利井佐紀³; 井口亮¹³; 鈴木淳²
KAN, Hironobu^{1*}; NAGAO, Masayuki²; TOGUCHI, Ken³; HORI, Nobuyuki⁴; URATA, Kensaku⁵; FUJITA, Kazuhiko³; YOKOYAMA, Yusuke⁶; NAKASHIMA, Yosuke⁷; HASEGAWA, Hitoshi⁸; NAKAI, Tatsuro⁸; GOTO, Kazuhisa⁹; KATAGIRI, Chiaki¹⁰; ONO, Rintaro¹¹; SINNIGER, Frederic¹²; PRASETIA, Rian³; HARI, Saki³; IGUCHI, Akira¹³; SUZUKI, Atsushi²

¹九州大学地球社会統合科学府, ²産総研地質情報, ³琉球大学, ⁴奈良大学, ⁵大阪経済法科大学, ⁶東京大学大気海洋研究所, ⁷有明高専, ⁸国土館大学, ⁹東北大学災害科学国際研究所, ¹⁰沖縄県立博物館美術館, ¹¹東海大学, ¹²海洋研究開発機構, ¹³沖縄高専

¹Graduate School of Integrated Sciences for Global Society, Kyushu University, ²Institute of Geology and Geoinformation, AIST, ³University of the Ryukyus, ⁴Nara University, ⁵Osaka University of Economics and Law, ⁶AORI, University of Tokyo, ⁷Ariake National College of Technology, ⁸Kokushikan University, ⁹IRIDeS, Tohoku University, ¹⁰Okinawa Prefectural Museum and Art Museum, ¹¹Tokai University, ¹²JAMSTEC, ¹³Okinawa National College of Technology

The geomorphology of shallow coastal regions has been modulated by repeated subaerial and submarine processes during glacio-eustatic sea-level change. However, in contrast to the vast knowledge that has been accumulated regarding terrestrial landforms, few previous studies have dealt with shallow seafloor landforms, which represent former terrestrial landscapes modified by present marine processes, from a geomorphological perspective.

A broadband multibeam echosounder (Sonic 2022, R2 Sonic, LLC) and its accessory system were introduced to H. Kan's laboratory in 2010 using JSPS Grant-in-Aid for Scientific Research A. We have carried out our bathymetric survey in Kume, Ishigaki, Kikai Islands and the southeastern and northwestern coasts of Okinawa Island in the Ryukyus, southwestern Japan since 2010.

The Sonic 2022 has a variable ultrasonic frequency of 200 to 400 kHz, 256 ultrasonic beams and selectable swath coverage of 10 to 160 degrees. The typical ultrasonic beam widths parallel and orthogonal to the direction of travel are within one degree of each other when an ultrasonic frequency of 400 kHz is selected. We used a VS111 GPS compass system with A20 and A30 antennas (Hemisphere Inc.) combined with a dynamic motion sensor (DMS-10, Teledyne TSS Ltd.), a sea surface sound velocity sensor (miniSVS, Valeport Ltd.), a sound velocity profiler (MicroSVP, AML Oceanographic Ltd.). Overlap of at least ~20% (typically ~50%) was implemented throughout the bathymetric survey to ensure 100% coverage of the surveyed area. The minimum and maximum depth was 1m and 400m, respectively. The HYPACK2010 software was used for both hydrographic survey and data processing. IVS3D Fledermaus was used for three-dimensional visualization.

We conducted geomorphological studies of the coastal seafloor in the coral reef areas of the Ryukyu Islands based on our high-resolution bathymetric map with a grid size of 1 m combined with SCUBA diving observations. For example, the submerged tropical karst features were discovered in Nagura Bay, Ishigaki Island (Kan *et al.* 2015). This is the first description of submerged humid tropical karst using multibeam bathymetry. Along with the geomorphological studies, we have also started biological and archeological studies in our bathymetric areas to promote interdisciplinary researches which link natural and human sciences.

Keywords: multibeam ecosounder, coastal seafloor geomorphology, biology, archaeology, coral reefs, Ryukyu Islands