

## CO<sub>2</sub> 地中貯留におけるジオメカニクモデリング：ナチュラルアナログ研究例 Geomechanical modelling for CO<sub>2</sub> geological storage: insights from natural analogue re- search

雷 興林<sup>1\*</sup>; 船津 貴弘<sup>1</sup>; 奥山 康子<sup>1</sup>; 中尾 信典<sup>1</sup>  
LEI, Xinglin<sup>1\*</sup>; FUNATSU, Takahiro<sup>1</sup>; OKUYAMA, Yasuko<sup>1</sup>; NAKAO, Shinsuke<sup>1</sup>

<sup>1</sup> 産業技術総合研究所

<sup>1</sup> National Institute of Advanced Industrial Science and Technology(AIST)

When CO<sub>2</sub> gas is pressure-injected into an underground reservoir for geological storage, the pore pressure underground increases, and the stress distribution underground may change. Stress redistribution within and surrounding the reservoir and caprock system may lead to geophysical changes, microseismicity, fault reactivation, and may even trigger large earthquakes. For example, at a gas field in In Salah, Algeria, where CO<sub>2</sub> is pressure-injected to enhance natural gas production, synthetic-aperture radar observations from a satellite have indicated a ground uplift rate of about 1 cm/year around the CO<sub>2</sub> pressure injection wells, along with a similar amount of subsidence around the gas production wells. In some gas fields in the Sichuan Basin, China, following injection of unwanted water into depleted gas reservoirs, a number of seismic sequences have been observed with sizable earthquakes ranging up to M5.

Indeed, geophysical changes and microseismicity are useful in the monitoring and management required during and after a large-scale injection project. However, the risks related to fluid leakage and earthquakes that can be felt may give rise to strong social impacts. The issue of noticeable or damage-causing earthquakes induced by artificial operations is controversial, and has been the cause of delays and threatened cancellation of some projects such as the EGS (Enhance Geothermal System) project at Basel. To carry out geological CO<sub>2</sub> storage safely and for this technology to be accepted not only by the inhabitants around the storage sites, but also by the society as a whole, technological developments that address such public concerns is essential. In addition, there is a strong desire to be able to control or predict the occurrence of damaging earthquakes. In these regards, geophysical/geomechanical modelling is key in site selection, injection operation, and post injection management.

In geological CO<sub>2</sub> storage, it is important to clarify the mechanisms and geomechanical conditions of worst-case events, such as damaging earthquakes and reservoir leakage, so that they can either be avoided or mitigated. It is most desirable to use an actual CO<sub>2</sub> geological storage site in which such events have actually occurred and have been well monitored. However, many pilot projects are sited in places with good conditions for safely pressing CO<sub>2</sub> into the reservoir. Thus it is valuable to carry out "natural analogue research", analysing similar phenomena caused by the activity of a natural CO<sub>2</sub>-quality fluid to examining the modelling technology. In the Matsushiro area, a series of more than 700,000 earthquakes occurred over a 2-year period (1965-1967). This swarm, termed the Matsushiro swarm, resulted in ground surface deformations (uplifts as large as 75 cm), cracking of the topsoil, enhanced spring outflows with changes in chemical compositions, and CO<sub>2</sub> degassing. Ten million tons of CO<sub>2</sub>-rich saltwater seeped was estimated to have seeped out from underground along the cracks. Thus the Matsushiro swarm is believed to have been triggered and driven by high pressure CO<sub>2</sub>-rich fluid from deep sources. Data observed during the Matsushiro swarm can therefore be used as a natural analogue for examining the geomechanical modelling technology based numerical simulation using the coupled THM (heat transferring, fluid flow, rock mechanics) analysis. Here, we make a brief review of studies on the Matsushiro fluid-driven earthquake swarm based on TOUGH-FLAC approach.

【謝辞】本研究は、経済産業省からの委託研究「二酸化炭素回収・貯蔵安全性評価技術開発事業（弾性波探査を補完するCO<sub>2</sub>挙動評価技術の開発）」の一部として実施した。

キーワード: CCS, ジョメカニクモデリング, 断層, 松代群発地震, 深部流体

Keywords: CCS, Geomechanical modelling, Fault, Matsushiro seismic swarm, Deep fluid