

Medium effect on the characteristics of electromagnetic signals accompanying with seismic waves
Medium effect on the characteristics of electromagnetic signals accompanying with seismic waves

HUANG, Qinghua^{1*} ; REN, Hengxin²
HUANG, Qinghua^{1*} ; REN, Hengxin²

¹Peking University, ²Univ Sci Tech China

¹Peking University, ²Univ Sci Tech China

Recently developed numerical simulation technique can simulate the coupled seismic and electromagnetic signals for a double couple point source or a finite fault planar source. Besides the source effect, the simulation results showed that both medium structure and medium property could affect the coupled seismic and electromagnetic signals. The waveform of coupled signals for a layered structure is more complicated than that for a simple uniform structure. Different from the seismic signals, the electromagnetic signals are sensitive to the medium properties such as fluid salinity and fluid viscosity. The results may provide some insights of understanding the difference in the detectability of co-seismic electromagnetic signals in different geological regions.

This study is supported partially by the National Natural Science Foundation of China (41025014) and the National Basic Research Program of China (2014CB845903).

キーワード: Electrokinetic effect, co-seismic electromagnetic signals, medium effect, a double couple point model, a finite fault planar model

Keywords: Electrokinetic effect, co-seismic electromagnetic signals, medium effect, a double couple point model, a finite fault planar model