

Strategy for carbon dioxide emissions reduction and CCS policy in Japan

*Sadayuki Kamada¹, Takeshi Nagasawa²

1.Tomakomai City, 2.Ministry of Economy, Trade and Industry(METI)

Widespread adoption of CCS technology could be key to limiting global average temperature increase. Supporters of carbon capture and storage technology say CCS needs to be brought to scale to limit global warming. This presentation covers an introduction on current status of research and development on CCS technology and CCS policy in Japan. Main topics are listed below.

- 1) overview of the Tomakomai large scale demonstration project
- 2) potential storage site survey
- 3) R&D of CO₂ capture and storage technology
- 4) international collaborations
- 5) Japanese government's policy on CCS

Keywords: CCS, policy, CO₂

Incentives for operational CCS projects in the World

*Ryozo Tanaka¹

1. Research Institute of Innovative Technology for the Earth

CCS is recognized as a promising technology to fulfill an ambitious target of CO₂ emission reductions. But the advancement of its deployment has been very slow than expected and acute growth in deployment cannot be anticipated at least for a short term. One of the reasons behind is the lack of economic incentives to compensate costs of CCS deployment. Then what are driving forces for existing large-scale CCS projects? There are currently 15 operational and 7 under-construction large-scale CCS projects in the world. The half of these projects have inherent CO₂ separation in the production process and sell the captured CO₂ to enhanced oil recovery (EOR) operation. This combination generally requires no additional investment for the installation of CO₂ separation and can generate revenue by selling CO₂. The remaining half has an additional CO₂ capture facility and/or use a saline formation as a CO₂ reservoir. To fill a financial gap, these projects receive public funding and/or enjoy other forms of financial incentives such as carbon credit, tax credit and avoidance of carbon tax. This presentation analyses factors making existing projects financially feasible and financial incentives implemented for future projects in major countries.

Development of geological model using core-well-seismic integration technique at the Nagaoka CO₂ storage site, Japan

*Takuma Ito¹, Takahiro Nakajima¹, Ziqiu Xue¹

1. Research Institute of Innovative Technology for the Earth

When utilizing saline aquifers as a geological storage site, available dataset is limited due to their sparse geological information. Under such conditions, however, development of geological model is essential for site characterization. To overcome this condition, applying core-well-seismic integration technique appears to be one of the feasible solutions in addition to use of existing available dataset. Here we propose a geological modeling procedure using saline aquifer for geological storage of CO₂. The proposes are (1) to identify the depositional environments and the sequence boundaries used as a stratigraphic framework of a geological model, (2) to make the voxel model using the sequence boundaries, and (3) to show the spatial gamma-ray, porosity and permeability distributions using core-log-seismic integration technique as a case study of the Nagaoka site.

In the Nagaoka project, total of about 10,000 tons of CO₂ was injected into the saline aquifer, which situates about 1,000m depth below the Niigata Plain. The target saline aquifer is correlated to the early Pleistocene Haizume formation. During the project, one injection well (IW-1) and three observation wells (OB-2, -3 and -4) were drilled. Sediment core of the target reservoir rock was taken from the IW-1, and well log data was obtained from all of the wells. During CO₂ injection to date, detailed monitoring has been made by well logs to monitor CO₂ behavior in the underground. Firstly, we carried out facies analysis and grain size measurements using the sediment core materials to identify depositional environment of the reservoir rock. Detailed sedimentological features indicate that the reservoir rock has fining-upward to coarsening-upward successions that developed on ravinement surface. The reservoir rock is attributed to a part of prodelta and deltafront deposits. Prodelta and deltafront deposits can be divided by mud content of about 40% as a threshold value at the Nagaoka site.

Secondly, we used geophysical logs at each well for stratigraphic correlation of the reservoir rock. Comparison between core and geophysical logs at the IW-1, profile of natural gamma-ray show similar pattern with that of mud content. Thus, prodelta and deltafront deposits can be divided by natural gamma-ray value of about 75 API. This fact indicates that natural gamma-ray value can be used as identification tool for depositional environments at the Nagaoka site. We defined the sequence boundary and correlated it at each wells. Moreover, we confirmed that positive correlation exists between natural gamma-ray intensity, porosity and permeability. The above information is used when constructing geological models.

Lastly, we used 3D seismic data for defining a stratigraphic framework. For making a stratigraphic framework, we defined the two sequence boundaries above and below the reservoir rock. The sequence boundaries were traced spatially by Petrel (Schlumberger software) using multiple 3D seismic slices, and then a grid model of the reservoir rock was developed. Spatial natural gamma-ray and permeability models were constructed using GDI (Geological Driven Integration)-based spatial porosity model as a guide by Sequential Gaussian simulation with collocated cokriging.

A given spatial distribution of natural gamma-ray and permeability shows the eastern part of the reservoir has fine-grained and low permeability. This trend is similar with the paleogeography that the sediments were supplied generally from west to east based on the previous geological survey around the Nagaoka site. Moreover, the result of CO₂ monitoring suggests that the CO₂ migration is not uniform that its breakthrough has not been observed at the OB-3, where is located at the most

east side. This fact is also supported that a given geological model is reasonable.

Keywords: Geological storage of CO₂, Nagaoka site, Sedimentology, Geological modeling, core-log-seismic integration

Construction of an integrated geological model characterized by a seismic survey data and calibrated by log-based monitoring data: A case study at Nagaoka CO₂ injection site

*Takahiro Nakajima¹, Takuma Ito¹, Ziqiu Xue¹, Shun Chiyonobu²

1.Research Institute of Innovative Technology for the Earth, 2.Faculty of International Resource Sciences, Akita University

This paper discusses a methodology for the site characterization of deep saline reservoirs evaluated through dynamic flow simulations. Not only the traditional site characterization techniques, but also the injection and monitoring data can be used for the geological modeling. In this study we carried out flow simulations using a geological model based on a seismic survey data and monitoring data after the CO₂ injection at Nagaoka site.

Nagaoka project was undertaken in order to verify an ability of CO₂ injection into Japanese formation. The target reservoir consists of marine strata at a depth of 1100m. Between 20 and 40 tons of CO₂ were injected and a total of 10.4 k-tons of CO₂ was injected into a thin permeable zone. Bottom-hole pressure measurement, time-lapse well loggings and cross-well seismic tomography were conducted using three observation wells drilled between 40m and 120m from the injection point. For the modeling of the reservoir with heterogeneity, the method presented by Ito et al. (2016) was used; determined the sequence boundaries of the formation from the analysis of depositional environments, constructed a 3D reservoir framework by horizon picking of seismic trace, and developed a 3D distribution of reservoir parameter after the integration of lithologic records, well logging data, and 3D seismic attributes. It is worth to note that the heterogeneous feature from NNE to SSW direction can be seen in the revised interpretation model. For the hydrological properties we referred measured results as reported in Nakajima et al. (2015).

For the simulation of multiphase flow, we used TOUGH2/ECON2 simulator. The model was calibrated through the process of history matching to the bottom-hole pressure and CO₂ saturation. Several absolute permeability models were tested manually and good matches were achieved between monitoring data and simulated CO₂ behaviour. The results of CO₂ distribution were also consistent with the observed velocity anomalies from the cross-well tomography. The numerical results revealed the migration of CO₂ plume to up-dip direction along the most permeable zone during the post-injection period.

Sensitivity studies were conducted to investigate the effect of poorly constrained model parameters. We tested alternative parameters on absolute permeability, ratio of horizontal to vertical permeabilities, and pore compressibilities. We found that the effect of the ratio between horizontal and vertical permeabilities was relatively large, and pore compressibility had effects on pressure response. A small anisotropy in horizontal direction could also explain a better matching. These anisotropies could be created during the depositional process of the reservoir. We will report the long-term fate of CO₂ in the reservoir to evaluate the contribution of the trapping mechanisms.

Keywords: CO₂ geological storage, Nagaoka site, multiphase flow, trapping mechanism

Simulation study on trapping processes of CO₂ at Nagaoka pilot project

*Hajime Yamamoto¹, Takahiro Nakajima², Ziqiu Xue²

1.Technology Center, Taisei Corporation, 2.Research Institute of Innovative Technology for the Earth

Long term stability of CO₂ stored in reservoir is of intrinsic importance for ensuring the viability of geologic sequestration of carbon dioxide. Demonstrating the permanence of storage is an important task of pilot projects. In the Nagaoka project, Japan's first pilot-test of geological CO₂ sequestration that injected about 10,400 tonnes of CO₂ from 2003 to 2005, a stable containment of CO₂ in a reservoir has been successfully demonstrated by kept monitoring the CO₂ behavior even after the end of injection during about 10 years. Systematic and continuous data acquisition of time-lapse well loggings (e.g., resistivity, neutron, and sonic velocity) successfully illustrated the detailed nature of CO₂ migration at intra-reservoir resolution.

In this study, a three-dimensional reservoir model with sub-meter spatial resolution has been developed with comprehensively involving coupled process of two-phase fluid flow and geochemical transport. The model was history-matched against a set of monitoring data acquired during the post-injection period including pressure, well loggings, and fluid samplings. The calibration of a large model is computationally demanding, hence we newly developed a parallel version of coupled fluid flow and geochemistry TOUGHREACT V2.0/ECO2N with MPI parallelism, in-house. The new code also features hysteretic effect in relative permeability and capillarity which was not implemented in the original TOUGHREACT V2.0.

The detailed 3D history matching study reproduced the observed distribution of CO₂ saturation at sub-meter scale over time. From the lessons learnt through the history matching study, the following insights into the trapping processes of CO₂ at the project have been obtained.

- During the injection, free CO₂ migrated preferentially through higher permeable layers. The uneven arrival times of CO₂ to the well-depths are well explained by, and consistent with the non-uniform permeability distribution measured at wells.
- Pressure-driven-flow during the injection squeezed the formation water out of the reservoir, and consequently resulted in hydrodynamic dispersion of dissolved CO₂ into over- and under-lying lower permeable layers. This behavior is highly consistent with the resistivity changes observed by well loggings.
- In the post-injection period, negligible vertical migration of free CO₂ suggests that even a thin, intra-reservoir muddy-layer behaves like an impermeable flow barrier to trap CO₂, by a combined effect of lower vertical permeability and high capillarity to prevent the invasion of CO₂.

Keywords: Reservoir Simulation, CO₂ trapping, Nagaoka, Parallel Computation, TOUGH2

Subsurface monitoring using seismic interferometry for the large-scale CCS Demonstration Project at the Tomakomai Area

*Ryuji Niiro¹, Motonori Higashinaka¹, Susumu Abe¹, Makoto Tsuchiya², Hideo Saito², Ziqiu Xue³, Tetsuma Toshioka³

1.JGI, inc., 2.Japan CCS Co., Ltd., 3.RITE

JCCS, commissioned from METI, deployed the permanent OBC (Ocean Bottom Cable), and seismic signal has been continuously recorded since July, 2014. The cable length of the OBC is 3.6km and the receiver interval is 50m, respectively.

The main purposes of this observation are the earthquake monitoring and the time-lapse seismic survey, what is more, subsurface imaging by seismic interferometry can be implemented by using the continuously observed data in the arbitrary spans of the 6 years monitoring period.

As the baseline survey, 3D seismic survey was already conducted in 2009 and 2D in 2013.

Furthermore, periodic monitoring seismic surveys will be conducted after the start of CO₂ injection. Seismic surveys in which active sources are used provide reliable subsurface images, but those expensive costs make it difficult to conduct monitoring surveys frequently. As an alternative approach, passive seismic survey methods have a potential to delineate the temporal change of CO₂ plume distributions in the reservoir in a shorter period, because the seismic interferometry can be applied to any period of the continuous observation data.

In this study, we applied the seismic interferometry to local earthquake seismograms recorded by the permanent OBC. We begin with synthesizing the pseudo shot gathers by applying seismic interferometry to the P-wave and P-coda of 158 earthquakes which have occurred from January 1, 2015 to November 21, 2015. Note that the selected earthquakes are larger than magnitude of 2.0 and those hypocentral distances are longer than 48 km. Processing the pseudo shot gathers, we obtained the seismic images through the CMP stacking method. As a result, we can clearly image the reflector at the depth of the reservoir.

It is necessary to examine the repeatability, the relation between the number of seismic events and S/N of the passive seismic section to confirm its applicability in CO₂ monitoring.

Keywords: Seismic Interferometry, CO₂, CCS, monitoring

Time-lapse observation and its interpretation in Al Wasse field in Saudi Arabia using ultra-stable seismic source

*Junzo Kasahara^{1,2,4}, Khaled Al Damegh³, Ghunaim Al-Anezi³, Kei Murase⁴, Aya Kamimura⁴, Osamu Fujimoto⁴, Hiroshi Ohnuma⁴, Yoko Hasada⁵

1.University of Shizuoka, Faculty of Earth Sciences, 2.Tokyo University of Marine Science and Technology, 3.KACST, 4.Kawasaki Geological Engineering Co. Ltd., 5.Daiwa Exploration and Consulting Co. Ltd.

1. Introduction

The Carbon Capture and Storage (CCS) is one of ways to reduce the CO₂ radiation to the air. In CCS, CO₂ is injected to the subsurface and is stored in the subsurface. Technologies of monitoring (time-lapse) of CO₂ leakage from the storage zone have been studied in many institutions. We have used the ACROSS seismic source for the time-lapse and have tested the technology in Al Wasee field, Saudi Arabia after the air injection study in Japan (Kasahara *et al.*, 2013). The same technology can be used in EOR (Enhanced Oil Recovery) and PRM (Permanent Reservoir Monitoring) cases.

2. Time-lapse observation in Saudi Arabia and data processing

The test site is a national water pumping field. Water is pumped up from aquifers around 400 m depth. The geology of this area comprises limestone, sandstone and unconsolidated sand. There is no seismic survey in this area before our study.

We used the ACROSS unit as an ultra-stable seismic source and 32 seismographs at 500 m spacing grids with distances between 500 m to 1.76 km. The source transmitted chirp signal from 10 to 40 Hz and the seismic waves were recorded by data-loggers. Because of so frequent power downs during the observation, the obtained data were intermittent. The transfer functions between the source and receivers were obtained by division of observed records by source signatures in spectral domain by the similar way as before (*e.g.*, Kasahara *et al.*, 2013, 2015). By processing, we obtained the transfer functions corresponding to vertical and horizontal forces. As the interpretation of one-day stacked data, we used the refraction survey in 2015 (Kasahara *et al.*, 2016; in this session).

3. Results

We obtained the transfer functions from April to December, 2015 for 30 stations, but the data are not continuous for whole period due to frequent power downs. The first arrivals disappear at the distance further than 1 km and large amplitude phase is dominant at the stations further than 1.5 km. The temporal variation in the arrivals later than 1.0 seconds is extremely large as same as that in April to June, 2015 (Kasahara *et al.*, 2015). The first arrivals closer than 1 km do not give large temporal changes, which is similar to the previous results in April to June 2015

Using the refraction data obtained in 2015 we interpreted the phases. The first arrivals at the distance less than 1 km are refracted wave with 3.5 km/s travelling the upper limestone layer. The phase with large amplitude at the distance further than 1 km is estimated as refracted wave with 4.5 km/s travelling in the basement. This phase shows some temporal variation. The Raleigh wave could have large amplitude and this is dominated after refracted waves. The temporal changes in surface waves do not show coherent characteristics from one to another.

4. Discussion and conclusions

The presence of low velocity zone just below the 3.5 km/s layer makes difficult to interpret the temporal change. The first arrivals quickly decay at the distance further than 1 km by the low-velocity layer. At the distance further than 1 km, large amplitude phase refracted at the layer deeper than 800 m is dominant. The upper limestone layer does not show large temporal changes and

the refracted arrivals show some temporal changes due to the migration of aquifer. The surface waves seem travel in the low velocity layer, and the temporal change of surface wave is so large and shows roughly week period. This may be caused by pumping of water from aquifer.

Acknowledgements

This survey was supported by JCCP (Japan Cooperative Center for Petroleum) in Japan and KACST in Saudi Arabia. We express our great thanks to members of JCCP and KACST for their aggressive support of this project.

Keywords: Time-lapse, ACROSS, shadow zone, refracted wave, low-velocity layer, aquifer

Geomechanical monitoring of caprock and wellbore integrity using fiber optic cable

*Ziqiu Xue¹, Tsutomu Hashimoto¹

1. Research Institute of Innovative Tech for the Earth

We have been developing a new technology to monitor the caprock and wellbore integrity at CO₂ injection sites by utilizing the Distributed Fiber Optic Sensing (DFOS). DFOS has an advantage to measure temperature and strain at any point in an unprocessed optical fiber, contrary to the conventional Fiber Bragg Grating (FBG) sensing which measures temperature and strain at a limited number of discrete points along the processed fiber cable. To put the DFOS technique into the practical use at the CCS sites, we measured the frequency shifts of the Rayleigh and Brillouin scattering in an optical fiber attached to sandstone samples under hydrostatic pressure, and also measured strain of the samples by conventional strain gages simultaneously. Strains measured by optical fiber are estimated based on the frequency shifts and those strains agreed well with the strains by conventional strain gages. The experimental results demonstrated the potential use of DFOS as a promising technology for monitoring the geomechanical deformation of geological formation at the CO₂ injection site.

Keywords: CO₂ geological storage, optic fiber sensing , integrity monitoring

Self-potential Monitoring Study for Geological Storage of CO₂ in AIST

*Yuji Nishi¹, Tsuneo Ishido¹

1.National Institute of Advanced Industrial Science and Technology (AIST), Geological Survey of Japan, Institute for Geo-Resources and Environment

An appropriate monitoring program is important for an CO₂ geological storage project to detecting subsurface changes within the reservoir, to provide for potential risk, and to improve the predictive capability of reservoir simulation. AIST have studied passive geophysical monitoring method to reduce the repetition of the expensive seismic sounding, especially in post-injection period (Nishi et al., 2015).

The self-potential (SP) method is mainly used in volcanic or geothermal field to delineate thermal anomaly from streaming potential generated by subsurface fluid flow. In CO₂ geological storage site, SP changes due to stream-potential might be a promising geophysical tool to monitor pressure changes in shallower levels (Ishido et al., 2009).

SP anomaly just around a well could be another important target for SP monitoring. As subsurface changes in geochemical condition might change the well-casing SP due to geo-battery effect (Ishido et al., 2013), simple surface SP monitoring could be an early warning alarm for CO₂ plume arrival to the well bottom.

In the presentation, some of our recent advances in SP monitoring & modeling will be summarized.

Keywords: monitoring, self-potential, geo-battery

A Study on seismic stability safety evaluation of the cap rock for geological CO₂ storage using non-linear dynamic response analysis

*Shigeo Horikawa¹, Takeshi Sasaki¹, Naohide Takada¹, Tsutomu Hashimoto¹, Takahiro Nakajima², Ziqiu Xue²

1.SuncoH Consultants Co., Ltd., 2.Research Institute of Innovative Technology for the Earth (RITE)

Authors studied non-linear dynamic response analysis at the geological CO₂ storage site, and tried the seismic stability evaluation of the cap rock and the reservoir. The test site is the Nagaoka CCS site. The input earthquake motion used the wave of the 'Mid Niigata Prefecture Earthquake in 2004' recorded by the surface-type seismograph installed in this site. The engineering characteristic values of the foundation used for analysis inputted the numerical value acquired at this site.

In advance of dynamic response analysis, the earthquake motion recorded on the earth surface assumed the horizontally layer model, and set up the input wave from a basement layer (We assumed Shiiya Formation distributed from the depth of 1,370m) by SHAKE (= One-Dimensional Seismic Response Analysis). This wave was inputted into the analysis model and the equation of motion was solved using the direct integral calculus by Newmark Beta Method. In Seismic Response Analysis, authors have used Multiple Yield Model (=MYM, Two-Dimensional Finite-Element Method), which can respond also to complicated geological structure.

The intensity deformation property of the foundation added the offloading characteristic to the composition rule of Duncan-Chang model in consideration of confining stress dependency, and used for and carried out the non-linear repetition model. The deformation characteristic which made it depend on confining stress with the cyclic loadings and un-loadings, and combined Mohr-Coulomb's law as a strength characteristic. Analysis ranges are about 1.2km * 1.4km focusing on an injection well.

The maximum dynamic shearing strain of the cap rock was generated about 1.1E-04 after the end of an earthquake. Although the dynamic safety factor was 1.925 on the beginning, after the end of an earthquake fell 0.05 point. This result is equivalent to having fallen about 2.5% from the beginning, the influence on safety is slight.

As a result of CO₂ migration monitoring by the seismic cross-hole tomography, CO₂ has stopped in the reservoir through two earthquakes till the present after injection, and the leak is not accepted till the present. By the result of non-linear dynamic response analysis, we obtained a result in support of them. That is, it turned out that the stability of the foundation is not spoiled after the earthquake. By carrying out performance simulation using this non-linear dynamic response analysis by MYM, the prediction of the safety assessment in rock masses at the deep depth accompanying the occurrence of a massive earthquake is possible also at geological CO₂ storage site planned from now on.

Acknowledgements : The 5th and 6th authors were funded by the Ministry of Economy, Trade and Industry (METI), Japan under the contract research of "Development of Safety Assessment Technology for Carbon Dioxide Capture and Storage".

Keywords: Carbon Dioxide Capture and Storage, non-linear dynamic response analysis, seismic stability evaluation

Numerical study mitigation of pressure build-up mitigation by production of formation water during CO₂ injection

*CLAUDIA FUJITA¹, Yusuke Hiratsuka¹, Hajime Yamamoto¹, Takahiro Nakajima², Ziqiu Xue²

1.Taisei Corporation , 2.Research Institute of Innovative Technology for the Earth

Due to injection of supercritical CO₂ into the deep underground, the pressure in the geologic formation increases, first locally around the injection point, later spreads radially throughout the capture formation. The range of pressure increase depends on the injection rate, injectivity and reservoir volume. The increase of pressure in the reservoir may cause several problems, including fault reactivation.

In this study, numerical simulation was applied in order to investigate the effect of production of formation water to mitigate pressure build-up during CO₂ injection into the storage aquifer. The hypothesis, that it will be possible to reduce the pressure buildup in the reservoir during injection by applying pre-injection formation water (brine) production as proposed by Buscheck et al. in 2014 (dual-mode wells), or by production of brine at the same time during injection of CO₂ will be explored in this paper. Numerical simulations were conducted, using the TOUGH2/ECO2N code for non-isothermal, multi-dimensional coupled fluid and heat flow, developed at the Lawrence Berkeley National Laboratory (LBNL).

We employed a simple reservoir model based on available data of the large-scale CCS demonstration project at the Tomakomai area in Hokkaido, Japan. The efficiency and influence of different production/injection rates, reservoir volumes, and the appropriate arrangement of production / injection well on pressure build-up in the storage formation were tested. Three models (15 km x 8 km x 100 m, 24 km x 24 km x 100 m, and 5 km x 5 km x 100 m) with different volumes were employed, and two production / injection rates (200 kt/yr and 1 Mt/yr) were applied for generally three different cases. The first case was only injection of CO₂ for 100 years without previous production. The second case included previous production for 3 and 5 years with subsequent injection for 100 years. The last (third) case considered production of brine while injection of CO₂ by using a separate installed production well. Furthermore, for the third case, appropriate installation and management methods for the wells also were investigated.

In the case of pre-injection brine production, we found that due to production, pressure can be lowered in the storage formation effectively, but due to the recovery effect of pressure, after starting injection of CO₂, the pressure increases rapidly and reaches almost the same value after a view years comparing to the base case without initially production of brine, thus the pre-injection pressure lowering is only effectively for a short time. Regarding to the three different sizes, the results have shown that with smaller reservoir volume the pressure lowering effect increases in efficiency. The most promising result brought up the system of a separate production well and production of brine at the same time during injection. Here, the recovery effect is neglected during the injection, thus the pressure can be kept almost constant during injection.

Judging by the results, the conclusion that can be drawn is that pre-injection, or especially production and injection at the same time can be very effective in order to lower the reservoir pressure and avoid too much pressure build-up and harmful effects on the hydrogeological conditions due to high pressure rise in the storage formation. Even regarding the capacity of injectable CO₂, these methods can be applied to make CCS technology much more sufficient.

For these results, it has to be emphasized, that the effectiveness of the production strategies may highly depend on site conditions. Therefore, the results obtained in this study should be regarded as a preliminary evaluation for the Tomakomai site specifications. Further investigations would be

necessary, when more data becomes available through the site investigation and even operations.

Keywords: Carbon Capture and Storage, pressure build-up, production of formation water

An Experiment study on dynamic displacement and non-equilibrium dissolution for CO₂ in porous media

*LANLAN JIANG^{1,2}, Ziqiu Xue¹, Hyuck Park¹, Yongchen Song²

1.Research Institute of Innovative Technology for the Earth, 2.Dalian University of Technology

A clear understanding of the displacement and dissolution processes in porous media is of importance for CO₂ trapping mechanism during geological storage. The porous media were filled with quartz glass beads. CO₂ and water injection with different flow rates in porous media were investigated using MRI. The intensity of MRI images decreased with CO₂ injection and increased with water injection in the longitudinal sections at various times. Flow patterns in the drainage, changed with different flow rates. However, water imbibition proceeded as the uniform displacement front even with the fast flow rates. The residual CO₂ saturation after imbibition was sensitive to the capillary number and initial CO₂ saturation. As capillary numbers increased, viscous forces dominated the flow resulting in a decreasing in CO₂ phase trapping. At high initial saturation range, the residual saturation decreased with initial CO₂ saturation. For post imbibition, CO₂ dissolution dominated the mass transfer reflecting the transition from capillary trapping to solubility trapping. The concentration of supercritical CO₂ (ScCO₂) decreased sharply during imbibition and slightly during post imbibition. In contrast, lots of gaseous CO₂ dissolved into water during post imbibition. The dissolution rate for ScCO₂ was around the order of magnitudes 10^{-6} - 10^{-7} Kg/m³.s. And the CO₂ saturation during post imbibition decreased. The study visualization measured dynamic drainage and imbibition processes and investigated the influence of dissolution to trapping characteristics which is useful for CO₂ geological storage.

Keywords: capillary trapping, dissolution, CO₂ saturation, geological storage, flow pattern

Effects of stress relaxation and clay mineral contents on permeability changes of mudstones during fracturing processes

*Takashi Fujii¹, Masao Sorai¹, Xinglin Lei¹

1.National Institute of Advanced Industrial Science and Technology

An understanding of fluid transport within aquifers plays an important role for geological CO₂ storage (GCS). During CO₂ injection into the reservoirs, a change in stress induced by increasing pore pressure might lead to deformation of surrounding reservoir rocks including caprocks, and this might also result in occurrence of seismic or aseismic slip along fractures/faults because of decreasing rock matrix and fault strengths. Thus, the presence of fractures and faults into caprocks such as mudstones and shales should provide an impact on the relationship between hydraulic properties (i.e., permeability and capillary pressure) and rock deformation. A few studies on measurement of permeability during shear fracturing in mudstones have been reported so far, but evolution of permeability throughout fracturing, slipping, stress-relaxing and variations of effective pressure levels processes has rarely been investigated. The objective of this study is to measure experimentally a change in permeability in a series of complex processes from fracturing to effective pressure dependency for mudstones. Particularly, we investigate impacts of stress relaxation and clay mineral contents on permeability evolution in response to variations of effective pressure levels which assume change in stress within targeted reservoirs resulting from the occurrence of overpressure. In this study, permeability tests were performed by employing the four steps: (i) fracturing, (ii) slipping, (iii) stress-relaxing, and (iv) effective pressure dependency at temperature of 40°C and effective pressure ranging from 2 to 15 MPa (confining pressures: 12-25 MPa and pore pressure: 10 MPa at constant) for two mudstones. The two samples tested were taken from GCS demonstration site of Tomakomai in Hokkaido (DS) and lower formation of Tentokuji in Akita associated with screening of all GCS sites in Japan (SS). Based on mode analysis of mineral compositions, it was shown that majority of mineral compositions for the SS sample was about 70 vol.% smectite-rich matrix. On the other hand, for the DS sample, little clay minerals was observed. Our results demonstrated that the rock samples tested exhibited brittle failure behaviours in stress-strain curves. As for the process (iii), it was apparent that permeability values measured after the long relaxation time (almost 7 days) were a significantly more susceptible to change in effective stress than that after the short time within 1 day. A comparison result showed that for the DS sample, magnitude of change in permeability values with decreasing effective pressure for the DS was almost two times larger than that for the SS sample relative to permeability values in the stress-relaxation state. This result showed that in the case of lower contents of clay minerals such as smectite and kaolinite, if the pre-existing fractures/faults into such mudstones had several events of tectonic movement over a long period, it might possibly lead to slipping behaviour easily due to the decrease of effective pressure induced by CO₂ injection. Also, it is further shown that its degree of slipping and magnitude of change in permeability could be depending strongly on the types of mudstones such as clay mineral contents. The present results should be pointed out that time of stress relaxation and clay mineral contents could provide a significant impact on change in permeability against effective pressure levels depending on the types of caprocks.

Keywords: Stress relaxation, clay mineral contents, change in permeability, mudstones

Influence of flow pattern of two-phase fluid flow on deformation of mudstones

*Hiroki Goto^{1,2}, Tomochika Tokunaga², Masaatsu Aichi²

1.JSPS Research Fellow, 2.University of Tokyo

Injection of carbon dioxide into geological formations may result in ground surface deformation. In order to control the ground surface deformation, understanding deformation of rock mass caused by infiltration of carbon dioxide is required. In this study, laboratory experiments were conducted to understand deformation of mudstones caused by infiltration of non-wetting phase fluid. In the experiment, air was injected into a water-saturated cylindrical mudstone sample, which belongs to the Umegase Formation of the Kazusa Group, under hydrostatic external stress condition. During the experiment, both axial and circumferential strains at half the height of the sample were monitored. Numerical simulation of the experiment was tried by using a simulator which can solve coupled two-phase fluid flow and deformation of porous media (Aichi, 2010). Calculated strains were larger than the measured ones. Considering the pore size distribution of the mudstone and the pressure condition set in the experiment, air was thought to flow through preferential flow paths in the sample. Since preferential paths of air were not formed in the numerical simulation due to two-phase fluid flow based on Darcy's law, flow pattern of two-phase fluid flow is suggested to affect deformation of mudstones.

Reference:

Aichi, M. (2010), Thermodynamically consistent multiphase poroelasticity and its application to water-dissolved gas reservoir simulation, PhD Thesis, Dep. of Geosys. Eng., Univ. of Tokyo.

Keywords: Geological sequestration of carbon dioxide, Mudstone, Deformation, Two-phase fluid flow, Laboratory experiment

In-situ observation of water, oil and coal under high CO₂ pressure for CO₂-EOR and ECBMR*Yuichi Sugai¹

1. Kyushu University

In geologic CO₂ sequestration, the pH of formation water may be reduced due to CO₂ dissolution, which may cause the change of porosity and permeability of reservoir rock. The pH changes of formation water are widely varied depending on CO₂ pressure and the content of substances having pH buffering action, therefore, it is important to determine the wide range of pH change of various types of formation water under the various CO₂ pressure conditions. We considered a determination method of pH change of various types of formation water under the various CO₂ pressure conditions based on the spectrophotometry using a windowed high-pressure cell and a mixed pH indicator consisting of 4 single pH indicators. The well-defined absorption peaks were found at the wavelength of 614 nm or 444 nm when the pH of the solution was ≥ 5.6 or < 5.6 respectively, therefore, two different calibration curves were derived from the absorbance of standard pH buffer solutions at each wavelength. The validity of this method was confirmed by an experimental result that the pH change of deionized water under 0.1 MPa CO₂ pressure had been determined accurately by this method. We carried out experiments on this method using the real formation water samples which contained bicarbonate ion having pH buffering action with different concentration under various CO₂ pressure. The results of the experiments demonstrated that this method is capable of determining the pH change of various types of formation water under various CO₂ pressure conditions.

Oil swelling is an important phenomenon in CO₂-EOR. According to various studies in the past, the degree of oil swelling depends on the partial pressure of CO₂, temperature, and oil composition. However, we expect that other factors, such as oil saturation, capillary pressure, and grain size of reservoir rock must be also considered in evaluating oil swelling because they may influence the interfacial area between oil and CO₂, which affects the dissolubility of CO₂ in oil. Therefore, we had made clear the effect of the interfacial area on oil swelling in this study. Oil and CO₂ were injected into a small see-through windowed high-pressure cell and oil swelling was observed under a microscope. The swelling factor increased with the increase of the specific interfacial area between oil and CO₂. Moreover, oil swelling in porous media was observed by using micro-models which had been made of 2 different diameter glass beads. Swelling factor in fine beads micro-model became larger than that in coarse beads micro-model whose interfacial area between oil and CO₂ was smaller than that of fine beads micro-model. Therefore, the swelling factor is expected to be larger with an increase in the interfacial area in porous media. These results suggest that the oil swelling should be expressed as a function of oil saturation, capillary pressure, and grain size of reservoir rock which are related to the interfacial area as well as the partial pressure of CO₂, temperature, and oil composition.

Coal swelling is also an important phenomenon in CO₂-ECBMR. The reduction of permeability of coal seam will be caused by the swelling phenomenon. The coal swelling should be controlled by a certain method in order to prevent the permeability reduction. Coal and CO₂ were injected into a small see-through windowed high-pressure cell and coal swelling was observed under a microscope. The coal swelling became smaller as the temperature was higher. This result suggest that the coal swelling can be controlled by heating the coal seam around the injection well.

Keywords: CO₂, water, oil, coal, pH, swelling

Field experiment of carbonate reactions in the CO₂-injected hot spring waters*Masao Sorai¹, Munetake Sasaki¹

1. Research Institute for Geo-Resources and Environment, National Institute of Advanced Industrial Science and Technology

On geological CO₂ storage (GCS), the evaluation of the injected CO₂ behavior over a long time requires the numerical simulation considering geochemical processes. Among such geochemical processes, both precipitation and dissolution of carbonate minerals are important from each perspective of storage potentials and leakage risks. However, there have remained many uncertainties on their kinetics under conditions of GCS.

In this regard, to obtain reliable dataset on carbonate kinetics, we have performed reaction experiments of carbonate minerals at bicarbonated springs, which can be regarded as a natural analogue of GCS. Specifically, an input of CO₂ gas and Mg ions into spring waters allowed to highlight the effects of these chemical species on the reaction rate and precipitating phase of carbonate minerals under natural conditions. Previous experiment injected CO₂ at an atmospheric pressure. Under this condition, the solubility of CO₂ was too low (i.e., the pH was too high) to dissolve carbonate minerals. This time, we tried to change the pH lower by injecting high pressure CO₂ using a stainless-steel tube.

The experiment was performed at the Utoro hot spring in Hokkaido, Japan. In this site, the spring water from a well was stored once in a tank, and then it was flew down through a pipe 50 meters long. We created the bypass system, where the spring water pumped up from the tank was flowed through a stainless-steel tube. After passing through the tube, the water was thrown down the existing pipe. Three sample holders were arranged in series within a tube; each holder set cleaved crystals of major carbonate species, calcite and aragonite (CaCO₃), dolomite (CaMg(CO₃)₂), and magnesite (MgCO₃). These samples were dipped into the flowing water over a period up to 24 hours. Then, the holder was taken out one by one at predetermined time. Present experiments included reactions injecting the CO₂ gas at 0.3 MPa with and without addition of magnesium chloride (i.e., Mg/Ca = 0.5, and 3, respectively), along with reactions in the untouched spring water.

Reaction rate was estimated from measurements of the height level difference between original and reacted surfaces by using a phase-shift interferometer and a laser microscope. The CO₂ injection tests resulted in the dissolution of calcite and aragonite. Although both dissolution rates were almost equal, addition of Mg ions induced an opposite trend: calcite dissolution rate was reduced by nearly half, whereas aragonite dissolution rate was slightly increased. On the other hand, the optical microscopic observation showed no obvious changes on dolomite and magnesite surfaces. These results suggest that the dissolution rate of carbonate minerals depends on both water compositions near a CO₂ injection well and mineral species of carbonates, and that the kinetics for carbonate reactions associated with GCS cannot be uniformly defined.

Keywords: Geological CO₂ storage, Bicarbonated spring, Dissolution rate, Reaction kinetics, Carbonate minerals

A numerical model for calculating the behavior of leaked CO₂ in the sea for assessing the potential impacts on the marine environment

*Keisuke Uchimoto¹, Yoshimasa Matsumura², Jun Kita¹

1.Research Institute of Innovative Technology for the Earth, 2.Institute of Low Temperature Science, Hokkaido University

To mitigate global warming, the reduction of carbon dioxide (CO₂) in the atmosphere is indispensable. We should make every endeavor to do it. Among options for it, CO₂ capture and storage (CCS) is thought to be one of the most important ones. Captured CO₂ in major CO₂ emission sources, such as power plants, is transported into deep geological formations and stored there. In Japan, mainly off shore areas will be selected as the storage sites. There is still concern that stored CO₂ may leak out into the sea and that leaked CO₂ may impact the marine organisms. To diminish the risk of CO₂ leakage, it goes without saying that it is necessary to select the storage sites and the formations where CO₂ will be stored stably and safely. In addition, we should enhance scientific knowledge and develop methods to assess the potential marine environmental impacts in case the stored CO₂ should leak out. How much the marine environment or organisms will be impacted depends on the rise in the CO₂ concentration in seawater consequent on the leakage.

Aiming at calculating dispersion of leaked CO₂ in the sea, we are developing a numerical model. In JpGU 2015 meeting, we presented a model where the leaked CO₂ dissolved into seawater (Δ DIC) is represented as a passive tracer. In the model, CO₂ bubbles were not calculated. However, it is considered that CO₂ would leak out from the seafloor mainly as bubbles. CO₂ bubbles from the seabed rise in the water column, dissolving into seawater. These processes may affect the distribution of Δ DIC because the dissolution rate and the movement of CO₂ bubbles depend on the size of the bubbles, and temperature and salinity of ambient water. Therefore, we have incorporated CO₂ bubbles into the model. The model is based on a non-hydrostatic ocean model, named kinaco, which has a Lagrangian particle tracking scheme. To represent CO₂ bubbles in the model, we apply properties of CO₂ bubbles, such as the mass and volume, to the particles. Based on the size of bubbles, and temperature and salinity of the cells that the bubbles exist in, the buoyancy and the dissolution rates are calculated. According to them, the movements and the sizes of CO₂ bubbles are computed. CO₂ dissolved into seawater is dispersed as Δ DIC, which is calculated as a passive tracer in the model. In our presentation, details of the model and examples of the calculation with the model will be presented.

Keywords: potential marine environmental impacts, carbon dioxide capture and storage, numerical model